optronics®
Better Value ▪ Better Options ▪ Better Lighting

CONTENTS

All Optronics products conform to DOT/SAE/FMVSS/CMVSS 108 standards where applicable when applied according to federal lighting requirements

LED TRUCK & TRAILER LIGHTING **2 - 229**

Headlamps 2
FUSION™ Stop/Turn/Tail/Back-Up Lamps....6
Sealed Stop/Turn/Tail Lights & Parking/Turn Signals 14
Combination Tail Lights & Kits 46
DOT Compliant Back-Up Lights 77
Warning Lights 89
Millennium® Series....101
Sealed Marker/Clearance Lights 108
Surface Mount Marker/Clearance Lights....138
Identification Light Bars 163
License Plate Lights 170
Interior & Utility Lights 179
Work & Off-Road Lights 211

INCANDESCENT TRUCK & TRAILER LIGHTING **230 - 293**

Sealed Stop/Turn/Tail Lights & Parking/Turn Signals 230
Combination Tail Lights & Kits 234
DOT Compliant Back-Up Lights 248
Millennium Series®....250
Sealed Marker/Clearance Lights 252
Surface Mount Marker/Clearance Lights....261
Identification Light Bars 275
License & Utility Lights 278
Utility & Interior Lights 287
Halogen Lights....291

RV LIGHTS & ACCESSORIES **294 - 322**

ACCESSORIES - CONSPICUITY, MOUNTING, WIRING **323 - 357**

FMVSS LIGHTING REQUIREMENTS **358 - 364**

INDEX **365 - 377**

MATRICES **378 - 383**

WARRANTY **384**

Optronics International

OKLAHOMA: 401 South 41st Street East, Muskogee OK 74403
toll free: 800-364-5483 • phone: 918-683-9514 • fax: 918-683-9517

INDIANA: 3535 Corrie Dr, Goshen, IN 46526
toll free: 800-826-5483 • phone: 574-389-0040 • fax: 574-389-0041

website: www.optronicsinc.com • email: sales@optronicsinc.com

©2019 Optronics International ZH2019M

Opti-Brite

HLL70HLB

HLL70 SERIES

DOT Compliant High/Low Beam Sealed LED Headlamp

- Replace standard 5” x 7” sealed beam halogen and HID headlights
- Light output whiter than incandescent for greater visibility
- Long lasting, energy efficient - diodes last up to 50 times longer than incandescent, draws just 1.1 amp
- Dual power: use with 12VDC or 24VDC systems
- Hard wired design with industry standard H4 three-blade connector
- Die cast aluminum construction with powder coat finish resists corrosion
- Tough polycarbonate lens
- IP67 rating: protected from dust and capable of withstanding water immersion, offering increased reliability and service life

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
HIGH/LOW BEAM HEADLAMP - 12 DIODES			
HLL70HLB	HLL70HLBP	12-24VDC High/Low beam	1
RETAIL			
HLL70HLS	Retail Ready	Single light, Retail Box	1

IP67 rating: protected from dust and capable of withstanding water immersion, offering increased reliability and service life

FMVSS	HL
MATERIALS	Polycarbonate lens, aluminum housing
VOLT/AMP	12.8VDC - High 1.13A, Low 0.85A
WT/DIMS	2.99 lbs. / 7.937” x 5.625” x 3.5”
WARRANTY	Lifetime LED Warranty

HLL93 SERIES

DOT Compliant High/Low Beam Sealed LED Headlamp

Opti-Brite

- Raw lumen output: 2460 lm, Effective lumen output: 1722 lm
- Replace standard 7” sealed beam halogen and HID headlights
- Light output whiter than incandescent for greater visibility
- Long lasting, energy efficient - diodes last up to 50 times longer than incandescent, draw less than 1 amp
- Dual power: use with 12VDC or 24VDC systems
- Die cast aluminum construction with powder coat finish resists corrosion
- Tough polycarbonate lens
- IP67 rating: protected from dust and capable of withstanding water immersion, offering increased reliability and service life

HLL93HLB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
HIGH/LOW BEAM HEADLAMP - 12 DIODES			
HLL93HLB	HLL93HLBP	12-24VDC High/low beam	1
RETAIL			
HLL93HLS	Retail Ready	Single light, Retail Box	1

IP67 rating: protected from dust and capable of withstanding water immersion, offering increased reliability and service life

HLL93HLS

FMVSS	HL
MATERIALS	Polycarbonate lens and aluminum housing
VOLT/AMP	12.8VDC - High Beam .84A / Low Beam .41A
WT/DIMS	1.721 lbs. / 7” x 7” x 3.25”
WARRANTY	Lifetime LED Warranty



Opti-Brite

HLL78/79 SERIES

DOT Compliant High and Low Beam Sealed LED Headlamps

HLL78LB

HLL79HB

HLL78LS

- Raw lumen output: 2340 lm, Effective lumen output: 1638 lm
- Replace standard 4" x 6" sealed beam halogen and HID headlamps
- Light output whiter than incandescent for greater visibility
- Long lasting, energy efficient – diodes last up to 50 times longer than incandescent, draw less than 1 amp
- Dual power: use with 12VDC or 24VDC systems
- Hard wired with standard H4 3-blade connector; 16 gauge, 7-inch leads
- Die cast aluminum construction with powder coat finish resists corrosion
- Tough polycarbonate lens with protective coating

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
LOW BEAM HEADLAMP - 11 DIODES			
HLL78LB	HLL78LBP	12-24VDC Low beam	1
HIGH BEAM HEADLAMP - 11 DIODES			
HLL79HB	HLL79HBP	12-24VDC High beam	1
RETAIL			
HLL78LS	Retail Ready	Low beam, Retail Box	10
HLL79HS		High beam, Retail Box	10

IP67 rating: protected from dust and capable of withstanding water immersion, offering increased reliability and service life

FMVSS	HL
MATERIALS	Polycarbonate lens, aluminum housing
VOLT/AMP	12.8VDC - High 1.47A / Low 1.35A
WT/DIMS	1.858 lbs. / 6.58" x 4.2" x 3.32"
WARRANTY	Lifetime LED Warranty





HLL90 & HLL88/89 SERIES

DOT Compliant High/Low Beam Sealed LED Headlamp

- Replace standard sealed beam halogen and HID headlamps
- Light output whiter than incandescent for greater visibility
- Dual power: use with 12VDC or 24VDC systems
- Hard wired with standard H4 3-blade connector; 16 gauge, 7-inch leads

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
7" HIGH/LOW BEAM HEADLAMP - 16 DIODES			
HLL90HLB	HLL90HLBP	12-24VDC High/low beam	1
4"x6" LOW BEAM HEADLAMP - 8 DIODES			
HLL88LB	HLL88LBP	12-24VDC Low beam	1
4"x6" HIGH BEAM HEADLAMP - 8 DIODES			
HLL89HB	HLL89HBP	12-24VDC High beam	1

HLL90HLB



IP67 rating: protected from dust and capable of withstanding water immersion, offering increased reliability and service life

FMVSS	HL
MATERIALS	Polycarbonate lens, aluminum housing
VOLT/AMP	HLL90: 12.8VDC - High Beam 1.85A / Low Beam 1.80A
	HLL88/89: 12.8VDC - 0.85A
WT/DIMS	HLL90: 2.05 lbs. / 7" x 7" x 2.8"
	HLL88/89: 1.14 lbs. / 6.563" x 4.188" x 3.313"
WARRANTY	Lifetime LED Warranty

HLL88LB



HLL89HB

STL201 GLOLIGHT® SERIES

GloLight® FUSION™ 4" Round Sealed Stop/Turn/Tail/Back-Up Light with Mounting Flange

STL201RFMB

PATENTED TECHNOLOGY

- DOT-compliant back-up light built into stop/turn/tail light
- Sonically sealed, weathertight connections
- Multi-function: Stop, turn, tail and back-up, all in one light
- Recess flange mount design for secure installation

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED STOP/TURN/TAIL/BACK-UP LIGHT - 24 DIODES			
STL201RFMB	STL201RFMBP	Weathertight connection	10
ACCESSORIES			
A45PMB	A45PMBP	Weathertight pigtail, 3-wire	50
A42PMB	A42PMBP	Weathertight pigtail, 2-wire	100

FMVSS	S2 T2 I6 (2)R
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - .316A Stop/Turn, .15A Tail, .3A Back-Up
WT/DIMS	.38 lbs. / 5.5" x 5.5" x 1.5"
WARRANTY	Lifetime LED Warranty





HOLE CUT-OUT: 4.5"

Weathertight connection

STL201X SERIES

FUSION™ 4" Round Sealed Stop/Turn/Tail/Back-Up Light

PATENTED TECHNOLOGY

- DOT-compliant back-up light built into stop/turn/tail light
- Sonically sealed, waterproof
- Multi-function: Stop, turn, tail and back-up, all in one light
- Accepts industry standard PL-3 plugs

STL201XRB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED STOP/TURN/TAIL/BACK-UP LIGHT - 16 DIODES			
STL201XRB	STL201XRBP	PL-3 connections	10
STL201XR1224B	STL201XR1224BP	PL-3 connections, 12/24V	10
ACCESSORIES			
A45GB	A45GBP	Grommet	50
A46GB	A46GBP	New design grommet	50
A45BB	A45BBP	Black plastic mounting flange	100
A45SB	A45SBP	Stainless steel mounting flange	20
A45PB	A45PBP	Straight pigtail, 3-wire PL-3	100
A47PB	A47PBP	Right angle pigtail, 3-wire PL-3	100
A45CB	A45CBP	Pigtail, 2-wire	100
A49PB	A49PBP	Right angle pigtail, 2-wire	100
BK45BB	BK45BBP	Black steel bracket	10

FMVSS	S2 T2 I6 (2)R
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - .375A Stop/Turn, .145A Tail, .3A Back-Up
WT/DIMS	.35 lbs. / 4.313" x 4.313" x 1.625"
WARRANTY	Lifetime LED Warranty

Standard PL3 connections



HOLE CUT-OUT: 4.5"

STL201XRFHXB

FUSION™ 4" Round Surface Mount Stop/Turn/Tail/Back-Up Light with Reflex Mounting Flange

STL201XRFHXB

PATENTED TECHNOLOGY

- Sonically sealed, waterproof
- Multi-Function: stop/turn/tail/back-up with reflex flange - all in one light
- FMVSS compliant for over 80" applications
- Surface mount
- Hard wired, includes 8" lead and ground wires

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED STOP/TURN/TAIL/BACK-UP LIGHT - 20 DIODES			
STL201XRFHXB	STL201XRFHXBP	Hard wired, 8" leads	10

FMVSS	S2 T2 I6 (2)R A
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - .375A Stop/Turn, .145A Tail, .3A Back-Up
WT/DIMS	.38 lbs. / 5.44" x 5.44" x .79"
WARRANTY	Lifetime LED Warranty



STL1211 SERIES

FUSION™ GloLight® LED 6" Surface Mount Stop/Turn/Tail/Back-Up Light

PATENTED TECHNOLOGY

- Sonically sealed, waterproof
- Multi-function: stop/turn/tail/back-up
- GloLight shape illuminates for tail light function
- Clear lens, red and white diodes
- Surface flange mount
- Hard wired with female PL-3 plugs



STL1211RCFHPG

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
STOP/TURN/TAIL/BACK-UP LIGHT - 22 DIODES			
STL1211RCFHPG	STL1211RCFHPGP	Red, hard wired	10
ACCESSORIES			
A211NCCB	A211NCCBP	Snap-on bezel, unfinished	50
A78RXB	A78RXBP	Red reflex, snap-on trim ring FMVSS "A"	25
A178TRSSB	A178TRSSBP	Stainless steel, screw mount trim ring	50

FMVSS	S2 T2 I6 (2)R
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - .375A Stop/Turn, .02A Tail, .242A Back-up
WT/DIMS	.4 lbs. / 7.52" x 3.29" x 1.01"
WARRANTY	Lifetime LED Warranty



STL211X SERIES

FUSION™ 6" Oval Sealed LED Stop/Turn/Tail/Back-Up Lights



STL211XRB



STL211XRCB

PATENTED TECHNOLOGY

- DOT-compliant back-up light built into stop/turn/tail light
- Sonically sealed, waterproof
- Multi-function: Stop, turn, tail and back-up, all in one light
- Accepts industry standard PL-3 plugs

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED STOP/TURN/TAIL/BACK-UP LIGHT - 16 DIODES			
STL211XRB	STL211XRBP	Red lens, PL-3 connection	10
STL211XRCB	STL211XRCBP	Clear lens, PL-3 connection	10
ACCESSORIES			
A70GB	A70GBP	Grommet, flush mount	50
A45PB	A45PBP	Pigtail, 3-wire	100
A47PB	A47PBP	Right angle pigtail, 3-wire	100
A45CB	A45CBP	Pigtail, 2-wire	100
A49PB	A49PBP	Right angle pigtail, 2-wire	100
A77S1B	A77S1BP	Gray, flat design steel bracket	50
BK70BB	BK70BBP	Black steel bracket	10
RETAIL			
TLL211XRTMK	Retail Ready	**Try Me** Retail Kit: (2) ea. STL211XRB, A70GB, A45PB, A45CB, and (1) A30W5BLB 5-way harness, clam	6

TLL211XRTMK

FMVSS	S2 T2 I6 (2)R
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - .375A Stop/Turn, .020A Tail, .242A Back-Up
WT/DIMS	.35 lbs. / 6.438" x 2.313" x 1.50"
WARRANTY	Lifetime LED Warranty



HOLE CUT-OUT: 6.85" X 2.5"
(1.25" R)



Standard PL3 connections

STL211XRFHB

FUSION™ LED 6" Surface Mount Stop/Turn/Tail/Back-Up Light

PATENTED TECHNOLOGY

- DOT-compliant back-up light built into stop/turn/tail light
- Flange surface mount–no panel cut-out required
- Sonically sealed, waterproof
- Hard wired, with 8-in leads

STL211XRFHB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
STOP/TURN/TAIL/BACK-UP LIGHT - 17 DIODES			
STL211XRFHB	STL211XRFHBP	Hard wired	10
STL211XRFHPG	STL211XRFHPGP	Hard wire, female PL-2 and PL-3 plugs	10
ACCESSORIES			
A211CB1	A211CB1P	Chrome, snap-on bezel	25
A211NCCB	A211NCCBP	Snap-on bezel, unfinished	50
A211RXB	A211RXBP	Red reflex flange ring	25
A178TRSSB	A178TRSSBP	Stainless steel, screw mount trim ring	50

FMVSS	S2 T2 (2)R
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - .265A Stop/Turn, .24A Tail, .3A Back-up
WT/DIMS	.4 lbs. / 7.5" x 3.25" x .75"
WARRANTY	Lifetime LED Warranty



STL68RB

A68SSB

STL68 SERIES

FUSION™ Surface Mount LED Combination Stop/ Turn/Tail/Back-Up Light

PATENTED TECHNOLOGY

- Sonically sealed, waterproof
- Low profile design–only 1/2" thick
- Surface mount on 9-11/16" centers
- Hard wired with separate ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
STOP/TURN/TAIL/BACK-UP LIGHT - 14 DIODES			
STL68RB	STL68RBP	Red, hard wired	10
STL68RPB	STL68RPBP	Red, .180 male bullets	10
ACCESSORIES			
A68SSB	A68SSBP	Stainless steel snap-on ring	20

FMVSS	S2 T2 I6 (2)R
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - .35A Stop/Turn, .05A Tail, .3A Back-up
WT/DIMS	.275 lbs. / 10.125" x 3.063" x 0.5"
WARRANTY	Lifetime LED Warranty



STL68RB



A68SSB

STL264 SERIES

FUSION™ LED Thinline Stop/ Turn/Tail/Back-Up Lights

STL264RB



STL264RCB

PATENTED TECHNOLOGY

- Sonically sealed, waterproof
- Low profile design–only 1/2” thick
- Surface mount on 9-11/16” centers
- Hard wired with separate ground wire



BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
STOP/TURN/TAIL/BACK-UP LIGHT - 19 DIODES			
STL264RB	STL264RBP	Red, hard wired	10
STL264RCB	STL264RCBP	Clear lens, red, hard wired	10
ACCESSORIES			
A64CRB	A64CRBP	Chrome base/bezel	50
A64BB	A64BBP	Black base/bezel	50

FMVSS	S2 T2 I6 (2)R
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - .265A Stop/Turn, .24A Tail, .3A Back-up
WT/DIMS	.441 lbs. / 20.5” x 1” x .75”
WARRANTY	Lifetime LED Warranty

FTL42/53 SERIES

4" Round Sealed LED Front Turn Signal

- Sonically sealed, waterproof
- 10 SMD diodes
- Dual power: use with 12VDC and 24VDC systems

FTL42A1224B

FTL53ALCPG

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW PARKING/TURN SIGNAL - 10 DIODES			
FTL42A1224B	FTL42A1224BP	Flange mount, hard wired, 12V/24V	10
FTL53ALCPG	FTL53ALCPGP	Grommet mount, hard wired, Deutsch connection, 12/24V, protective coating on lens, EMC	10
ACCESSORIES			
A45GB	A45GBP	Grommet	50

FMVSS	Yellow I6 I7 P
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	FTL42: 12.8VDC - .413A Turn, .028A Park
	FTL53: 12.8VDC - .357A Turn, .014A Park
WT/DIMS	FTL42: .617 lbs. / 5.5" x 5.5" x 1.938"
	FTL53: .265 lbs. / 4.313" x 4.313" x .82"
WARRANTY	Lifetime LED Warranty



FTL53ALCPG

Deutsch connection on FTL53ALCPG

STL603 SERIES

LightGuide™ LED 4" Stop/Turn/Tail Light

PATENTED TECHNOLOGY

- Central X-shaped feature illuminates for tail light function
- Surrounding diodes light for stop and turn functions
- Sonically sealed, waterproof
- Grommet mount
- Accepts industry standard PL-3 connector

STL603RB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED STOP/TURN/TAIL LIGHT - 12 DIODES			
STL603RB	STL603RBP	PL-3 connection	10
ACCESSORIES			
A45GB	A45GBP	Grommet	50
A45PB	A45PBP	Pigtail, 3-wire	100
A47PB	A47PBP	Right angle pigtail, 3-wire	100
BK45BB	BK45BBP	Black steel bracket	10
A45BB	A45BBP	Black plastic flange	100
A45SB	A45SBP	Stainless steel mounting flange	20
A45CGB	A45CGBP	Chrome grommet cover	20



HOLE CUT-OUT: 4.5"

FMVSS	Red S2 T2 I6
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - .421A Stop/Turn, .114A Tail
WT/DIMS	.375 lbs. / 4.313" x 4.313" x 1.688"
WARRANTY	Lifetime LED Warranty

GloLight®

STL101 GROMMET MOUNT SERIES

GloLight® 4" Sealed LED Lights

STL101RB

STL101RCB

STL101AB

STL101ACB

PATENTED TECHNOLOGY

- Sonically sealed, waterproof
- Mount in any 360 degree position
- Available in tinted and clear lens models
- Available with standard PL-3 or optional weathertight connection

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED STOP/TURN/TAIL LIGHT - 21 DIODES			
STL101RB	STL101RBP	PL-3 connection	10
STL101R1224B	STL101R1224BP	PL-3 connection 12/24V	10
STL101RMB	STL101RMBP	Weathertight connection	10
STL101RCB	STL101RCBP	Clear lens, red diodes, PL-3	10
STL101RCMB	STL101RCMBP	Clear lens, red diodes, weathertight	10
STL101RKB	STL101RKBP	Kit: Red stop/turn/tail light, PL-3 connection, A45GB grommet, A47PB pigtail	10
YELLOW PARKING/TURN SIGNAL - 21 DIODES			
STL101AB	STL101ABP	PL-3 connection	10
STL101ACB	STL101ACBP	Clear lens, yellow diodes, PL-3	10
ACCESSORIES			
A45GB	A45GBP	Grommet	50
A45PB	A45PBP	Pigtail, 3-wire	100
A47PB	A47PBP	Right angle pigtail, 3-wire	100
A45PMB	A45PMBP	Weathertight pigtail	100
AL45PWTB	AL45PWTBP	Weathertight to PL-3 adaptor	50
BK45BB	BK45BBP	Black steel bracket	10
A45BB	A45BBP	Black plastic flange	100
A45SB	A45SBP	Stainless steel mounting flange	20
A45CGB	A45CGBP	Chrome grommet cover	20

FMVSS	Red S2 T2 I6; Yellow I6 P
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	Red: 12.8VDC - .375A Stop/Turn, .145A Tail Yellow: 12.8VDC - .315A Turn, .143A Parking
WT/DIMS	.35 lbs. / 4.313" dia x 1.375" D
WARRANTY	Lifetime LED Warranty



HOLE CUT-OUT: 4.5"

STL101 FLANGE MOUNT SERIES

GloLight® 4" Sealed LED Lights with Mounting Flange

PATENTED TECHNOLOGY

- Sonically sealed, waterproof
- Flange mount for security, theft reduction
- Available in tinted and clear lens models
- Available with standard PL-3 or optional weathertight connection

STL101RFB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED STOP/TURN/TAIL LIGHT - 21 DIODES			
STL101RFB	STL101RFBP	PL-3 connection	10
STL101RFMB	STL101RFMBP	Weathertight connection	10
STL101RCFB	STL101RCFBP	Clear lens, red diodes, PL-3	10
STL101RCFMB	STL101RCFMBP	Clear lens, red diodes, weathertight	10
ACCESSORIES			
A45PB	A45PBP	Pigtail, 3-wire	100
A47PB	A47PBP	Right angle pigtail, 3-wire	100
A45PMB	A45PMBP	Weathertight pigtail	100
AL45PWTB	AL45PWTBP	Weathertight to PL-3 adaptor	50
BK45BB	BK45BBP	Black steel bracket	10
A101TRSSB	A101TRSSBP	Stainless steel trim ring	50
A42GB	A42GBP	Mounting gasket, black	100

STL101RCFB

FMVSS	Red S2 T2 I6
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - .375 Stop/Turn, .145A Tail
WT/DIMS	.38 lbs. / 5.48" x 5.48" x 1.53"
WARRANTY	Lifetime LED Warranty

Industry-standard connections

Easy retrofit of lights to existing harness



Standard PL3 connection

Weathertight connection



HOLE CUT-OUT: 4.5"

STL43 SERIES
4" Round Sealed LED Lights

- Sonically sealed, waterproof
- Kits include grommet and plug
- Mount in any 360 degree position
- Available in 12-24V models
- Available with standard PL-3 or optional weathertight connection

STL43RB

STL53RCB

STL43AB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED STOP/TURN/TAIL LIGHT - 10 DIODES			
STL43RB	STL43RBP	PL-3 connection, 12V	10
STL43RKB	STL43RKBP	Kit with A45GB & A47PB, PL-3, 12V	10
STL43R24B	STL43R24BP	PL-3 connection, 12-24V	10
STL43RMB	STL43RMBP	Weathertight connection, 12V	10
STL53RCB	STL53RCBP	Clear lens, red diode, PL-3, 12V	10
YELLOW PARKING/TURN SIGNAL - 10 DIODES			
STL43AB	STL43ABP	PL-3 connection, 12V	10
STL43A24B	STL43A24BP	PL-3 connection, 12-24V	10
STL43AKB	STL43AKBP	Kit with A45GB & A47PB, PL-3, 12V	10
ACCESSORIES			
A45GB	A45GBP	Grommet	50
A45PB	A45PBP	Pigtail, 3-wire PL-3	100
A47PB	A47PBP	Right angle pigtail, 3-wire PL-3	100
A45PMB	A45PMBP	Weathertight pigtail	100
AL45PWTB	AL45PWTBP	Weathertight to PL-3 adaptor	50
BK45BB	BK45BBP	Black steel bracket	10
A45BB	A45BBP	Black plastic flange	100
A45SB	A45SBP	Stainless steel mounting flange	20
A45CGB	A45CGBP	Chrome grommet cover	20
RETAIL			
STL43RK	Retail Ready	12V kit with A45GB & A47PB, clam	6



HOLE CUT-OUT: 4.5"

FMVSS	Red S T I P2; Yellow I6 P
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	Red: 12.8VDC - .360A Stop/Turn, .030A Tail
	Yellow: 12.8VDC - .310A Turn, .046A Parking
WT/DIMS	.265 lbs. / 4.313" x 4.313" x 1.938"
WARRANTY	Lifetime LED Warranty

STL42 SERIES

4" Round Sealed LED Lights with Mounting Flange

- Sonically sealed, waterproof
- Flange mount for security, theft reduction
- Available with standard PL-3 or optional weathertight connection

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED STOP/TURN/TAIL LIGHT - 10 DIODES			
STL42RB	STL42RBP	Black flange, PL-3	10
STL42RMB	STL42RMBP	Black flange, weathertight	10
YELLOW PARKING/TURN SIGNAL - 10 DIODES			
STL42AB	STL42ABP	Black flange, PL-3	10
STL42AMB	STL42AMBP	Black flange, weathertight	10
ACCESSORIES			
A45PB	A45PBP	Pigtail, 3-wire PL-3	100
A47PB	A47PBP	Right angle pigtail, 3-wire PL-3	100
A45PMB	A45PMBP	Weathertight pigtail	100
AL45PWTB	AL45PWTBP	Weathertight to PL-3 adaptor	50
BK45BB	BK45BBP	Black steel bracket	10
A42FCB	A42FCBP	Chrome flange cover	100
A5TRSSB	A5TRSSBP	Stainless steel trim ring	100
A42GB	A42GBP	Mounting gasket, black	100
RETAIL			
STL42RS	Retail Ready	Light only, clam	6

STL42RB

STL42AB

A42GB



HOLE CUT-OUT: 4.5"

FMVSS	Red S T I P2; Yellow I6 P	
MATERIALS	Polycarbonate lens and housing	
VOLT/AMP	Red:	12.8VDC - .413 Stop/Turn, .026A Tail
	Yellow:	12.8VDC - .310 Turn, .046A Parking
WT/DIMS	.617 lbs. / 5.5" x 5.5" x 1.938"	
WARRANTY	Lifetime LED Warranty	

STL43 REFLEX FLANGE SERIES

4" Round Sealed LED Lights with Reflex Mounting Flange

STL43RBX

STL43ABX

- Sonically sealed, waterproof
- Flange mount for security, theft reduction
- Accepts standard PL-3 connector
- Reflex flange meets SAE A for reflector

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED STOP/TURN/TAIL LIGHT - 10 DIODES			
STL43RBX	STL43RBXP	Red reflex flange, gasket, PL-3	10
STL43RBHX	STL43RBHXP	Red reflex flange, hard wire, gasket	10
YELLOW PARKING/TURN SIGNAL - 10 DIODES			
STL43ABX	STL43ABXP	Yellow reflex flange, gasket, PL-3	10
ACCESSORIES			
A45PB	A45PBP	Pigtail, 3-wire PL-3	100
A47PB	A47PBP	Right angle pigtail, 3-wire PL-3	100
RETAIL			
STL43ABXS	Retail Ready	Yellow light only, clam	6
STL43RBXS		Red light only, clam	6



HOLE CUT-OUT: 4.5"

FMVSS	Red S T I; Yellow I6 P; Reflex A
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	Red: 12.8VDC - .413 Stop/Turn, .026A Tail
	Yellow: 12.8VDC - .310 Turn, .046A Parking
WT/DIMS	.397 lbs. / 5.75" x 5.75" x 1.625"
WARRANTY	Lifetime LED Warranty

STL13 GROMMET MOUNT SERIES

FLEET Count™ 4" Round Sealed LED Stop/Turn/Tail Lights

- Sonically sealed, waterproof
- Available with standard PL-3, male pin, weathertight or hard wired connections
- Retail kit includes grommet and plug

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED STOP/TURN/TAIL - 7 DIODES			
STL13RB	STL13RBP	PL-3 connection	10
STL13R1224B	STL13R1224BP	PL-3 connection, 12/24V	10
STL13RMB	STL13RMBP	Weathertight connection	10
STL13RGB	STL13RGBP	Male pin connection	10
STL13RH1B	STL13RH1BP	Hard wired, PL-3 female plug	10
STL13RH3B	STL13RH3BP	Hard wired, .180 male bullets	10
STL13RHBB	STL13RHBBP	Hard wired	10
STL13RLVB	STL13RLVBP	PL-3 connection, low-voltage cut-off at 9V	10
STL13RMB10GK	STL13RMB10GKP	Kit: STL13RMB and A45GB grommet	10
STL13RKB	STL13RKBP	Kit: STL13RB, with A45GB grommet and A45PB plug, PL-3 connection	10
YELLOW PARKING/TURN SIGNAL - 7 DIODES			
STL13AB	STL13ABP	PL-3 connection	10
ACCESSORIES			
A45GB	A45GBP	Grommet	50
A45PB	A45PBP	Pigtail, 3-wire PL-3	100
A47PB	A47PBP	Right angle pigtail, 3-wire PL-3	100
A45PMB	A45PMBP	Weathertight pigtail	100
AL45PWTB	AL45PWTBP	Weathertight to PL-3 adaptor	50
BK45BB	BK45BBP	Black steel bracket	10
A45BB	A45BBP	Black plastic flange	100
A45SB	A45SBP	Stainless steel flange	20
A45CGB	A45CGBP	Chrome grommet cover	20
RETAIL			
STL13RK		Kit with A45GB & A47PB, clam	6
STL13RS		Light only, clam	6

FMVSS	Red: S T I; Yellow: I6 P
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - .234A Stop/Turn, .033A Tail
WT/DIMS	STL13 grommet mount: .265 lbs. / 4.31" x 4.31" x 1.81"
WARRANTY	Lifetime LED Warranty

STL13RB

STL13AB



HOLE CUT-OUT: 4.5"

STL13RGB male pin connection

STL13 FLANGE MOUNT SERIES

FLEET Count™ 4" Round Sealed LED Stop/Turn/Tail Lights

STL13RFB



- Sonically sealed, waterproof
- Available with standard PL-3 and weathertight connections

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED STOP/TURN/TAIL - 7 DIODES			
STL13RFB	STL13RFBP	Flange, PL-3	10
STL13RFMB	STL13RFMBP	Flange, weathertight	10
ACCESSORIES			
A45PB	A45PBP	Pigtail, 3-wire PL-3	100
A47PB	A47PBP	Right angle pigtail, 3-wire PL-3	100
A45PMB	A45PMBP	Weathertight pigtail	100
AL45PWTB	AL45PWTBP	Weathertight to PL-3 adaptor	50
RETAIL			
STL13RFS	Retail Ready	Flange mount light only, clam	6

FMVSS	S T I
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - .234A Stop/Turn, .033A Tail
WT/DIMS	STL13 flange mount: .275 lbs. / 5.5" x 5.5" x 1.938"
WARRANTY	Lifetime LED Warranty

STL13RFHXB SERIES

4" Round Surface Mount Sealed LED Lights with Reflex



STL13RFHXB



- Sonically sealed, waterproof
- Multi-function: stop/turn/tail with reflex flange - all in one light
- FMVSS compliant for under 80" applications
- Surface mount
- Hard wired

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED STOP/TURN/TAIL LIGHT - 7 DIODES			
STL13RFHXB	STL13RFHXBP	Hard wired, with reflex	10
ACCESSORIES			
A42GB	A42GBP	Mounting gasket, black	100

FMVSS	S T I A
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - .234A Stop/Turn, .033A Tail
WT/DIMS	.38 lbs. / 5.625" x 5.625" x .75"
WARRANTY	Lifetime LED Warranty

STL413 SERIES

FLEET Count™ 4" Round Sealed LED Lights

- Sonically sealed, waterproof
- Mount in any 360˚ position
- Available in standard PL-3 or optional weathertight connection

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED STOP/TURN/TAIL LIGHT - 4 DIODES			
STL413RB	STL413RBP	PL-3 connection	10
STL413RMB	STL413RMBP	Weathertight connection	10
ACCESSORIES			
A45GB	A45GBP	Grommet	50
A45PB	A45PBP	Straight pigtail, 3-wire PL-3	100
A47PB	A47PBP	Right angle pigtail, 3-wire PL-3	100
A45PMB	A45PMBP	Weathertight pigtail, 3-wire	50
AL45PWTB	AL45PWTBP	Weathertight pigtail to PL-3	50
A45BB	A45BBP	Black mounting flange	100
A45SB	A45SBP	Stainless steel mounting flange	20
BK45BB	BK45BBP	Black steel bracket	10
A45CGB	A45CGBP	Chrome grommet cover	20

FMVSS	S2 T2 I6
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - .160A Stop/Turn, .008A Tail
WT/DIMS	.265 lbs. / 4.313" x 4.313" x 1.625"
WARRANTY	Lifetime LED Warranty

STL413RB



HOLE CUT-OUT: 4.5"

STL413RFHXB SERIES

FLEET Count™ 4" Round Sealed LED Light with Reflex Flange

- Sonically sealed, waterproof
- FMVSS compliant for over/under 80" applications
- Surface mount, hard wired

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED STOP/TURN/TAIL LIGHT - 4 DIODES			
STL413RFHXB	STL413RFHXBP	Hard wired, with reflex	10

FMVSS	S2 T2 I6 A
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - .160A Stop/Turn, .008A Tail
WT/DIMS	.25 lbs. / 5.625 x 5.625" x 0.75"
WARRANTY	Lifetime LED Warranty

STL413RFHXB

ONE™ LED LAMPS

STL003 SERIES

ONE™ LED 4" Round Sealed Lights

- Sonically sealed, waterproof
- Mount in any 360˚ position
- Available in grommet and flange mount models with PL-3 and weathertight connections

STL003RB

STL003AB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED STOP/TURN/TAIL LIGHT - 1 DIODE			
STL003RB	STL003RBP	PL-3 connection	50
STL003R1224B	STL003R1224BP	PL-3 connction, 12V/24V	50
STL003RMB	STL003RMBP	Weathertight connection	50
STL003RFB	STL003RFBP	Flange mount, PL-3 connection	10
STL003RFLB	STL003RFLBP	Flange mount, locking PL-3 connection	10
STL003RFMB	STL003RFMBP	Flange mount, weathertight connection	10
YELLOW PARKING/TURN SIGNAL - 1 DIODE			
STL003AB	STL003ABP	PL-3 connection	50
STL003A1224B	STL003A1224BP	PL-3 connection, 12V/24V	50
ACCESSORIES			
A45GB	A45GBP	PVC grommet, flush mount	50
A45PB	A45PBP	Straight pigtail, 3-wire PL-3	100
A47PB	A47PBP	Right angle pigtail, 3-wire PL-3	100
AL45PWTB	AL45PWTBP	Weathertight pigtail, plug to female PL-3	50
A45PMB	A45PMBP	Weathertight 3-wire pigtail, plug to bare wire	50
For more details on mounting and wiring accessories, see Accessories section at back of catalog.			
RETAIL			
STL003RK	Retail Ready	Kit with grommet and pigtail, clam	6
STL003RS		Light only, clam	6

STL003RFLB

FMVSS	Red: S T I, Yellow: I P
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - .25A Stop/Turn, .007A Tail 24.0VDC
WT/DIMS	Grommet mount: .35 lbs. / 4.313" x 4.313" (depth varies) Flange mount: .275 lbs. / 5.5" x 5.5" (depth varies)
WARRANTY	Lifetime LED Warranty

Locking PL-3 connection



Grommet mount, PL-3

STL23 SERIES

Miro-Flex™ 4" Round Sealed LED Lights

- Sonically sealed, waterproof
- Mount in any 360 degree position
- Accepts standard PL-3 plugs
- Available in 12V and 24V models

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED STOP/TURN/TAIL - 12 DIODES			
STL23RB	STL23RBP	PL-3 connection, 12V	10
STL23CCRB	STL23CCRBP	Clear lens, red reflector, PL-3, 12V	10
STL23R24B	STL23R24BP	PL-3 connection, 24V	10
YELLOW PARKING/TURN SIGNAL - 16 DIODES			
STL23AB	STL23ABP	PL-3 connection, 12V	10
STL23A24B	STL23A24BP	PL-3 connection, 24V	10
ACCESSORIES			
A45GB	A45GBP	Grommet	50
A45PB	A45PBP	Pigtail, 3-wire PL-3	100
A47PB	A47PBP	Right angle pigtail, 3-wire PL-3	100
BK45BB	BK45BBP	Black steel bracket	10
A45BB	A45BBP	Black plastic flange	100
A45SB	A45SBP	Stainless steel flange	20
A45CGB	A45CGBP	Chrome grommet cover	20

STL23RB

STL23CCRB

STL23AB

FMVSS	Red S T I; Yellow I P
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	Red: 12.8VDC - .208 Stop/Turn, .013A Tail 24.0VDC - .171 Stop/Turn, .061A Tail Yellow: 12.8VDC - .310 Turn, .046A Parking 24.0VDC - .171 Stop/Turn, .061A Tail
WT/DIMS	.265 lbs. / 4.313" x 4.313" x 1.938"
WARRANTY	Lifetime LED Warranty



HOLE CUT-OUT: 4.5"

HyperX®

STL543 SERIES

HyperX® 4" Round Sealed LED Stop/Turn/Tail Light

STL543RB

- Sonically sealed, waterproof
- Mount in any 360 degree position
- Accepts standard PL-3 plugs
- 12 diodes and contemporary, automotive style optics

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED STOP/TURN/TAIL - 12 DIODES			
STL543RB	STL543RBP	PL-3 connection	10
ACCESSORIES			
A45GB	A45GBP	Grommet	50
A45PB	A45PBP	Pigtail, 3-wire PL-3	100
A47PB	A47PBP	Right angle pigtail, 3-wire PL-3	100
BK45BB	BK45BBP	Black steel bracket	10
A45BB	A45BBP	Black plastic flange	100
A45SB	A45SBP	Stainless steel flange	20
A45CGB	A45CGBP	Chrome grommet cover	20



HOLE CUT-OUT: 4.5"

FMVSS	S T I
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - .208 Stop/Turn, .013A Tail
WT/DIMS	.265 lbs. / 4.313" x 4.313" x 1.938"
WARRANTY	Lifetime LED Warranty

STL55 SERIES

High LED Count 4" Round Sealed Lights for Recess Mount

- Sonically sealed, waterproof
- 21 LEDs for high diode count appearance
- Mount in any 360 degree position
- Accepts standard PL-3 plugs; red available with optional weathertight connection

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED STOP/TURN/TAIL - 21 DIODES			
STL55RB	STL55RBP	Grommet mount, PL-3 connection	10
STL55RMB	STL55RMBP	Flange mount, weathertight connection	10
STL55RFMB	STL55RFMBP	Flange mount, weathertight connection	10
YELLOW PARKING/TURN SIGNAL - 21 DIODES			
STL55AB	STL55ABP	Grommet mount, PL-3 connection	10
ACCESSORIES			
A45GB	A45GBP	Grommet	50
A45PB	A45PBP	Pigtail, 3-wire PL-3	100
A47PB	A47PBP	Right angle pigtail, 3-wire PL-3	100
A45PMB	A45PMBP	Weathertight pigtail	100
AL45PWTB	AL45PWTBP	Weathertight to PL-3 adaptor	50
BK45BB	BK45BBP	Black steel bracket	10
A45BB	A45BBP	Black plastic flange	100
A45SB	A45SBP	Stainless steel flange	20
A45CGB	A45CGBP	Chrome grommet cover	20

FMVSS	Red S T I; Yellow I6 P
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	Red: 12.8VDC - .208 Stop/Turn, .013A Tail Yellow: 12.8VDC - .310 Turn, .046A Parking
WT/DIMS	Grommet mount: .265 lbs. / 4.313" x 4.313" x 1.5" Flange mount: .265 lbs. / 5.5" x 5.5" x 1.5"
WARRANTY	Lifetime LED Warranty



STL55RB

STL55RFMB

STL55AB



HOLE CUT-OUT: 4.5"

HOLE CUT-OUT: 4.5"

STL602 SERIES

LightGuide™ LED 6" Stop/Turn/Tail Light



STL602RB



PATENTED TECHNOLOGY

- Central X-shaped feature illuminates for tail light function
- Surrounding diodes light for stop and turn functions
- Sonically sealed, waterproof
- Grommet mount
- Accepts industry standard PL-3 connector

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED STOP/TURN/TAIL LIGHT - 12 DIODES			
STL602RB	STL602RBP	PL-3 connection	10
ACCESSORIES			
A70GB	A70GBP	Grommet	50
A45PB	A45PBP	Pigtail, 3-wire	100
A47PB	A47PBP	Right angle pigtail, 3-wire	100
BK70BB	BK70BBP	Black steel bracket	10
A77S1B	A77S1BP	Gray, flat design steel bracket	50

FMVSS	S2 T2 I6
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - .421A Stop/Turn, .114A Tail
WT/DIMS	.375 lbs. / 6.5" x 2.28" x 1.80"
WARRANTY	Lifetime LED Warranty

STL111 GROMMET MOUNT SERIES

GloLight® 6" Sealed LED Lights

PATENTED TECHNOLOGY

- Sonically sealed, waterproof
- Mount in any 360 degree position
- Available in tinted and clear lens models
- Available with standard PL-3 or optional weathertight connection

STL111RB

STL111RCB


STL111AB

STL111ACB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED STOP/TURN/TAIL LIGHT - 22 DIODES			
STL111RB	STL111RBP	PL-3 connection	10
STL111R1224B	STL111R1224BP	PL-3 connection, 12/24V	10
STL111RMB	STL111RMBP	Weathertight	10
STL111RHB	STL111RHBP	Hard wired	10
STL111RCB	STL111RCBP	Clear lens, red diodes, PL-3	10
STL111RCMB	STL111RCMBP	Clear lens, red diodes, weathertight	10
YELLOW PARKING/TURN SIGNAL - 22 DIODES			
STL111AB	STL111ABP	PL-3	10
STL111ACB	STL111ACBP	Clear lens, yellow diodes, PL-3	10
ACCESSORIES			
A70GB	A70GBP	Grommet	50
A45PB	A45PBP	Pigtail, 3-wire	100
A47PB	A47PBP	Right angle pigtail, 3-wire	100
A45PMB	A45PMBP	Weathertight pigtail	100
AL45PWTB	AL45PWTBP	Weathertight to PL-3 adaptor	50
BK70BB	BK70BBP	Black steel bracket	10
A77S1B	A77S1BP	Gray, flat design steel bracket	50
RETAIL			
TLL112RK	Retail Ready	**Try Me** kit with (2) ea. STL111RB, A70GB and A47PB, clam	2

FMVSS	Red S2 T2 I6; Yellow I6 P
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	Red: 12.8VDC - .59A Stop/Turn, .295A Tail
	Yellow: 12.8VDC - .515A Turn, .27A Parking
WT/DIMS	.35 lbs. / 6.5" x 2.25" x 1.75"
WARRANTY	Lifetime LED Warranty

TLL112RK



HOLE CUT-OUT: 6.85" X 2.5" (1.25" R)

GloLight®

STL111 FLANGE MOUNT SERIES

GloLight® 6" Sealed LED Lights with Mounting Flange

STL111RFB

STL111RCFB

PATENTED TECHNOLOGY

- Sonically sealed, waterproof
- Recess flange mount for security, theft reduction
- Available in tinted and clear lens models
- Available with standard PL-3 or optional weathertight connection

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED STOP/TURN/TAIL LIGHT - 22 DIODES			
STL111RFB	STL111RFBP	PL-3 connection	10
STL111RFMB	STL111RFMBP	Weathertight connection	10
STL111RCFB	STL111RCFBP	Clear lens, red diodes, PL-3	10
STL111RCFMB	STL111RCFMBP	Clear lens, red diodes, weathertight	10
ACCESSORIES			
A45PB	A45PBP	Pigtail, 3-wire	100
A47PB	A47PBP	Right angle pigtail, 3-wire	100
A45PMB	A45PMBP	Weathertight pigtail	100
AL45PWTB	AL45PWTBP	Weathertight to PL-3 adaptor	50
BK70BB	BK70BBP	Black steel bracket	10
A77S1B	A77S1BP	Gray, flat design steel bracket	50
A111TRSSB	A111TRSSBP	Stainless steel trim ring	50

FMVSS	Red S2 T2 I6
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - .59 Stop/Turn, .295A Tail
WT/DIMS	.38 lbs. / 7.5" x 3.3" x 1.938"
WARRANTY	Lifetime LED Warranty



HOLE CUT-OUT: 6.85" X 2.5" (1.25" R)

STL178 SERIES

GloLight® 6" Sealed LED Stop/Turn/Tail Lights for Surface Mount

PATENTED TECHNOLOGY

- Sonically sealed, waterproof
- Mount in any 360 degree position
- Flange surface mount–no panel cut-out required
- Hard wired, with optional molded connectors
- Available in tinted and clear lens models

TAIL LIGHT

STOP/ TURN

STL178RB

STL178RCCFPB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED STOP/TURN/TAIL LIGHT - 22 DIODES			
STL178RB	STL178RBP	Hard wired	10
STL178RFPB	STL178RFPBP	Hard wired, female PL-3 plug	10
STL178RK1B	STL178RK1BP	Hard wired, EVA gasket	10
STL178RCCFPB	STL178RCCFPBP	Clear lens, red diodes, hard wired with female PL-3 connector	10
ACCESSORIES			
BK70BB	BK70BBP	Black steel bracket	10
A77S1B	A77S1BP	Gray, flat design steel bracket	50
A178TRSSB	A178TRSSBP	Stainless steel trim ring	50

FMVSS	S2 T2 I6
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - .59 Stop/Turn, .295A Tail
WT/DIMS	.38 lbs. / 7.5" x 3.3" x 1.1"
WARRANTY	Lifetime LED Warranty



HD500 SERIES

STL512 SERIES

HD500™ 6" Sealed LED Lights

- Sonically sealed, waterproof
- Mount in any 360˚ position
- Available in tinted and clear lens models



STL512RB

STL512RCB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED STOP/TURN/TAIL LIGHT - 18 DIODES			
STL512RB	STL512RBP	PL-3 connection	10
STL512RCB	STL512RCBP	Weathertight connection	10
ACCESSORIES			
A70GB	A70GBP	Grommet	50
A45PB	A45PBP	Pigtail, 3-wire	100
A47PB	A47PBP	Right angle pigtail, 3-wire	100
A77S1B	A77S1BP	Gray, flat design steel bracket	50
BK70BB	BK70BBP	Black steel bracket	10



FMVSS	S T I
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - .294A Stop/Turn, .024A Tail
WT/DIMS	.262 lbs. / 6.50" x 2.313" x 1.84"
WARRANTY	Lifetime LED Warranty

STL72/82 SERIES
6" Oval Sealed LED Lights

- Sonically sealed, waterproof
- Kits include grommet and plug
- Mount in any 360 degree position
- Available with standard PL-3 or optional weathertight connection

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED STOP/TURN/TAIL LIGHT - 10 DIODES			
STL72RB	STL72RBP	PL-3 connection	10
STL72R1224B	STL72R1224BP	PL-3 connection, 12V/24V	10
STL72RKB	STL72RKBP	Kit with A70GB, PL-3	10
STL74RBK	STL74RBKP	Kit with A70GB & A47PB, PL-3	50
STL74RKB	STL74RKBP	Kit with A70GB & A45PB, PL-3	10
STL72RMB	STL72RMBP	Weathertight connection	10
STL82RCB	STL82RCBP	Clear lens, red diodes, PL-3	10
YELLOW PARKING/TURN SIGNAL - 10 DIODES			
STL72AB	STL72ABP	PL-3	10
STL72AMB	STL72AMBP	Weathertight connection	10
STL72CAB	STL72CABP	Clear lens, amber diodes, PL-3	10
ACCESSORIES			
A70GB	A70GBP	Grommet	50
A45PB	A45PBP	Pigtail, 3-wire PL-3	100
A47PB	A47PBP	Right angle pigtail, 3-wire PL-3	100
A45PMB	A45PMBP	Weathertight pigtail	100
AL45PWTB	AL45PWTBP	Weathertight to PL-3 adaptor	50
BK70BB	BK70BBP	Black steel bracket	10
A77S1B	A77S1BP	Gray, flat design steel bracket	50
RETAIL			
STL72RK	Retail Ready	12V kit with A70GB & A47PB, clam	6
STL72RS		12V, clam	6

FMVSS	Red S2 T2 I6; Yellow I6 P
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	Red: 12.8VDC - .243A Stop/Turn, .046A Tail
	Yellow: 12.8VDC - .275A Turn, .042A Parking
WT/DIMS	.309 lbs. / 6.438" x 2.313" x 1.75"
WARRANTY	Lifetime LED Warranty

STL72RB

STL82RCB



STL72AB

STL72CAB



HOLE CUT-OUT: 6.85" X 2.5" (1.25" R)

STL78/88 SERIES

6" Oval Sealed LED Lights for Surface Mount

STL78RB

STL88RCB

STL78AB

- Sonically sealed, waterproof
- Mount in any 360 degree position
- Flange surface mount–no panel cut-out required
- Hard wired, with optional molded connectors

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED STOP/TURN/TAIL LIGHT - 10 DIODES			
STL78RB	STL78RBP	Hard wired	10
STL78RPG	STL78RPGP	.180 male bullets	10
STL78REZB	STL78REZBP	3-way female PL-3 plug	10
STL78RLPB	STL78RLPBP	Low profile 9/16" thick, female PL-3 plug, gasket included	10
STL88RCB	STL88RCBP	Clear lens, red diodes, hard wired	10
STL88RCPG	STL88RCPGP	Clear lens, red diodes, 3-way female PL-3 plug	10
STL88RC1PG	STL88RC1PGP	Clear lens, red diodes, hard wired .180 male bullets	10
STL88RCBPG	STL88RCBPBP	Clear lens, red diodes, hard wired .180 female bullets	10
YELLOW PARKING/TURN SIGNAL - 10 DIODES			
STL78AB	STL78ABP	Hard wired	10
ACCESSORIES			
A78CB1	A78CB1P	Chrome flange cover	25
A78RXB	A78RXBP	Red reflex flange cover & gasket	25
RETAIL			
STL78RK	Retail Ready	Single light, clam	6



FMVSS	Red S2 T2 I6 P3; Yellow I6 P
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	Red: 12.8VDC - .243A Stop/Turn, .046A Tail
	Yellow: 12.8VDC - .275A Turn, .042A Parking
WT/DIMS	STL78/88:.265 lbs. / 7.563" x 3.313" x 0.750"
	STL78RLPB: .260 lbs. / 7.563" x 3.313" x .563"
WARRANTY	Lifetime LED Warranty

STL12 SERIES

FLEET Count™ 6" Oval Sealed LED Stop/Turn/Tail Lights

- Sonically sealed, waterproof
- Available with standard PL-3 or optional weathertight connection
- Retail kit includes light, grommet and plug

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED STOP/TURN/TAIL - 6 DIODES			
STL12RB	STL12RBP	PL-3 connection	10
STL12R1224B	STL12R1224BP	PL-3 connection, 12/24V	10
STL12RMB	STL12RMBP	Weathertight connection	10
STL12RKB	STL12RKBP	Kit: STL12RB, A45PB, & A70GB	10
STL12RK2B	STL12RK2BP	Kit: STL12RB, A45PB, & A60GB	10
STL12RK3B	STL12RK3BP	Kit: STL12RB, A70GB	10
STL12RK4B	STL12RK4BP	Kit: STL12RB, A70GB, .156 female bullets	10
STL12RLVB	STL12RLVBP	PL-3 connection, low voltage cuttoff at 9V	10
STL12RCB	STL12RCBP	Clear lens, red diodes, PL-3 connection	10
STL12RCKB	STL12RCKBP	Clear lens, red diodes kit: STL12RCB, A45PB, A70GB	10
YELLOW PARKING/TURN SIGNAL - 6 DIODES			
STL12AB	STL12ABP	PL-3 connection	10
ACCESSORIES			
A70GB	A70GBP	Grommet	50
A45PB	A45PBP	Pigtail, 3-wire PL-3	100
A47PB	A47PBP	Right angle pigtail, 3-wire PL-3	100
A45PMB	A45PMBP	Weathertight pigtail	100
AL45PWTB	AL45PWTBP	Weathertight to PL-3 adaptor	50
BK70BB	BK70BBP	Black steel bracket	10
A77S1B	A77S1BP	Gray, flat design steel bracket	50
A78CB1	A78CB1P	Chrome flange cover	25
A78RXB	A78RXBP	Red reflex flange cover & gasket	25
RETAIL			
STL12RK	Retail Ready	Kit with A70GB & A47PB, clam	6
STL12RS		Light only, clam	6
TLL12RK		Kit with (2) each STL12RB, A70GB & A45PB, clam	2

FMVSS	Red: S T I; Yellow: I6 P
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - .161A Stop/Turn, .007A Tail
WT/DIMS	.375 lbs. / 6.5" x 2.25" x 1.75"
WARRANTY	Lifetime LED Warranty

STL12RB



STL12AB



STL12RCB

TLL12RK



HOLE CUT-OUT: 6.85" X 2.5" (1.25" R)

STL73 SERIES

FLEET Count™ 6" Oval Sealed LED Stop/Turn/Tail Lights

STL73RB



STL73RCB

A78CB1

- Sonically sealed, waterproof
- Flange surface mount is hard wired requiring no panel cut-out; includes ground

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED STOP/TURN/TAIL - 6 DIODES			
STL73RB	STL73RBP	Flange surface mount, hard wired	10
STL73RKB	STL73RKBP	Light with A73GB gasket	100
STL73REZB	STL73REZBP	Flange surface mount, hard wired with PL-3 female plug	10
STL73RCB	STL73RCBP	Clear lens, red diodes, flange surface mount, hard wired	10
ACCESSORIES			
BK70BB	BK70BBP	Black steel bracket	10
A77S1B	A77S1BP	Gray, flat design steel bracket	50
A78CB1	A78CB1P	Chrome flange cover	25
A78RXB	A78RXBP	Red reflex flange cover & gasket	25
RETAIL			
STL73RK	Retail Ready	Kit with STL73RB and A78CB1, clam	6



FMVSS	S T I
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - .161A Stop/Turn, .007A Tail
WT/DIMS	.287 lbs. / 7.563" x 3.263" x 0.75"
WARRANTY	Lifetime LED Warranty

STL412 SERIES

FLEET Count™ 6" Sealed LED Lights

- Sonically sealed, waterproof
- Mount in any 360˚ position
- Accepts standard PL-3 connector

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED STOP/TURN/TAIL LIGHT - 4 DIODES			
STL412RB	STL412RBP	PL-3 connection	10
ACCESSORIES			
A70GB	A70GBP	Grommet	50
A45PB	A45PBP	Pigtail, 3-wire	100
A47PB	A47PBP	Right angle pigtail, 3-wire	100
BK70BB	BK70BBP	Black steel bracket	10
A77S1B	A77S1BP	Gray, flat design steel bracket	50

FMVSS	S T I
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - .161A Stop/Turn, .007A Tail
WT/DIMS	.375 lbs. / 6.438" x 2.313" x 1.75"
WARRANTY	Lifetime LED Warranty



STL412RB



ONE™ LED LAMPS

STL002 SERIES

ONE™ LED 6" Sealed Lights

- Sonically sealed, waterproof
- Mount in any 360 degree position
- Available in grommet and flange mount models

STL002RB

STL002RFB

STL002AB

TLL002RK

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED STOP/TURN/TAIL LIGHT - 1 DIODE			
STL002RB	STL002RBP	PL-3 connection	50
STL002RK2B	STL002RK2BP	Kit with A60GB and A45PB, PL-3	10
STL002RMB	STL002RMBP	Weathertight connection	50
STL002RFB	STL002RFBP	Flange mount, PL-3 connection	10
YELLOW PARKING/TURN SIGNAL - 1 DIODE			
STL002AB	STL002ABP	PL-3 connection	50
ACCESSORIES			
A70GB	A70GBP	Grommet	50
A45PB	A45PBP	Pigtail, 3-wire PL-3	100
A47PB	A47PBP	Right angle pigtail, 3-wire PL-3	100
A45PMB	A45PMBP	Weathertight pigtail	100
AL45PWTB	AL45PWTBP	Weathertight to PL-3 adaptor	50
BK70BB	BK70BBP	Black steel bracket	10
A77S1B	A77S1BP	Gray, flat design steel bracket	50
RETAIL			
STL002RK	Retail Ready	Kit with grommet and plug, clam	6
STL002RS		Grommet mount light only, clam	6
TLL002RK	Set with (2) each STL002RB, A70GB and A47PB, clam		2

FMVSS	Red: S2 T2 I6, Yellow: I6 P
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - .25A Stop/Turn, .007A Tail
WT/DIMS	Grommet mount: .262 lbs. / 6.50" x 2.313" x 1.875"
	Flange mount: .262 lbs. / 7.563" x 3.313" x 1.125"
WARRANTY	Lifetime LED Warranty



HOLE CUT-OUT: 6.85" x 2.5" (1.25" R)



NO PANEL CUT-OUT REQUIRED

STL22 SERIES

Miro-Flex™ 6" Oval Sealed LED Lights

- Sonically sealed, waterproof
- Mount in any 360 degree position
- Accepts standard PL-3 plugs
- Available with tinted or clear lens and chrome or tinted reflector

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED STOP/TURN/TAIL - 12 DIODES			
STL22RB	STL22RBP	PL-3 connection	10
STL22RBH	STL22RBHP	Hard wired	10
STL22CCRB	STL22CCRBP	Clear lens, red reflector, PL-3	10
STL22RCB	STL22RCBP	Clear lens, PL-3	10
YELLOW PARKING/TURN SIGNAL - 16 DIODES			
STL22AB	STL22ABP	PL-3 connection	10
STL22CCAB	STL22CCABP	Clear lens, yellow reflector, PL-3	10
ACCESSORIES			
A70GB	A70GBP	Grommet	50
A45PB	A45PBP	Pigtail, 3-wire PL-3	100
A47PB	A47PBP	Right angle pigtail, 3-wire PL-3	100
BK70BB	BK70BBP	Black steel bracket	10
A77S1B	A77S1BP	Gray, flat design steel bracket	50

FMVSS	Red S T I; Yellow I P
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	Red: 12.8VDC - .161 Stop/Turn, .009A Tail
	Yellow: 12.8VDC - .181 Turn, .023A Parking
WT/DIMS	.397 lbs. / 6.5" x 2.313" x 2.188"
WARRANTY	Lifetime LED Warranty



STL22RB

STL22CCRB



STL22RCB

STL22AB

STL22CCAB



HOLE CUT-OUT:
6.85" X 2.5" (1.25" R)

HyperX®

STL572 SERIES

HyperX® 6" Oval Sealed LED Lights

- Sonically sealed, waterproof
- Accepts standard PL-3 plugs

STL572RB

STL572AB



HOLE CUT-OUT:
6.85" X 2.5" (1.25" R)

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED STOP/TURN/TAIL - 12 DIODES			
STL572RB	STL572RBP	PL-3 connection	10
YELLOW PARKING/TURN SIGNAL - 12 DIODES			
STL572AB	STL572ABP	PL-3 connection	10

FMVSS	Red S T I; Yellow I P
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	Red: 12.8VDC - .174 Stop/Turn, .007A Tail
	Yellow: 12.8VDC - .261 Turn, .013A Parking
WT/DIMS	.331 lb. / 6.438" x 2.313" x 1.75"
WARRANTY	Lifetime LED Warranty

Optronics LED

STL70 SERIES

High Diode Count 6" Oval Sealed LED Lights

- Sonically sealed, waterproof
- 48-56 LEDs for high diode count appearance
- Accepts standard PL-3 plugs

HIGH L.E.D COUNT

STL70RB

STL70AB





HOLE CUT-OUT: 6.85" X 2.5" (1.25" R)

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED STOP/TURN/TAIL - 48 DIODES			
STL70RB	STL70RBP	PL-3 connection	10
YELLOW PARKING/TURN SIGNAL - 56 DIODES			
STL70AB	STL70ABP	PL-3 connection	10

FMVSS	Red S T I P2; Yellow I P2 P
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	Red: 12.8VDC - .362 Stop/Turn, .013A Tail
	Yellow: 12.8VDC - .400 Turn, .046A Parking
WT/DIMS	.353 lbs. / 6.5" x 2.25" x 1.125"
WARRANTY	Lifetime LED Warranty

STL572 & STL70 ACCESSORIES			
A70GB	A70GBP	Grommet	50
A45PB	A45PBP	Pigtail, 3-wire PL-3	100
A47PB	A47PBP	Right angle pigtail, 3-wire PL-3	100
BK70BB	BK70BBP	Black steel bracket	10
A77S1B	A77S1BP	Gray, flat design steel bracket	50

STL175 SERIES

GloLight® 6" Oval Sealed LED E Rated Mid-Ship Turn Signal and Intermediate Marker Light

PATENTED TECHNOLOGY

- Sonically sealed, waterproof
- SAE "E" compliant–meets California requirements for mid-ship turn signal on vehicles 30 feet or longer
- Weathertight connection standard

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
E RATED - 10 DIODES			
STL175AMFB	STL175AMFBP	Weathertight connection	10
ACCESSORIES			
A45PMB	A45PMBP	Weathertight pigtail	100
AL45PWTB	AL45PWTBP	Weathertight to PL-3 adaptor	50
BK70BB	BK70BBP	Black steel bracket	10
A77S1B	A77S1BP	Gray, flat design steel bracket	50
A7TRSSB	A7TRSSBP	Stainless steel flange cover	20



Marker

STL175AMFB Turn

FMVSS	E P2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - .59 Stop/Turn, .11A Marker
WT/DIMS	.35 lbs. / 7.875" x 3.33" x 2.52"
WARRANTY	Lifetime LED Warranty



STL71/75 SERIES

6" Oval Sealed LED E Rated Mid-Ship Turn Signal and Intermediate Marker Light



STL71AMB



HOLE CUT-OUT: 6.85" X 2.5" (1.25" R)

- Sonically sealed, waterproof
- SAE "E" compliant–meets California requirements for mid-ship turn signal on vehicles 30 feet or longer
- Weathertight connection standard

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
E RATED - 10 DIODES			
STL71AMB	STL71AMBP	Weathertight connection	10
STL71AKMB	STL71AKMBP	Kit: STL71AMB, A70GB	10
STL75AMFB	STL75AMFBP	Flange, weathertight connection	10
ACCESSORIES			
A70GB	A70GBP	Grommet	50
A45PMB	A45PMBP	Weathertight pigtail	100
AL45PWTB	AL45PWTBP	Weathertight to PL-3 adaptor	50
BK70BB	BK70BBP	Black steel bracket	10
A77S1B	A77S1BP	Gray, flat design steel bracket	50
A7TRSSB	A7TRSSBP	Stainless steel flange cover	20

STL75AMFB



HOLE CUT-OUT: 6.85" X 2.5" (1.25" R)

FMVSS	E P2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - .201A Turn, .054 Marker
WT/DIMS	Grommet Mount: .309 lbs. / 6.5" x 2.375" x 2.5"
	Flange Mount: .309 lbs. / 7.875" x 3.313" x 2.5"
WARRANTY	Lifetime LED Warranty

STL75 SERIES

6" Oval Sealed LED E2 Rated Mid-Ship Turn Signal and Intermediate Marker Light

- Sonically sealed, waterproof
- "E2" rated for vehicles less than 30 feet in length
- Available with standard PL-3 or optional weathertight connection

STL75AB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
E2 RATED - 9 DIODES			
STL75AB	STL75ABP	PL-3 connection	10
STL75AMB	STL75AMBP	Weathertight connection	10
ACCESSORIES			
A70GB	A70GBP	Grommet	50
A45PB	A45PBP	Pigtail, 3-wire PL-3	100
A47PB	A47PBP	Right angle pigtail, 3-wire PL-3	100
A45PMB	A45PMBP	Weathertight pigtail	100
AL45PWTB	AL45PWTBP	Weathertight to PL-3 adaptor	50
BK70BB	BK70BBP	Black steel bracket	10
A77S1B	A77S1BP	Gray, flat design steel bracket	50
RETAIL			
STL75AS	Retail Ready	Single light, clam	6



HOLE CUT-OUT: 6.85" X 2.5" (1.25" R)

FMVSS	A E2 P2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - .141A Turn, .060 Marker
WT/DIMS	PL-3 Connection: .309 lbs. / 6.5" x 2.313" x 2.75"
	Weathertight: .309 lbs. / 6.5" x 2.313" x 2.58"
WARRANTY	Lifetime LED Warranty

STL33 SERIES

Sealed Rectangular LED Stop/Turn/Tail Lights

STL33RB

- Sonically sealed, waterproof
- Accepts standard PL-3 plugs

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED STOP/TURN/TAIL - 12 DIODES			
STL33RB	STL33RBP	Grommet mount, PL-3 connection	10
STL34RB	STL34RBP	Kit: STL33RB, A33GB & A45PB	10
ACCESSORIES			
A33GB	A33GBP	Grommet	50
A45PB	A45PBP	Pigtail, 3-wire PL-3	100
A47PB	A47PBP	Right angle pigtail, 3-wire PL-3	100



STL33RB

HOLE CUT-OUT: 5.453" X 3.578" (1" R)

FMVSS	S2 T2 I6
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - .405 Stop/Turn, .038A Tail
WT/DIMS	.309 lbs. / 5.313” x 3.438” x 1.938”
WARRANTY	Lifetime LED Warranty

STL35 SERIES
Sealed Rectangular LED Lights

- Sonically sealed, waterproof
- Accepts standard PL-3 plugs
- Available in red and amber
- Miro-Flex™ combines smooth lens and faceted reflector design for a contemporary automotive appearance

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED STOP/TURN/TAIL - 16 DIODES			
STL35RB	STL35RBP	PL-3 connection	10
STL24RB	STL24RBP	PL-3 connection, 12-24V	10
STL35CCRB	STL35CCRBP	Clear lens, red diodes, PL-3 connection	10
YELLOW PARKING/TURN SIGNAL - 16 DIODES			
STL35AB	STL35ABP	PL-3 connection	10
STL24AB	STL24ABP	PL-3 connection, 12-24V	10
STL35ACB	STL35ACBP	Clear lens, yellow diodes, PL-3 connection	10
ACCESSORIES			
A33GB	A33GBP	Grommet	50
A45PB	A45PBP	Pigtail, 3-wire PL-3	100
A47PB	A47PBP	Right angle pigtail, 3-wire PL-3	100

FMVSS	STL35RB:	S2 T2 I6
	STL35AB:	I6 P
MATERIALS	Polycarbonate lens and housing	
VOLT/AMP	STL35RB:	12.8VDC - .301 Stop/Turn, .020A Tail
	STL35AB:	12.8VDC - .301 Turn, .020A Parking
WT/DIMS	.309 lbs. / 5.313" x 3.438" x 2.313"	
WARRANTY	Lifetime LED Warranty	



HOLE CUT-OUT: 5.453" X 3.578" (1" R)

STL35RB

STL35CCRB

STL35AB

STL35ACB

STL63 SERIES
Thinline LED Stop/Turn/Tail Lights



STL63RB

STL63CRB

- Sonically sealed, waterproof
- Low profile design–only 5/8" thick
- Surface mount on 14-1/8" centers
- Hard wired with separate ground wire
- Available with tinted or clear lens



BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED STOP/TURN/TAIL LIGHTS - 9 DIODES			
STL63RB	STL63RBP	Red	10
STL63CRB	STL63CRBP	Clear lens, red diodes	10

FMVSS	S T I
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - .350 Stop/Turn, .022A Tail
WT/DIMS	.275 lbs. / 15" x 1.625" x .75"
WARRANTY	Lifetime LED Warranty

STL69 SERIES

Thinline Sealed LED Stop/Turn/Tail Lights

- Sonically sealed, waterproof
- Low profile design–only 5/8" thick
- Surface mount on 14-1/8" centers; optional gasket
- STL69RRXB meets SAE S2T2I6 for over 80" wide vehicles and has built-in reflex meeting SAE A
- Hard wired with separate ground wire; available with optional molded plugs

STL69RB



STL69RCB

STL69RRXB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED STOP/TURN/TAIL LIGHTS - 11 DIODES			
STL69RB	STL69RBP	Red, hard wired	10
STL69RPG	STL69RPGP	Red, .180 molded bullets	10
STL69R2PG	STL69R2PGP	Red, .156 molded barrels	10
STL69RCB	STL69RCBP	Clear lens, red diodes	10
STL69CRPG	STL69CRPGP	Clear lens, red diodes, .180 male bullets	10
STL69RRXB	STL69RRXBP	Built-in reflex	10
STL69RRXBPG	STL69RRXBPGP	Red, hard wired, .156 female barrels	10
STL69RRXPG	STL69RRXPGP	Red, hard wired .180 male bullets	10
ACCESSORIES			
A69GB	A69GBP	Gasket	10
A69CB	A69CBP	Chrome base for STL69	10
A69RXCB	A69RXCBP	Chrome base for STL69RRXB	10
RETAIL			
STL69RS		STL69RB light only, clam	6
STL69RK	Retail Ready	STL69RB with A69CB, clam	6
STL69RRXCS		STL69RRXB with A69RXCB, clam	6



STL69RB/RCB



STL69RRXB





A69CB



A69RXCB

FMVSS	STL69:	S T I
	STL69RRXB:	S2 T2 I6 A
MATERIALS	Polycarbonate lens and housing	
VOLT/AMP	STL69:	.350A Stop, .022 Tail
	STL69RRXB:	.161A Stop, .013A Tail
WT/DIMS	STL69:	.441 lbs. / 15" x 1.375" x .625"
	STL69RRXB:	.445 lbs. / 15" x 1.625" x .625"
WARRANTY	Lifetime LED Warranty	

STL179 SERIES
GloLight® Streamline LED Light

STL179RB

PATENTED TECHNOLOGY

- Sonically sealed, waterproof
- Low profile design–only 1-3/8” high x 1” thick
- Surface mount on 16-1/8” centers
- Hard wired with separate ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED STOP/TURN/TAIL - 28 DIODES			
STL179RB	STL179RBP	Stop/turn/tail light	10
ACCESSORIES			
A79CB	A79CBP	Chrome mounting base	10

A79CB

FMVSS	S T I
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - .634 Stop/Turn, .445A Tail
WT/DIMS	.353 lbs. / 17” x 1.375” x 1”
WARRANTY	Lifetime LED Warranty



STL179RB



A79CB

STL79 SERIES
Streamline Sealed LED Lights

STL79RB/80RB

STL89RCB

- Sonically sealed, waterproof
- Low profile design–only 1-3/8” high x 1” thick
- Surface mount on 16-1/8” centers
- Available as stop/turn/tail lights and third brake lights
- Hard wired with separate ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED STOP/TURN/TAIL - 11 DIODES			
STL79RB	STL79RBP	Stop/turn/tail light, hard wired	10
STL79RPG	STL79RPGP	Stop/turn/tail light, .180 male bullets	10
STL80RB	STL80RBP	Third brake light, hard wired	10
STL89RCB	STL89RCBP	Clear lens stop/turn/tail light, hard wired	10
ACCESSORIES			
A79CB	A79CBP	Chrome mounting base	10
RETAIL			
STL79RS	Retail Ready	Stop/turn/tail light, clam	6

FMVSS	STL79/89:	S T I
	STL80:	U
MATERIALS	Polycarbonate lens and housing	
VOLT/AMP	STL79/89:	12.8VDC - .350 Stop/Turn, .022A Tail
	STL80:	12.8VDC - .216 Stop
WT/DIMS	.353 lbs. / 17” x 1.375” x 1”	
WARRANTY	Lifetime LED Warranty	



STL76 SERIES

Thinline Sealed LED Stop/Turn/Tail Light for Over 80" Wide Applications



STL76RB

PATENTED TECHNOLOGY

- Replaceable, snap-on red lens
- Clear lens sonically sealed to housing making light completely waterproof
- Surface mount on 12-7/8" centers
- Meets SAE S2T2I6 for over 80" wide vehicles
- Hard wired with separate ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED STOP/TURN/TAIL LIGHT - 11 DIODES			
STL76RB	STL76RBP	Stop/turn/tail light	10

FMVSS	S2 T2 I6
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8V / .275A Stop, .022A Tail
WT/DIMS	.529 lbs. / 13.26" x 2.13" x 1.42"
WARRANTY	Lifetime LED Warranty



STL59 SERIES

Thinline Sealed LED Stop/Turn/Tail Lights

- Sonically sealed, waterproof
- Low profile design–only 1/2" thick
- Surface mount on 11-3/4" centers
- Hard wired with separate ground wire



STL59RB



STL59RCB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED STOP/TURN/TAIL LIGHTS - 9 DIODES			
STL59RB	STL59RBP	Red, hard wired	10
STL59RCB	STL59RCBP	Clear lens, red, hard wired	10

FMVSS	S T I
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - .2A Stop, .01A Tail
WT/DIMS	.441 lbs. / 12.625" x 1" x .5"
WARRANTY	Lifetime LED Warranty



STL64 SERIES
Thinline Sealed LED Stop/Turn/Tail Lights

STL64RB

STL64RCB



- Sonically sealed, waterproof
- Low profile design–only 3/4" thick
- Surface mount on 19-5/8" centers
- Hard wired with separate ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED STOP/TURN/TAIL - 15 DIODES			
STL64RB	STL64RBP	Red, hard wired	10
STL64RCB	STL64RCBP	Clear lens, red diodes, hard wired	10
ACCESSORIES			
A64CRB	A64CRBP	Chrome bezel	50
A64BB	A64BBP	Black bezel	50

FMVSS	S2 T2 I6
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - .2A Stop, .01A Tail
WT/DIMS	.441 lbs. / 20.5" x 1" x .75"
WARRANTY	Lifetime LED Warranty

STL87 SERIES

Thinline Sealed LED Stop/Turn/Tail Lights

- Sonically sealed, waterproof
- Low profile design–only 5/8" thick
- Surface mount on 14-9/16" centers
- Hard wired with separate ground wire



STL87RCB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED STOP/TURN/TAIL LIGHTS - 11 DIODES			
STL87RCB	STL87RCBP	Clear lens, red diodes	10
STL87RCPG	STL87RCPGP	Clear lens, red diodes .180 male bullets	10

FMVSS	S2 T2 I6
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - .2A Stop, .01A Tail
WT/DIMS	.441 lbs. / 16.188" x 1.25" x .688"
WARRANTY	Lifetime LED Warranty



GloLight®

STL153 SERIES

GloLight® LED Dual Face Pedestal Mount Lights

STL153ARPBB

STL153ARDBB

PATENTED TECHNOLOGY

- 25 LEDs per side
- Ring illuminates for tail light function; inner LEDs light and ring brightens for brake/turn
- Includes built-in 3-LED yellow side marker with reflex
- Hard wired, includes separate ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	DUAL FACE RED	YELLOW - 25 DIODES	
STL153ARDBB	STL153ARDBBP	Driver side	10
STL153ARPBB	STL153ARPBBP	Passenger side	10

FMVSS	S2 T2 I6, I6 P, A P2
MATERIALS	Chrome plastic housing, acrylic lens
VOLT/AMP	12.8V / .360A Stop, .030A Tail
WT/DIMS	1.477 lbs. / 4.688" x 4.875" x 2.438"
WARRANTY	Lifetime LED Warranty



STL52/53 SERIES
LED Pedestal Mount Lights

- Lead wires exit through mounting post; separate ground wire
- 21 LEDs per side
- STL53 available in driver and passenger side models with built-in yellow side marker with reflex

STL52ARB

STL52ARB profile

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	DUAL FACE RED YELLOW - 42 DIODES		
STL52ARB	STL52ARBP	Round	10
STL53ARPB	STL53ARPBP	Square, passenger side	10
STL53ARDB	STL53ARDBP	Square, driver side	10
	RETAIL		
STL52ARS	Retail Ready	Round, clam	6

FMVSS	STL52:	S T I P
	STL53:	Tail S T I P, Side Marker A P2
MATERIALS	STL52:	Die cast housing, polycarbonate lens
	STL53:	Polycarbonate lens and housing
VOLT/AMP	STL52:	12.8VDC - .360 Stop/Turn, .030A Tail
	STL53:	12.8VDC - .750 Stop/Turn, .114A Tail
WT/DIMS	STL52:	1.477 lbs. / 4.25" x 4.25" x 1.938"
	STL53:	.882 lb. / 4.5" x 4.75" x 2.25"
WARRANTY	Lifetime LED Warranty	

STL53ARPB



STL52ARB



STL53ARDB/ARPB

GloLight®

STL190 SERIES

GloLight® 7" LED Transit Lights

STOP/ TURN

STL190RB

TAIL LIGHT

PATENTED TECHNOLOGY

- Sonically sealed, waterproof
- Surface mount light with mounting gasket
- Built-in reflector meets reflex requirement "A"
- Hard wired with separate ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED STOP/TURN/TAIL LIGHT - 32 DIODES			
STL190RB	STL190RBP	Stop/turn/tail light	5
STL190RPG	STL190RPGP	Stop/turn/tail light, amp plug	5
YELLOW PARKING/TURN SIGNAL - 32 DIODES			
STL190AB	STL190ABP	Parking/turn signal	5

FMVSS	Red S2 I6 T2 P2 A; Yellow I6 P2 A
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	Red: 12.8VDC - .340A Stop/Turn, .135A Tail
	Yellow: 12.8VDC - .410A Turn, .072A Parking
WT/DIMS	.970 lb. / 7" x 7" x 1.625"
WARRANTY	Lifetime LED Warranty

TURN

STL190AB



PARKING



STL90 SERIES
7" Round LED Transit Lights

- Sonically sealed, waterproof
- Surface mount light with mounting gasket
- Built in reflector meets reflex requirement "A"
- Hard wired with separate ground wire
- Available in 12V and 12-24V models

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED STOP/TURN/TAIL LIGHT - 31 DIODES			
STL90RB	STL90RBP	Stop/turn/tail light, 12V	5
STL90R24B	STL90R24BP	Stop/turn/tail light, 12-24V	5
YELLOW TURN SIGNAL - 31 DIODES			
STL90AB	STL90ABP	Parking/turn signal, 12V	5
STL90A24B	STL90A24BP	Parking/turn signal, 12-24V	5



STL90RB

FMVSS	Red S2 I6 T2 P2 A; Yellow I6 P2 A
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	Red: 12.8VDC - .243A Stop/Turn, .046A Tail
	Yellow: 12.8VDC - .275A Turn, .042A Parking
WT/DIMS	.970 lb. / 7" x 7" x 1.438"
WARRANTY	Lifetime LED Warranty



STL90AB





GloLight®

STL161 SERIES

GloLight® LED Combination Tail Lights

TAIL LIGHT

STOP/TURN/BACK-UP

STL161RB

PATENTED TECHNOLOGY

- Stud mount stop/turn/tail light with built-in back-up light and reflex
- 30-LED tail light; 6-LED back-up light
- Driver side light also includes 3-LED license light
- Hard wired; wire exits through back of housing
- Includes ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
GLOLIGHT® COMBINATION TAIL LIGHTS - 36 DIODES			
STL161RB	STL161RBP	Passenger side, 30-LED tail, 6-LED back-up	5
STL161RLB	STL161RLBP	Driver side with 3-LED license light	5

FMVSS	STL161RB: A I6 (2)R S2 (3)T STL161RLB: A I6 (2)R S2 (3)T L
MATERIALS	Acrylic lens, plastic housing
VOLT/AMP	12.8VDC - Tail .19A, Stop/Turn .30A, Back-up .21A
WT/DIMS	.882 lb. / 5.813" x 6.75" x 2.688"
WARRANTY	Lifetime LED Warranty



STL60/61 SERIES
LED Combination Tail Lights

- Stud mount stop/turn/tail lights with built-in back-up light and reflex
- Choose from Optronics® LED 52-diode and FLEET Count™ 15-diode tail lights
- Hard wired; wire exits through back of housing
- Includes ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
OPTRONICS® COMBINATION TAIL LIGHTS - 52 DIODES			
STL60RB	STL60RBP	Passenger side, 16-LED tail, 36-LED back-up	5
STL60RLB	STL60RLBP	Driver side with 5-LED license light	5
FLEET COUNT™ COMBINATION TAIL LIGHTS - 15 DIODES			
STL61RB	STL61RBP	Passenger side, 9-LED tail, 6-LED back-up	5
STL61RLB	STL61RLBP	Driver side with 3-LED license light	5

STL60RB

STL61RB

FMVSS	STL61RB:	S2 T2 I6 A (2)R
	STL61RLB:	S2 T2 I6 A (2)R L
MATERIALS	Acrylic lens, plastic housing	
VOLT/AMP	12.8VDC - Tail .015A, Stop/Turn .308A, Back-up .328A	
WT/DIMS	.882 lb. / 5.813" x 6.75" x 2.688"	
WARRANTY	Lifetime LED Warranty	



STL60RB



STL61RB

STL82/83 SERIES
LED Combination Tail Lights



STL82RB



STL83RB

- Low profile style fits standard footprint
- Meets requirements for over and under 80” wide trailers
- SMD LED technology for reliable, waterproof performance
- Stud mount lights mount on 2” centers
- Hard wired, with separate ground wire
- 7-function: stop, turn, tail, rear clearance, rear reflex, side marker and side reflex
- Driver side light also includes license illuminator

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
COMBINATION TAIL LIGHTS			
STL82RB	STL82RBP	Passenger side, 11 diodes	10
STL83RB	STL83RBP	Driver side, 14 diodes	10

FMVSS	Stop/Tail S2 T2 I6 A, Side Marker A PC, License L
MATERIALS	Acrylic lens and plastic housing
VOLT/AMP	12.8VDC - Stop/Turn .163A, Marker .095A, Tail/License .163A
WT/DIMS	.45 lb. / 5.25” x 4.5” x 1.75”
WARRANTY	Lifetime LED Warranty



STL82RB



STL83RB

STL108/109 SERIES
GloLight® LED Combination Tail Lights

PATENTED TECHNOLOGY
- Traditional style fits many applications
- Stud mount lights mount on 2” centers
- Hard wired, with separate ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
COMBINATION TAIL LIGHTS - 25 DIODES			
STL108RB	STL108RBP	Passenger side	10
STL109RB	STL109RBP	Driver side, 3-LED license light	10
RETAIL			
TLL190RK	Set: STL108RB, STL109RB, mounting hardware; **Try Me** package, clam	Retail Ready	2

TAIL LIGHT

STOP/TURN

STL108/109RB

FMVSS	Stop/Tail A I S T, Side Marker A P2, License L
MATERIALS	Acrylic lens, ABS housing
VOLT/AMP	12.8VDC - Stop/Turn .310A, Marker .230A
WT/DIMS	.970 lb. / 5.031” x 4.563” x 2.625”
WARRANTY	Lifetime LED Warranty

TLL190RK



STL38/39 SERIES
Waterproof LED Combination Tail Lights

- Traditional style fits many applications
- SMD LED technology for reliable, waterproof performance
- Stud mount lights mount on 2” centers
- Hard wired, with separate ground wire
- Available in bulk, polypack and retail packaging

STL39RB

STL38RB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
COMBINATION TAIL LIGHTS - 7 DIODES			
STL38RB	STL38RBP	Passenger side	10
STL39RB	STL39RBP	Driver side, 3-LED license light	10
RETAIL			
STL6RS		Passenger side, clam	6
STL7RS		Driver side with 3-LED license light, clam	6
TLL9RK		Kit: STL38RB, STL39RB, 25-ft harness, license plate bracket, mounting hardware, clam	2
TLL90RK		Set: STL38RB, STL39RB, mounting hardware, clam	2

Retail Ready

TLL9RK

TLL90RK

FMVSS	Stop/Tail A I S T, Side Marker A PC, License L
MATERIALS	Acrylic lens and plastic housing
VOLT/AMP	12.8VDC - Stop/Turn .19A, Marker .065A
WT/DIMS	.970 lb. / 5” x 4.5” x 2.688”
WARRANTY	Lifetime LED Warranty





STL8/9 SERIES
LED Combination Tail Lights

- Traditional style fits many applications
- Stud mount lights mount on 2” centers
- Hard wired, with separate ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
COMBINATION TAIL LIGHTS - 11 DIODES			
STL8RB	STL8RBP	Passenger side	10
STL8R3B	STL8R3BP	Passenger side, female PL-3 plug	10
STL8RGB	STL8RGBP	Passenger side, self-grounding	10
STL9RB	STL9RBP	Driver side, 3-LED license light	10
STL9R3B	STL9R3BP	Driver side, 3-LED license light, female PL-3 plug	10
STL9RGB	STL9RGBP	Driver side, 3-LED license light, self-grounding	10

STL8/9RB

FMVSS	Stop/Tail A I S T, Side Marker A P2, License L
MATERIALS	Acrylic lens and plastic housing
VOLT/AMP	12.8VDC - Stop/Turn .259A, Marker .062A
WT/DIMS	.970 lb. / 5.25” x 4.75” x 2.688”
WARRANTY	Lifetime LED Warranty



STL2/3 SERIES

LED Combination Tail Lights for Over 80" Applications



STL3RB

STL2RB

- Designed for over 80" wide applications
- Stud mount lights mount on 2" centers
- Hard wired, with separate ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
OVER 80 COMBINATION TAIL LIGHTS - 18 DIODES			
STL2RB	STL2RBP	Passenger side	10
STL2RGB	STL2RGBP	Passender side, self-grounding	10
STL3RB	STL3RBP	Driver side, license light	10
STL3RGB	STL3RGBP	Driver side, license light, self-grounding	10

FMVSS	Stop/Tail S2 T2 I6 A, Side Marker PC A, License L
MATERIALS	Acrylic lens and plastic housing
VOLT/AMP	12.8VDC - Stop/Turn .268A, Marker .059A
WT/DIMS	.970 lb. / 6.25" x 4.75" x 2.688"
WARRANTY	Lifetime LED Warranty





STL008/009 SERIES

ONE™ LED Combination Tail Lights

- Sealed, waterproof design
- Traditional style fits many applications
- Stud mount lights mount on 2” centers
- Hard wired with separate ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
COMBINATION TAIL LIGHTS - 1 DIODE			
STL008RB	STL008RBP	Passenger side	10
STL009RB	STL009RBP	Driver side	10
STL008RPG	STL008RPGP	Passenger side, .180 bullets	10
STL009RPG	STL009RPGP	Driver side, .180 bullets	10
RETAIL			
STL008RS	Passenger side	Retail Ready	6
STL009RS	Driver side with 3-LED license light		6
TLL008RK	Set: STL008RB, STL009RB, mounting hardware, clam		2

STL008RB

STL009RB

FMVSS	S T I A, P2 A, L
MATERIALS	Acrylic lens and plastic housing
VOLT/AMP	12.8VDC - Stop/Turn .25A, Marker .062A
WT/DIMS	.970 lb. / 5.063” x 4.563” x 2.875”
WARRANTY	Lifetime LED Warranty

TLL008RK



STL28/29 SERIES

Miro-Flex™ LED Combination Tail Lights

STL29RB

STL28RB

TLL29RK



- Chrome-plated, multi-faceted reflector paired with smooth lens offers unique automotive appearance
- Universal design fits many applications
- SMD LED technology for reliable, waterproof performance
- Stud mount lights mount on 2" centers
- Hard wired with separate ground wire
- STL28 is 6-function: stop, turn, tail, rear reflex, side marker and side reflex
- STL29 is 7-function: above plus license illuminator

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
COMBINATION TAIL LIGHTS - 15 DIODES			
STL28RB	STL28RBP	Passenger side	10
STL29RB	STL29RBP	Driver side, with 5-LED license light	10
Retail Ready		**RETAIL**	
TLL28RK		Set: STL28RB, STL29RB, mounting hardware; clam	2
TLL29RK		Kit: STL28RB, STL29RB, 25-ft harness, license plate bracket, mounting hardware; clam	2

FMVSS	STL28: Stop/Tail A I S T, Side Marker A P2
	STL29: Stop/Tail A I S T, Side Marker A P2, License L
MATERIALS	Acrylic lens and plastic housing
VOLT/AMP	STL28: 12.8VDC - .174A Stop/Turn, .054A Marker
	STL29: 12.8VDC - .174A Stop/Turn, .054A Marker
WT/DIMS	.750 lb. / 5.25" x 5" x 2.625"
WARRANTY	Lifetime LED Warranty

STL116/117 SERIES

GloLight® LED Low Profile Combination Tail Lights

PATENTED TECHNOLOGY

- PATENTED TECHNOLOGY
- Designed for marine trailer application
- Sealed, waterproof construction
- Universal mount
- Hard wired, with separate ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
COMBINATION TAIL LIGHTS - 28 DIODES			
STL116RB	STL116RBP	Passenger side	10
STL117RB	STL117RBP	Driver side, with 6-LED license light	10
RETAIL			
TLL170RK		Set: STL116RB, STL117RB, mounting hardware, **Try Me** package	2

FMVSS	STL116: A I S T, P2 A ; STL117: A I S T, P2 A, L
MATERIALS	Acrylic lens and plastic housing
VOLT/AMP	12.8VDC - Stop/Turn .252A, Marker .135A
WT/DIMS	.816 lb. / 8" x 2.9" x 2.6"
WARRANTY	Lifetime LED Warranty

TAIL LIGHT STL116RB

STOP/TURN STL117RB

TLL170RK
Try Me Kit





LIGHTGUIDE™



TAIL LIGHT STL616NTRB

STOP/TURN STL617NTRB

STL616/617 SERIES

LightGuide™ LED Combination Stop/Turn/Tail Light

PATENTED TECHNOLOGY

- Central X-shaped feature illuminates for tail light function
- Surrounding diodes light for stop and turn functions
- Designed for marine trailer application
- Sealed, waterproof construction
- Universal mount
- Hard wired, with separate ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
COMBINATION TAIL LIGHTS - 16 DIODES			
STL616NTRB	STL616NTRBP	Passenger side	10
STL617NTRB	STL617NTRBP	Driver side, with 3-LED license light	10



FMVSS	S T I A P2, P2 A, L
MATERIALS	Acrylic lens and plastic housing
VOLT/AMP	12.8VDC - Stop .259/Tail .062
WT/DIMS	.816 lb. / 8.063” x 2.875” x 2.813”
WARRANTY	Lifetime LED Warranty

STL16/17 SERIES
LED Combination Tail Lights

- Designed for marine trailer application
- Sealed, waterproof construction
- Universal mount
- Hard wired, with separate ground wire
- STL16/17NTRB feature light tube technology and SMD LED

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
COMBINATION TAIL LIGHTS - 18 DIODES			
STL16RB	STL16RBP	Passenger side	10
STL17RB	STL17RBP	Driver side, with 4-LED license light	10
STL16NTRB	STL16NTRB	Passenger side, SMD LED	10
STL17NTRB	STL17NTRB	Driver side, SMD LED with 4-LED license light	10
ACCESSORIES			
AL16RB	AL16RBP	Tail light lens for STL16/17RB	50
AL17RB	AL17RBP	Side marker lens STL16/17RB	50
RETAIL			
STL16RS	Passenger side, stainless hardware		6
STL17RS	Driver side with 4-LED license light, stainless hardware		6
TLL160RK	Set: STL16RB, STL17RB, mounting hardware; clam		2
TLL16RK	Kit: STL16RB, STL17RB, 25-ft harness, license plate bracket, stainless steel mounting hardware; clam		2

FMVSS	STL16: Stop/Tail A I S T P2 PC, Side Marker A P2
	STL17: Stop/Tail A I S T P2 PC, Side Marker A P2, License L
MATERIALS	Acrylic lens and plastic housing
VOLT/AMP	STL16: 12.8VDC - .259A Stop/Turn, .062A Marker
	STL17: 12.8VDC - .268A Stop/Turn, .059A Marker
WT/DIMS	.816 lb. / 8.063" x 2.875" x 2.813"
WARRANTY	Lifetime LED Warranty



STL17RB



STL16NTRB





TLL16RK



STL15RB

STL14RB





STL14/15 SERIES

FLEET Count™ LED Low Profile Combination Tail Lights

- Designed for marine trailer application
- Sealed, waterproof construction
- Universal mount
- Hard wired, with separate ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
COMBINATION TAIL LIGHTS - 12 DIODES			
STL14RB	STL14RBP	Passenger side	10
STL14R1B	STL14R1BP	Passenger side, 16-in. leads	10
STL15RB	STL15RBP	Driver side, with 6-LED license light	10
STL15R1B	STL15R1BP	Driver side, with 6-LED license light, 16-in. leads	10

FMVSS	STL14: A I S T, P2 A; STL15: A I S T, P2 A, L
MATERIALS	Acrylic lens and plastic housing
VOLT/AMP	12.8VDC - Stop/Turn .252A. Marker .135A
WT/DIMS	.816 lb. / 8" x 2.875" x 2.813"
WARRANTY	Lifetime LED Warranty

STL0016/0017 SERIES

ONE™ LED Combination Tail Lights

ONE LED LAMPS

- Designed for marine trailer application
- Sealed, waterproof construction
- Universal mount
- Hard wired, with separate ground wire

STL0016RB

STL0017RB

TLL0016RK

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
COMBINATION TAIL LIGHTS			
STL0016RB	STL0016RBP	Passenger side	10
STL0017RB	STL0017RBP	Driver side, with license light	10
STL0016RP2G	STL0016RP2GP	Passenger side, 2-pin male/female plug, ring terminal on ground	10
STL0017RP2G	STL0017RP2GP	Driver side, with license light, 2-pin male/female plug, ring terminal on ground	10
RETAIL			
STL0016RS	Passenger side, clam	Retail Ready	6
STL0017RS	Driver side with 4-LED license light, clam		6
TLL0016RK	Set: STL0016RB, STL0017RB, mounting hardware, clam		2

FMVSS	STL0016: Stop/Tail A I S T P2, Side Marker A P2
	STL0017: Stop/Tail A I S T P2, Side Marker A P2, License L
MATERIALS	Acrylic lens and plastic housing
VOLT/AMP	STL0016: 12.8VDC - .31A Stop/Turn, .12A Marker
	STL0017: 12.8VDC - .32A Stop/Turn, .26A Marker
WT/DIMS	.816 lb. / 8.0" x 2.9" x 2.6"
WARRANTY	Lifetime LED Warranty



STL26/27 SERIES

Miro-Flex™ LED Combination Tail Lights

STL26RB

STL27RB

TLL26RK

- Designed for marine trailer application
- Sealed, waterproof construction
- Universal mount
- Hard wired, with separate ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
COMBINATION TAIL LIGHTS - 14 DIODES			
STL26RB	STL26RBP	Passenger side	10
STL27RB	STL27RBP	Driver side with 4-LED license light	10
RETAIL			
TLL26RK		Set: STL26RB, STL27RB, mounting hardware; clam	2

Retail Ready

FMVSS	STL26: S2 T2 I6 A PC STL27: S2 T2 I6 A PC L
MATERIALS	Acrylic lens and plastic housing
VOLT/AMP	STL26: 12.8VDC - .167A Stop/Turn, .054A Marker STL27: 12.8VDC - .167A Stop/Turn, .107A Marker/License
WT/DIMS	.882 lb. / 8.063" x 2.938" x 2.688"
WARRANTY	Lifetime LED Warranty



STL36/37 SERIES
LED Combination Tail Lights

- Designed for marine trailer application
- Sealed, waterproof construction
- Universal mount
- Hard wired, with separate ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
COMBINATION TAIL LIGHTS - 17 DIODES			
STL36RB	STL36RBP	Passenger side	20
STL36RPG	STL36RPGP	Passenger side, dual plug and ground eyelet	20
STL37RB	STL37RBP	Driver side, 6-LED license light	20
STL37RPG	STL37RPGP	Driver side, 6-LED license light, dual plug and ground eyelet	20
RETAIL			
STL36RS	Passenger side		6
STL37RS	Driver side with 4-LED license light		6
TLL36RK	Kit: STL36RB, STL37RB, (2) MCL91AK sealed yellow marker lights with chrome bases, 25-ft harness, license plate bracket, stainless steel mounting hardware; clam		2

Retail Ready



STL36/37RB



TLL36RK

FMVSS	STL36: Stop/Tail A S T I P2, Side Marker A PC
	STL37: Stop/Tail A S T I P2, Side Marker A PC, License L
MATERIALS	Acrylic lens and plastic housing
VOLT/AMP	12.8VDC - .181A Stop/Turn, .047A Marker
WT/DIMS	.992 lb. / 7.875" x 3.25" x 2.875"
WARRANTY	Lifetime LED Warranty



STL56/57 SERIES
LED Combination Tail Lights



STL56/57RB

- Designed for marine trailer application
- Sealed, waterproof construction
- Universal mount
- Hard wired, with separate ground wire
- Stainless steel hardware

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
COMBINATION TAIL LIGHTS - 18 DIODES			
STL56RB	STL56RBP	Passenger side	10
STL57RB	STL57RBP	Driver side, 5-LED license light	10
RETAIL			
TLL56RK		Kit: STL56RB, STL57RB, 25-ft harness, license plate bracket, stainless steel mounting hardware; clam	2

Retail Ready



TLL56RK

FMVSS	STL56:	Stop/Tail A S T I P2, Side Marker A P2
	STL57:	Stop/Tail A S T I P2, Side Marker A P2, License L
MATERIALS		Acrylic lens and plastic housing
VOLT/AMP	STL56:	12.8VDC - .259A Stop/Turn, .062A Marker
	STL57:	12.8VDC - .268A Stop/Turn, .059A Marker
WT/DIMS		.816 lb. / 6.063" x 3.625" x 2.25"
WARRANTY		Lifetime LED Warranty



TLL21RK

LED Wireless Towing Light Kit

- Sonically sealed, waterpoof stop/turn/tail lights
- Magnetic base mounts securely on metal surfaces
- Wire harness connects to towing vehicle

TLL21RK

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		RETAIL	
TLL21RK		Towing light kit with wiring harness, clam	2

FMVSS	S T I
MATERIALS	Polycarbonate
VOLT/AMP	12.8VDC - .360A Stop/Turn, .030A Tail
WT/DIMS	2 lbs. / 3.938" x 5.875" x 2.186"
WARRANTY	Lifetime LED Warranty



TLL31RK

LED Wireless Towing Light Kit

TLL31RK

- Battery powered stop/turn/tail lights
- Sonically sealed, waterpoof
- Magnetic base mounts securely on metal surfaces
- Wireless design simplifies installation, includes wireless transmitter

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		RETAIL	
TLL31RK		LED wireless magnet mount towing light kit, clam	2

FMVSS	S T I
MATERIALS	Polycarbonate
VOLT/AMP	12.8VDC - .360A Stop/Turn, .030A Tail
WT/DIMS	2 lbs. / 3.938" x 6" x 2.188"
WARRANTY	Lifetime LED Warranty



BUL603 SERIES

LightGuide™ 4" Round Sealed Back-Up Lights

PATENTED TECHNOLOGY

- Sonically sealed, waterproof
- Grommet mount
- Accepts industry standard PL-3 connector
- Central X-shaped feature illuminates for auxiliary tail light function (BUL603CRB only)

BUL603CB



BUL603CRB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
CLEAR BACK-UP LIGHTS - 12 DIODES			
BUL603CB	BUL603CBP	Clear lens, grommet mount, 2-pin connection	10
BUL603CRB	BUL603CRBP	Clear lens, grommet mount, red auxiliary tail function, PL-3 connection	10
ACCESSORIES			
A45GB	A45GBP	Grommet	50
A45CB	A45CBP	Pigtail, 2-wire	100
A49PB	A49PBP	Right angle pigtail, 2-wire	100
A45PB	A45PBP	Pigtail, 3-wire	100
A47PB	A47PBP	Right angle pigtail, 3-wire	100

FMVSS	(2) R
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.216A
WT/DIMS	.28 lbs. / 4.3" x 4.3" x 1.08"
WARRANTY	Lifetime LED Warranty



GloLight®

BUL101 SERIES

GloLight® 4" Round Sealed DOT LED Back-Up Lights

BUL101CB

PATENTED TECHNOLOGY

- Sonically sealed, waterproof
- Certified for back-up light function when installed as pair in two-lamp system [SAE (2)R]

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
CLEAR BACK-UP LIGHTS - 21 DIODES			
BUL101CB	BUL101CBP	Standard 2-pin connection	10
BUL101CKB	BUL101CKBP	Kit with A45GB and A49PB	10
ACCESSORIES			
A45GB	A45GBP	Grommet	50
A45CB	A45CBP	Pigtail, 2-wire	100
A49PB	A49PBP	Right angle pigtail, 2-wire	100
BK45BB	BK45BBP	Black steel bracket	10
A45BB	A45BBP	Black plastic flange	100
A45SB	A45SBP	Stainless steel mounting flange	20
A45CGB	A45CGBP	Chrome grommet cover	20



HOLE CUT-OUT: 4.5"

FMVSS	(2) R
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.425A
WT/DIMS	.309 lbs. / 4.313" x 4.313" x 1.625"
WARRANTY	Lifetime LED Warranty

BUL11 SERIES

4" Round Sealed Clear DOT LED Back-Up Lights

- Sonically sealed, waterproof
- Certified for back-up light function when installed as pair in two-lamp system [SAE (2)R]
- Available in grommet and flange mount models
- Grommet mount version available with standard 2-pin, or optional weathertight connection
- Grommet mount version available in 12V and 24V

BUL11CB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
CLEAR BACK-UP LIGHTS - 10 DIODES			
BUL11CB	BUL11CBP	12V, two-pin connection	10
BUL11CKB	BUL11CKBP	12V kit: BUL11CB, A45GB & A49PB	10
BUL11CMB	BUL11CMBP	12V, weathertight connection	10
BUL11CM24B	BUL11CM24BP	24V, weathertight connection	10
CLEAR BACK-UP LIGHT WITH REFLEX - 10 DIODES			
BUL11CBX	BUL11CBXP	12V, two-pin connection	10
ACCESSORIES			
A45GB	A45GBP	Grommet	50
A45CB	A45CBP	Pigtail, 2-wire	100
A49PB	A49PBP	Right angle pigtail, 2-wire	100
A45PMB	A45PMBP	Weathertight pigtail	100
AL45PWTB	AL45PWTBP	Weathertight to PL-3 adaptor	50

BUL11CBX

FMVSS	(2) R	
MATERIALS	Polycarbonate lens and housing	
VOLT/AMP	12.8VDC - 0.26A	
WT/DIMS	BUL11CB/CKB:	.309 lbs. / 4.313" x 4.313" x 1.625"
	BUL11CMB/CM24B:	.309 lbs. / 4.313" x 4.313" x 1.625"
	BUL11CBX:	.353 lbs. / 5.75" x 5.75" x 1.625"
WARRANTY	Lifetime LED Warranty	



HOLE CUT-OUT: 4.5"

FLEET COUNT

BUL06 SERIES

FLEET Count™ 4" Round Sealed DOT LED Back-Up Lights

- Sonically sealed, waterproof
- Certified for back-up light function when installed as pair in two-lamp system [SAE (2)R]

BUL06CB

BUL06CFB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
CLEAR BACK-UP LIGHTS - 6 DIODES			
BUL06CB	BUL06CBP	Grommet mount, 2-pin connection	10
BUL06C1224B	BUL06C1224BP	Grommet mount, 2-pin connection, 12/24V	10
BUL06CKB	BUL06CKBP	Kit with A45GB and A49PB, 2-pin	10
BUL06CMB	BUL06CMBP	Grommet mount, weathertight connection	10
BUL06CK1MB	BUL06CK1MBP	Kit: BUL06CMB with A45GB grommet, weathertight connection	10
BUL06CFB	BUL06CFBP	Flange mount, 2-pin connection	10
BUL06CFMB	BUL06CFMBP	Flange mount, weathertight connection	10
ACCESSORIES			
A45GB	A45GBP	Grommet	50
A45CB	A45CBP	Pigtail, 2-wire	100
A49PB	A49PBP	Right angle pigtail, 2-wire	100
BK45BB	BK45BBP	Black steel bracket	10
A45BB	A45BBP	Black plastic flange	100
A45SB	A45SBP	Stainless steel mounting flange	20
A45CGB	A45CGBP	Chrome grommet cover	20
A45PMB	A45PMBP	Weathertight pigtail	100

FMVSS	(2) R
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.180A
WT/DIMS	Grommet mount: .309 lbs. / 4.25" x 4.25" x 1.625"
	Flange mount: .350 lbs. / 5.5" x 5.5" x 1.875"
WARRANTY	Lifetime LED Warranty



BUL06CFB

HOLE CUT-OUT: 4.579"



BUL06CB

HOLE CUT-OUT: 4.528"

BUL003 SERIES

ONE™ LED 4" Round Sealed DOT Back-Up Lights

ONE LED LAMPS

- Sonically sealed, waterproof
- Certified for back-up light function when installed as pair in two-lamp system [SAE (2)R]

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
CLEAR BACK-UP LIGHTS - 1 DIODE			
BUL003CB	BUL003CBP	Grommet mount, 2-pin connection	10
BUL003CKB	BUL003CKBP	Kit with A45GB grommet and A45CB pigtail	10
BUL003C1224B	BUL003C1224BP	Grommet mount, 2-pin connection 12-24V	50
ACCESSORIES			
A45GB	A45GBP	Grommet	50
A45CB	A45CBP	Pigtail, 2-wire	100
A49PB	A49PBP	Right angle pigtail, 2-wire	100

BUL003CB

FMVSS	(2) R
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - .26A
WT/DIMS	.22 lbs. / 4.313" x 4.313" x 1.688"
WARRANTY	Lifetime LED Warranty



BUL23/53 SERIES

4" Round Sealed Clear DOT LED Back-Up Lights

HIGH L.E.D COUNT

BUL23CB

BUL53CB

- Sonically sealed, waterproof
- Certified for back-up light function when installed as pair in two-lamp system [SAE (2)R]
- High diode count; choose from 27- or 36-LED models
- 27-LED version available in 12V and 12-24V

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
CLEAR BACK-UP LIGHTS - 27 DIODES			
BUL23CB	BUL23CBP	12V, 2-pin connection	10
BUL23C24B	BUL23C24BP	12-24V, 2-pin connection	10
CLEAR BACK-UP LIGHT - 36 DIODES			
BUL53CB	BUL53CBP	12V, two-pin connection	10
ACCESSORIES			
A45GB	A45GBP	Grommet	50
A45CB	A45CBP	Pigtail, 2-wire	100
A49PB	A49PBP	Right angle pigtail, 2-wire	100

FMVSS	(2) R
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	BUL23: 12.8VDC - 0.145A
	BUL53: 12.8VDC - 0.275A
WT/DIMS	.309 lbs. / 4.313" x 4.313" x 2"
WARRANTY	Lifetime LED Warranty





HOLE CUT-OUT: 4.5"

BUL602 SERIES

LightGuide™ 6" Oval Sealed DOT Back-Up Lights

PATENTED TECHNOLOGY (pat. D820,486)

- Sonically sealed, waterproof
- Grommet mount
- Certified for back-up light function when installed as pair in two-lamp system [SAE (2)R]
- BUL602CRB includes auxiliary tail light function

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
CLEAR BACK-UP LIGHTS - 12 DIODES			
BUL602CB	BUL602CBP	Grommet mount, 2-pin connection	10
BUL602CRB	BUL602CRBP	Grommet mount, supplemental tail light function, PL-3 connection	10
ACCESSORIES			
A70GB	A70GBP	Grommet	50
A45PB	A45PBP	Pigtail, 3-wire	100
A47PB	A47PBP	Right angle pigtail, 3-wire	100
A45CB	A45CBP	Pigtail, 2-wire	100
A49PB	A49PBP	Right angle pigtail, 2-wire	100

FMVSS	(2) R
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.381A
WT/DIMS	.375 lbs. / 6.5" x 2.8" x 1.80"
WARRANTY	Lifetime LED Warranty



BUL602CB



BUL602CRB



HOLE CUT-OUT: 6.85" x 2.52" (1.26" R)

GloLight®

BUL111CB



HOLE CUT-OUT:
6.85" x 2.52" (1.26" R)

BUL111 SERIES

GloLight® 6" Oval Sealed DOT LED Back-Up Lights

PATENTED TECHNOLOGY

- Sonically sealed, waterproof
- Certified for back-up light function when installed as pair in two-lamp system [SAE (2)R]

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
CLEAR BACK-UP LIGHTS - 22 DIODES			
BUL111CB	BUL111CBP	Standard two-pin connection	10
ACCESSORIES			
A70GB	A70GBP	Grommet	50
A45CB	A45CBP	Pigtail, 2-wire	100
A49PB	A49PBP	Right angle pigtail, 2-wire	100

FMVSS	(2) R
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.386A
WT/DIMS	.265 lbs. / 6.5" x 2.375" x 1.75"
WARRANTY	Lifetime LED Warranty

BUL10/22/52 SERIES

6" Oval Sealed Clear DOT LED Back-Up Lights

- Sonically sealed, waterproof
- Certified for back-up light function when installed as pair in two-lamp system [SAE (2)R]
- Low to high diode count; choose from 10-, 27- or 36-LED models
- Accept standard two-pin plugs

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
CLEAR BACK-UP LIGHT - 10 DIODES			
BUL10CB	BUL10CBP	Standard two-pin connection	10
CLEAR BACK-UP LIGHT - 27 DIODES			
BUL22CB	BUL22CBP	Standard two-pin connection	10
CLEAR BACK-UP LIGHT - 36 DIODES			
BUL52CB	BUL52CBP	Standard two-pin connection	10
ACCESSORIES			
A70GB	A70GBP	Grommet	50
A45CB	A45CBP	Pigtail, 2-wire	100
A49PB	A49PBP	Right angle pigtail, 2-wire	100

FMVSS	(2) R	
MATERIALS	Polycarbonate lens and housing	
VOLT/AMP	BUL10:	12.8VDC - 0.260A
	BUL22:	12.8VDC - 0.125A
	BUL52:	12.8VDC - 0.275A
WT/DIMS	BUL10:	.265 lbs. / 6.438" x 2.25" x 1.75"
	BUL22/52:	.397 lbs. / 6.5" x 2.313" x 1.813"
WARRANTY	Lifetime LED Warranty	

BUL10CB



HOLE CUT-OUT: 6.85" x 2.5" (1.25" R)

BUL22CB

BUL52CB



HOLE CUT-OUT: 6.85" x 2.5" (1.25" R)

BUL12 SERIES

FLEET Count™ 6" Oval Sealed DOT LED Back-Up Lights

BUL12CB

BUL12CFB





BUL12CFB



BUL12CB



BUL12CSB

- Sonically sealed, waterproof
- Available with standard or weathertight connection
- Flange mount models available for recess or surface mount installation
- Certified for back-up light function when installed as pair in two-lamp system [SAE (2)R]

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
CLEAR BACK-UP LIGHTS - 6 DIODES			
BUL12CB	BUL12CBP	Recess mount, 2-pin	10
BUL12C1224B	BUL12C1224BP	Recess mount, 2-pin, 12/24V	10
BUL12CKB	BUL12CKBP	Kit with A70GB and A45CB, 2-pin	10
BUL12CFB	BUL12CFBP	Recess flange mount, 2-pin	10
BUL12CB1FPG	BUL12CB1FPGP	Kit: Hard wired recess mount light with black mounting flange, female PL-3 plug	10
BUL12CSB	BUL12CSBP	Surface flange mount, hard wired	10
ACCESSORIES			
A70GB	A70GBP	Grommet	50
A45CB	A45CBP	Pigtail, 2-wire	100
A49PB	A49PBP	Right angle pigtail, 2-wire	100
A45PMB	A45PMBP	Pigtail, weathertight	50
AL45PWTB	AL45PWTBP	Weathertight to PL-3 adaptor	50
A111TRSSB	A111TRSSBP	Stainless steel trim ring	50

FMVSS	(2) R
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.260A
WT/DIMS	.265 lbs. / 6.5" x 2.25" x 1.75"
WARRANTY	Lifetime LED Warranty

BUL002 SERIES

ONE™ LED 6" Oval Sealed DOT Back-Up Lights

ONE LED LAMPS

- Sonically sealed, waterproof
- Certified for back-up light function when installed as pair in two-lamp system [SAE (2)R]

BUL002CB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
CLEAR BACK-UP LIGHTS - 1 DIODE			
BUL002CB	BUL002CBP	Standard two-pin connection	10
BUL002CM3B	BUL002CM3BP	Weathertight connection, three-pin	10
ACCESSORIES			
A70GB	A70GBP	Grommet	50
A45CB	A45CBP	Pigtail, 2-wire	100
A49PB	A49PBP	Right angle pigtail, 2-wire	100
A45PMB	A45PMBP	Pigtail, weathertight	50
AL45PWTB	AL45PWTBP	Weathertight to PL-3 adaptor	50

FMVSS	(2) R
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.30A
WT/DIMS	.265 lbs. / 6.5" x 2.375" x 1.75"
WARRANTY	Lifetime LED Warranty



HOLE CUT-OUT: 6.85" x 2.52" (1.26" R)

BUL35/90 SERIES
Sealed Clear DOT LED Back-Up Lights

BUL35CB



HOLE CUT-OUT: 5.462" x 3.562" (1" R)

BUL90CB



- Sonically sealed, waterproof
- Certified for back-up light function when installed as pair in two-lamp system [SAE (2)R]
- BUL35 and BUL24 are 5.5" x 3.5" recess mount models that accept standard two-pin plugs
- BUL90 is 7" surface mount model, hard wired, with separate ground wire; designed for transit vehicles

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
CLEAR 5.5" x 3.5" BACK-UP LIGHTS - 16 DIODES			
BUL35CB	BUL35CBP	Standard two-pin connection, 12V	10
BUL24CB	BUL24CBP	Standard two-pin connection, 12-24V	10
CLEAR 7" BACK-UP LIGHTS - 42 DIODES			
BUL90CB	BUL90CBP	12V, hard wired	5
BUL90C24B	BUL90C24BP	24V, hard wired	5
ACCESSORIES			
A33GB	A33GBP	Grommet for BUL35CB	50
A45CB	A45CBP	Pigtail, 2-wire	100
A49PB	A49PBP	Right angle pigtail, 2-wire	100

FMVSS	(2) R	
MATERIALS	Polycarbonate lens and housing	
VOLT/AMP	BUL35:	12.8VDC - 0.295A
	BUL24:	24.VDC - 0.198A
	BUL90:	12.8VDC - 0.301A
	BUL90:	24.0VDC - 0.089A
WT/DIMS	BUL35/24:	.397 lbs. / 5.313" x 3.438" x 2.313"
	BUL90:	.970 lbs. / 7" x 7" x 1.438"
WARRANTY	Lifetime LED Warranty	

SLL43 SERIES
4" Round Sealed LED Warning Lamps

- Sonically sealed, waterproof
- Flashing lights with double-flash function, meeting SAE J595 and J845 standards for Class 2 and Class 3 directional warning lamps
- Use two Function 1 or Function 2 lights for synchronous flashing or pair a Function 1 with a Function 2 light for alternating flash pattern
- Accepts standard PL-3 plugs
- Operating voltage 9-30VDC, suitable for 12V or 24V systems

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW WARNING LIGHTS - 22 DIODES			
SLL43AB1	SLL43AB1P	12V-24V Function 1	10
SLL43AB2	SLL43AB2P	12V-24V Function 2	10
SLL43AKB1	SLL43AKB1P	12V-24V Function 1, kit with A45GB & A45PB	10
SLL43AKB2	SLL43AKB2P	12V-24V Function 2, kit with A45GB & A45PB	10
ACCESSORIES			
A45GB	A45GBP	Grommet, 4" round	50
A45PB	A45PBP	Pigtail, 3-wire	100
A47PB	A47PBP	Right angle pigtail, 3-wire	100

FMVSS	W-2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.56A
WT/DIMS	.60 lbs. / 4.25" x 4.25" x 1.75"
WARRANTY	Lifetime LED Warranty

SLL43AB1
SLL43AB2



HOLE CUT-OUT: 4.5"

SLL72 SERIES
6" Oval Sealed LED Warning Lamps



SLL72AB1
SLL72AB2

- Sonically sealed, waterproof
- Flashing lights with double-flash function, meeting SAE J595 and J845 standards for Class 2 and Class 3 directional warning lamps
- Use two Function 1 or Function 2 lights for synchronous flashing or pair a Function 1 with a Function 2 light for alternating flash pattern
- Accepts standard PL-3 plugs
- Operating voltage 9-30VDC, suitable for 12V or 24V systems

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW WARNING LAMPS - 22 DIODES			
SLL72AB1	SLL72AB1P	12V-24V Function 1	10
SLL72AB2	SLL72AB2P	12V-24V Function 2	10
SLL72AKB1	SLL72AKB1P	12V-24V Function 1, kit with A70GB & A45PB	10
SLL72AKB2	SLL72AKB2P	12V-24V Function 2, kit with A70GB & A45PB	10
ACCESSORIES			
A70GB	A70GBP	Grommet, 6" oval	50
A45PB	A45PBP	Pigtail, 3-wire	100
A47PB	A47PBP	Right angle pigtail, 3-wire	100

FMVSS	W-2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.54A
WT/DIMS	.62 lbs. / 6.5" x 2.375" x 1.75"
WARRANTY	Lifetime LED Warranty



HOLE CUT-OUT: 6.85" x 2.5" (1.25" R)

SLL93 SERIES

7" Round LED Warning Lights for Surface Mount

- 8-LED school bus warning lights
- Acrylic lens, die cast aluminum base plate
- Sealed, waterproof design

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED WARNING LIGHTS - 8 DIODES			
SLL93RB	SLL93RBP	Warning light, 12V	5
YELLOW WARNING LIGHTS - 8 DIODES			
SLL93AB	SLL93ABP	Warning light, 12V	5
ACCESSORIES			
A94VB	A94VBP	Black Steel Visor	25

FMVSS	W2 SAE J887
MATERIALS	Acrylic len, die cast aluminum base
VOLT/AMP	12.8VDC - 2.0A
WT/DIMS	1.3875lb. / 7.25" x 7.25" x 1.9"
WARRANTY	Lifetime LED Warranty



SLL93RB

SLL93AB

SLL93AB with A94VB

RBL10C SERIES

LED Dual-Function Strobe/Beacon

RBL10CA

RBL10CC

- Sonically sealed, waterproof
- Five flash patterns
- Surface mount design
- Operating voltage 9-36VDC
- SAE J845/EMC R10 approved

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW BEACON LIGHT - 12 DIODES			
RBL10CA	-	Clear lens, yellow diodes	1
WHITE STROBE LIGHT - 12 DIODES			
RBL10CC	-	Clear lens, white diodes	1

FMVSS	SAE J845 WS3-2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 1.04A / 36VDC - .36A
WT/DIMS	1.53 lbs. / 6.377" x 6.377" x 4.173"
WARRANTY	Lifetime LED Warranty



RBL10AS SERIES
LED Beacon

- 36-LED array produces bright yellow light
- Dual power: use with 12VDC or 24VDC systems
- Long lasting, energy efficient - diodes last up to 50 times longer than incandescent, draw less than 1/2 amp
- Heavy duty magnetic base mounts securely to metal surfaces
- Durable ABS housing resists corrosion
- 12-ft coil cord with power plug

RBL10AS

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW BEACON - 36 DIODES			
RBL10AS	–	Clam	2

FMVSS	W-2
MATERIALS	ABS base, PMMA lens
VOLT/AMP	10-30VDC - 0.5A
WT/DIMS	.88 lbs - 5.125” x 5.125” x 3.5”
WARRANTY	Lifetime LED Warranty



RBL13/14 SERIES

LED Surface Mount, Dual-Function Class 1 Beacon

RBL13AB

- Sonically sealed, waterproof
- 30 selectable flash patterns
- Surface mount design
- Operating voltage 9-36VDC
- SAE J845 Class 1
- CA T13 Class B
- Packaged in color retail box

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW BEACON - 12 DIODES			
RBL13AB	–	5.5”, 12-ft. cord, dual switch	1
RBL14AB	–	7”, 12-ft. cord, dual switch	1

RBL14AB

FMVSS	SAE J595 Class I
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 1.04A / 36VDC - .36A
WT/DIMS	RBL13 - 1.863 lbs. / 6.5” dia x 5.5”
	RBL14 - 1.863 lbs. / 6.5” dia x 7”
WARRANTY	Lifetime LED Warranty

SLL15 SERIES

Surface Mount LED Class 1 Directional Warning Lights

- Clear lens, ultrabright SMD LED's
- Surface mount design with gasket
- Operating voltage 10-30VDC
- Up to 133 selectable modes
- Synchronize up to eight units
- Meets SAE J595 for Class 1 vehicles
- IP67 rated for dust and water resistance
- Packaged in colorful retail boxes

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW WARNING LIGHT - 6 DIODES			
SLL15AC1B	-	Single color - yellow	1
WHITE WARNING LIGHT - 6 DIODES			
SLL15C1B	-	Single color - white	1
YELLOW/WHITE WARNING LIGHT - 12 DIODES			
SLL15ACC2B	-	Dual color - yellow/white	1
YELLOW/RED/WHITE WARNING LIGHT - 18 DIODES			
SLL15ARC3B	-	Triple color - red/yellow/white	1

FMVSS	SAE J595 - Class 1
MATERIALS	Polycarbonate lens, aluminum housing
VOLT/AMP	12.8VDC - 2.0A Max / 28.0VDC - 1.2A Max
WT/DIMS	.2 lbs. / 5.13" x 0.87" x 0.74"
WARRANTY	Lifetime LED Warranty

SLL15AC1B

SLL15C1B

SLL15ACC2B

SLL15ARC3B



SLL16 SERIES

Surface Mount LED, Class 1, Directional Warning Light

SLL16C1B

- Clear lens, ultrabright LED's
- Surface mount design with gasket
- Operating voltage 10-30VDC
- Up to 72 selectable modes
- Synchronize up to eight units
- Meets SAE J595 for Class 1 vehicles
- IP67 rated for dust and water resistance
- Packaged in colorful retail boxes

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
WHITE WARNING LIGHT - 6 DIODES			
SLL16C1B	-	Clear lens, white diodes	1



FMVSS	SAE J595 - Class 1
MATERIALS	Polycarbonate lens, aluminum housing
VOLT/AMP	12.8VDC - 1.2A Max / 28.0VDC - 0.6A Max
WT/DIMS	.2 lbs. / 5.13" x 0.87" x 0.74"
WARRANTY	Lifetime LED Warranty

SLL17 SERIES

Surface Mount LED Class 1 Directional Warning Lights

- Clear lens, ultrabright LED's
- Surface mount design with gasket
- Operating voltage 10-30VDC
- Up to 133 selectable modes
- Synchronize up to eight units
- Meets SAE J595 for Class 1 vehicles
- IP67 rated for dust and water resistance
- Packaged in colorful retail boxes

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW WARNING LIGHT - 6 DIODES			
SLL17AC1B	-	Single color - yellow	1
WHITE WARNING LIGHT - 6 DIODES			
SLL17C1B	-	Single color - white	1
YELLOW/WHITE WARNING LIGHT - 12 DIODES			
SLL17ACC2B	-	Dual color - yellow/white	1
YELLOW/RED/WHITE WARNING LIGHT - 18 DIODES			
SLL17ARC3B	-	Triple color - red/yellow/white	1

FMVSS	SAE J595 - Class 1
MATERIALS	Polycarbonate lens, aluminum housing
VOLT/AMP	12.8VDC - 1.2A Max / 28.0VDC - 0.6A Max
WT/DIMS	.2 lbs. / 4.73" x 1.24" x 0.59"
WARRANTY	Lifetime LED Warranty

SLL17AC1B

SLL17C1B

SLL17ACC2B

SLL17ARC3B



SLL22 SERIES

Surface Mount LED Directional Warning Light

SLL22ACB

- Sonically sealed, waterproof
- Compact, surface mount design with gasket
- 12 flash patterns and synchronization capability: random, steady, single, mega, double, triple, quad, quint, 8-flash, single-quad, single h/l and single-triple quint
- Operating voltage 9-36VDC
- Hard wired; 4-wire, 7” leads
- Wiring - red: positive, black: negative, white: alternating flash, yellow: synchronization and flash pattern change
- Meets SAE J845 for Class II vehicles
- IP67 rating: protected from dust and capable of withstanding water immersion, offering increased reliability and service life



BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW WARNING LIGHT - 3 DIODES			
SLL22ACB	SLL22ACBP	Clear lens, yellow diodes	1

FMVSS	SAE J845 Class II
MATERIALS	Polycarbonate lens, ABS trim ring
VOLT/AMP	13.5V - 0.45A
WT/DIMS	.22 lbs / 4.70” x 1.04” x 1.84”
WARRANTY	Lifetime LED Warranty

SLL51 SERIES

Surface Mount LED Directional Warning Light

- Sonically sealed, waterproof
- Designed to flash simultaneously
- Operating voltage 9-36VDC
- Surface mount design with gasket
- Hard wired; 3-wire, 7” leads
- Wiring - red: positive, white: negative, yellow: sync
- Meets SAE J845 for Class II vehicles
- IP67 rating: protected from dust and capable of withstanding water immersion, offering increased reliability and service life



SLL51ACB

SLL51CB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW WARNING LIGHT - 6 DIODES			
SLL51ACB	SLL51ACBP	Clear lens, yellow diodes	40
WHITE WARNING LIGHT - 6 DIODES			
SLL51CB	SLL51CBP	Clear lens, white diodes	40

FMVSS	SAE J845 Class II
MATERIALS	Polycarbonate lens, ABS trim ring
VOLT/AMP	13.5V - 0.33A
WT/DIMS	.49 lbs / 5.54” x 1.67” x 3.67”
WARRANTY	Lifetime LED Warranty



SLL81 SERIES

Recess Mount LED Directional Warning Light

SLL81ACB

SLL81CB

- Sonically sealed, waterproof
- Compact, surface mount design with gasket
- 12 flash patterns and synchronization capability: random, single flash, triple flash, mega, double, triplealt, quad, quintalt, flash, single-quad, single h/l and single-triple quint
- Operating voltage 9-36VDC
- Hard wired; 4-wire, 7” leads
- Wiring - red: positive, black: negative, white: alternating flash, yellow: synchronization and flash pattern change
- Meets SAE J845 for Class II vehicles
- IP67 rating: protected from dust and capable of withstanding water immersion, offering increased reliability and service life

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW WARNING LIGHT - 6 DIODES			
SLL81ACB	SLL81ACBP	Clear lens, yellow diodes	100
WHITE WARNING LIGHT - 6 DIODES			
SLL81CB	SLL81CBP	Clear lens, white diodes	100

FMVSS	SAE J845 Class II
MATERIALS	Polycarbonate lens, ABS trim ring
VOLT/AMP	13.5V - 1.3A
WT/DIMS	00.27 lb / 4.36” x 1.55” x 1.69”
WARRANTY	Lifetime LED Warranty

GloLight® M1 SERIES
6.5" LED Marker/Clearance Lights

GloLight®

Panelite® MILLENNIUM SERIES™

PATENTED TECHNOLOGY
- Sealed, waterproof design
- Hard wired, includes separate ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW - 13 DIODES			
11212307B	11212355P	.180 male bullets	50
11212376B	11212356P	Clear lens, .180 male bullets	50
-	11212335P	Kit: .180 male bullets, chrome bezel	10
-	11212336P	Clear lens kit: .180 male bullets, chrome bezel	10
RED - 13 DIODES			
11212309B	11212357P	.180 male bullets	50
11212378B	11212358P	Clear lens, .180 male bullets	50
-	11212337P	Kit: .180 male bullets, chrome bezel	10
-	11212338P	Cleanr lens kit: .180 male bullets, chrome bezel	10
ACCESSORIES			
00212317B	00212327P	Bezel	200/20



M1 LED WITH BEZEL

M1 CLEAR LENS LED WITH BEZEL

FMVSS	P2
MATERIALS	Polycarbonate lens, housing and bezel
VOLT/AMP	12.8VDC - 0.12A
WT/DIMS	.132 lbs. / 6.625" x 2.188" x 1"
WARRANTY	Three Year Warranty



HOLE CUT-OUT: 1.5"

GloLight®

Panelite® MILLENNIUM SERIES™

GloLight® M3 SERIES

3" LED Marker/Clearance Lights

PATENTED TECHNOLOGY

- Sealed, waterproof design
- Hard wired, includes separate ground wire

M3 LED WITH BEZEL

M3 CLEAR LENS LED WITH BEZEL

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW - 5 DIODES			
11212207B	11212255P	.180 male bullets	50
11212276B	11212256P	Clear lens, .180 male bullets	50
-	11212235P	Kit: .180 male bullets with chrome bezel	10
-	11212236P	Clear lens kit: .180 male bullets with chrome bezel	10
RED - 5 DIODES			
11212209B	11212257P	.180 male bullets	50
11212278B	11212258P	Clear lens, .180 male bullets	50
-	11212237P	Kit: .180 male bullets with chrome bezel	10
-	11212238P	Clear lens kit: .180 male bullets with chrome bezel	10
ACCESSORIES			
00212217B	00212227P	Bezel	500/20



HOLE CUT-OUT:
1.375"

FMVSS	P2
MATERIALS	Polycarbonate lens, housing and bezel
VOLT/AMP	12.8VDC - 0.12A
WT/DIMS	.132 lbs. / 3" x 2" x 1"
WARRANTY	Three Year Warranty

GloLight® M5 SERIES
4" LED Marker/Clearance Lights

PATENTED TECHNOLOGY
- Sealed, waterproof design
- Hard wired, includes separate ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW - 6 DIODES			
11212700B	11212708P	.180 male bullets	10
11212700BB	11212700BBP	Blunt cut leads	10
11212702B	11212710P	Clear lens, .180 male bullets	10
-	11212704P	Kit: .180 male bullets with chrome bezel	10
-	11212706P	Clear lens kit: .180 male bullets with chrome bezel	10
RED - 6 DIODES			
11212701B	11212709P	.180 male bullets	10
11212703B	11212711P	Clear lens, .180 male bullets	10
-	11212705P	Kit: .180 male bullets with chrome bezel	10
-	11212707P	Clear lens kit: .180 male bullets with chrome bezel	10
ACCESSORIES			
00212717B	00212727P	Bezel	500/20

M5 LED WITH BEZEL

M5 CLEAR LENS LED WITH BEZEL

FMVSS	P2
MATERIALS	Polycarbonate lens, housing and bezel
VOLT/AMP	12.8VDC - 0.033A
WT/DIMS	.066 lb. / 4.156" x 1.5" x .75"
WARRANTY	Three Year Warranty



HOLE CUT-OUT: 1"

Panelite MILLENNIUM SERIES

M1 SERIES

Millennium Series® 6.5" Sealed LED Marker/Clearance Lights

- Sealed, waterproof design
- Hard wired, includes separate ground wire
- Available with .180 male bullets or metripack connector
- Choose from light only or kit with chrome bezel

M1 LED WITH BEZEL

M1 CLEAR LENS LED WITH BEZEL

M1 LED WITH BEZEL

M1 CLEAR LENS LED WITH BEZEL

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		YELLOW - 4 DIODES	
00212307B	00212355P	.180 male bullets	50
-	00212335P	Kit: .180 male bullets, bezel	10
-	00212345P	Kit: Metripack connector, bezel	10
-	00212365P	Kit: Packard connector, bezel	10
00212376B	00212356P	Clear lens, .180 male bullets	10
-	00212336P	Kit: Clear lens, .180 male bullets, bezel	10
-	00212346P	Kit: Clear lens, metripack connector, bezel	10
		RED - 4 DIODES	
00212309B	00212357P	.180 male bullets	50
00212316B	00212367P	Metripack connector	100
-	00212337P	Kit: .180 male bullets, bezel	10
-	00212347P	Kit: Metripack connector, bezel	10
00212378B	00212358P	Clear lens, .180 male bullets	50
00212386B	00212368P	Clear lens, metripack connector	100
-	00212338P	Kit: Clear lens, .180 male bullets, bezel	10
		ACCESSORIES	
00212317B	00212327P	Bezel	200/20

FMVSS	P2
MATERIALS	Polycarbonate lens, housing and bezel
VOLT/AMP	12.8VDC - 0.12A
WT/DIMS	.132 lbs. / 6.625" x 2.188" x 1"
WARRANTY	Three Year Warranty



HOLE CUT-OUT: 1.5"

M3 SERIES

Millennium Series® 3" Sealed LED Marker/Clearance Lights

- Sealed, waterproof design
- Hard wired, includes separate ground wire
- Available with .180 male bullets or metripack connector
- Choose from light only or kit with chrome bezel

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		YELLOW - 2 DIODES	
00212207B	00212255P	.180 male bullets	50
-	00212235P	Kit: .180 male bullets, bezel	10
00212276B	00212256P	Clear lens, .180 male bullets	50
00212213B	00212263P	Clear lens, metripack connector	50
-	00212236P	Kit: Clear lens, .180 male bullets, bezel	10
		RED - 2 DIODES	
00212209B	00212257P	.180 male bullets	50
-	00212237P	Kit: .180 male bullets, bezel	10
00212278B	00212258P	Clear lens, .180 male bullets	50
-	00212238P	Kit: Clear lens, .180 male bullets, bezel	10
		ACCESSORIES	
00212217B	00212227P	Bezel	500/20

FMVSS	P2
MATERIALS	Polycarbonate lens, housing and bezel
VOLT/AMP	12.8VDC - 0.36A
WT/DIMS	.132 lbs. / 3" x 2" x 1"
WARRANTY	Three Year Warranty

M3 LED WITH BEZEL

M3 CLEAR LENS LED WITH BEZEL

M3 LED WITH BEZEL

M3 CLEAR LENS LED WITH BEZEL



HOLE CUT-OUT: 1.375"

Panelite MILLENNIUM SERIES

M4 SERIES

Millennium Series®
9" Sealed LED Lights



M4 LED MARKER/CLEARANCE LIGHTS WITH BEZEL

- Sealed, waterproof design
- Hard wired, includes separate ground wire
- Chrome trim ring included in kits or available separately

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW MARKER/CLEARANCE - 6 DIODES			
00212104B	00212155P	.180 male bullets	10
-	00212135P	Kit: .180 male bullets, bezel	10
RED MARKER/CLEARANCE - 6 DIODES			
-	00212157P	.180 male bullets	10
-	00212137P	Kit: .180 male bullets, bezel	10
ACCESSORIES			
00212117B	00212127P	Bezel	70/20



HOLE CUT-OUT: 2.5"

FMVSS	P2
MATERIALS	Polycarbonate lens, housing and bezel
VOLT/AMP	12.8VDC - 0.090A
WT/DIMS	.132 lbs. / 9" x 3.25" x 1"
WARRANTY	Three Year Warranty

M5 SERIES

Millennium Series® 4" Sealed LED Marker/Clearance Lights

- Sealed, waterproof design
- Hard wired, includes separate ground wire
- Available with .180 male bullets or metripack connector
- Choose from light only or kit with chrome bezel

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		YELLOW - 3 DIODES	
00212700B	00212708P	.180 male bullets	10
00212702B	00212710P	Clear lens, .180 male bullets	10
-	00212704P	Kit: .180 male bullets, bezel	10
-	00212706P	Kit: Clear lens, .180 male bullets, bezel	10
-	00212712P	Clear lens, metripack connector	10
		RED - 3 DIODES	
00212701B	00212709P	.180 male bullets	10
00212703B	00212711P	Clear lens, .180 male bullets	10
-	00212705P	Kit: .180 male bullets, bezel	10
-	00212707P	Kit: Clear lens, .180 male bullets, bezel	10
		ACCESSORIES	
00212717B	00212727P	Bezel	500/20



M5 LED WITH BEZEL

M5 CLEAR LENS LED WITH BEZEL

M5 LED WITH BEZEL

M5 CLEAR LENS LED WITH BEZEL

FMVSS	P2
MATERIALS	Polycarbonate lens, housing and bezel
VOLT/AMP	12.8VDC - 0.033A
WT/DIMS	.066 lb. / 4.156" x 1.5" x .75"
WARRANTY	Three Year Warranty



HOLE CUT-OUT: 1"

LAMPLOCK™ Anti-Theft Technology

MCL11SAB

MCL11SRB

MCL11SACKB

MCL11SRCKB

A11SRB

MCL11S SERIES

3/4" Sealed LED Marker/Clearance Lights with Theft-Deterrent Design

PATENTED TECHNOLOGY

PC Rated

- Sealed, waterproof design
- Recess mount lights with theft-deterrent mounting design
- Easy to install: insert light into mounting hole and secure with locking ring
- PC rated: fulfills requirement for marker and clearance light when properly mounted

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW - 1 DIODE			
MCL11SAB	MCL11SABP	Light with gasket, .180 bullets	50
MCL11SAKB	MCL11SAKBP	Light with gasket & locking ring .180 bullets	50
MCL11SAK1B	MCL11AK1BP	Light with gasket and locking ring	50
MCL11SACKB	MCL11SACKBP	Clear lens, yellow diodes with gasket & locking ring, .180 bullets	50
RED - 1 DIODE			
MCL11SRB	MCL11SRBP	Light with gasket, .180 bullets	50
MCL11SRKB	MCL11SRKBP	Light with gasket & locking ring .180 bullets	50
MCL11SRK1B	MCL11SRK1BP	Light with gasket and locking ring	50
MCL11SRCKB	MCL11SRCKBP	Clear lens, red diodes with gasket & locking ring, .180 bullets	50
ACCESSORIES			
A11SRB	A11SRBP	Stainless steel locking ring	100

FMVSS	PC
MATERIALS	Polycarbonate lens and housing, stainless steel locking ring, EPDM rubber gasket
VOLT/AMP	12.8VDC - .082A
WT/DIMS	.10 lbs. / 1" x 1" x .875"
WARRANTY	Lifetime LED Warranty







MCL110 SERIES

GloLight® Uni-Lite™ 3/4" LED Non-Directional Marker/Clearance Lights

PC Rated

PATENTED TECHNOLOGY

- Sealed, waterproof design
- PC rated when mounted in any direction - 360 degrees!
- Hard wired, includes separate ground wire
- Choose from light only or kit with A11GB grommet

MCL110AB

MCL110RB

MCL110AKB

MCL110RKB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW - PC RATED - 2 DIODES			
MCL110AB	MCL110ABP	Light only	50
MCL110AKB	MCL110AKBP	Light with A11GB grommet	50
MCL110AKBF	MCL110AKBFP	Light kit with grommet, .156 female barrels on 8" leads	50
RED - PC RATED - 2 DIODES			
MCL110RB	MCL110RBP	Light only	50
MCL110RKB	MCL110RKBP	Light with A11GB grommet	50
MCL110RKBF	MCL110RKBFP	Light kit with grommet, .156 female barrels on 8" leads	50
ACCESSORIES			
A11AXB	A11AXBP	Yellow reflector	100
A11RXB	A11RXBP	Red reflector	100
A11GB	A11GBP	Grommet	100
A12GB	A12GBP	Sealing grommet, .070-.125"	100
A14GB	A14GBP	Sealing grommet, .125-.250"	100
A11PB	A11PBP	Black plastic snap-in flange	100
A11CRB	A11CRBP	Chrome finish grommet cover	120
A11SSB	A11SSBP	Stainless steel grommet cover	120





FMVSS	PC
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.052A
WT/DIMS	.022 lbs. / .073" x .073" x 0.938"
WARRANTY	Lifetime LED Warranty



A11RXB



A11AXB

GloLight®

MCL111 SERIES

GloLight® Uni-Lite™ 3/4" Sealed LED Marker/Clearance Lights

MCL111AKB

MCL111RKB

PATENTED TECHNOLOGY

PC Rated

- Sealed, waterproof design
- PC rated two diode models
- Hard wired, includes separate ground wire
- Choose from light only or kit with A11GB grommet
- Dual function models MCL121AK9PVG/RK9PVG provide a supplemental stop/turn function

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW - PC RATED - 2 DIODES			
MCL111AB	MCL111ABP	Light only	50
MCL111AKB	MCL111AKBP	Light with A11GB grommet	50
MCL111AKPG	MCL111AKPGP	Kit with .180 male bullets, A11GB	50
MCL121AK9PVG	MCL121AK9PVGP	Supplemental turn - kit with closed grommet, .180 male bullets	20
RED - PC RATED - 2 DIODES			
MCL111RB	MCL111RBP	Light only	50
MCL111RKB	MCL111RKBP	Light with A11GB grommet	50
MCL111RKPG	MCL111RKPGP	Kit with .180 male bullets, A11GB	50
MCL121RK9PVG	MCL121RK9PVGP	Supplemental turn - kit with closed grommet, .180 male bullets	20
ACCESSORIES			
A11AXB	A11AXBP	Yellow reflector	100
A11RXB	A11RXBP	Red reflector	100
A11GB	A11GBP	Grommet	100
A12GB	A12GBP	Sealing grommet, .070-.125"	100
A14GB	A14GBP	Sealing grommet, .125-.250"	100
A11PB	A11PBP	Black plastic snap-in flange	100
A11CRB	A11CRBP	Chrome finish grommet cover	120
A11SSB	A11SSBP	Stainless steel grommet cover	120





FMVSS	PC
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.04A
WT/DIMS	.022 lbs. / .75" x .75" x 0.875"
WARRANTY	Lifetime LED Warranty

A11PB

MCL112 SERIES

GloLight® Uni-Lite™ 3/4" Sealed LED Marker/Clearance Lights

PATENTED TECHNOLOGY

- Sealed, waterproof design
- P2 rated single diode models
- Hard wired, includes separate ground wire
- Choose from light only or kit with A11GB grommet

MCL112AKB

MCL112RKB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW - P2 RATED - 1 DIODE			
MCL112AKB	MCL112AKBP	Light with A11GB grommet	50
RED - P2 RATED - 1 DIODE			
MCL112RB	MCL112RBP	Light only	50
MCL112RKB	MCL112RKBP	Light with A11GB grommet	50
ACCESSORIES			
A11AXB	A11AXBP	Yellow reflector	100
A11RXB	A11RXBP	Red reflector	100
A11GB	A11GBP	Grommet	100
A12GB	A12GBP	Sealing grommet, .070-.125"	100
A14GB	A14GBP	Sealing grommet, .125-.250"	100
A11PB	A11PBP	Black plastic snap-in flange	100
A11CRB	A11CRBP	Chrome finish grommet cover	120
A11SSB	A11SSBP	Stainless steel grommet cover	120

FMVSS	P2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - .075A
WT/DIMS	.022 lbs. / .75" x .75" x 0.875"
WARRANTY	Lifetime LED Warranty



MCL10 SERIES

Uni-Lite™ 3/4" LED Non-Directional Marker/Clearance Lights

NON DIRECTIONAL

PC Rated

- Sonically sealed, waterproof
- PC rated when mounted in any direction - 360 degrees!
- Hard wired, includes separate ground wire

MCL10AB

MCL10AKB

MCL10ACKB



HOLE CUT-OUT: .75"

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW - 1 DIODE			
MCL10AB	MCL10ABP	Light only	50
MCL10AKB	MCL10AKBP	Light with A11GB grommet	50
MCL10AK1224B	MCL10AK1224BP	Light with A11GB grommet, 12/24V	50
MCL10AKA12B	MCL10AKA12BP	Light with A12GB grommet, 7.5-in. leads	50
MCL10AKL12B	MCL10AKL12BP	Light with A12GB grommet, 12-in. leads	50
MCL10AK12JPG	MCL10AK12JPGP	Light with A11GB grommet, 12-in. leads, .156 male bullets	50
MCL10AKL12PG	MCL10AKL12PGP	Light with A11GB grommet, 12-in. leads, .180 male bullets	50
MCL10AKL12PGN	MCL10AKL12PGNP	Light with A12GB grommet, 12-in. leads, .180 male bullets	50
MCL10AKL18JPG	MCL10AKL18JPGP	Light with A12GB grommet, 18-in. leads, .180 male bullets	50
MCL10AKA10PG	MCL10AKA10PGP	Light with A10GB grommet, .180 male bullets	50
MCL10AK1FPG	MCL10AK1FPGP	Light with A12GB grommet, .156 female barrels	50
MCL10ACKB	MCL10ACKBP	Clear lens with A11GB grommet	50
MCL10ACKA12B	MCL10ACKA12BP	Clear lens with A12GB grommet	50
MCL10CAK14B	MCL10CAK14BP	Clear lens with grommet, 14-in. leads	50
MCL10ACKPG	MCL10ACKPGP	Clear lens with A11GB grommet .180 male bullets	50
MCL10ACKA12PG	MCL10ACKA12PGP	Clear lens with A12GB grommet, .180 male bullets	50
MCL10ACK12JPG	MCL10ACK12JPGP	Clear lens light with A11GB grommet, 12-in. leads, .156 male bullets	50

FMVSS	PC
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.52A
WT/DIMS	.022 lbs. / .073" x .073" x .938"
WARRANTY	Lifetime LED Warranty

MCL10 SERIES

Uni-Lite™ 3/4" LED Non-Directional Marker/Clearance Lights

NON DIRECTIONAL

PC Rated

- Sonically sealed, waterproof
- PC rated when mounted in any direction - 360 degrees!
- Hard wired, includes separate ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED - 1 DIODE			
MCL10RB	MCL10RBP	Light only	50
MCL10RKB	MCL10RKBP	Light with A11GB grommet	50
MCL10RK1224B	MCL10RK1224BP	Light with A11GB grommet, 12/24V	50
MCL10RKA12B	MCL10RKA12BP	Light with A12GB grommet, 7.5-in. leads	50
MCL10RKL12B	MCL10RKL12BP	Light with A12GB grommet, 12-in. leads	50
MCL10RK12JPG	MCL10RK12JPGP	Light with A11GB grommet, 12-in. leads, .156 male bullets	50
MCL10RKL12PG	MCL10RKL12PGP	Light with A11GB grommet, 12-in. leads, .180 male bullets	50
MCL10RKL12PGN	MCL10RKL12PGNP	Light with A12GB grommet, 12-in. leads, .180 male bullets	50
MCL10RKL18JPG	MCL10RKL18JPGP	Light with A12GB grommet, 18-in. leads, .180 male bullets	50
MCL10RKA10PG	MCL10RKA10PGP	Light with A10GB grommet, .180 male bullets	50
MCL10RKDTPG	MCL10RKDTPGP	Light with A11GB grommet, .180 male bullets, three-wire	20
MCL10RK1FPG	MCL10RK1FPGP	Light with A12GB grommet, .156 female barrels	50
MCL10RCKB	MCL10RCKBP	Clear lens with A11GB grommet	50
MCL10RCKA12B	MCL10RCKA12BP	Clear lens with A12GB grommet	50
MCL10CRK14B	MCL10CRK14BP	Clear lens with grommet, 14-in. leads	50
MCL10RCKA12PG	MCL10RCKA12PGP	Clear lens with A12GB grommet, .180 male bullets	50
MCL10RCKPG	MCL10RCKPGP	Clear lens with A11GB grommet, .180 male bullets	50
MCL10RCK12JPG	MCL10RCK12JPGP	Clear lens light with A11GB grommet, 12-in. leads, .156 male bullets	50

MCL10RB

MCL10RKB

MCL10RCKB



HOLE CUT-OUT: .75"

FMVSS	PC
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.52A
WT/DIMS	.022 lbs. / .073" x .073" x .938"
WARRANTY	Lifetime LED Warranty

MCL11 SERIES

Uni-Lite™ 3/4" Sealed LED Marker/Clearance Lights

PC Rated

- Sealed, waterproof design
- Hard wired, includes separate ground wire

MCL11AB

MCL11RB

MCL11AKB

MCL11RKB



HOLE CUT-OUT: 0.75"

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW - PC RATED - 2 DIODES			
MCL11AB	MCL11ABP	Light only	50
MCL11APG	MCL11APGP	Light with .180 male bullets	50
MCL11AKB	MCL11AKBP	Kit with A11GB grommet	50
MCL11AK12B	MCL11AK12BP	Kit with A11GB grommet, 12" leads	50
MCL11A24KB	MCL11A24KBP	Kit with A11GB grommet, 24V, 24" leads	50
MCL11AHPG	MCL11AHPGP	Kit with .180 male bullets, A11GB	50
MCL11AKPVG	MCL11AKPVGP	Kit with sealed grommet, .180 male bullets	50
MCL11AK12PG	MCL11AK12PGP	Kit with 12" leads, A11GB, .156 male bullets	50
MCL11AKBF	MCL11AKBFP	Kit with .156 female barrels, A11GB	50
MCL11AKAB	MCL11AKABP	Kit with .156 female barrels, A11GB	50
MCL11AKPRB	MCL11AKPRBP	Kit with A11GB, .150 female barrels, 2.5" leads	50
MCL11CAB	MCL11CABP	Light only, clear lens	50
MCL11CAKB	MCL11CAKBP	Kit with A11GB, clear lens	50
MCL11CAKPG	MCL11CAKPGP	Kit with A11GB, clear lens, .180 male bullets	50
MCL11CAKBF	MCL11CAKBFP	Kit with A11GB, clear lens, .156 female barrels	50
MCL21AKRGVB	MCL21AKRGVBP	Assembly: (2) MCL11, sealing grommets, ring terminals on 262-in. 3-wire	10
MCL21AKRYVB	MCL21AKRYVBP	Assembly: (2) MCL11, sealing grommets, ring terminals on 190-in. 3-wire	10
RED - PC RATED - 2 DIODES			
MCL11RB	MCL11RBP	Light only	50
MCL11RPG	MCL11RPGP	Light with .180 male bullets	50
MCL11RKB	MCL11RKBP	Kit with A11GB grommet	50
MCL11RK12B	MCL11RK12BP	Kit with 12" leads, A11GB	50
MCL11R24KB	MCL11R24KBP	Kit with A11GB grommet, 24V, 24" leads	50
MCL11RK12PG	MCL11RK12PGP	Kit with 12" leads, A11GB, .156 male bullets	50
MCL11RHPG	MCL11RHPG	Kit with .180 male bullets, A11GB	50
MCL11RKPVG	MCL11RKPVG	Kit with sealed grommet, .180 male bullets	50
MCL11RKBF	MCL11RKBFP	Kit with .156 female barrels, A11GB	50
MCL11RKAB	MCL11RKABP	Kit with .156 female connectors, A11GB	50
MCL11CRB	MCL11CRBP	Light only, clear lens	50
MCL11CRKB	MCL11CRKBP	Kit with A11GB, clear lens	50
MCL11CRKPG	MCL11CRKPGP	Kit with A11GB, clear lens, .180 male bullets	50
MCL11CRKBF	MCL11CRKBFP	Kit with A11GB, clear lens, .156 female barrels	50
MCL11RKPV4G	MCL11RKPV4GP	Kit with sealed grommet, female amp connector	50
MCL21RKPVG	MCL21RKPVGP	Kit with sealed grommet, 12-ft. leads, .180 male bullets	10
MCL21RKPV4G	MCL21RKPV4GP	Assembly: (2) MCL11, sealing grommets, ring terminals on 262-in. 3-wire	10

See Accessories section at back of catalog or listing on previous pages for additional mounting options

FMVSS PC

MATERIALS
Polycarbonate lens and housing

VOLT/AMP
12.8VDC - 0.03A

WT/DIMS
.022 lbs. / .074" x .074" x 0.90"

WARRANTY
Lifetime LED Warranty

MCL12 SERIES

Uni-Lite™ 3/4" Sealed LED Marker/Clearance Lights - P2

- Sealed, waterproof, P2 rated single diode models
- Hard wired, includes separate ground wire
- Three-piece identification light harnesses available; optional supplemental turn function
- MCL922RB is three-piece identification light bar

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW - P2 RATED - 1 DIODE			
MCL12AB	MCL12ABP	Light only	50
MCL12AKB	MCL12AKBP	Light kit with A11GB	50
MCL12AKPG	MCL12AKPGP	Light kit with .180 male bullets, A11GB	50
RED - P2 RATED - 1 DIODE			
MCL12RB	MCL12RBP	Light only	50
MCL12RKB	MCL12RKBP	Light kit with A11GB	50
MCL12RKPG	MCL12RKPGP	Light kit with .180 male bullets, A11GB	50
RED IDENTIFICATION LIGHT KIT WITH MOLDED HARNESS			
MCL12RK3B	MCL12RK3BP	(3) red MCL12 lights	20
MCL12RK3RMB	MCL12RK3RMBP	(3) red MCL12 lights, weathertight plug	20
MCL22RK3B	MCL22RK3BP	(3) red MCL12 lights, supplemental turn function	20
MCL22RK4B	MCL22RK4BP	(3) red MCL12 lights, supplemental turn function, amp connector	20
RED IDENTIFICATION LIGHT BAR			
MCL922RB	MCL922RBP	(3) red MCL12 lights, molded bar, black	10
ACCESSORIES			
A11AXB	A11AXBP	Yellow reflector	100
A11RXB	A11RXBP	Red reflector	100
A11GB	A11GBP	Grommet	100
A12GB	A12GBP	Sealing grommet, .070-.125"	100
A14GB	A14GBP	Sealing grommet, .125-.250"	100
A11PB	A11PBP	Black plastic snap-in flange	100
A11CRB	A11CRBP	Chrome finish grommet cover	120
A11SSB	A11SSBP	Stainless steel grommet cover	120
RETAIL			
MCL12AK	Retail Ready	Yellow light kit, card/slipover blister	12
MCL12RK		Red light kit, card/slipover blister	12

MCL12AKB

MCL12RKB

MCL12RK3B

MCL922RB



HOLE CUT-OUT: 0.75"

FMVSS P2

MATERIALS
Polycarbonate lens and housing

VOLT/AMP
12.8VDC - 0.47A

WT/DIMS
.022 lbs. / .074" x .074" x 0.90"

WARRANTY
Lifetime LED Warranty

MCL12AR SERIES

Uni-Lite™ 3/4" Sealed LED Fender Lights

MCL12ARRB
MCL12ARLB

- Sealed, waterproof, P2 rated single diode lights pre-installed in durable ABS, surface mount bracket
- Hard wired, includes separate ground wire
- Available with clear or tinted lenses

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		YELLOW / RED FENDER LIGHTS	
MCL12ARLB	MCL12ARLBP	Driver side assembly, 2-wire	50
MCL12ARRB	MCL12ARRBP	Passenger side assembly, 2-wire	50
MCL12CA2RLB	MCL12CA2RLBP	Clear lens, driver side assembly, self grounding	50
MCL12CA2RRB	MCL12CA2RRBP	Clear lens, passenger side assembly, self grounding	50
		ACCESSORIES	
A11GB	A11GBP	Grommet	100

FMVSS	P2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.047A
WT/DIMS	.20 lbs. / 4.75" x 1.625" x 1.25"
WARRANTY	Lifetime LED Warranty

MCL12CA2RLB
MCL12CA2RRB



MCL21/23 SERIES

2" & 2.5" Sealed LED Beehive Style Marker/Clearance Lights

- Sonically sealed, waterproof
- Clearance, side marker, or rear tracking light applications
- Accepts standard two-pin PL-10 plug

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		YELLOW - 8 DIODES	
MCL21AB	MCL21ABP	2" light	20
MCL23AB	MCL23ABP	2.5" light	20
		RED - 8 DIODES	
MCL21RB	MCL21RBP	2" light	20
MCL23RB	MCL23RBP	2.5" light	20
		ACCESSORIES	
A46PB	A46PBP	Straight PL-10 plug, 6" lead	100
A86PB	A86PBP	Straight PL-10 plug, 18" lead	100
A54GB	A54GBP	2" Flush mount grommet	100
A54GK	A54GKP	2" Kit: A54GB and A46PB	100
A55CB	A55CBP	2" Chrome trim ring	20
A55GB	A55GBP	2.5" Flush mount grommet (open back)	50
A56GB	A56GBP	2.5" Recess mount grommet (closed back)	100
A57GB	A57GBP	2.5" Recess mount grommet (open back)	50
A55GK	A55GKP	2.5" Kit: A55GB and A46PB	100
A57GK	A57GKP	2.5" Kit: A57GB and A46PB	100
A57CB	A57CBP	2.5" Chrome trim ring	20
BK5557GB	BK5557GBP	2"/2.5" Cam-on mounting bracket	50

MCL21AB

MCL21RB



MCL23AB

MCL23RB

FMVSS	P2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	MCL21: 12.8VDC - 0.061A
	MCL23: 12.8VDC - 0.051A
WT/DIMS	MCL21: .110 lbs. / 2" x 2" x 1.75"
	MCL23: .176 lbs. / 2.5" x 2.5" x 2.313"
WARRANTY	Lifetime LED Warranty

MCL21 SERIES
HOLE CUT-OUT: 2.313"



MCL23 SERIES
HOLE CUT-OUT: 2.75"

GloLight®

MCL155 SERIES

GloLight® 2" Round Sealed LED Marker/Clearance Lights

MCL155AB

MCL155RB

PATENTED TECHNOLOGY

- Sonically sealed, waterproof
- Accepts standard two-pin PL-10 plug
- Recess grommet mount design

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW - 6 DIODES			
MCL155AB	MCL155ABP	Grommet mount	20
RED - 6 DIODES			
MCL155RB	MCL155RBP	Grommet mount	20
ACCESSORIES			
A46PB	A46PBP	Straight PL-10 plug, 6" lead	100
A86PB	A86PBP	Straight PL-10 plug, 18" lead	100
A54GB	A54GBP	2" Flush mount grommet	100
A54GK	A54GKP	2" Kit: A54GB and A46PB	100
A55CB	A55CBP	2" Chrome trim ring	20
BK5557GB	BK5557GBP	Cam-on mounting bracket	50

FMVSS	P2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.06A
WT/DIMS	Grommet Mount: .066 lbs. / 2" x 2" x 1"
	Flange Mount: .078 lbs. / 2.938" x 2.938" x .938"
WARRANTY	Lifetime LED Warranty



MCL155AB/RB

HOLE CUT-OUT: 2.313"

MCL55 SERIES

2" Round Sealed LED Marker/Clearance Lights

- Sonically sealed, waterproof
- Accepts standard two-pin PL-10 plug
- Available in 12V and 12-24V models

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW - 3 DIODES			
MCL55AB	MCL55ABP	Grommet mount, 12V	20
MCL55ACB	MCL55ACBP	Clear lens grommet mount, 12V	20
MCL55A1224B	MCL55A1224BP	Grommet mount, 12-24V	20
RED - 3 DIODES			
MCL55RB	MCL55RBP	Grommet mount, 12V	20
MCL55RCB	MCL55RCBP	Clear lens grommet mount, 12V	20
MCL55R1224B	MCL55R1224BP	Grommet mount, 12-24V	20
MCL55FRB	MCL55FRBP	Flange mount, 12V	50
UTILITY LIGHT - 3 DIODES			
UCL55CB	UCL55CBP	White LED, 12V	20
ACCESSORIES			
A46PB	A46PBP	Straight PL-10 plug, 6" lead	100
A86PB	A86PBP	Straight PL-10 plug, 18" lead	100
A54GB	A54GBP	2" Flush mount grommet	100
A54GK	A54GKP	2" Kit: A54GB and A46PB	100
A55CB	A55CBP	2" Chrome trim ring	20
BK5557GB	BK5557GBP	Cam-on mounting bracket	50
RETAIL			
MCL55AK	Yellow kit with A54GB & A46PB, clam		12
MCL55RK	Red kit with A54GB & A46PB, clam		12

Retail Ready

MCL55AB

MCL55RB

MCL55ACB
MCL55RCB
UCL55CB



HOLE CUT-OUT: 2.313"

MCL55FRB



HOLE CUT-OUT: 2.313"

FMVSS	P2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.06A
WT/DIMS	MCL55: .066 lbs. / 2" x 2" x 1"
	MCL55FRB: .078 lbs. / 2.875" x 2.875" x 1"
WARRANTY	Lifetime LED Warranty

MCL505 SERIES

2" Round Sealed LED ABS Lights

- Sonically sealed, waterproof
- Accept standard two-pin PL-10 plugs
- Available in grommet and flange mount models
- MCL505GABSB includes A54GB grommet

MCL505ABSB





HOLE CUT-OUT: 2.313"

MCL505GABSB



HOLE CUT-OUT: 2.313"

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW - 3 DIODES			
MCL505ABSB	MCL505ABSBP	Flange mount	50
MCL505GABSB	MCL505GABSBP	Grommet mount kit, with A54GB grommet	20
ACCESSORIES			
A46PB	A46PBP	Straight PL-10 plug, 6" lead	100
A86PB	A86PBP	Straight PL-10 plug, 18" lead	100

FMVSS	P2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - .06A
WT/DIMS	MCL505ABSB: .078 lbs. / 2.875" x 2.875" x 1"
	MCL505GABSB: .066 lbs. / 2" x 2" x 1"
WARRANTY	Lifetime LED Warranty

MCL56 SERIES

FLEET Count™ 2" Round Sealed LED Marker/Clearance Lights

- Sonically sealed, waterproof
- Accepts standard two-pin PL-10 plug
- Multiple mounting options available

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW - 1 DIODE			
MCL56AB	MCL56ABP	Grommet mount, PL-10 connection	20
MCL56AFB	MCL56AFBP	Flange mount, PL-10 connection	20
MCL56AFMB	MCL56AFMBP	Flange mount, weathertight connection	20
RED - 1 DIODE			
MCL56RB	MCL56RBP	Grommet mount, PL-10 connection	20
MCL56RMB	MCL56RMBP	Grommet mount, weathertight connection	20
MCL56RFB	MCL56RFBP	Flange mount, PL-10 connection	20
MCL56RFMB	MCL56RFMBP	Flange mount, weathertight connection	20
ACCESSORIES			
A46PB	A46PBP	Straight PL-10 plug, 6" lead	100
A86PB	A86PBP	Straight PL-10 plug, 18" lead	100
A54GB	A54GBP	2" Flush mount grommet	100
A54GK	A54GKP	2" Kit: A54GB and A46PB	100
A55CB	A55CBP	2" Chrome trim ring	20
BK5557GB	BK5557GBP	Cam-on mounting bracket	50
RETAIL			
MCL56AK	Retail Ready	Yellow kit with A54GB & A46PB, clam	12
MCL56AK6		Yellow kit with A54GB & A46PB, clam	6
MCL56AS		Yellow light only, clam	12
MCL56RK		Red kit with A54GB & A46PB, clam	12
MCL56RK6		Red kit with A54GB & A46PB, clam	6
MCL56RS		Red light only, clam	12

FMVSS	P2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.045A
WT/DIMS	Grommet mount: .066 lbs. / 2" x 2" x 1"
	Flange mount: .071 lbs. / 2.938" x 2.938" x .938"
WARRANTY	Lifetime LED Warranty



HOLE CUT-OUT: 2.313"



HOLE CUT-OUT: 2.313"

MCL56AB

MCL56AFMB

MCL56AFB

MCL56RB

MCL56RFMB

MCL56RFB





MCL52AHXB

MCL52AHXB

2" Round Sealed LED Marker/Clearance Light with Reflex Lens and Flange

- Recess flange mount
- Sonically sealed, waterproof
- Hard wired, includes separate ground wire
- Built-in reflex eliminates the need for a separate reflector

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW - 7 DIODES			
MCL52AHXB	MCL52AHXBP	Reflex flange	50

FMVSS	A P2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.63A
WT/DIMS	.088 lbs. / 3.063" x 3.063" x .813"
WARRANTY	Lifetime LED Warranty



HOLE CUT-OUT: 2.313"

MCL50 SERIES

Miro-Flex™ 2" Round Sealed LED Marker/Clearance Lights

- Sonically sealed, waterproof
- Accepts standard two-pin PL-10 plug
- Multiple mounting options available



MCL50AB

MCL50RB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW - 9 DIODES			
MCL50AB	MCL50ABP	Light only	20
RED - 9 DIODES			
MCL50RB	MCL50RBP	Light only	20
ACCESSORIES			
A46PB	A46PBP	Straight PL-10 plug, 6" lead	100
A86PB	A86PBP	Straight PL-10 plug, 18" lead	100
A54GB	A54GBP	2" Flush mount grommet	100
A54GK	A54GKP	2" Kit: A54GB and A46PB	100
A55CB	A55CBP	2" Chrome trim ring	20
BK5557GB	BK5557GBP	Cam-on mounting bracket	50

FMVSS	P2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.047A
WT/DIMS	.088 lbs. / 2" x 2" x 1.188"
WARRANTY	Lifetime LED Warranty



HOLE CUT-OUT: 2.313"

MCL52/54 SERIES

2" Round Sealed LED Marker/Clearance Lights

PC Rated

MCL54AB MCL54RB

- Sonically sealed, waterproof
- Available with standard PL-10 or optional weathertight connection
- PC rated: functions as both clearance and side marker light when properly mounted on a 45 degree angle
- Available in flange mount and grommet mount models

MCL52AB



MCL52RB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW - 5 DIODES			
MCL52AB	MCL52ABP	Flange mount, PL-10 connection	20
MCL52AMB	MCL52AMBP	Flange mount, weathertight connection; pigtail included	20
MCL54AB	MCL54ABP	Grommet mount, PL-10 connection	20
RED - 5 DIODES			
MCL52RB	MCL52RBP	Flange mount, PL-10 connection	20
MCL52RMB	MCL52RMBP	Flange mount, weathertight connection; pigtail included	20
MCL54RB	MCL54RBP	Grommet mount, PL-10 connection	20
ACCESSORIES			
A46PB	A46PBP	Straight PL-10 plug, 6" lead	100
A86PB	A86PBP	Straight PL-10 plug, 18" lead	100
AL42PB	AL42PBP	Weathertight pigtail	100
A54GB	A54GBP	2" Flush mount grommet	100
A54GK	A54GKP	2" Kit: A54GB and A46PB	100
A55CB	A55CBP	2" Chrome trim ring	20
BK5557GB	BK5557GBP	Cam-on mounting bracket	50
A52GB	A52GBP	Gasket for flange mount, black	100

detail of weathertight connection on MCL52AMB/RMB; pigtail included

FMVSS	P2 PC
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.063A
WT/DIMS	Flange mount: .088 lbs. / 2.938" x 2.938" x 0.938"
	Grommet mount: .066 lbs. / 2.063" x 2.063" x 0.875"
WARRANTY	Lifetime LED Warranty



MCL52

HOLE CUT-OUT: 2.313"



MCL54

HOLE CUT-OUT: 2.313"

MCL157 SERIES

GloLight® 2.5" Round Sealed LED Marker/Clearance Lights

PATENTED TECHNOLOGY

- Sonically sealed, waterproof
- Accepts standard two-pin PL-10 plug

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW - 9 DIODES			
MCL157AB	MCL157ABP	Light only	20
RED - 9 DIODES			
MCL157RB	MCL157RBP	Light only	20
ACCESSORIES			
A46PB	A46PBP	Straight PL-10 plug, 6" lead	100
A86PB	A86PBP	Straight PL-10 plug, 18" lead	100
A55GB	A55GBP	Flush mount grommet (open back)	50
A56GB	A56GBP	Recess mount grommet (closed back)	100
A57GB	A57GBP	Recess mount grommet (open back)	50
A55GK	A55GKP	Kit: A55GB and A46PB	100
A57GK	A57GKP	Kit: A57GB and A46PB	100
A57CB	A57CBP	Chrome trim ring	20
BK5557GB	BK5557GBP	Cam-on mounting bracket	50

MCL157AB

MCL157RB

FMVSS	P2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.099A
WT/DIMS	.132 lbs. / 2.5" x 2.5" x 1.125"
WARRANTY	Lifetime LED Warranty



HOLE CUT-OUT: 2.75"

MCL57 SERIES

2.5" Round Sealed LED Marker/Clearance Lights

- Sonically sealed, waterproof
- Accepts standard two-pin PL-10 plug
- Available in 12V and 24V models

MCL57AB

MCL57RB

MCL57ACB/RCB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW - 3 DIODES			
MCL57AB	MCL57ABP	Light only, 12V	20
MCL57A24B	MCL57A24BP	Light only, 24V	20
MCL57ACB	MCL57ACBP	Clear lens light only, 12V	20
RED - 3 DIODES			
MCL57RB	MCL57RBP	Light only, 12V	20
MCL57RKB	MCL57RKBP	Kit with grommet and plug	20
MCL57R1224B	MCL57R1224BP	Light only, 12-24V	20
MCL57RCB	MCL57RCBP	Clear lens light only, 12V	20
ACCESSORIES			
A46PB	A46PBP	Straight PL-10 plug, 6" lead	100
A86PB	A86PBP	Straight PL-10 plug, 18" lead	100
A55GB	A55GBP	Flush mount grommet (open back)	50
A56GB	A56GBP	Recess mount grommet (closed back)	100
A57GB	A57GBP	Recess mount grommet (open back)	50
A55GK	A55GKP	Kit: A55GB and A46PB	100
A57GK	A57GKP	Kit: A57GB and A46PB	100
A57CB	A57CBP	Chrome trim ring	20
BK5557GB	BK5557GBP	Cam-on mounting bracket	50
RETAIL			
MCL57AK	Retail Ready	Yellow kit with A55GB & A46PB, clam	12
MCL57RK		Red kit with A55GB & A46PB, clam	12



HOLE CUT-OUT: 2.75"

FMVSS	P2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.06A
WT/DIMS	.132 lbs. / 2.5" x 2.5" x 1"
WARRANTY	Lifetime LED Warranty

MCL527 SERIES

FLEET Count™ 2.5" Round Sealed LED Marker/Clearance Lights

- Sonically sealed, waterproof
- Accepts standard two-pin PL-10 plug
- Multiple mounting options available

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW - 2 DIODES			
MCL527AB	MCL527ABP	Light only	20
MCL527AMB	MCL527AMBP	Light only, weathertight connection	20
MCL527AFB	MCL527AFBP	Flange mount	20
RED - 2 DIODES			
MCL527RB	MCL527RBP	Light only	20
MCL527RMB	MCL527RMBP	Light only, weathertight connection	20
MCL527RFB	MCL527RFBP	Flange mount	20
ACCESSORIES			
A46PB	A46PBP	Straight PL-10 plug, 6" lead	100
A86PB	A86PBP	Straight PL-10 plug, 18" lead	100
A55GB	A55GBP	Flush mount grommet (open back)	50
A56GB	A56GBP	Recess mount grommet (closed back)	100
A57GB	A57GBP	Recess mount grommet (open back)	50
A55GK	A55GKP	Kit: A55GB and A46PB	100
A57GK	A57GKP	Kit: A57GB and A46PB	100
A57CB	A57CBP	Chrome trim ring	20
BK5557GB	BK5557GBP	Cam-on mounting bracket	50
RETAIL			
MCL527AK		Yellow kit with A57GB & A46PB, clam	12
MCL527AK6	Retail Ready	Yellow kit with A57GB & A46PB, clam	6
MCL527AS		Yellow light only, clam	12
MCL527RK		Red kit with A57GB & A46PB, clam	12
MCL527RK6		Red kit with A57GB & A46PB, clam	6
MCL527RS		Red light only, clam	12

FMVSS	P2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.034A
WT/DIMS	Grommet Mount: .088 lbs. / 2.5" x 2.5" x 1.063"
	Flange Mount: .088lbs. / 3.438" x 3.438" x .938"
WARRANTY	Lifetime LED Warranty

MCL527AB

MCL527AFB

MCL527RB

MCL527RFB



HOLE CUT-OUT: 2.75"



HOLE CUT-OUT: 2.75"

MCL58 SERIES

2.5" Round Sealed LED Marker/Clearance Lights

PC Rated

- Sonically sealed, waterproof
- Available with standard PL-10 or optional weathertight connection
- Multiple mounting options available
- PC rated: functions as both clearance and side marker light when properly mounted on a 45 degree angle

MCL58AB

MCL58ACB

MCL58RB

MCL58AMFB

MCL58RMFB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW - 7 DIODES			
MCL58AB	MCL58ABP	Light only, PL-10	20
MCL58ACB	MCL58ACBP	Clear lens, yellow diodes, light only, PL-10	20
MCL58APMB	MCL58APMBP	Light only, weathertight connection	20
MCL58AMFB	MCL58AMFBP	Flange mount, weathertight connection	50
RED - 7 DIODES			
MCL58RB	MCL58RBP	Light only	20
MCL58RPMB	MCL58RPMBP	Light only, weathertight connection	20
MCL58RMFB	MCL58RMFBP	Flange mount, weathertight connection	50
ACCESSORIES			
A46PB	A46PBP	Straight PL-10 plug, 6" lead	100
A86PB	A86PBP	Straight PL-10 plug, 18" lead	100
AL42PB	AL42PBP	Weathertight pigtail	100
AL42PG	AL42PGP	Weathertight pigtail, .180 bullets	100
A55GB	A55GBP	Flush mount grommet (open back)	50
A56GB	A56GBP	Recess mount grommet (closed back)	100
A57GB	A57GBP	Recess mount grommet (open back)	50
A55GK	A55GKP	Kit: A55GB and A46PB	100
A57GK	A57GKP	Kit: A57GB and A46PB	100
A57CB	A57CBP	Chrome trim ring	20
BK5557GB	BK5557GBP	Cam-on mounting bracket	50

FMVSS	P2 PC
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.057A
WT/DIMS	Grommet Mount: .132 lbs. / 2.5" x 2.5" x 0.938"
	Flange Mount: .112lbs. / 3.42" x 3.42" x 1.30"
WARRANTY	Lifetime LED Warranty


weathertight connection: MCL58APMB/RPMB


weathertight connection: MCL58AMFB/RMFB





MCL59 SERIES

2.5" Round Sealed LED Marker/ Clearance Lights with Reflex

- Sonically sealed, waterproof
- Accepts standard two-pin PL-10 plug
- Multiple mounting options available
- Built-in reflex eliminates the need for a separate reflector

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW - 8 DIODES			
MCL59AB	MCL59ABP	Light only	20
MCL59A1224B	MCL59A1224B	Light only, 12/24V	20
RED - 8 DIODES			
MCL59RB	MCL59RBP	Light only	20
MCL59R1224B	MCL59R1224B	Light only, 12/24V	20
ACCESSORIES			
A46PB	A46PBP	Straight PL-10 plug, 6" lead	100
A86PB	A86PBP	Straight PL-10 plug, 18" lead	100
A55GB	A55GBP	Flush mount grommet (open back)	50
A56GB	A56GBP	Recess mount grommet (closed back)	100
A57GB	A57GBP	Recess mount grommet (open back)	50
A55GK	A55GKP	Kit: A55GB and A46PB	100
A57GK	A57GKP	Kit: A57GB and A46PB	100
A57CB	A57CBP	Chrome trim ring	20
BK5557GB	BK5557GBP	Cam-on mounting bracket	50

FMVSS	A P2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.047A
WT/DIMS	.088 lbs. / 2.5" x 2.5" x 1.063"
WARRANTY	Lifetime LED Warranty



MCL59AB





MCL59RB



HOLE CUT-OUT: 2.75"

MCL002 SERIES

2.5" Recess Flange Mount LED Marker/ Clearance Lights with Locking Clip



MCL002AXB



MCL002RXB

- Sonically sealed, waterproof
- Recess flange mount design fits 2.75" diameter hole cut-out
- Locking clip for PL-10 style plugs secures connection against road vibration
- Built-in reflex eliminates the need for a separate reflector
- Available in bulk and polypack packaging

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW - 1 DIODE			
MCL002AXB	MCL002AXBP	Reflex flange, locking clip	50
RED - 1 DIODE			
MCL002RXB	MCL002RXBP	Reflex flange, locking clip	50

FMVSS	A P2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.45A
WT/DIMS	.112 lbs / 3.52" x 3.52" x 1.56"
WARRANTY	Lifetime LED Warranty



AL91 SERIES

Mini Thinline Sealed LED Marker/Clearance Lights

PC Rated

- Sonically sealed, waterproof
- Standard models accept standard 1- or 2-wire plugs
- Hard wired design available in 1- and 2-wire models
- Single wire design grounds through mounting hardware
- Two-wire design includes both lead and ground wire for mounting to all surfaces
- PC rated light functions as both clearance and side marker light when properly mounted on a 45 degree angle



AL91AB

AL91RB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW - 3 DIODES			
AL91AB	AL91ABP	PC rated	50
AL91CAB	AL91CABP	PC rated, clear lens	50
AL91A1224B	AL91A1224BP	PC rated, 12-24V	50
MCL91AB	MCL91ABP	Kit: AL91AB, A91CB & A91LW	50
AL82AB	AL82ABP	PC rated, hard wired, 2-wire	50
MCL96AB	MCL96ABP	P2 rated kit, hard wired, 1-wire, A91BB base	50
RED - 3 DIODES			
AL91RB	AL91RBP	PC rated	50
MCL91RB	MCL91RBP	Kit: AL91RB, A91CB & A91LW	50
AL82RB	AL82RBP	PC rated, hard wired, 2-wire	50
MCL96RB	MCL96RBP	P2 rated kit, hard wired, 1-wire, A91BB base	50
ACCESSORIES			
A46PB	A46PBP	2-wire PL-10 plug, 6” lead	100
A86PB	A86PBP	2-wire PL-10 plug, 18” lead	100
A90CB	A90CBP	Chrome snap-on cover	50
A91LW	A91LWP	1-wire plug, 12” lead	100
A91BB	A91BBP	Black base, self grounding	100
A91BOB	A91BOBP	Black base, open back	100
A91CB	A91CBP	Chrome base, self grounding	100
A91OB	A91OBP	Chrome base, open back	100
A91GB	A91GBP	Grommet	100
RETAIL			
MCL91AK		Yellow P2 kit with A91CB & A91LW, clam	12
MCL90AS		Yellow P2 light only, clam	12
MCL91RK	Retail Ready	Red P2 kit with A91CB & A91LW, clam	12
MCL90RS		Red P2 light only, clam	12

FMVSS	PC (unless noted)
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.051A
WT/DIMS	.088 lbs. 2.5” x 1.25” x 1”
WARRANTY	Lifetime LED Warranty



AL90 SERIES

FLEET Count™ Mini Thinline Sealed LED Marker/Clearance Light

AL90AB

AL90RB

AL90RCB



- Sonically sealed, waterproof
- Accept standard 1- or 2-wire plugs
- Single wire design grounds through mounting hardware
- Two-wire design includes both lead and ground wire for mounting to all surfaces

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW - 1 DIODE			
AL90AB	AL90ABP	Light only	50
RED - 1 DIODE			
AL90RB	AL90RBP	Light only	50
AL90RCB	AL90RCBP	Clear lens, red, light only	??
ACCESSORIES			
A46PB	A46PBP	2-wire PL-10 plug, 6" lead	100
A86PB	A86PBP	2-wire PL-10 plug, 18" lead	100
A90CB	A90CBP	Chrome snap-on cover	50
A91LW	A91LWP	1-wire plug, 12" lead	100
A91BB	A91BBP	Black base, self grounding	100
A91BOB	A91BOBP	Black base, open back	100
A91CB	A91CBP	Chrome base, self grounding	100
A91OB	A91OBP	Chrome base, open back	100
A91GB	A91GBP	Grommet	100
RETAIL			
AL90AK	Retail Ready	Yellow kit with A91BB & A91LW, clam	12
AL90AS		Yellow light only, clam	12
AL90RK		Red kit with A91BB & A91LW, clam	12
AL90RS		Red light only, clam	12

FMVSS	P2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.023A
WT/DIMS	.044 lbs. / 2.5" x 1.25" x 1"
WARRANTY	Lifetime LED Warranty

MCL165 SERIES

GloLight® Thinline Sealed LED Marker/Clearance Lights

PATENTED TECHNOLOGY

- Sonically sealed, waterproof
- Accept standard 1- or 2-wire plugs
- Single wire design grounds through mounting hardware
- Two-wire design includes both lead and ground wire for mounting to all surfaces

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW - 10 DIODES			
MCL165AB	MCL165ABP	Light only	20
RED - 10 DIODES			
MCL165RB	MCL165RBP	Light only	20
ACCESSORIES			
A65B	A65BP	Black bracket	50
A65P	A65PP	Single wire plug, .156 male bullet	50
A65PB	A65PBP	Kit: A65B black bracket & A65P plug	50
A66PB	A66PBP	Kit: Gray bracket & A65P plug	50
A67CB	A67CBP	Kit: Chrome bracket & A65P plug	50
A68PB	A68PBP	Kit: Black bracket & 2-wire plug	50
For more details on mounting and wiring accessories, see Accessories section at back of catalog.			

MCL165AB

MCL165RB

FMVSS	P2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.09A
WT/DIMS	.066 lbs. / 3.875" x 1.25" x 1"
WARRANTY	Lifetime LED Warranty





MCL65AB



MCL65RB

MCL75AB

MCL75RB

MCL77AB

MCL77RB

MCL65 SERIES

Thinline Sealed LED Marker/Clearance Lights

- Sonically sealed, waterproof
- Accept standard 1- or 2-wire plugs
- Single wire design grounds through mounting hardware
- Two-wire design includes both lead and ground wire for mounting to all surfaces

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		YELLOW	
MCL65AB	MCL65ABP	12V, 3 diodes	20
MCL65A24B	MCL65A24BP	24V, 3 diodes	20
MCL65CAB	MCL65CABP	12V, 3 diodes, clear lens	20
MCL65AKB	MCL65AKBP	12V, 3 diodes, kit with A67CB1, A68P	20
MCL67AB	MCL67ABP	12V, 3 diodes, kit with A65PB	20
MCL75AB	MCL75ABP	12V, 4 diodes	20
MCL77AB	MCL77ABP	12V, 4 diodes, kit with A65PB	20
		RED	
MCL65RB	MCL65RBP	12V, 3 diodes	20
MCL65R24B	MCL65R24BP	24V, 3 diodes	20
MCL65CRB	MCL65CRBP	12V, 3 diodes, clear lens	20
MCL65RKB	MCL65RKBP	12V, 3 diodes, kit with A67CB1, A68P	20
MCL67RB	MCL67RBP	12V, 3 diodes, kit with A65PB	20
MCL75RB	MCL75RBP	12V, 4 diodes	20
MCL77RB	MCL77RBP	12V, 4 diodes, kit with A65PB	20
		ACCESSORIES	
A65B	A65BP	Black bracket	50
A65P	A65PP	Single wire plug, .156 male bullet	50
A68P	A68PP	Two wire plug, 6" lead	
A65PB	A65PBP	Kit: A65B black bracket & A65P plug	50
A66PB	A66PBP	Kit: Gray bracket & A65P plug	50
A67CB	A67CBP	Kit: Chrome bracket & A65P plug	50
A68PB	A68PBP	Kit: Black bracket & 2-wire plug	50

For more details on mounting and wiring accessories, see Accessories section at back of catalog.

FMVSS	P2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.048A
WT/DIMS	.066 lbs. / 3.938" x 1.25" x 1.25"
WARRANTY	Lifetime LED Warranty



MCL61 SERIES

FLEET Count™ Thinline Sealed LED Marker/Clearance Lights

- Sonically sealed, waterproof
- Accept standard 1- or 2-wire plugs
- Single wire design grounds through mounting hardware
- Two-wire design includes both lead and ground wire for mounting to all surfaces

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW - 2 DIODES			
MCL61AB	MCL61ABP	Light only	20
RED - 2 DIODES			
MCL61RB	MCL61RBP	Light only	20
ACCESSORIES			
A65B	A65BP	Black bracket	50
A65P	A65PP	Single wire plug, .156 male bullet	50
A68P	A68PP	Two wire plug, 6" lead	
A65PB	A65PBP	Kit: A65B black bracket & A65P plug	50
A66PB	A66PBP	Kit: Gray bracket & A65P plug	50
A67CB	A67CBP	Kit: Chrome bracket & A65P plug	50
A68PB	A68PBP	Kit: Black bracket & 2-wire plug	50
For more details on mounting and wiring accessories, see Accessories section at back of catalog.			
RETAIL			
MCL61AK	Retail Ready	Yellow kit with A65PB, clam	12
MCL61RK		Red kit with A65PB, clam	12
MCL61AS		Yellow light only, clam	12
MCL61RS		Red light only, clam	12

FMVSS	P2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.051A
WT/DIMS	.066 lbs. / 4" x 1.25" x 1"
WARRANTY	Lifetime LED Warranty



MCL61AB

MCL61RB



MCL63 SERIES

Miro-Flex™ Thinline Sealed LED Marker/Clearance Lights

MCL63AB

MCL63CAB



MCL63CRB

MCL63RB

- Sonically sealed, waterproof
- Accept standard 1- or 2-wire plugs
- Single wire design grounds through mounting hardware
- Two-wire design includes both lead and ground wire for mounting to all surfaces

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW - 4 DIODES			
MCL63AB	MCL63ABP	Light only	20
MCL63CAB	MCL63CABP	Light only, clear lens	20
RED - 4 DIODES			
MCL63RB	MCL63RBP	Light only	20
MCL63CRB	MCL63CRBP	Light only, clear lens	20
ACCESSORIES			
A65B	A65BP	Black bracket	50
A65P	A65PP	Single wire plug, .156 male bullet	50
A68P	A68PP	Two wire plug, 6" lead	
A65PB	A65PBP	Kit: A65B black bracket & A65P plug	50
A66PB	A66PBP	Kit: Gray bracket & A65P plug	50
A67CB	A67CBP	Kit: Chrome bracket & A65P plug	50
A68PB	A68PBP	Kit: Black bracket & 2-wire plug	50

For more details on mounting and wiring accessories, see Accessories section at back of catalog.

FMVSS	P2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.051A
WT/DIMS	.066 lbs. / 4" x 1.25" x 1"
WARRANTY	Lifetime LED Warranty



MCL61/65 SERIES

Thinline Sealed LED Fender Lights

- Sonically sealed, waterproof
- Accept standard 1- or 2-wire plugs
- Single wire design grounds through mounting hardware
- Two-wire design includes both lead and ground wire for mounting to all surfaces

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
DUAL RED/YELLOW - 10 DIODES			
MCL65ARB	MCL65ARBP	Light only	20
MCL65CARB	MCL65CARBP	Light only, clear lens	20
MCL67ARB	MCL67ARBP	Kit with A65PB bracket & plug	20
DUAL RED/YELLOW - 2 DIODES			
MCL61ARB	MCL61ARBP	Light only	20
MCL61AR26BK	MCL61AR26BKP	Kit with A67BB black base & 26" power wire with .150 male bullet	20
ACCESSORIES			
A67BB	A67BBP	Black fender bracket	50
A67GB	A67GBP	Gray fender bracket	50
A67CVB	A67CVBP	Curved fender bracket, gray	50
A65B	A65BP	Black bracket	50
A65P	A65PP	Single wire plug, .156 male bullet	50
A68P	A68PP	Two wire plug, 6" lead	50
A65PB	A65PBP	Kit: A65B black bracket & A65P plug	50
A66PB	A66PBP	Kit: Gray bracket & A65P plug	50
A67CB	A67CBP	Kit: Chrome bracket & A65P plug	50
A68PB	A68PBP	Kit: Black bracket & 2-wire plug	50

For more details on mounting and wiring accessories, see Accessories section at back of catalog.

FMVSS	P2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.048A
WT/DIMS	.066 lbs. / 3.875" x 1.25" x 0.875"
WARRANTY	Lifetime LED Warranty

MCL65ARB



MCL65CARB

MCL61ARB



light with base



light only



A67BB

MCL99 SERIES

Mini Sealed LED Horizontal-Vertical Marker/Clearance Lights

MCL99AB

MCL99RB

MCL99AC1B

MCL99RC1B

- Sealed, waterproof design
- Surface mount installation at either horizontal or vertical
- Single wire design grounds through mounting hardware
- Two-wire design includes both lead and ground wire for mounting to all surfaces

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW - 1 DIODE			
MCL99AB	MCL99ABP	2-wire	20
MCL99AC1B	MCL99AC1BP	Clear lens, single wire, self-grounding	50
RED - 1 DIODE			
MCL99RB	MCL99RBP	2-wire	20
MCL99RC1B	MCL99RC1BP	Clear lens, single wire, self-grounding	50

FMVSS	P2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - .06A
WT/DIMS	.088 lbs. / 2.5” x 1.125” x 0.625”
WARRANTY	Lifetime LED Warranty



MCL13 SERIES

Mini Sealed LED Surface Mount Marker/Clearance Lights

- Sonically sealed, waterproof
- Single wire design grounds through mounting hardware
- Two-wire design includes both lead and ground wire for mounting to all surfaces

MCL13A2B

MCL13CA2B

MCL13CR2B

MCL13R2B

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW - 2 DIODES			
MCL13A2B	MCL13A2BP	2-wire	20
MCL13A2MB	MCL13A2MBP	2-wire, .156 male bullets, 5.5-in. leads	20
MCL13APG	MCL13APGP	2-wire, .156 male bullets, 12-in. leads	20
MCL13A21PG	MCL13A21PGP	2-wire, .156 female plugs	20
MCL131A2B	MCL131A2BP	1-wire, self-grounding	20
MCL13CA2B	MCL13CA2BP	2-wire, clear lens	20
MCL13CA3B	MCL13CA3BP	2-wire, clear lens, no ring on ground	50
MCL131CA3B	MCL131CA3BP	1-wire, clear lens, self grounding	50
MCL131A210B	MCL131A210BP	1-wire, self grounding, fits #10 screws	20
MCL131AC210B	MCL131AC210BP	1-wire, clear lens, self grounding, fits #10 screws	20
RED - 2 DIODES			
MCL13R2B	MCL13R2BP	2-wire	20
MCL13R2MB	MCL13R2MBP	2-wire, .156 male bullets	20
MCL13R21PG	MCL13R21PGP	2-wire, .156 female plugs	20
MCL131R2B	MCL131R2BP	1-wire	20
MCL13CR2B	MCL131CR2BP	2-wire, clear lens	20
MCL131CR3B	MCL131CR3BP	1-wire, clear lens, self grounding	50
MCL131R210B	MCL131R210BP	1-wire, self grounding, fits #10 screws	20
MCL131RC210B	MCL131RC210BP	1-wire, clear lens, self grounding, fits #10 screws	20
ACCESSORIES			
A13B2B	A13B2BP	Black base/bezel	100
A13C2B	A13C2BP	Chrome base/bezel	100
A13NCC2B	A13NCCBP	Unfinished base/bezel	100
A13B210B	A13B210BP	Matte black base/bezel, fits #10 screws	100
A13C210B	A13C210BP	Chrome base/bezel, fits #10 screws	100
A13G2B	A13G2BP	Gasket	200
RETAIL			
MCL13ATRS	Retail Ready	Yellow, 2-wire, chrome bezel	12
MCL13AS		Yellow 2-wire light only	12
MCL13RTRS		Red, 2-wire, chrome bezel	12
MCL13RS		Red 2-wire light only	12



FMVSS	P2 P3 (except UCL13)
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.046A
WT/DIMS	.088 lbs. / 2.5" x 1.063" x 0.688"
WARRANTY	Lifetime LED Warranty

MCL14 SERIES

Mini Sealed LED Horizontal-Vertical Marker/Clearance Lights

PC Rated

- Sonically sealed, waterproof
- Surface mount installation at either horizontal or vertical
- Single wire design grounds through mounting hardware
- Two-wire design includes both lead and ground wire for mounting to all surfaces
- Available in red, yellow, and clear lens

MCL14AB

MCL14RB

MCL14CABF

MCL14CRBF

MCL14 clear lens, unlit

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW - 3 DIODES			
MCL14AB	MCL14ABP	2-wire	20
MCL14ABF	MCL14ABFP	2-wire, female PL-10 plug	20
MCL14AGB	MCL14AGBP	1-wire, self grounding, 6-in. lead	20
MCL14A12GB	MCL14A12GBP	1-wire, self grounding, 12-in. lead	20
MCL14AGPB	MCL14AGPBP	1-wire, .180 male bullet	20
MCL14CABF	MCL14CABFP	Clear lens, 2-wire, .156 female barrels	20
MCL14CAGB	MCL14CAGBP	Clear lens, 1-wire, self grounding	20
RED - 3 DIODES			
MCL14RB	MCL14RBP	2-wire	20
MCL14R2B	MCL14R2BP	2-wire, .180 male bullets	20
MCL14RBF	MCL14RBFP	2-wire, female plug	20
MCL14RGB	MCL14RGBP	1-wire, self grounding	20
MCL14RPG	MCL14RPGP	2-wire, .156 male bullets, 12-in. leads	20
MCL14CRGB	MCL14CRGBP	Clear lens, 1-wire, self grounding	20
MCL14CRBF	MCL14CRBFP	Clear lens, 2-wire, .156 female barrels	20
ACCESSORIES			
A13C2B	A13C2BP	Chrome base/bezel	100
A13B2B	A13B2BP	Black base/bezel	100
A13G2B	A13G2BP	Gasket	200



FMVSS	P2 PC
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.06A
WT/DIMS	.088 lbs. / 2.5" x 1.125" x 0.625"
WARRANTY	Lifetime LED Warranty

A13C2B

MCL15 SERIES
Surface Mount LED Marker/Clearance Lights

- Sonically sealed, waterproof
- Surface mount installation
- Hard wired, includes both lead and ground wire with molded .180 male bullets
- Chrome finish ABS trim ring included with kits

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW - 2 DIODES			
MCL15APG	MCL15APGP	Light only, .180 male bullets	20
MCL15AKPG	MCL15AKPGP	Kit: MCL15APG, chrome trim ring	20
RED - 2 DIODES			
MCL15RPG	MCL15RPGP	Light only, .180 male bullets	20
MCL15RKPG	MCL15RKPGP	Kit: MCL15RPG, chrome trim ring	20
ACCESSORIES			
A15CB	A15CBP	Chrome base/bezel	100
A15GB	A15GBP	Gasket	50
A15CGB	A15CGBP	Chrome base/bezel and gasket	100

MCL15APG

MCL15AKPG

MCL15RPG

MCL15RKPG

FMVSS	P2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.047A
WT/DIMS	Light: .088 lbs. / 2.625" x 1.375" x .563"
	Kit: .092 lbs. / 3.938" x 1.344" x .688"
WARRANTY	Lifetime LED Warranty



MCL15APG/RPG



MCL15AKPG/RKPG

MCL299 SERIES
Sealed LED Marker/Clearance Light



MCL299AB

MCL299RB

- Sonically sealed, waterproof
- Adhesive mount
- Hard wired, includes separate ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW - 1 DIODE			
MCL299AB	MCL299ABP	Light only	50
MCL290APG	MCL290APGP	Light, .180 male bullets	50
RED - 1 DIODE			
MCL299RB	MCL299RBP	Light only	50
MCL290RPG	MCL290RPGP	Light, .180 male bullets	50

FMVSS	PC
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	Yellow: 12.8VDC - 0.12A
	Red: 12.8V - 0.065A
WT/DIMS	.03 lbs. / 1.50” x .625” x .75”
WARRANTY	Lifetime LED Warranty



MCL17/19 SERIES

Miro-Flex™ Surface Mount Sealed LED Marker/Clearance Lights

- Sonically sealed, waterproof
- Two-wire design includes both lead and ground wire for mounting to all surfaces
- Snap-on chrome trim ring included
- Available in 3-LED 4” model and 4-LED 6” model

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		YELLOW	
MCL17AB	MCL17ABP	3-LED	20
MCL17ABB	MCL17ABBP	3-LED, black trim ring	20
MCL17CAB	MCL17CABP	3-LED, clear lens	20
MCL19AB	MCL19ABP	4-LED	20
MCL19CAB	MCL19CABP	4-LED, clear lens	20
		RED	
MCL17RB	MCL17RBP	3-LED	20
MCL17RBB	MCL17RBBP	3-LED, black trim ring	20
MCL17CRB	MCL17CRBP	3-LED, clear lens	20
MCL19RB	MCL19RBP	4-LED	20
MCL19CRB	MCL19CRBP	4-LED, clear lens	20
		ACCESSORIES	
A17GB	A17GBP	Black gasket for 3-LED models	100
A19CB	A19CBP	Chrome bezel	50

FMVSS	P2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	MCL17: 12.8VDC - 0.047A
	MCL19: 12.8VDC - 0.051A
WT/DIMS	MCL17: .088 lbs. / 4.188” x 1.375” x .75”
	MCL19: .132 lbs. / 5.75” x 1.563” x .75”
WARRANTY	Lifetime LED Warranty



MCL17



MCL19

MCL17AB

MCL17CAB/CRB

MCL17RB

MCL19AB

MCL19CAB/CRB

MCL19RB


A17GB

MCL0030 SERIES

Surface Mount LED Marker/Clearance Lights with Reflex



MCL0030ABB



MCL0030RBB

- Ultrathin design - only 3/8” thick
- Surface mount on 2.7” centers
- Snap-on lens with reflex eliminates the need for a separate reflector
- Hard wired

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW - 1 DIODE			
MCL0030ABB	MCL0030ABBP	Hard wired	20
RED - 1 DIODE			
MCL0030RBB	MCL0030RBBP	Hard wired	20
ACCESSORIES			
A0028CRB	A0028CRBP	Chrome snap-on bezel	50

FMVSS	A P2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.073A
WT/DIMS	.08 lbs. / 3.77” x 1.79” x .36”
WARRANTY	Lifetime LED Warranty





MCL0039 SERIES

2.5" Round LED Marker/Clearance Lights with Reflex

- Surface mount black base
- Snap-on lens with reflex eliminates the need for a separate reflector
- Hard wired with power and ground wires

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW - 1 DIODE			
MCL0039ABB	MCL0039ABBP	Hard wired	20
RED - 1 DIODE			
MCL0039RBB	MCL0039RBBP	Hard wired	20

FMVSS	A P2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.073A
WT/DIMS	.08 lbs. / 2.5" x 2.5" x .8"
WARRANTY	Lifetime LED Warranty



MCL0039ABB

MCL0039RBB



MCL31 SERIES

Surface Mount LED Marker/ Clearance Lights with Reflex



MCL31AB

MCL31RB

- Snap-on, replaceable lens
- Lens with reflex eliminates need for separate reflector
- Two-wire design includes both lead and ground wire for mounting to all surfaces

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW - 6 DIODES			
MCL31AB	MCL31ABP	Light only, white base	20
RED - 6 DIODES			
MCL31RB	MCL31RBP	Light only, white base	20
MCL31RPG	MCL31RPGP	Light only, white base, .180 male bullets	20

FMVSS	A P2
MATERIALS	Acrylic lens, ABS housing
VOLT/AMP	12.8VDC - 0.040A
WT/DIMS	.132 lbs. / 4" x 2.063" x 1"
WARRANTY	Lifetime LED Warranty



MCL32 SERIES

Surface Mount LED Marker/ Clearance Lights with Reflex

- Snap-on, replaceable lens
- Lens with reflex eliminates need for separate reflector
- Two-wire design includes both lead and ground wire for mounting to all surfaces

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW - 3 DIODES			
MCL32AB	MCL32ABP	Light only, white base	100
MCL32ATB	MCL32ATBP	Supplemental turn, white base	50
MCL32ABB	MCL32ABBP	Light only, black base	100
RED - 3 DIODES			
MCL32RB	MCL32RBP	Light only, white base	100
MCL32RBB	MCL32RBBP	Light only, black base	100
ACCESSORIES			
A32AB	A32ABP	Yellow replacement lens	10
A32RB	A32RBP	Red replacement lens	50
RETAIL			
MCL32ABS	Retail Ready	Yellow light with black base	12
MCL32RBS		Red light with black base	12
MCL32AS		Yellow light with white base	12
MCL32RS		Red light with white base	12

FMVSS	A P2
MATERIALS	Acrylic lens, ABS housing
VOLT/AMP	12.8VDC - 0.6A
WT/DIMS	.132 lbs. / 4" x 2" x 1"
WARRANTY	Lifetime LED Warranty





MCL32AB



MCL32ABB

MCL32RB

MCL32RBB

MCL0032 SERIES

Surface Mount LED Marker/ Clearance Lights with Reflex



MCL0032ABB

MCL0032RBB



- Snap-on, replaceable lens
- Surface mount base, mounts on 3” centers
- Lens with reflex eliminates need for separate reflector
- Two-wire design includes both lead and ground wire for mounting to all surfaces

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW - 1 DIODE			
MCL0032ABB	MCL0032ABBP	Light only, black base	100
RED - 1 DIODE			
MCL0032RBB	MCL0032RBBP	Light only, black base	100
ACCESSORIES			
A32AB	A32ABP	Yellow replacement lens	50
A32RB	A32RBP	Red replacement lens	50
RETAIL			
MCL0032ABS	Retail Ready	Yellow light with black base, clam	12
MCL0032RBS		Red light with black base, clam	12

FMVSS	A P2
MATERIALS	Acrylic lens, ABS housing
VOLT/AMP	12.8VDC - 0.6A
WT/DIMS	.132 lbs. / 4” x 2” x 1”
WARRANTY	Lifetime LED Warranty

MCL35AEB

Surface Mount LED Marker/ Clearance Light with Reflex

- Surface ear mount black base, mounts on 3.25” centers
- Lens with reflex eliminates need for separate reflector
- Single wire design grounds through mounting hardware

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW - 3 DIODES			
MCL35AEB	MCL35AEBP	Light only	50

FMVSS	A P2
MATERIALS	Acrylic lens, ABS housing
VOLT/AMP	12.8VDC - 0.07A
WT/DIMS	.132 lb / 3.75” x 2.03” x .96”
WARRANTY	Lifetime LED Warranty



MCL35AEB



MCL35A32G

Surface Mount LED Marker/ Clearance Light with Reflex

- Surface mount black base, mounts on 3-5/16” centers
- Lens with reflex eliminates need for separate reflector
- Self grounding; 32” power wire with .180 male bullet

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW - 6 DIODES			
MCL35A32G	MCL35A32GP	Light, 32” lead with .180 male bullet	50

FMVSS	A P2
MATERIALS	Acrylic lens, ABS housing
VOLT/AMP	12.8VDC - 0.165A
WT/DIMS	.110 lbs. / 3.875” x 2.375” x 0.938”
WARRANTY	Lifetime LED Warranty



MCL35A32G



MCL36 SERIES

Stud Mount LED Marker/ Clearance Light with Reflex



MCL36AB



MCL36RB

- Stud mount black base; two-wire design
- Lens with reflex eliminates need for separate reflector

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW - 6 DIODES			
MCL36AB	MCL36ABP	Hard wired	20
RED - 6 DIODES			
MCL36RB	MCL36RBP	Hard wired	20
RETAIL			
MCL36AS	Retail Ready	Yellow light with hardware, clam	12
MCL36AS6		Yellow light with hardware, clam	6

FMVSS	A P2
MATERIALS	Acrylic lens, ABS housing
VOLT/AMP	12.8VDC - 0.054A
WT/DIMS	.110 lbs. / 2.875" x 2.125" x .938"
WARRANTY	Lifetime LED Warranty



MCL40/44 SERIES

Surface Mount LED Marker/ Clearance Lights with Reflex

- Select from 2-LED and 6-LED models in yellow and red
- Snap-on, replaceable lens
- Surface mount white base, mounts on 3” centers
- Lens with reflex eliminates need for separate reflector
- Single wire and two-wire designs available

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		YELLOW	
MCL40AB	MCL40ABP	2-LED, 2-wire, power and ground	20
MCL40APB	MCL40APBP	2-LED, 2-wire .180 male bullets	20
MCL44AB	MCL44ABP	6-LED, 2-wire, power and ground	20
MCL44AB1	MCL44AB1P	6-LED, 1-wire, self grounding	20
		RED	
MCL40RB	MCL40RBP	2-LED, 2-wire, power and ground	20
MCL44RB	MCL44RBP	6-LED, 2-wire, power and ground	20
MCL44RB1	MCL44RB1P	6-LED, 1-wire, self grounding	20
		ACCESSORIES	
A44AB	A44ABP	Yellow replacement lens	10
A44RB	A44RBP	Red replacement lens	10
		RETAIL	
MCL40AS	Retail Ready	Yellow 2-LED, 2-wire, clam	12
MCL40RS		Red 2-LED, 2-wire, clam	12

FMVSS	P2 A
MATERIALS	Acrylic lens, ABS housing
VOLT/AMP	12.8VDC - 2-LED 0.040A; 6-LED .054A
WT/DIMS	.088 lbs. / 4” x 1.5” x 0.938”
WARRANTY	Lifetime LED Warranty

MCL40AB

MCL40RB



MCL45/46 SERIES

LED Double Bullseye Style Marker/Clearance Lights

PC Rated

- Snap-on, replaceable lens
- Surface mount white base, mounts on 3" centers
- Single wire and two-wire designs available



MCL45/46AB

MCL45/46RB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW - 10 DIODES			
MCL45AB	MCL45ABP	1-wire, self grounding	20
MCL46AB	MCL46ABP	2-wire, power and ground	20
RED - 10 DIODES			
MCL45RB	MCL45RBP	1-wire, self grounding	20
MCL46RB	MCL46RBP	2-wire, power and ground	20
ACCESSORIES			
AL46AB	AL46ABP	Yellow replacement lens	50
AL46RB	AL46RBP	Red replacement lens	50
RETAIL			
MCL45AS	Retail Ready	Yellow 1-wire, clam	12
MCL45RS		Red 1-wire, clam	12





FMVSS	P2 PC
MATERIALS	Acrylic lens, ABS housing
VOLT/AMP	12.8VDC - 0.087A
WT/DIMS	.088 lbs. / 4.063" x 2.125" x 1.125"
WARRANTY	Lifetime LED Warranty

MCL49 SERIES

Surface Mount Sealed LED Marker/Clearance Light

PC Rated

- Sonically sealed, waterproof
- Surface mount, mounts on 3” centers
- Includes both lead and gound

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW - 14 DIODES			
MCL49AB	MCL49ABP	Light only	20
RED - 14 DIODES			
MCL49RB	MCL49RBP	Light only	20

FMVSS	P2 PC
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.87A
WT/DIMS	.132 lbs. / 3.875” x 2” x 1”
WARRANTY	Lifetime LED Warranty



MCL49AB

MCL49RB



MCL48 SERIES

LED Intermediate Side Marker Light with Supplemental Mid-Ship Turn

MCL48AB

MCL48CAB





- Sonically sealed, waterproof
- Surface mount, mounts on 4-13/16" centers
- Includes both lead and ground wires

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW - 16 DIODES			
MCL48AB	MCL48ABP	Light	20
MCL48CAB	MCL48CABP	Light, clear lens	20
MCL48AKB	MCL48AKBP	Kit: Light and A48CB	20
ACCESSORIES			
A48CB	A48CBP	Chrome bezel	50

FMVSS	P2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - Side marker .074A; Turn signal .248A
WT/DIMS	.221 lbs. / 6" x 2.25" x 1.375"
WARRANTY	Lifetime LED Warranty

MCL73 SERIES

LED Surface Mount Marker/Clearance Lights

PC Rated



MCL73AB



MCL73RB

- Sonically sealed, waterproof
- Surface mount, mounts on 4-13/16" centers
- Includes both lead and ground wires

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW - 16 DIODES			
MCL73AB	MCL73ABP	Light	20
RED - 16 DIODES			
MCL73RB	MCL73RBP	Light	20
ACCESSORIES			
A48CB	A48CBP	Chrome bezel	50

FMVSS	P2 PC
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - .248A
WT/DIMS	.221 lbs. / 6" x 2.25" x 1.375"
WARRANTY	Lifetime LED Warranty

MCL66 SERIES

Sealed LED Surface Mount Marker/Clearance Lights

- Sonically sealed, waterproof
- Surface mount, mounts on 3” centers
- Includes both lead and ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW - 6 DIODES			
MCL66AB	MCL66ABP	12V	20
MCL66APG	MCL66APGP	12V, .180 male bullets	20
MCL66A24B	MCL66A24BP	12-24V	20
MCL66CAB	MCL66CABP	12V, clear lens	20
RED - 6 DIODES			
MCL66RB	MCL66RBP	12V	20
MCL66RPG	MCL66RPGP	12V, .180 male bullets	20
MCL66R24B	MCL66R24BP	12-24V	20
MCL66CRB	MCL66CRBP	12V, clear lens	20
ACCESSORIES			
A66GB	A66GBP	Gasket, black	100
BK66DB	BK66DBP	Heavy duty armored base, die cast metal	50
BK66D1B	BK66D1BP	Heavy duty armored base, metal, black finish, open design	50
RETAIL			
MCL66AS	Retail Ready	Yellow 6-LED, 12V, clam	12
MCL66RS		Red 6-LED, 12V, clam	12

FMVSS	P2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.057A
WT/DIMS	.088 lbs. / 4” x .875” x 1.188”
WARRANTY	Lifetime LED Warranty

MCL66AB

MCL66RB

MCL66CAB



MCL66CRB





MCL71 SERIES

Low Profile LED Marker/ Clearance Light

MCL71RB



- Chrome plated housing, replaceable lens
- Includes both lead and ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED - 2 DIODES			
MCL71RB	MCL71RBP	Flush mount marker light	20

FMVSS	P2
MATERIALS	Acrylic lens, chrome plated ABS bezel
VOLT/AMP	12.8VDC - 0.054A
WT/DIMS	.088 lbs. / 3.75" x 2.25" x 1/2"
WARRANTY	Lifetime LED Warranty

MCL76 SERIES

Sealed LED Surface Mount Marker/ Clearance Lights with Reflex



MCL76AB



MCL76RB



- Sonically sealed, waterproof
- Surface mount, mounts on 4-13/16" centers
- Lens with reflex eliminates need for a separate reflector
- Includes weathertight pigtail with both lead and ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW - 4 DIODES			
MCL76AB	MCL76ABP	Light with reflex	20
RED - 4 DIODES			
MCL76RB	MCL76RBP	Light with reflex	20
RETAIL			
MCL76AS	Retail Ready	Yellow light, clam	6
MCL76RS		Red light, clam	6

FMVSS	A P2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.063A
WT/DIMS	.132 lbs. / 5.813" x 2" x 1.188"
WARRANTY	Lifetime LED Warranty

MCL82 SERIES

Flush Mount LED Marker/Clearance Lights with Reflex

- Sonically sealed, waterproof
- Low profile, flush mount design
- Lens with reflex eliminates need for a separate reflector
- Hard wired, includes lead and ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW - 3 DIODES			
MCL82AB	MCL82ABP	Light only, 2-wire	50
RED - 3 DIODES			
MCL82RB	MCL82RBP	Light only, 2-wire	50

FMVSS	A P2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.05A
WT/DIMS	.09 lbs / 4.50" x 1.63" x .75"
WARRANTY	Lifetime LED Warranty



MCL82AB



MCL82RB



MCL85 SERIES

Sealed LED Surface Mount Marker/Clearance Lights

MCL85AB

- Sonically sealed, waterproof
- Surface mount, mounts on 2-3/4" centers
- Single wire design grounds through mounting hardware



BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW - 3 DIODES			
MCL85AB	MCL85ABP	Surface mount light	50
RETAIL			
MCL85AS	Retail Ready	Yellow light with hardware, clam	12
MCL85RS		Red light with hardware, clam	12

FMVSS	P2 P3
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.066A
WT/DIMS	.044 lbs. / 3.188" x 1.063" x 1.188"
WARRANTY	Lifetime LED Warranty

MCL81 SERIES

Chrome Plated LED Marker/Clearance Lights

MCL81AB

MCL81RB

- Chrome plated ABS housing
- Includes both lead and ground wire

PC Rated



BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW - 6 DIODES			
MCL81AB	MCL81ABP	Light with ABS housing	20
RED - 6 DIODES			
MCL81RB	MCL81RBP	Light with ABS housing	20

FMVSS	P2 PC
MATERIALS	Acrylic lens, chrome plated ABS bezel
VOLT/AMP	12.8VDC - 0.153A
WT/DIMS	.265 lbs. / 4.781" x 2.125" x 1.375"
WARRANTY	Lifetime LED Warranty

MCL86 SERIES

Armored Die Cast LED Marker/Clearance Lights

PC Rated

- Die cast steel housing, mounting gasket
- Surface mount, mounts on 3-7/8" centers
- Two-wire design with power and ground wires

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW - 6 DIODES			
MCL86AB	MCL86ABP	Light with steel housing	20
RED - 6 DIODES			
MCL86RB	MCL86RBP	Light with steel housing	20

FMVSS	P2 PC
MATERIALS	Acrylic lens, steel housing
VOLT/AMP	12.8VDC - 0.20A
WT/DIMS	.463 lbs. / 4.5" x 2.25" x 1.5"
WARRANTY	Lifetime LED Warranty

MCL86AB

MCL86RB



MCL95 SERIES

Sealed Stud Mount LED Marker/Clearance Lights

- Sonically sealed, waterproof
- Single wire design grounds through mounting hardware

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW - 3 DIODES			
MCL95AB	MCL95ABP	1-wire, 20" lead	50
MCL95ABF	MCL95ABFP	2-wire, 5mm female barrels	50
RED - 3 DIODES			
MCL95RB	MCL95RBP	1-wire, 20" lead	50
MCL95RBF	MCL95RBFP	2-wire, 5mm female barrels	50
RETAIL			
MCL95AS		Yellow, single wire, clam	12
MCL95RS	Retail Ready	Red, single wire, clam	12

FMVSS	P2 P3
MATERIALS	Polycarbonate lens and housing, plated steel stud
VOLT/AMP	12.8VDC - 0.051A
WT/DIMS	.088 lbs. / 2.125" x 1.125" x 1.063"
WARRANTY	Lifetime LED Warranty

MCL95AB

MCL95RB





CBL22 SERIES

Sealed LED Triangular Cab/Clearance Light

PC Rated

- Sonically sealed, waterproof
- Design includes lead and ground wire
- Mounting gasket included

CBL22AB

CBL22RB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW - 15 DIODES			
CBL22AB	CBL22ABP	Cab light	50
CBL22CAB	CBL22CABP	Cab light, clear lens	50
RED - 15 DIODES			
CBL22RB	CBL22RBP	Cab light	50
RETAIL			
CBL22AS	Retail Ready	Yellow cab light, clam	12

FMVSS	P2 PC
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.107A
WT/DIMS	.176 lbs. / 3.5" x 2.75" x 1.688"
WARRANTY	Lifetime LED Warranty





MCL180 SERIES
LED Fender Light Assembly

- Reversible - one product can be used for either driver or passenger side of trailer
- Sonically sealed, waterproof
- P2 rated
- Hard wired, includes separate ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
FENDER LIGHT - 2 DIODES			
MCL180ARB	MCL180ARBP	Amber/red, reversible	50
RETAIL			
MCL180ARFK	Retail Ready	Kit: (2) MCL180ARB, clam	2

FMVSS	P2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - .033A
WT/DIMS	.05 lbs. / 8.50" x 1.688" x .813"
WARRANTY	Lifetime LED Warranty



MCL180ARB

MCL181 SERIES
LED Fender Light Assembly

MCL181ARCRB

- Reversible - one product can be used for both driver and passenger side of trailer
- Sonically sealed, waterproof
- Snap-on chrome-plated ABS trim ring
- Hard wired, includes separate ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
FENDER LIGHT - 2 DIODES			
MCL181ARCRB	MCL181ARCRBP	Amber/red, reversible, 2-wire, 5.5-in. leads	50
MCL181ARCRL12B	MCL181ARCRL12BP	Amber/red, reversible, 2-wire, 12-in. leads	50
MCL181ARCRGB	MCL181ARCRGBP	Amber/red, reversible, single wire self-grounding, 9-in. lead	50

FMVSS	P2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.04A
WT/DIMS	.04 lbs. / 1.70" x 1.21" x .82"
WARRANTY	Lifetime LED Warranty



MCL10 SERIES

Sealed 3/4" LED Identification Lights for Over 80" Applications

- Three 3/4-inch lights with grommets and insulated wiring harness
- Sonically sealed, waterproof
- Design includes both lead and ground wire
- Available in bulk and polypack packaging

MCL10ACK3L12B

MCL10RCK3L12B

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW ID LIGHTS - 3 DIODES			
MCL10ACK3L12B	MCL10ACK3L12BP	Clear lens (3) MCL10 lights, A12GB grommets, 29-in. molded harness	20
RED ID LIGHTS - 3 DIODES			
MCL10RCK3L12B	MCL10RCK3L12BP	Clear lens (3) MCL10 lights, A12GB grommets, 29-in. molded harness	20

FMVSS	P2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.022A
WT/DIMS	.25 lbs. / 0.75" x 0.75" x 0.95"
WARRANTY	Lifetime LED Warranty

MCL12/22/122 SERIES

Sealed 3/4" LED Identification Lights for Over 80" Applications

MCL12RK3B

- Sonically sealed, waterproof
- Design includes both lead and ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED ID LIGHTS - 3 DIODES			
MCL12RK3B	MCL12RK3BP	(3) red MCL12 lights, molded harness	20
MCL12RK3RMB	MCL12RK3RMBP	(3) red MCL12 lights, molded harness, weathertight plug	50
MCL22RK3B	MCL122RK3BP	(3) red MCL12 lights, supplemental turn function, .180 male bullets	20
MCL22RK4B	MCL22RK4BP	(3) red MCL12 lights, supplemental turn function, amp connector	20
MCL22RK5B	MCL22RK5BP	(3) red MCL12 lights, supplemental turn function, amp connector, 48-in. leads	20

FMVSS	P2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.022A
WT/DIMS	.25 lbs. / 0.75" x 0.75" x 0.95"
WARRANTY	Lifetime LED Warranty

MCL922 SERIES

Sealed 3/4" LED Identification Light Bar for Over 80" Applications



MCL922RB

- Three 3/4-inch lights installed in a corrosion proof ABS base
- Sonically sealed, waterproof
- Design includes both lead and ground wire



BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED ID LIGHTS - 3 DIODES			
MCL922RB	MCL922RBP	ID light bar, molded black base	10

FMVSS	P2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.022A
WT/DIMS	MCL922RB: .441 lb. / 14.875" x 1.25" x 1"
WARRANTY	Lifetime LED Warranty

MCL98 SERIES

Sealed LED Identification Light Bar for Over 80" Applications

- Sonically sealed, waterproof
- Compact – 14.25" x 1.125"
- Design includes both lead and ground wire



MCL98RB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED ID LIGHT BAR - 3 DIODES			
MCL98RB	MCL98RBP	ID light bar, 6-in. leads	10
MCL98RBTKPG	MCL98RBTKPGP	ID light bar, .156 bullets, 48-in. leads	20
MCL98RL60B	MCL98RL60BP	ID light bar, 60-in. leads	10
MCL98RL601B	MCL98RL601BP	ID light bar, 60-in. power lead, 10-in. ground lead	10
RETAIL			
MCL98RK	Retail Ready	Light bar, slipover blister	6

FMVSS	P2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.020A
WT/DIMS	.243 lb. / 14.25" x 1.125" x .875"
WARRANTY	Lifetime LED Warranty



MCL98RK

MCL70 SERIES

Sealed LED Identification Light Bars for Over 80" Applications

MCL70RB

MCL70RCB



- Sonically sealed, waterproof
- Ultra thin – only 5/8" thick
- Design includes both lead and ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED ID LIGHT BAR - 3 DIODES			
MCL70RB	MCL70RBP	ID light bar	10
MCL70RBF2	MCL70RBF2P	ID light bar, .180 female barrels	10
MCL70RCB	MCL70RCBP	ID light bar, clear lens	10
MCL70RCGB	MCL70RCGBP	ID light bar, self grounding	10
ACCESSORIES			
A69CB	A69CBP	Chrome base/bezel	10
A69GB	A69GBP	Mounting gasket, black	10
RETAIL			
MCL70RS	Retail Ready	Red, clam	6

FMVSS	P2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.038A
WT/DIMS	.441 lb. / 15" x 1.375" x .625"
WARRANTY	Lifetime LED Warranty

MCL78/88 SERIES

Sealed LED Identification Light Bars for Over 80" Applications

MCL78RB

MCL88RCB



- Sonically sealed, waterproof
- Ultra thin – only 1" thick
- Design includes both lead and ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED ID LIGHT BAR - 3 DIODES			
MCL78RB	MCL78RBP	ID light bar	10
MCL88RCB	MCL88RCBP	ID light bar, clear lens	10
ACCESSORIES			
A79CB	A79CBP	Chrome base/bezel	10

FMVSS	P2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.022A
WT/DIMS	.441 lb. / 17" x 1.375" x 1"
WARRANTY	Lifetime LED Warranty

MCL964 SERIES

Sealed LED Identification Light Bar for Over 80" Applications

- Sonically sealed, waterproof
- Low profile – only 0.79" thick
- Design includes both lead and ground wire

MCL964RB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED ID LIGHT BAR - 3 DIODES			
MCL964RB	MCL964RBP	ID light bar	10
ACCESSORIES			
A64CRB	A64CRBP	Chrome base/bezel	50



FMVSS	P2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC
WT/DIMS	0.441 / 20.56" x 1.09" x 0.79"
WARRANTY	Lifetime LED Warranty

MCL83 SERIES

FLEET Count™ Sealed LED Identification Light Bar for Over 80" Applications

- Sonically sealed, waterproof lights snap onto corrosion proof polycarbonate base
- Design includes both lead and ground wire

MCL83RB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED ID LIGHT BAR - 3 DIODES			
MCL83RB	MCL83RBP	3-LED ID light bar	10
AL90RB	AL90RBP	1-LED replacement light	50
RETAIL			
MCL83RK	Retail Ready	3-LED ID light bar, slipover blister	6



FMVSS	P2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - .069A
WT/DIMS	.397 lb. / 15.938" x 1.469" x 1.625"
WARRANTY	Lifetime LED Warranty

MCL93 SERIES

Sealed LED Identification Light Bar for Over 80" Applications

MCL93RB

- Sonically sealed, waterproof lights snap onto corrosion proof polycarbonate base
- Design includes both lead and ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED ID LIGHT BAR - 9 DIODES			
MCL93RB	MCL93RBP	9-LED ID light bar	10
MCL93RPG	MCL93RPGP	9-LED ID light bar, .180 male bullet on power, eyelet on ground	10
AL91RB	AL91RBP	3-LED replacement light	50
RETAIL			
MCL93RK	Retail Ready	9-LED ID light bar, slipover blister	6



FMVSS	P2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.153A
WT/DIMS	.397 lb. / 15.938" x 1.469" x 1.625"
WARRANTY	Lifetime LED Warranty

MCL914R1PG

Sealed LED Identification Light Bar for Over 80" Applications

MCL914R1PG

- Sonically sealed, waterproof
- Hard wired, with .180 female barrels

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED ID LIGHT BAR - 9 DIODES			
MCL914R1PG	MCL914R1PGP	ID light bar, black base	10



FMVSS	P2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.147A
WT/DIMS	.397 lb. / .287 lbs / 17.32" x 1.25" x .95"
WARRANTY	Lifetime LED Warranty

MCL84 SERIES

Sealed LED Identification Light Bar for Over 80" Applications

- Sonically sealed, waterproof lights snap onto stainless steel base
- Design includes both lead and ground wire

MCL84RB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED ID LIGHT BAR - 9 DIODES			
MCL84RB	MCL84RBP	9-LED ID light bar	10
AL91RB	AL91RBP	3-LED replacement light	50

FMVSS	P2
MATERIALS	Polycarbonate light, stainless steel housing
VOLT/AMP	12.8VDC - .153A
WT/DIMS	.397 lb. / 16.5" x 1.375" x 1.625"
WARRANTY	Lifetime LED Warranty



MCL97 SERIES

Sealed LED Identification Light Bar for Over 80" Applications

- Sealed, waterproof lights on stainless steel base
- Single wire, grounds through mounting hardware

MCL97RB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED ID LIGHT BAR - 9 DIODES			
MCL97RB	MCL97RBP	9-LED ID light bar	10
MCL97RPG	MCL97RPGP	9-LED ID light bar, .180 male bullet	10
RETAIL			
MCL97RK	Retail Ready	ID light bar, slipover blister	6

FMVSS	P2 P3
MATERIALS	Polycarbonate light, stainless steel base
VOLT/AMP	12.8VDC - .153A
WT/DIMS	.287 lb. / 14.25" x 1.188" x 1.313"
WARRANTY	Lifetime LED Warranty



LPL11 SERIES

Snap-In LED
Mini License Plate Light

- Chrome-plated brass construction
- Easy snap-in mounting
- Sonically sealed, waterproof
- Two-wire design includes both lead and ground wire

LPL11CB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
LICENSE LIGHT - 2 DIODES			
LPL11CB	LPL11CBP	Snap-in, license light	50
LPL11CPG	LPL11CPGP	Snap-in, license light, .180 male bullets	50

FMVSS	(2) L
MATERIALS	Polycarbonate lens and brass housing
VOLT/AMP	12.8VDC - .0306A
WT/DIMS	.068lbs. / 1.5” x 1.5” x 1.125”
WARRANTY	Lifetime LED Warranty





HOLE CUT-OUT: 1.25”

LPL12 SERIES

3/4" Sealed LED License Light

- Sealed, waterproof
- Meets SAE J587 when properly mounted using brackets listed below
- Design includes both lead and ground wire

LPL12CB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
LICENSE LIGHT - 2 DIODES			
LPL12CB	LPL12CBP	Light with .180 female barrels	20
LPL12CPGB	LPL12CPGBP	Light with .180 male bullets	20
LPL12CKM2B	LPL12CKM2BP	Kit: LPL12CPGB, A12B2LPB surface mount bracket, A12GLPB grommet	50
LPL12CKMB	LPL12CKMBP	Kit: LPL12CPGB with A11BLPB bracket	20
LPL12CKF2B	LPL12CKF2BP	Kit: LPL12CB, A12B2LPB surface mount bracket, A12GLPB grommet	50
ACCESSORIES			
A11BLPB	A11BLPBP	Black flush mount bracket	50
A11GLPB	A11GLPBP	Gray flush mount bracket	50
A12B2LPB	A12B2LPBP	Black vertical mount bracket	50
A12GLPB	A12GLPBP	Grommet for A12B2LPB	50

Kit with A12B2LPB bracket

LPL12CKMB

FMVSS	L
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.11A
WT/DIMS	.022 lb. / 0.74" x 0.74" x .938"
WARRANTY	Lifetime LED Warranty



LPL12CB



A12B2LPB



A11GLPB

LPL21 SERIES

LED Heavy Duty License Plate Light

- Armored light made of durable, chrome plated steel
- Surface mount on 2” centers
- Design includes both lead and ground wire

LPL21CB



BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
LICENSE LIGHT - 1 DIODE			
LPL21CB	LPL21CBP	Armored license light	20

FMVSS	L
MATERIALS	Steel, polycarbonate lens
VOLT/AMP	12.8VDC - 0.054A
WT/DIMS	.132 lb. / 2.5” x 1.813” x 2”
WARRANTY	Lifetime LED Warranty

LPL31 SERIES

Mini LED License Light

- Polished, chrome plated housing
- Surface mount on 2” centers
- Design includes both lead and ground wire
- Two LPL31CB/CEZB required to meet DOT requirements, mounted on each side
- Single LPL31CSB required to meet DOT requirements, mounted at center

LPL31CB

LPL31CSB



LPL31CB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
LICENSE LIGHT - 2 DIODES			
LPL31CB	LPL31CBP	License light	20
LPL31C1PG	LPL31C1PGP	License light, .180 male bullets	20
LPL31CPG	LP31CPGP	License light, .156 female barrels	20
LPL31CEZB	LPL31CEZBP	License light, .180 female barrels	20
LPL31CSB	LPL31CSBP	Light with spacer	50
LPLB31CPG	LPLB31CPGP	Light with black bracket, .156 female barrels	25
RETAIL			
LPL31CS	Retail Ready	Light with mounting hardware, clam	12

FMVSS	(2) L
MATERIALS	Polycarbonate lens, chrome plated stainless steel bezel
VOLT/AMP	12.8VDC - 0.027A
WT/DIMS	.066 lb. / 2.72” x 1.34” x 1”
WARRANTY	Lifetime LED Warranty

LPL41/42/43 SERIES
Surface Mount LED License Light

- Armored housing
- Surface mount using stainless steel ears or studs
- Design includes both lead and ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
LICENSE LIGHT			
LPL41CB	LPL41CBP	5-LED ear mount license light, chrome finish housing	20
LPL42CBF	LPL42CBFP	5-LED stud mount license light, chrome finish housing	20
LPL43CB	LPL43CBP	3-LED ear mount license light, stainless steel base	20
LPL43CGBF	LPL43CGBFP	3-LED stud mount license light, self grounding	20

FMVSS	L
MATERIALS	Polycarbonate lens, chrome plated plastic housing, stainless steel base
VOLT/AMP	12.8VDC - 0.054A
WT/DIMS	.176 lb. / 4" x 2.188" x 1.563"
WARRANTY	Lifetime LED Warranty

LPL41CB



LPL43CB



LPL41CB





LPL42CBF

1.75" Center, Stainless Steel Studs

LPL55/56 SERIES
LED License Light with Bracket

- Light attached to corrosion proof black bracket
- Surface mount on 3-1/4" centers
- Design includes both lead and ground wire

LPL55CB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
LICENSE LIGHT - 5 DIODES			
LPL55CB	LPL55CBP	Light with ABS bracket	10
LPL55CPG	LPL55CPGP	Light with ABS bracket, female PL-10 plug	10
LPL55CKB	LPL55CKBP	Light/bracket, gasket and hardware	10
LPL56CB	LPL56CBP	Light with steel bracket and gasket	10

FMVSS	L
MATERIALS	Polycarbonate lens and housing, plastic bracket
VOLT/AMP	12.8VDC - 0.045A
WT/DIMS	.198 lb. / 8.625" x 3.25" x 2.375"
WARRANTY	Lifetime LED Warranty



LPL57 SERIES

LED License Light with Bracket

LPL57CB

- One-piece design, light molded into bracket
- Surface mount, low profile
- Hard wired, with both lead and ground wires



BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
LICENSE LIGHT - 1 DIODE			
LPL57CB	LPL57CBP	Light with bracket	10
LPL57CKB	LPL57CKBP	Kit: light with bracket, mounting hardware	10
ACCESSORIES			
LP52HP	LP52HPP	Mounting hardware: two bolts, two washers, two weld nuts	50

FMVSS	L
MATERIALS	Polycarbonate lens and housing, plastic bracket
VOLT/AMP	12.8VDC - 0.054A
WT/DIMS	.198 lb. / 8.6" x 2.5" x 2.6"
WARRANTY	Lifetime LED Warranty

LPL58/59 SERIES

LED Single Piece Molded License Lights

- Stud mount and ear mount models available
- Chrome finish plastic housing
- Design includes both lead and ground wire
- Available in bulk and polypack packaging

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
LICENSE LIGHT - 1 DIODE			
LPL58CB	LPL58CBP	License light, 2-wire, stud mount	20
LPL59CB	LPL59CBP	License light, 2-wire, ear mount	20

FMVSS	L
MATERIALS	Chrome finish plastic housing, polycarbonate lens
VOLT/AMP	12VDC - .054A
WT/DIMS	LPL58: .13lbs 2.55" x 2.88" x 1.47"
	LPL59: .13lbs 4.13" x 2.71" x 1.88"
WARRANTY	Lifetime LED Warranty

LPL58CB

LPL59CB



LPL58CB



LPL59CB

LPL61 SERIES
LED License Light

LPL61C24B

- Sonically sealed, waterproof
- Dual power - use with 12V and 24V systems
- Corrosion proof polycarbonate construction
- Design includes both lead and ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
LICENSE LIGHT - 6 DIODES			
LPL61C24B	LPL61C24BP	LED license light, black housing, 12-24V	50
LPL61C24PG	LPL61C24PGP	LED license light, black housing, 12-24V .156 female barrels	10



FMVSS	L
MATERIALS	Polycarbonate
VOLT/AMP	12.8VDC - 0.02A
WT/DIMS	.132 lb. / 3.55" x 1.2" x 1.82"
WARRANTY	Lifetime LED Warranty

LPL65 SERIES
LED License Light

LPL65CB

- Sonically sealed, waterproof
- Accept standard 1- or 2-wire plugs
- Single wire design grounds through mounting hardware
- Two-wire design includes both lead and ground wire for mounting to all surfaces

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
LICENSE LIGHT - 3 DIODES			
LPL65CB	LPL65CBP	LED license light, gray housing	20
LPL65CBB	LPL65CBBP	LED license light, black housing	20
ACCESSORIES			
A65PB	A65PBP	Kit: A65B bracket, A65P plug	50
A66PB	A66PBP	Kit: grey bracket, A65P plug	50
A67CB	A67CBP	Kit: chrome bracket, A65P plug	50
A68PG	A68PBP	Kit: A65B bracket, A68P plug	50

LPL65CBB



FMVSS	L
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.052A
WT/DIMS	.089 lb. / 3.9" x 1.3" x 1.2"
WARRANTY	Lifetime LED Warranty

LPL81 SERIES

Sealed LED Ear Mount License Light

- Sealed, waterproof electronics
- Surface ear mount
- Design includes both lead and ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
LICENSE LIGHT - 3 DIODES			
LPL81CB	LPL81CBP	License light, stainless steel mounting ears	20

FMVSS	L
MATERIALS	Polycarbonate lens, ABS housing, stainless steel base
VOLT/AMP	12.8VDC - 0.035A
WT/DIMS	.162 lbs / 4" x 2" x 1.91"
WARRANTY	Lifetime LED Warranty

LPL81CB



LPL82 SERIES

Sealed LED Stud Mount License Light

- Sealed, waterproof electronics
- Stud mount on 1.75" centers
- Design includes both lead and ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
LICENSE LIGHT - 3 DIODES			
LPL82CB	LPL82CBP	License light, stud mount grey housing	20
LPL82CBB	LPL82CBBP	License light, stud mount black housing	20

FMVSS	L
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.035A
WT/DIMS	.131 lbs / 2.87" x 2" x 1.91"
WARRANTY	Lifetime LED Warranty

LPL82CB

LPL82CBB



LPL91 SERIES
Sealed LED License Light

- Sonically sealed, waterproof
- Use with LP25SB bracket and designated license plate brackets
- Design includes both lead and ground wire

LPL91

LPL26SKB







LPL91

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
LICENSE LIGHT - 2 DIODES			
LPL91CB	LPL91CBP	License light	50
LPL91CAB	LPL91CABP	License light, .156 female plugs	50
LPL91CPG	LPL91CPGP	License light, female PL-10 connector	50
LPL91CKALPB	LPL91CKALPBP	License light, .150 female barrels, black light bracket, gasket	50
LPL26SKB	LPL26SKBP	License light, .180 male bullets, gray light bracket	50
LICENSE PLATE BRACKETS			
LP25SB	LP25SBP	Bracket, black coated	100
LP25SGGB	LP25SGGBP	Bracket, gray coated	
LP5SB	LP5SBP	Straight license plate bracket	100
LP15SB	LP15SBP	Zinc license plate bracket	12
LP35BB	LP35BBP	License plate holder	25
ACCESSORIES			
A91BB	A91BBP	Black base, self grounding	100
A91BOB	A91BOBP	Black base, open back	100
A91CB	A91CBP	Chrome base, self grounding	100
A91OB	A91OBP	Chrome base, open back	100
A91GB	A91GBP	Grommet	100
RETAIL			
LPL91CS	Retail Ready	Light, clam	12

FMVSS	L
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.027A
WT/DIMS	.066 lb. / 2.5" x 1.25" x 0.813"
WARRANTY	Lifetime LED Warranty





LPL26SKB bracket

BUL13 SERIES

4" Round Sealed LED Utility Light

- Miro-Flex™ design with Crystal Clear™ lens
- Sonically sealed, waterproof
- Accepts standard two-pin plugs

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
UTILITY LIGHT - 12 DIODES			
BUL13CB	BUL13CBP	Utility light	10
ACCESSORIES			
A45GB	A45GBP	Grommet	50
A45CB	A45CBP	Pigtail, 2-wire	100
A49PB	A49PBP	Right angle pigtail, 2-wire	100

MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.074A
WT/DIMS	.331 lb. / 4.313" x 4.313" x 2.375"
WARRANTY	Lifetime LED Warranty

BUL13CB



BUL43 SERIES

4" Round Sealed LED Utility Light

- Crystal Clear™ lens
- Sonically sealed, waterproof
- Accepts standard two-pin plugs

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
UTILITY LIGHT - 10 DIODES			
BUL43CB	BUL43CBP	Utility light	10
BUL43CBK	BUL43CBKP	Kit with A45GB grommet and A45CB pigtail	10
ACCESSORIES			
A45GB	A45GBP	Grommet	50
A45CB	A45CBP	Pigtail, 2-wire	100
A49PB	A49PBP	Right angle pigtail, 2-wire	100

MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.275A
WT/DIMS	.529 lb. / 4.313" x 4.313" x 1.938"
WARRANTY	Lifetime LED Warranty

BUL43CB



BUL69 SERIES
Sealed LED Thinline Utility Light

BUL69CB

- Sonically sealed, waterproof
- Ultra thin – only 5/8" thick
- Design includes both lead and ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
UTILITY LIGHT - 11 DIODES			
BUL69CB	BUL69CBP	Utility light	10
BUL69CPG	BUL69CPGP	Light with .180 male bullets	10
BUL69CBMCV2B	BUL69CBMCV2BP	Kit: 2-wire female PL-3, A69CB base	10
ACCESSORIES			
A69CB	A69CBP	Chrome base/bezel	10
A69GB	A69GBP	Gasket	50



MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.025A
WT/DIMS	.265 lb. / 15" x 1.375" x .625"
WARRANTY	Lifetime LED Warranty

BUL72 SERIES
6" Oval Sealed LED Utility Lights

BUL72CB

BUL72CBGK

- Crystal Clear™ lens
- Sonically sealed, waterproof
- Accepts standard two-pin plugs

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
UTILITY LIGHT - 10 DIODES			
BUL72CB	BUL72CBP	Utility light	10
BUL72CBGK	BUL72CBGKP	Utility light with A70GB grommet	50
BUL74CBK	BUL74CBKP	Utility light with A70GB & A49PB	50
ACCESSORIES			
A70GB	A70GBP	Grommet	50
A45CB	A45CBP	Pigtail, 2-wire	100
A49PB	A49PBP	Right angle pigtail, 2-wire	100



MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.080A
WT/DIMS	.529 lb. / 6.438" x 2.313" x 1.75"
WARRANTY	Lifetime LED Warranty

BUL73 SERIES

FLEET Count™ 6" Oval Sealed LED Utility Light for Surface Mount

- Sonically sealed, waterproof
- Surface flange mount – no panel cutout required
- Design includes both lead and ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
UTILITY LIGHT - 6 DIODES			
BUL73CB	BUL73CBP	Utility light	10
ACCESSORIES			
A78CB1	A78CB1P	Chrome snap-on trim ring	25

MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.054A
WT/DIMS	.265 lb. / 7.563" x 3.313" x .75"
WARRANTY	Lifetime LED Warranty

BUL73CB



BUL78 SERIES

6" Oval Sealed LED Utility Light for Surface Mount

- Sonically sealed, waterproof
- Surface flange mount – no panel cutout required
- Design includes both lead and ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
UTILITY LIGHT - 10 DIODES			
BUL78CB	BUL78CBP	Utility light	10
BUL78CEZB	BUL78CEZBP	Utility light with 2-way female PL-3	10
BUL78C3MB	BUL78C3MBP	Utility light with 2-way female PL-3 plug, adhesive back	10
BUL28CLPB	BUL28CLPBP	Low profile utility light with 2-way female PL-3 connector and gasket	10
ACCESSORIES			
A78CB1	A78CB1P	Chrome snap-on trim ring	25
A78RXB	A78RXBP	Red reflex snap-on trim ring	25
A178TRSSB	A178TRSSBP	Stainless steel screw mount trim ring	50

MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.054A
WT/DIMS	BUL78: .265 lb. / 7.563" x 3.313" x .75"
	BUL28: .255 lb. / 7.50" x 3.313" x .5625"
WARRANTY	Lifetime LED Warranty

BUL78CB





BUL28CLPB

ILL01 SERIES

3/4" LED Emergency Egress Light

- 3/4" recess mount light for use in transit vehicles
- Hard wired, includes lead and ground with female Staykon connectors
- Sealed, waterproof construction – maintenance free
- Snap-in design for quick and easy installation

BULK P/N	BOX/UPC P/N	DESCRIPTION	QTY
EGRESS LIGHT - 1 DIODE			
ILL01RB	ILL01RBP	3/4" egress light	50



MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - .1A
WT/DIMS	0.018 lb. / .695" x .695" x .81"
WARRANTY	Lifetime LED Warranty

ILL06/07 SERIES

Opti-Brite™ LED Mini Dome Light

ILL06COB

A06TR

- Compact 11-inch dome light fits many applications
- Design includes 6-inch, 16-gauge power and ground wires with tinned ends
- Available with neutral white or cool white LEDs

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
COOL WHITE - 16 DIODES			
ILL06COB	ILL06COBP	Dome light, white trim ring	12
NEUTRAL WHITE - 16 DIODES			
ILL07COB	ILL07COBP	Neutral white LEDs	12
ACCESSORIES			
A06TR	A06TRP	White trim ring	50



Raw lumen output:	643 lm
Effective lumen output:	354 lm

MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - .48A
WT/DIMS	.05 lbs. / 11" x 4" x .94"
WARRANTY	Lifetime LED Warranty

ILL08/ILL28 SERIES

Opti-Brite™ LED Dome Lights

- Designed for use in extreme temperatures; ideal for refrigerated trucks and trailers (-40 to 140 degrees F)
- Operating voltage 7-30VDC; voltage cut-off at 7VDC prevents battery drain
- Use with both 12VDC and 24VDC systems; light output remains consistent at all operating voltages (no dimming), cutting off when voltage is outside range
- Design includes 16-inch, 16-gauge power and ground wires with tinned ends

ILL08COB

ILL28CMB

BULK P/N	BOX/UPC P/N	DESCRIPTION	QTY
DOME LIGHT - 8 DIODES			
ILL08COB	ILL08COBP	Light	6
ILL08COPG	ILL08COPGP	Light, .180 male bullets	6
MOTION SENSOR DOME LIGHT - 8 DIODES			
ILL28CMB	ILL28CMBP	Light with motion sensor	6
ILL28CMPG	ILL28CMPGP	Light with motion sensor, .180 male bullets	6

Raw lumen output: 1400 lm
Effective lumen output: 990 lm

MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 1.61A; 24VDC - 0.80A
WT/DIMS	1 lb. / 18.25" x 5.75" x 1.078"
WARRANTY	Lifetime LED Warranty



ILL08/28/10 SERIES DIMENSIONS

ILL10 SERIES

Opti-Brite™ LED Dome Light

For 12VDC systems, general applications

ILL10CCB

BULK P/N	BOX/UPC P/N	DESCRIPTION	QTY
DOME LIGHT - 10 DIODES			
ILL10CCB	ILL10CCBP	11-16VDC Dome light	6

Raw lumen output: 1100 lm
Effective lumen output: 880 lm

MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 1.8A
WT/DIMS	1 lb. / 18.25" x 5.75" x 1.078"
WARRANTY	Lifetime LED Warranty

ILL11 SERIES

Opti-Brite™ LED Dome Lights

ILL11CCB



- Designed for extreme temperatures; ideal for refrigerated trucks and trailers (-40 to 185 degrees F)
- Color temperature of light: 5300-7000K
- Design includes 18-inch, 16-gauge power and ground wires with tinned ends

BULK P/N	BOX/UPC P/N	DESCRIPTION	QTY
DOME LIGHT - 10 DIODES			
ILL11CCB	ILL11CCBP	Light	6

Raw lumen output: 1100 lm
Effective lumen output: 880 lm

MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 1.33A
WT/DIMS	1.43 lbs / 18.25" x 5.75" x 1.09"
WARRANTY	Lifetime LED Warranty

ILL21 SERIES

Opti-Brite™ LED 6" Dome Light

- Low profile dome light – less than 5/8" thick
- Operating voltage 12-24VDC; use with both 12VDC and 24VDC systems
- Low voltage cut-off at 11VDC, prevents battery drain
- Sealed, waterproof

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
DOME LIGHT - 21 DIODES			
ILL21CB	ILL21CBP	Dome light, two-wire, .180 male bullets	10
ILL21CTPB	-	ILL21CB with adhesive mounting pad	10
ACCESSORIES			
A21CHB	-	Chrome trim ring	25

ILL21CB



Raw lumen output: 250 lm
Effective lumen output: 214 lm

MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - .408A; 24VDC - .385A
WT/DIMS	.250 lb. / 6.0938" x 6.0938" x .625"
WARRANTY	Lifetime LED Warranty

ILL22 SERIES

Sealed LED Dome Lights

- Low profile dome lights – only 1" thick
- Sealed, waterproof design
- Hard wired with 6" power and ground wires

ILL22CB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
DOME LIGHT - 18 DIODES			
ILL22CB	ILL22CBP	Dome light, on/off switch	10
ILL22C1224B	ILL22C1224BP	Dome light, on/off switch,12/24V	10
ILL22CBB	ILLCBBP	Dome light, on/off switch, black circuit board	10
ILL22CHB	ILL22CHBP	Dome light, no switch	10
RETAIL			
ILL22CFS		Dome light, clam	12

ILL22CBB



Raw lumen output: 1044 lm
Effective lumen output: 810 lm

MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - .7A
WT/DIMS	.182 lb. / 4.5" x 2.875" x 1"
WARRANTY	Lifetime LED Warranty

GloLight®

ILL124 SERIES
Opti-Brite™ LED 6" Dome Light

ILL124CPG



- Low profile dome lights – only 7/8" thick
- Sealed, waterproof
- Hard wired design includes power and ground wires

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
DOME LIGHT - 36 DIODES			
ILL124CPG	ILL124CPGP	Dome light, .180 male bullets	10

Raw lumen output: 585 lm
Effective lumen output: 431 lm

MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.127A
WT/DIMS	.353 lb. / 6.125" x 6.125" x 0.875"
WARRANTY	Lifetime LED Warranty

Optronics LED

ILL24 SERIES
Sealed LED 6" Dome Light

ILL24CB





- Low profile dome light – only 7/8" thick
- Sealed, waterproof
- Hard wired design includes power and ground wires

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
DOME LIGHT - 36 DIODES			
ILL24CB	ILL24CBP	Dome light	10
ILL24CPG	ILL24CPGP	Dome light, .180 male bullets	10

Raw lumen output: 585 lm
Effective lumen output: 453 lm

MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - .127A
WT/DIMS	.353 lb. / 6.125" x 6.125" x 0.875"
WARRANTY	Lifetime LED Warranty

ILL29 Series

Opti-Brite™ 4" LED Dome Lights

- Sonically sealed, waterproof
- Recess mount design
- Available in grommet and flange mount models
- Hard wired with .180 male bullets

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
DOME LIGHT - 7 DIODES			
ILL29CB	ILL29CBP	Dome light, grommet mount	10
ILL29CFB	ILL29CFBP	Dome light, flange mount	10
ACCESSORIES			
A45GB	A45GBP	PVC grommet	50
A46GB	A46GBP	PVC grommet, new design	50

ILL29CB

ILL29CFB

Raw lumen output: 500 lm
Effective lumen output: 360 lm

MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.3A
WT/DIMS	Grommet: .26 lb / 4.25" x 4.25" x .9"
	Flange: .3 lb / 5.5" x 5.5" x .9"
WARRANTY	Lifetime LED Warranty



ILL29CB



ILL29CFB

ILL30CBB SERIES
Constellation™ LED Bullet Light

- Surface mount fixture; trim ring covers mounting hardware
- Ratchet motion design with on/off switch
- Lightly frosted lens
- Hard wired design includes power and ground wires

ILL30CBB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
BULLET LIGHT - 1 DIODE			
ILL30CBB	ILL30CBBP	Bullet light	25

MATERIALS	Plastic housing
VOLT/AMP	12.8VDC - .288A
WT/DIMS	.250 lb. / 3.75" x 1.938" x 3.5"
WARRANTY	Lifetime LED Warranty

ILL31/32/35 SERIES
LED Low Profile Dome Lights

- Low profile dome lights for semi-recess or surface mount
- Durable steel housing and replaceable polycarbonate lens
- Hard wired design includes power and ground wires
- Select from standard diode or SMD LED models

ILL31CB



ILL31/32/35

ILL31/35 - recess mount

ILL32 - surface mount

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RECESS MOUNT DOME LIGHT - 10 DIODES			
ILL31CB	ILL31CBP	Standard LED	10
ILL35CB	-	SMD LED	10
SURFACE MOUNT DOME LIGHT - 10 DIODES			
ILL32CB	ILL32CBP	SMD LED	10
ILL32CPG	-	SMD LED, .180 male bullets	10

Raw lumen output: 70 lm
Effective lumen output: 53 lm

MATERIALS	Polycarbonate lens, plated steel housing
VOLT/AMP	12.8VDC - .024A
WT/DIMS	ILL31/35: .243 lb. / 5.75" x 2.75" x .938" ILL32: .243 lb. / 5.75" x 2.75" x .75"
WARRANTY	Lifetime LED Warranty

ILL33 SERIES

Opti-Brite™ LED Sealed Dome Light

- Low profile surface mount design – less than 3/4" thick
- Hard wired design includes 18-gauge lead wires
- Sealed, waterproof

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
DOME LIGHT - 10 DIODES			
ILL33CB	ILL33CBP	Dome light	10

ILL33CB

Raw lumen output: 210 lm
Effective lumen output: 160 lm

MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - .147A
WT/DIMS	.154 lb. / 5.125" x 2.25" x .75"
WARRANTY	Lifetime LED Warranty



ILL36 SERIES

Opti-Brite™ LED Sealed Dome Light

- Low profile surface mount design – less than 3/4" thick
- Sealed, waterproof
- Durable polycarbonate construction

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
DOME LIGHT - 9 DIODES			
ILL36CB	ILL36CBP	Dome light	10
ILL36CPG	ILL36CPGP	Dome light, .180 male bullets	10



ILL36CB

Raw lumen output: 400 lm
Effective lumen output: 227 lm

MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - .33A
WT/DIMS	.154 lb. / 5.75" x 2.75" x .688"
WARRANTY	Lifetime LED Warranty



ILL38CMB

LED Corner Mount Interior Lamp

- Modular design with PIR-based motion sensor for interior cargo applications
- 30 ultra-bright white SMD LED's
- Dual power 12/24VDC
- Operating environment -4˚ to 140˚ F
- 16-inch leads

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
INTERIOR LIGHT - 30 DIODES			
ILL38CMB	ILL38CMBP	Corner mount interior lamp, hard wired	20

MATERIALS	Polycarbonate lens, metal housing with white finish
VOLT/AMP	12/24VDC
WT/DIMS	.89 lb. / 17.72" x 2.45" x 2.22"
WARRANTY	Lifetime LED Warranty

ILL39 SERIES
Opti-Brite™ LED 7” Dome Light

- Low profile dome light – less than 5/8” thick
- Operating voltage 12-24VDC; use with both 12VDC and 24VDC systems
- Low voltage cut-off at 11VDC, prevents battery drain
- Hard wired design includes 16-gauge power and ground wires with .180 male bullets
- Sealed, waterproof

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
DOME LIGHT - 39 DIODES			
ILL39CB	ILL39CBP	Dome light	5/10
ILL39RCB	ILL39RCBP	Dome light, red diodes, .180 male bullets, 11V voltage cut-off	5

Raw lumen output: 460 lm
Effective lumen output: 390 lm

MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - .669A; 24VDC - .217A
WT/DIMS	.350 lb. / 6.969” x 6.969” x .625”
WARRANTY	Lifetime LED Warranty

ILL39CB



ILL39RCB



ILL45 SERIES
Opti-Brite™ LED Interior Light

- Low profile surface mount design – less than 1” thick
- Durable polycarbonate construction

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
INTERIOR LIGHT - 42 DIODES			
ILL45CB	ILL45CBP	Interior light	50

Raw lumen output: 300 lm
Effective lumen output: 260 lm

MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - .37A
WT/DIMS	.206 lbs. / 4.625” x 4.625” x .79”
WARRANTY	Lifetime LED Warranty

ILL45CB



ILL46 SERIES
Opti-Brite™ Sealed LED Dome Light

- Low profile surface mount design – less than 3/4" thick
- Sealed, waterproof
- Durable polycarbonate construction

ILL46CB



BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
DOME LIGHT - 9 DIODES			
ILL46CB	ILL46CBP	Dome light	10

Raw lumen output: 540 lm
Effective lumen output: 380 lm

MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - .33A
WT/DIMS	.154 lbs. / 5.75" x 2.75" x .688"
WARRANTY	Lifetime LED Warranty

ILL48 SERIES
Opti-Brite™ Sealed LED Dome Light

- Low profile surface mount design
- Sealed, waterproof
- Durable polycarbonate construction
- Hard wired with both power and ground wire
- Available in bulk and polypack packaging



ILL48CB



MOUNT ON 4.68" CENTERS

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
DOME LIGHT - 9 DIODES			
ILL48CB	ILL48CBP	Dome light, 5-in. lead, black base	50

Raw lumen output: 540 lm
Effective lumen output: 380 lm

MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - .33A
WT/DIMS	.154 lbs. / 5.75" x 2.75" x .69"
WARRANTY	Lifetime LED Warranty

ILL70/71/72 SERIES

Opti-Brite™ LED Interior Strip Lights for Surface Mount

- Low profile, slimline lights – only 1" wide by 5/8" thick
- Hard wired design includes both lead and ground wires
- Select from 9-inch, 16-inch and 22-inch models
- Sealed, waterproof

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
9" WHITE LED STRIP LIGHT - 9 DIODES			
ILL70CB	ILL70CBP	Strip light	20/10
ILL70CSB	ILL70CSBP	Strip light with on/off switch	10
ILL70C24B	ILL70C24BP	Strip light, 24-in. leads	10
Raw lumen output: 189 lm **Effective lumen output:** 171 lm			
16" WHITE LED STRIP LIGHT - 18 DIODES			
ILL71CB	ILL71CBP	Strip light	20/10
ILL71CSB	ILL71CSBP	Strip light with on/off switch	10
ILL71CPG	ILL71CPGP	Strip light, .180 male bullets	10
Raw lumen output: 370 lm **Effective lumen output:** 342 lm			
22" WHITE LED STRIP LIGHT - 27 DIODES			
ILL72CB	ILL72CBP	Strip light	20/10
Raw lumen output: 567 lm **Effective lumen output:** 513 lm			



MATERIALS

Polycarbonate lens and housing

VOLT/AMP

ILL70: 12.8VDC - .150A
ILL71: 12.8VDC - .300A
ILL72: 12.8VDC - .480A

WT/DIMS

ILL70: .154 lb. / 9.625" x 1" x .625"
ILL71: .187 lb. / 15.75" x 1" x .625"
ILL72: .210 lb. / 21.875" x 1" x .625"

WARRANTY

Lifetime LED Warranty

ILL70/71 AWNING SERIES

Opti-Brite™ LED Awning Lights for Surface Mount

ILL70CBAWN

ILL71CBAWN

- Low profile awning mount lights with wedge base that directs light at a 45-degree angle
- Hard wired design includes both lead and ground wires
  - Select from 11-inch and 18-inch models
- Available in amber and white LED
- Sealed, waterproof



ILL70

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
11" WHITE LED - 9 DIODES			
ILL70CBAWN	ILL70CBAWNP	No switch, chrome housing	10
ILL70CBBAWN	ILL70CBBAWNP	No switch, black housing	10
ILL70CBSBAWN	ILL70CBSBAWNP	On/off switch, black housing	10
ILL70CCSBAWN	ILL70CCSBAWNP	On/off switch, chrome housing	10
11" AMBER LED - 9 DIODES			
ILL70ABBAWN	ILL70ABBAWNP	No switch, black housing	10
RETAIL			
ILL70CBAWNFS		Light, no switch, chrome bezel	12

Raw lumen output: 189 lm

Effective lumen output: 171 lm



ILL71

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
18" WHITE LED - 18 DIODES			
ILL71CBAWN	ILL71CBAWNP	No switch, chrome housing	10
ILL71C1BAWN	ILL71C1BAWNP	No switch, chrome housing, high lumen output	10
ACCESSORIES			
A71CBAWN	A71CBAWNP	Chrome base for ILL71CBAWN	10
A71CCBWAN	A71CCBWANP	Chrome base and bezel for ILL71CBAWN	10
A71C1BAWN	A71C1BAWNP	Chrome base for ILL71C1BAWN	25
RETAIL			
ILL71CBAWNFS		Light, no switch, chrome bezel	12

Raw lumen output: 370 lm

Effective lumen output: 342 lm

IP67 rating: protected from dust and capable of withstanding water immersion, offering increased reliability and service life

MATERIALS	Polycarbonate lens and housing
VOLT/AMP	ILL70: 12.8VDC - .150A
	ILL71: 12.8VDC - .300A
WT/DIMS	ILL70: .154 lb. / 11.313" x 1.625" x 1.125"
	ILL71: .187 lb. / 18" x 2.125" x 1.063"
WARRANTY	Lifetime LED Warranty

ILL85 SERIES
LED Exterior Step/Area Light

- Illuminate step well or pavement at base of steps or ramps
- Meets ADA lighting standard
- Surface mount, 3.662” mounting centers
- Hard wired design includes both lead and ground wires
- Operating voltage 8-30VDC, for use with 12VDC or 24VDC systems
- Polycarbonate construction with polished chrome finish
- Mounting gasket included

ILL85CB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
STEP/AREA LIGHT - 10 DIODES			
ILL85CB	ILL85CBP	Step/area light	10

MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - .107A
WT/DIMS	.154 lb. / 4.25” x 1.24” x 1.69”
WARRANTY	Lifetime LED Warranty



ILL86 SERIES
LED Exterior Step/Area Light

- Illuminate step well or pavement at base of steps or ramps
- Meets ADA lighting standard
- Surface mount, 2.92” mounting centers
- Hard wired design includes both lead and ground wires
- Die cast aluminum housing coated for protection against corrosion and UV exposure; polycarbonate lens

ILL86CB

ILL86BCB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
STEP/AREA LIGHT - 5 DIODES			
ILL86CB	ILL86CBP	Step/area light, white finish	10
ILL86BCB	ILL86BCBP	Step/area light, black finish	10

MATERIALS	Die cast aluminum housing, polycarbonate lens
VOLT/AMP	12.8VDC - .25A
WT/DIMS	.154 lb. / 4” x 2.5” x 1.313”
WARRANTY	Lifetime LED Warranty



ILL87 SERIES
LED ADA Exterior Step/Area Light

ILL87CB



- Illuminate step well or pavement at base of steps or ramps
- Meets ADA lighting standard
- Surface mount, 2.92" mounting centers
- Hard wired design includes both lead and ground wires

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
STEP/AREA LIGHT - 5 DIODES			
ILL87CB	ILL87CBP	Step/area light	10

MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - .17A
WT/DIMS	.231 lbs / 4" x 2.5" x 1.29"
WARRANTY	Lifetime LED Warranty

ILL91 SERIES
6" LED Interior Dome Light

ILL91CB



- Surface mount steel base, chrome plated
- Hard wired design includes both lead and ground wires
- Two diodes provide low amp draw, bright white light

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
DOME LIGHT - 6 DIODES			
ILL91CB	ILL91CBP	Dome light	50
ILL91CPG	ILL91CPGP	Dome light, .180 male bullets	50

Raw lumen output: 600 lm
Effective lumen output: 540 lm

MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - .35A
WT/DIMS	.154 lb. / 6.438" x 6.438" x 1.625"
WARRANTY	Lifetime LED Warranty

LM SERIES
LED Courtesy & Accent Lights

- LM315BB is semi-recess mount courtesy light
- LM835CB is eight-diode recess mount accent light with clear lens and chrome trim ring; screw mount
- All models are hard wired with ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
COURTESY LIGHT - 3 DIODES			
LM315BB	LM315BBP	Courtesy light, black	50
ACCENT LIGHT - 8 DIODE			
LM835CB	LM835CBP	Recess mount accent light	50

MATERIALS	Polycarbonate lens and housing	
VOLT/AMP	LM315BB:	12.8VDC - .007A
	LM835CB:	12.8VDC - .087A
WT/DIMS	LM315BB:	.187 lb. / 2.25" x 2.25" x 1.625"
	LM835CB:	.210 lb. / 3.75" x 3.75" x 0.75"
WARRANTY	Lifetime LED Warranty	

LM315BB

LM835CB

UCL07 SERIES
Silicone LED Rope Light

- Lumen rating: 1800 lm
- Sonically sealed, waterproof
- Flexible silicone design
- Surface adhesive mount
- Hard wired
- IP66 rating

UC07CB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
STRIP LIGHT - 76 COB			
UCL07CB	UCL07CBP	Rope light, silicone color	1

MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - .892A
WT/DIMS	33"
WARRANTY	Lifetime LED Warranty

UCL09 SERIES

3" Sealed LED Utility/Hitch Light for Surface Mount

- Designed to illuminate hitch area of trailer
- Sonically sealed, waterproof
- Flange surface mount – no panel cutout required
- Design includes both lead and ground wire

UCL09CB

UCL09CBB



UCL09RCB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
WHITE UTILITY LIGHT - 9 DIODES			
UCL09CB	UCL09CBP	Utility light, 9 white LEDs	50
BLUE UTILITY LIGHT - 9 DIODES			
UCL09CBB	UCL09CBBP	Utility light, 6 white, 3 blue LEDs, 3-wire	50
RED UTILITY LIGHT - 9 DIODES			
UCL09RCB	UCL09RCBP	Utility light, 9 red LEDs	50
ACCESSORIES			
A09BB	A09BBP	Black snap-on trim ring	50
A09CB	A09CBP	Chrome snap-on trim ring	50
A09WB	A09WBP	White snap-on trim ring	50
A09GB	A09GBP	Black gasket	50

MATERIALS	Polycarbonate lens and housing
VOLT/AMP	UCL09CB: 12.8VDC - 0.074A
	UCL09CBB: 12.8VDC - 0114A
WT/DIMS	.265 lb. / 3.25" x 3.25" x .813"
WARRANTY	Lifetime LED Warranty



UCL10 SERIES

3/4" Sealed LED Utility Light

- Sealed, waterproof
- Compact – fits 3/4" hole
- Design includes both lead and ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
UTILITY LIGHT - 1 DIODE			
UCL10CKB	UCL10CKBP	Clear utility light, A11GB	50
UCL10CK1B	UCL10CK1BP	Clear utility light, A11GB, .156 male bullets	50
BLUE - 1 DIODE			
UCL10BCKB	UCL10BCKBP	Blue utility light, A11GB	20

MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.054A
WT/DIMS	.265 lb. / 0.74" x 0.74" x 0.938"
WARRANTY	Lifetime LED Warranty

UCL10CKB

UCL10BCKB



UCL11 SERIES
3/4" Sealed LED Utility Light

- Sealed, waterproof
- Compact – fits 3/4" hole
- Design includes both lead and ground wire

UCL11CKB





BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
UTILITY LIGHT - 2 DIODES			
UCL11CB	UCL11CBP	Utility light	50
UCL11CKB	UCL11CKBP	Kit: UCL11CB & A11GB grommet	50
UCL11CKPG	UCL11CKPGP	Kit: UCL11CB with .180 male bullets & A14GB grommet	50
ACCESSORIES			
A11GB	A11GBP	Grommet	100
A14GB	A14GBP	Sealing grommet, .125-.250" material	100
A11PB	A11PBP	Snap-in mounting flange	100

MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.054A
WT/DIMS	.265 lb. / 0.74" x 0.74" x 0.938"
WARRANTY	Lifetime LED Warranty

UCL13 SERIES
Sealed LED Utility Light

- Sealed, waterproof
- Compact, surface mount design
- Design includes both lead and ground wire

UCL13C2PG



UCL13CB2B





BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
WHITE UTILITY LIGHT - 2 DIODES			
UCL13C2PG	UCL13C2PGP	Utility light, .180 female barrels	20
UCL13CPG	UCL13CPGP	Utility light, .156 male bullets	20
BLUE - 2 DIODES			
UCL13CB2B	UCL13CB2BP	Blue LED utility light	20
ACCESSORIES			
A13C2B	A13C2BP	Chrome base/bezel	100
A13B2B	A13B2BP	Black base/bezel	100
A13G2B	A13G2BP	Gasket	200

MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.020A
WT/DIMS	.088 lb. / 2.5" x 1.063" x .688"
WARRANTY	Lifetime LED Warranty

UCL19 SERIES

Miro-Flex™ Sealed LED Utility Light

- Sealed, waterproof
- Surface mount, mounts on 4-5/8" centers
- Design includes both lead and ground wire

UCL19CB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
UTILITY LIGHT - 4 DIODES			
UCL19CB	UCL19CBP	Utility light	20
ACCESSORIES			
A19CB	A19CBP	Chrome bezel	100

MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.051A
WT/DIMS	.132 lb. / 5.75" x 1.563" x .75"
WARRANTY	Lifetime LED Warranty



UCL41 SERIES

LED Low Profile Exterior Scene Light

- Sonically sealed, waterproof
- Low profile design with 45-degree downward angle (lens angle at 15 degrees)
- Surface flange mount on 7.875" centers
- Operating voltage 12-24VDC; use with both 12VDC and 24VDC systems
- IP67 Rated
- Hard wired with 6" lead and ground wires

UCL41CB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
UTILITY LIGHT - 12 DIODES			
UCL41CB	UCL41CBP	Exterior scene light, 12V-24V	10
ACCESSORIES			
A41CBB	A41CBBP	Black plastic bezel	50
A41CRB	A41CRBP	Chrome bezel	50

Raw lumen output: 2400 lm

Effective lumen output: 1200 lm

MATERIALS	Aluminum base, polycarbonate lens
VOLT/AMP	12.8VDC - 2.07A / 24VDC - 0.96A
WT/DIMS	1 lb. / 8.7" x 2.95" x 1.59"
WARRANTY	Lifetime LED Warranty



UCL50 SERIES

Miro-Flex™ 2" Sealed LED Utility Light

UCL50CB



- Miro-Flex™ design with Crystal Clear™ lens
- Operating voltage 12-24VDC
- Sonically sealed, waterproof
- Accepts standard two-pin PL-10 plug

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
UTILITY LIGHT - 9 DIODES			
UCL50CB	UCL50CBP	12-24VDC Utility light	20
ACCESSORIES			
A46PB	A46PBP	Straight plug, 6" lead	100
A86PB	A86PBP	Straight plug, 18" lead	100
A54GB	A54GBP	2" Flush mount grommet	100
A54GK	A54GKP	2" Kit: A54GB and A46PB	100
A55CB	A55CBP	2" Chrome trim ring	20
BK5557GB	BK5557GBP	Cam-on mounting bracket	50

MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.013A
WT/DIMS	.088 lb. / 2" x 2" x 1.188"
WARRANTY	Lifetime LED Warranty

UCL55 SERIES

2" Sealed LED Utility Light

UCL55CB



- Sonically sealed, waterproof
- Accepts standard two-pin PL-10 plug

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
UTILITY LIGHT - 3 DIODES			
UCL55CB	UCL55CBP	Utility light	20
ACCESSORIES			
A46PB	A46PBP	Straight plug, 6" lead	100
A86PB	A86PBP	Straight plug, 18" lead	100
A54GB	A54GBP	2" Flush mount grommet	100
A54GK	A54GKP	2" Kit: A54GB and A46PB	100
A55CB	A55CBP	2" Chrome trim ring	20
BK5557GB	BK5557GBP	Cam-on mounting bracket	50

MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.047A
WT/DIMS	.088 lb. / 2" x 2" x 1"
WARRANTY	Lifetime LED Warranty

UCL59 SERIES
Thinline Sealed LED Utility Light

UCL59CB

- Sonically sealed, waterproof
- Low profile design - less than 1/2” thick
- Surface mount on 11-3/4” centers
- Hard wired with separate ground wire
- Available in bulk and polypack packaging

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
THINLINE UTILITY LIGHT - 9 DIODES			
UCL59CB	UCL59CBP	Bar style utility light, 2-wire	10

Raw lumen output: 585 lm
Effective lumen output: 386 lm

MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.22A
WT/DIMS	0.2 lbs. / 12.625” x 1” x .41”
WARRANTY	Lifetime LED Warranty



UCL60/160 SERIES
Sealed LED Utility Light

UCL60CB

UCL60CSBB

TOUCH ON/OFF

UCL60CSNB

- Sealed, waterproof
- Compact, surface mount design
- Design includes both lead and ground wire
- CSA certified for use in sleeping quarters
- Snap-on trim ring included, multiple finishes available

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
TOUCH SWITCH UTILITY LIGHT - 6 DIODES			
UCL60CSBB	UCL60CSBBP	Utility light, black trim ring	20
UCL60CSNB	UCL60CSNBP	Utility light, brushed nickel trim ring	20
UCL60CSWNB	UCL60CSWNBP	Utility light, warm white LED, brushed nickel trim ring	20
UTILITY LIGHT, NO SWITCH - 6 DIODES			
UCL60CB	UCL60CBP	Utility light, chrome trim ring	20
UCL60CBPG	UCL60CBPGP	Utility light, chrome trim ring, .180 female barrels	20

Raw lumen output: 224 lm
Effective lumen output: 168 lm

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
GLOLIGHT™ UTILITY LIGHT - 6 DIODES			
UCL160CB	UCL160CBP	Utility light, chrome trim ring	20

Raw lumen output: 224 lm
Effective lumen output: 168 lm

GloLight®
PATENTED TECHNOLOGY

UCL160CB

MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.020A
WT/DIMS	.088 lb. / 3" x 3" x .375"
WARRANTY	Lifetime LED Warranty



UCL65 SERIES
Sealed LED Thinline Utility Light

- Sealed, waterproof
- Multiple mounting and wiring options available

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
UTILITY LIGHT - 6 DIODES			
UCL65CB	UCL65CBP	Utility light	20
ACCESSORIES			
A65B	A65BP	Black bracket	50
A65P	A65PP	Single wire plug, .156 male bullet	50
A65PB	A65PBP	Kit: A65B black bracket & A65P plug	50
A66PB	A66PBP	Kit: Gray bracket & A65P plug	50
A67CB	A67CBP	Kit: Chrome bracket & A65P plug	50
A68PB	A68PBP	Kit: Black bracket & 2-wire plug	50

For more details on mounting and wiring accessories, see Accessories section at back of catalog.

UCL65CB





MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.048A
WT/DIMS	.066 lb. / 3.875" x 1.25" x 1.125"
WARRANTY	Lifetime LED Warranty

UCL66 SERIES
Sealed LED Surface Mount Utility Light

- Sonically sealed, waterproof
- Surface mount, mounts on 3" centers
- Includes both lead and ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
GREEN UTILITY LIGHT - 6 DIODES			
UCL66GB	UCL66GBP	Utility light	20

UCL66GB



MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.057A
WT/DIMS	.088 lbs. / 4" x .875" x 1.188"
WARRANTY	Lifetime LED Warranty

UCL90 SERIES
LED Flexible Strip Lighting

UCL90CB

UCL90BCB



- Cut to desired length
- Flexible design fits many applications
- Supplied in 17-ft rolls
- Adhesive mount
- Available with white or blue diodes

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
WHITE STRIP LIGHT			
UCL90CB	UCL90CBP	17-foot roll	10
BLUE STRIP LIGHT			
UCL90BCB	UCL90BCBP	17-foot roll	10
ACCESSORIES			
A90PB	A90PBP	Snap-on connector, wire leads	20
A90P1B	A90P1BP	Snap-on connector, strip-to-strip	20

MATERIALS	Diodes, copper, polyimide polymer, adhesive
VOLT/AMP	12.8VDC
WT/DIMS	Reel: .39 lbs / 6.10” x 6.10” x 0.48” Strip: .39 lbs / 204” x 0.375” x 0.125”
WARRANTY	Lifetime LED Warranty

UCL91/92 SERIES
LED Flexible Strip Lighting

- Cut to desired length
- Flexible design fits many applications
- Kits include strip light and two each snap-on connectors A90PB and A90P1B
- Supplied in rolls (17ft and 5ft)
- 3M adhesive backing
- IP65 rated for dust and water resistance
- Available with white or blue diodes
- Supplied in color retail boxes

UCL91CB

UCL91BCB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
WHITE STRIP LIGHT			
UCL91CB	-	17-foot roll, color box	10
UCL92CB	-	5-foot roll, color box	10
UCL91CKB	-	Kit: 17-foot roll, color box	10
UCL92CKB	-	Kit: 5-foot roll, color box	10
BLUE STRIP LIGHT			
UCL91BCB	-	17-foot roll, color box	10
UCL92BCB	-	5-foot roll, color box	10
UCL91BCKB	-	Kit: 17-foot roll, color box	10
UCL92BCKB	-	Kit: 5-foot roll, color box	10
ACCESSORIES			
A90PB	A90PBP	Snap-on connector, wire leads	20
A90P1B	A90P1BP	Snap-on connector, strip-to-strip	20

UCL92CB

UCL92BCB

MATERIALS	Diodes, copper, polyimide polymer, adhesive
VOLT/AMP	12.8VDC
WT/DIMS	.39 lbs / Reel: 6.10" x 6.10" x 0.48"
	Strip: 204" x 0.375" x 0.125"
WARRANTY	Lifetime LED Warranty



GloLight®

UCL178 SERIES

GloLight® 6" Oval Sealed LED Utility Lights for Surface Mount

Tail and Utility

Unlit

UCL178RFP2B Auxiliary



- LED utility light with built-in auxiliary tail light
- Sonically sealed, waterproof
- Surface flange mount – no panel cutout required
- Design includes both lead and ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
UTILITY LIGHT - 22 DIODES			
UCL178RFP2B	UCL178RFP2BP	Hard wired, female PL-3 connector	10
ACCESSORIES			
A78CB1	A78CB1P	Chrome flange cover	25
A78RXB	A78RXBP	Red reflex flange cover & gasket	25
A7TRSSB	A7TRSSBP	Stainless steel trim ring	100

MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.50A
WT/DIMS	.265 lbs. / 7.5" x 3.25" x 1.25"
WARRANTY	Lifetime LED Warranty

UCL299 SERIES
Utility Light

- Sonically sealed, waterproof
- Adhesive mount
- Hard wired, includes separate ground wire
- Available in bulk and polypack packaging

UCL299CPG

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
UTILITY LIGHT - 1 DIODE			
UCL299CPG	UCL299CPGP	Clear utility light, .180 male bullets	50

MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - .12A
WT/DIMS	.046 lb. / 1.53" x .73" x .5"
WARRANTY	Lifetime LED Warranty



ULL25 SERIES
COB LED Utility Strip Light

- Waterproof
- Slim design - only 5/8" wide and 3/16" thick
- Design includes both lead and ground wire
- Ultrawhite – color temperature 6500K

ULL25CTB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
STRIP LIGHT - 76 COB			
ULL25CTVRB	ULL25CTVRBP	12V strip light, voltage regulator	50
ULL25CTB	ULL25CTBP	12V strip light	50
Raw lumen output: 380 lm **Effective lumen output:** 220 lm			

MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - .3A
WT/DIMS	.25 lb. / 6.829" x .616" x 0.14"
WARRANTY	Lifetime LED Warranty



ULL69APG

Thinline Sealed LED Utility Light

ULL69APG

- Sonically sealed, waterproof
- Low profile design–only 5/8” thick
- Surface mount on 14-1/8” centers; optional gasket
- Three-wire design - low and bright functions
- Hard wired with separate ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW - 11 DIODE			
ULL69APG	ULL69APGP	Bar style utility light, 2-wire	10
ACCESSORIES			
A69CB	A69CBP	Chrome base/bezel	10
A69GB	A69GBP	Gasket	50



MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8V - 0.28A/0.01A
WT/DIMS	.441 lbs. / 15” x 1.375” x .625”
WARRANTY	Lifetime LED Warranty

TLL149 SERIES
Opti-Brite™ LED Work Light

- Heavy duty design with powder coated, die cast aluminum housing and polycarbonate lens
- Dual power: use with 12VDC and 24VDC systems
- Stainless steel mounting hardware

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
FLOOD BEAM - 10 DIODES			
TLL149FB	TLL149FBP	Flood beam	1

Raw lumen output: 2400 lm
Effective lumen output: 1680 lm

MATERIALS	Polycarbonate lens, aluminum housing
VOLT/AMP	13.5V at 2.05A±0.18A, 28V at 0.97A±0.08A
WT/DIMS	0.95 lbs. / 6.625" x 3.5" x 2.665"
WARRANTY	Lifetime LED Warranty

TLL149FB



IP69K RATING

Highest designation available for water ingress testing, offering increased reliability and service life when subjected to severe environmental conditions or cleaning methods.



TLL30 SERIES

Opti-Brite™ LED Work Light

TLL30FB

- Compact design – only 3.25” diameter
- Die cast aluminum housing with powder coat finish
- Stainless steel hardware
- 16-gauge, 20” lead and ground wire; IP69K rating

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
FLOOD BEAM - 4 DIODES			
TLL30FB	TLL30FBP	Flood beam	1t

Raw lumen output: 960 lm
Effective lumen output: 670 lm



MATERIALS	Polycarbonate lens, aluminum housing
VOLT/AMP	12.8VDC - 0.75A, 24.0VDC - 0.37A
WT/DIMS	1.468 lbs. / 3.27” x 5.70” x 2.36”
WARRANTY	Lifetime LED Warranty



IP69K RATING

Highest designation available for water ingress testing, offering increased reliability and service life when subjected to severe environmental conditions or cleaning methods.

TLL44/45 SERIES

Opti-Brite™ LED Work Lights

- Heavy duty design with powder coated, die cast aluminum housing and polycarbonate lens
- Low profile design – only 2 inches deep
- Dual power: use with 12VDC and 24VDC systems
- Stainless steel mounting hardware
- 14-gauge, 10” lead and ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
ROUND LED WORK LIGHT - 6 DIODES			
TLL44FB	TLL44FBP	Flood beam	2
RETAIL			
TLL144FSL	Retail Ready	Flood beam, window box	3

Raw lumen output: 1200 lm
Effective lumen output: 720 lm

MATERIALS	Polycarbonate lens, aluminum housing
VOLT/AMP	12.8VDC - 1.1A, 24.0VDC - 0.48A
WT/DIMS	0.98 lbs. / 4” x 6.281” x 2.375”
WARRANTY	Lifetime LED Warranty

TLL44FB



BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
ROUND LED WORK LIGHT - 8 DIODES			
TLL45FB	TLL45FBP	Flood beam	3

Raw lumen output: 1600 lm
Effective lumen output: 897 lm

MATERIALS	Polycarbonate lens, aluminum housing
VOLT/AMP	12.8VDC - 1.38A, 24.0VDC - 0.65A
WT/DIMS	1.389 lbs. / 4.5” x 7” x 2”
WARRANTY	Lifetime LED Warranty

TLL45FB



TLL144FSL

TLL46 SERIES

Opti-Brite™ LED Work Lights

TLL46CFB

- Heavy duty design with powder coated, die cast aluminum housing and polycarbonate lens
- Low profile design – less than 2.5 inches deep
- Dual power: use with 12VDC and 24VDC systems
- Stainless steel mounting hardware
- 14-gauge, 10” lead and ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
FLOOD BEAM - 9 DIODES			
TLL46CFB	TLL46CFBP	Flood beam	3

Raw lumen output: 2160 lm
Effective lumen output: 1492 lm

MATERIALS	Polycarbonate lens, aluminum housing
VOLT/AMP	12.8VDC - 1.70A, 24.0VDC - 1.0A
WT/DIMS	1.764 lbs. / 5” x 7” x 2.375”
WARRANTY	Lifetime LED Warranty

TLL46TB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
TRAPEZOID BEAM - 9 DIODES			
TLL46TB	TLL46TBP	Trapezoid beam	3

Raw lumen output: 1800 lm
Effective lumen output: 707 lm

MATERIALS	Polycarbonate lens, aluminum housing
VOLT/AMP	12.8VDC - 1.50A, 24.0VDC - 0.73A
WT/DIMS	1.764 lbs. / 5” x 7” x 2.375”
WARRANTY	Lifetime LED Warranty



IP69K RATING

Highest designation available for water ingress testing, offering increased reliability and service life when subjected to severe environmental conditions or cleaning methods.

TLL48 SERIES
Opti-Brite™ LED Work Light

- Heavy duty design with powder coated, die cast aluminum housing and polycarbonate lens
- Low profile design – less than 2.5 inches deep
- Dual power: use with 12VDC and 24VDC systems
- Stainless steel mounting hardware
- 14-gauge, 10” lead and ground wire; IP69K rating

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
FLOOD BEAM - 6 DIODES			
TLL48FB	TLL48FBP	Flood beam	5

Raw lumen output: 1200 lm
Effective lumen output: 617 lm

MATERIALS	Polycarbonate lens, aluminum housing
VOLT/AMP	12.8VDC - 1.52A, 24.0VDC - 0.65A
WT/DIMS	1.14 lbs. / 4.15” x 6.375” x 2.14”
WARRANTY	Lifetime LED Warranty

TLL48FB



TLL50 SERIES
Opti-Brite™ LED Work Light

- Lightweight, compact LED work light
- Corrosion proof housing and polycarbonate lens
- Dual power: use with 12VDC and 24VDC systems
- 22-gauge, 10” lead and ground wire
- IP69K rating

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
FLOOD BEAM - 9 DIODES			
TLL50FB	TLL50FBP	Flood beam	3
RETAIL			
TLL150FSL	Retail Ready	Flood beam, window box	3

Raw lumen output: 324 lm
Effective lumen output: 252 lm

MATERIALS	Polycarbonate lens and housing, stainless steel hardware
VOLT/AMP	12.8VDC - 1.50A, 24.0VDC - 0.73A
WT/DIMS	1 lbs. / 4.938” x 6.938” x 2.375”
WARRANTY	Lifetime LED Warranty

TLL50FB

TLL150FSL



TLL51 SERIES

Opti-Brite™ LED Work Light

TLL51FB



- Heavy duty design with powder coated, die cast aluminum housing and polycarbonate lens
- Compact design – only 2 inches square
- Dual power: use with 12VDC and 24VDC systems
- Stainless steel mounting hardware
- 14-gauge, 10” lead and ground wire; IP69K rating

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
FLOOD BEAM - 1 DIODE			
TLL51FB	TLL51FBP	Flood beam	10
TLL51FRPG	TLL51FRPGP	Flood beam, .180 male bullet on power, ring terminal on ground	10

Raw lumen output: 800 lm
Effective lumen output: 549 lm

MATERIALS	Polycarbonate lens, aluminum housing
VOLT/AMP	12.8VDC - 0.91A, 24.0VDC - 0.42A
WT/DIMS	0.37 lbs. / 2” x 3” x 2.5”
WARRANTY	Lifetime LED Warranty

TLL52 SERIES

Opti-Brite™ LED Work Light

TLL52FWB TLL52FB

TLL152FSL

- Heavy duty design with powder coated, die cast aluminum housing and polycarbonate lens
- Compact design – only 2.75 inches square
- Dual power: use with 12VDC and 24VDC systems
- Stainless steel mounting hardware
- 14-gauge, 10” lead and ground wire; IP69K rating

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
FLOOD BEAM - 3 DIODES			
TLL52FB	TLL52FBP	Flood beam, black housing	10
TLL52FWB	TLL52FWBP	Flood beam, white housing	10
RETAIL			
TLL152FSL	Retail Ready	Flood beam, window box	3

Raw lumen output: 600 lm
Effective lumen output: 325 lm



MATERIALS	Polycarbonate lens and housing, stainless steel hardware
VOLT/AMP	12.8VDC - 1.50A, 24.0VDC - 0.73A
WT/DIMS	.38 lbs. / 2.75” x 5.171” x 1.687”
WARRANTY	Lifetime LED Warranty

TLL54 SERIES
Opti-Brite™ LED Work Light

- Heavy duty design with powder coated, die cast aluminum housing and polycarbonate lens
- Low profile design – less than 2.5 inches deep
- Dual power: use with 12VDC and 24VDC systems
- Stainless steel mounting hardware
- 14-gauge, 10” lead and ground wire; IP69K rating

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
SPOT BEAM - 9 DIODES			
TLL54TB	TLL54TBP	Spot beam	5

Raw lumen output: 1800 lm
Effective lumen output: 900 lm

MATERIALS	Polycarbonate lens, aluminum housing
VOLT/AMP	12.8VDC - 1.50A, 24.0VDC - 0.73A
WT/DIMS	1.51 lbs. / 5” x 7” x 2.375”
WARRANTY	Lifetime LED Warranty

TLL54TB



TLL55 SERIES
Opti-Brite™ LED Work Light

WIDE ANGLE BEAM

- Contoured lens for wide angle beam
- Die cast aluminum housing with powder coat finish
- Stainless steel hardware
- 14-gauge, 10” lead and ground wire; IP69K rating

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
FLOOD BEAM - 9 DIODES			
TLL55FB	TLL55FBP	Flood beam	1

Raw lumen output: 2160 lm
Effective lumen output: 1512 lm

MATERIALS	Polycarbonate lens, aluminum housing
VOLT/AMP	12.8VDC - 1.50A, 24.0VDC - 0.73A
WT/DIMS	1.35 lbs. / 4.87” x 6.90” x 2.03”
WARRANTY	Lifetime LED Warranty

TLL55FB



TLL56/57 SERIES
Opti-Brite™ LED Work Lights

TLL56FB



- Heavy duty design with powder coated, die cast aluminum housing and polycarbonate lens
- Dual power: use with 12VDC and 24VDC systems
- Stainless steel mounting hardware
- 16-gauge, 20" lead and ground wire; IP69K rating

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
FLOOD BEAM - 8 DIODES			
TLL56FB	TLL56FBP	Flood beam	2
TLL57FB	TLL57FBP	Flood beam, shock mount	2

Raw lumen output: 4000 lm
Effective lumen output: 2800 lm

MATERIALS	Polycarbonate lens, aluminum housing
VOLT/AMP	12.8VDC - 5.0A, 24.0VDC - 2.5A
WT/DIMS	3.53 lbs. / 7.161" x 9" x 4.313"
WARRANTY	Lifetime LED Warranty

TLL60 SERIES
Opti-Brite™ LED Work Light

TLL60FB



- Heavy duty design with powder coated, die cast aluminum housing and polycarbonate lens
- Rectangular design – 6 inches wide by 2 inches high
- Dual power: use with 12VDC and 24VDC systems
- Stainless steel mounting hardware
- 14-gauge, 10" lead and ground wire; IP69K rating

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
FLOOD BEAM - 6 DIODES			
TLL60FB	TLL60FBP	Flood beam	5

Raw lumen output: 1200 lm
Effective lumen output: 720 lm

MATERIALS	Polycarbonate lens, aluminum housing
VOLT/AMP	12.8VDC - 1.1A, 24.0VDC - 0.48A
WT/DIMS	0.95 lbs. / 6" x 4.5" x 2.4"
WARRANTY	Lifetime LED Warranty

TLL64 SERIES
Opti-Brite™ LED Work Light

- Heavy duty design with powder coated, die cast aluminum housing and polycarbonate lens
- Ultrabright output in standard size light – 2240 lumens
- Dual power: use with 12VDC and 24VDC systems
- Stainless steel mounting hardware
- 14-gauge, 10” lead and ground wire; IP69K rating

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
FLOOD BEAM - 4 DIODES			
TLL64FB	TLL64FBP	Flood beam	2

Raw lumen output: 3200 lm
Effective lumen output: 2240 lm

MATERIALS	Polycarbonate lens, aluminum housing
VOLT/AMP	12.8VDC - 3.16A, 24.0VDC - 1.41A
WT/DIMS	1.41 lbs. / 4.187” x 6.5” x 3”
WARRANTY	Lifetime LED Warranty

TLL64FB



TLL70 SERIES
Opti-Brite™ LED Work Light

WIDE ANGLE BEAM

- Contoured lens for wide angle beam
- Heavy duty design with powder coated, die cast aluminum housing and polycarbonate lens
- Ultrabright output in standard size light – 3360 lumens
- Dual power: use with 12VDC and 24VDC systems
- Stainless steel mounting hardware
- 14-gauge, 10” lead and ground wire; IP69K rating

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
FLOOD BEAM - 6 DIODES			
TLL70FB	TLL70FBP	Flood beam	2

Raw lumen output: 4800 lm
Effective lumen output: 3360 lm

MATERIALS	Polycarbonate lens, aluminum housing
VOLT/AMP	12.8VDC - 2.8A, 24.0VDC - 1.43A
WT/DIMS	1.41 lbs. / 5” x 4.375” x 2.625”
WARRANTY	Lifetime LED Warranty

TLL70FB



TLL71 SERIES
Opti-Brite™ LED Work Light

TLL71FB



- Contoured lens for wide angle beam
- Heavy duty design with powder coated, die cast aluminum housing and polycarbonate lens
- Dual power: use with 12VDC and 24VDC systems
- Stainless steel mounting hardware
- 14-gauge, 10” lead and ground wire; IP69K rating

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
FLOOD BEAM - 9 DIODES			
TLL71FB	TLL71FBP	Flood beam	2

Raw lumen output: 2160 lm
Effective lumen output: 1492 lm

MATERIALS	Polycarbonate lens, aluminum housing
VOLT/AMP	12.8VDC - 1.43A, 24.0VDC - 0.66A
WT/DIMS	1.41 lbs / 4” x 5” x 2.25”
WARRANTY	Lifetime LED Warranty

TLL72 SERIES
Opti-Brite™ LED Work Light

TLL72FB



- Contoured lens for wide angle beam
- Heavy duty design with powder coated, die cast aluminum housing and polycarbonate lens
- Dual power: use with 12VDC and 24VDC systems
- Stainless steel mounting hardware
- 14-gauge, 10” lead and ground wire; IP69K rating

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
FLOOD BEAM - 9 DIODES			
TLL72FB	TLL72FBP	Flood beam	2

Raw lumen output: 2160 lm
Effective lumen output: 1492 lm

MATERIALS	Polycarbonate lens, aluminum housing
VOLT/AMP	12.8VDC - 1.48A, 24.0VDC - 0.7A
WT/DIMS	1.5 lbs / 5” x 5.375” x 2.25”
WARRANTY	Lifetime LED Warranty

TLL73 SERIES
Opti-Brite™ LED Work Light

- Heavy duty design with powder coated, die cast aluminum housing and polycarbonate lens
- Dual power: use with 12VDC and 24VDC systems
- Stainless steel mounting hardware; built in handle
- 14-gauge, 10” lead and ground wire; IP69K rating

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
FLOOD BEAM - 9 DIODES			
TLL73FB	TLL73FBP	Flood beam	3

Raw lumen output: 2160 lm
Effective lumen output: 1492 lm

MATERIALS	Polycarbonate lens, aluminum housing
VOLT/AMP	12.8VDC - 1.48A, 24.0VDC - 0.7A
WT/DIMS	1.61 lbs / 5” x 7.5” x 3.25”
WARRANTY	Lifetime LED Warranty



TLL73FB



TLL80 SERIES
Opti-Brite™ LED Mini Flood Light

TLL80FB

- Coated die cast aluminum housing, polycarbonate lens
- Compact design – only 3 inches wide by 2 inches high
- Bright white SMD diodes for bright, dependable light

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
FLOOD BEAM - 6 DIODES			
TLL80FB	TLL80FBP	Flood beam, black housing	5

Raw lumen output: 270 lm
Effective lumen output: 150 lm



MATERIALS	Polycarbonate lens, aluminum housing
VOLT/AMP	12.8VDC - .19A
WT/DIMS	.7 lbs. / 3" x 2" x 1.563"
WARRANTY	Lifetime LED Warranty

DLL25/50 SERIES
LED Docking/Utility Lights

DLL50CB

- Wide, low beam ideal for docking or loading applications
- Die cast aluminum housing coated for protection against corrosion and UV exposure; durable polycarbonate lens
- Sealed lens, gasket at wire entry; IP44 rating
- Dual power: use with 12VDC and 24VDC systems
- Stainless steel mounting hardware
- 20-gauge lead and ground wire with tinned ends

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
DOCKING/UTILITY LIGHTS - 2 DIODES			
DLL50CB	DLL50CBP	Black housing	10
RETAIL			
TLL25FS	Retail Ready	Black housing, clam	3
DLL50CC		Pair of lights, black housing, box	3

Raw lumen output: 440 lm
Effective lumen output: 396 lm



MATERIALS	Polycarbonate lens, aluminum housing	
VOLT/AMP	12.8/24.0VDC - 0.683A	
WT/DIMS	DLL50CB:	1.23 lbs. / 5" x 4" x 3.5"
	DLL50CC:	3.00 lbs. / 5" x 4" x 3.5"
WARRANTY	Lifetime LED Warranty	

UCL20 SERIES
22” LED Spot/Flood Light Bar

- Heavy duty aluminum housing and polycarbonate lens
- Dual power: use with 12VDC and 24VDC systems
- IP65 rated for dust and water resistance
- Hard wired
- Supplied in color retail window box

UCL20CB



BK20BB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
FLOOD BEAM - 40 DIODES			
UCL20CB	-	Spot/flood beam	1
ACCESSORIES			
BK20BB	-	Mounting bracket kit	20

Raw lumen output: 7500 lm
Effective lumen output: 4521 lm

MATERIALS	Die Cast Aluminum with Powder Coat Finish Housing and Polycarbonate Lens
VOLT/AMP	12.8VDC - 6.8A / 24VDC - 3.1A
WT/DIMS	4.8 lbs / 21.26” x 3.07” x 3.39”
WARRANTY	Lifetime LED Warranty

Opti-Brite

UCL21 SERIES

13” LED Spot/Flood Light Bar

UCL21CB

BK20BB

- Heavy duty aluminum housing and polycarbonate lens
- Dual power: use with 12VDC and 24VDC systems
- IP65 rated for dust and water resistance
- Hard wired
- Supplied in color retail window box

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
FLOOD BEAM - 24 DIODES			
UCL21CB	-	Spot/flood beam	1
ACCESSORIES			
BK20BB	-	Mounting bracket kit	20

Raw lumen output: 3700 lm

Effective lumen output: 2717 lm

MATERIALS	Die Cast Aluminum with Powder Coat Finish Housing and Polycarbonate Lens
VOLT/AMP	12.8VDC - 4A / 24VDC - 1.8A
WT/DIMS	3.19 lbs / 13.58” x 3.15” x 3.46”
WARRANTY	Lifetime LED Warranty

UCL22 SERIES
33” LED Spot/Flood Light Bar

- Heavy duty aluminum housing and polycarbonate lens
- Dual power: use with 12VDC and 24VDC systems
- IP65 rated for dust and water resistance
- Hard wired
- Supplied in color retail window box

UCL22CB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
FLOOD BEAM - 60 DIODES			
UCL22CB	-	Spot/flood beam	1
ACCESSORIES			
BK20BB	-	Mounting bracket kit	20

Raw lumen output: 12,600 lm
Effective lumen output: 6777 lm

BK20BB

MATERIALS	Die Cast Aluminum with Powder Coat Finish Housing and Polycarbonate Lens
VOLT/AMP	12VDC - 9.8A / 24VDC - 5.7A
WT/DIMS	5.625 lbs / 33” x 3.15” x 3.46”
WARRANTY	Lifetime LED Warranty

Opti-Brite

UCL23 SERIES

9" LED Spot/Flood Light Bar

UCL23CB



BK20BB

- Heavy duty aluminum housing and polycarbonate lens
- Dual power: use with 12VDC and 24VDC systems
- IP65 rated for dust and water resistance
- Hard wired, 16-in leads
- Supplied in color retail window box

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
FLOOD BEAM - 12 DIODES			
UCL23CB	-	Spot/flood beam	1
ACCESSORIES			
BK20BB	-	Mounting bracket kit	20

Raw lumen output: 2520 lm

Effective lumen output: 1550 lm

MATERIALS	Die Cast Aluminum with Powder Coat Finish Housing and Polycarbonate Lens
VOLT/AMP	12.8VDC - 3A / 24VDC - 1.5A
WT/DIMS	2.4 lbs / 7.25" x 3" x 3.5"
WARRANTY	Lifetime LED Warranty

UCL24 SERIES
3” LED Flood Lights

- 3” cube design fits many applications
- Post mount and recess flange mount models available
- Heavy duty aluminum housing and impact resistant polycarbonate lens
- IP65 rated for dust and water resistance
- Hard wired, 16” leads
- Packaged in full color retail box

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
FLOOD BEAM - 6 DIODES			
UCL24CB	-	Flood beam, post mount	1
UCL24CFB	-	Flood beam, flange mount	1

Raw lumen output: 1800 lm

Effective lumen output: 780 lm

MATERIALS	Die Cast Aluminum with Powder Coat Finish Housing and Polycarbonate Lens
VOLT/AMP	12.8VDC - 1.4A
WT/DIMS	Post: 1.2 lbs 3.25” x 3” x 2.75”
	Recess Flange: 1.2 lb / 4.25” x 3.625” x 2.75”
WARRANTY	Lifetime LED Warranty

UCL24CB

UCL24CFB

UCL24CB

UCL24CFB

Opti-Brite

UCL25 SERIES
50" LED Spot/Flood Light Bar

UCL25CB

- Heavy duty aluminum housing and polycarbonate lens
- Dual power - use with 12VDC and 24VDC systems
- IP65 rated for dust and water resistance
- Hard wired
- Supplied in color retail window box

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
FLOOD BEAM - 96 DIODES			
UCL25CB	-	Spot/flood beam	1
ACCESSORIES			
BK20BB	-	Mounting bracket kit	20

Raw lumen output: 20,000 lm

Effective lumen output: 11,600 lm

MATERIALS	Die Cast Aluminum with Powder Coat Finish Housing and Polycarbonate Lens
VOLT/AMP	12.8VDC - 22.9A / 24VDC - 11.9A
WT/DIMS	8.1 lbs. / 50" x 3" x 3.5"
WARRANTY	Lifetime LED Warranty

BK20BB



UCL32 SERIES

30" LED Light Bar with Supplemental Turn Function

UCL32CDTB

- Central white LEDs produce bright flood beam, red LEDs on left and right ends provide supplemental turn function (rear facing)
- White LEDs emit 6000K daylight white beam
- Dual power: use with 12VDC and 24VDC systems
- Heavy duty aluminum housing and polycarbonate lens
- Adjustable, sliding brackets for mounting versatility
- IP65 rated for dust and water resistance
- Hard wired with 24-in. leads (4-wire)
- Stainless steel mounting hardware

BK21BB

BULK P/N	DESCRIPTION	QTY
FLOOD BEAM - 96 DIODES		
UCL32CDTB	White flood beam, red supplemental turn	1
ACCESSORIES		
BK21BB	Mounting bracket kit	3

Raw lumen output: 7200 lm
Effective lumen output: 4000 lm

MATERIALS	Die Cast Aluminum with Powder Coat Finish Housing and Polycarbonate Lens
VOLT/AMP	12.8VDC - 6.8A / 24VDC - 3.1A
WT/DIMS	4.8 lbs / 29.6" x 2.3" x 2.875"
WARRANTY	Lifetime LED Warranty

ST45 SERIES

4" Round Sealed Lights

- Sonically sealed, waterproof
- Shock-proof socket guarantees long bulb life
- Accepts standard PL-3 plug
- Kits include grommet and plug

ST45RB

ST45AB

ST46RB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED STOP/TURN/TAIL LIGHTS			
ST45RB	ST45RBP	Light with PL-3 connection	50
ST44RB	ST44RBP	Kit: ST45RB, A45GB & A45PB	10
ST45RGB	ST45RGBP	Light with male pin connection	50
ST46RB	ST46RBP	Light with reflex lens, PL-3 connection	50
YELLOW PARKING/TURN SIGNALS			
ST45AB	ST45ABP	Light	50
ST44AB	ST44ABP	Kit: ST45AB, A45GB & A45PB	10
ACCESSORIES			
A45GB	A45GBP	Grommet	50
A45PB	A45PBP	Pigtail, 3-wire	100
A47PB	A47PBP	Right angle pigtail, 3-wire	100
BK45BB	BK45BBP	Black steel bracket	10
RETAIL			
ST45RK	Retail Ready	Kit: ST45RB, A45GB & A45PB, clam	6
ST45RS		Light only, clam	6

ST45RGB male pin connection detail

FMVSS	ST45RB: S T I P2
	ST45AB: I P P2
	ST46RB: S T I P2 A
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 2.4A Stop/Turn, 0.49A Tail/Parking
WT/DIMS	ST45/46: .221 lbs. / 4.25" x 4.25" x 2.063"
WARRANTY	Three Year Warranty



ST45AB/RB & 46RB

ST47 Series
4" Flange Mount Stop/Turn/Tail Light

- Sonically sealed, waterproof
- Shock-proof socket guarantees long bulb life

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED STOP/TURN/TAIL LIGHT			
ST47RB	ST47RBP	Flange mount, PL-3 connection, gray	50
ST47RKB	ST47RKBP	Kit: ST47RB & A45PB	10
ACCESSORIES			
A45PB	A45PBP	Pigtail, 3-wire	100
A47PB	A47PBP	Right angle pigtail, 3-wire	100

FMVSS	S T I P2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 2.4A Stop/Turn, .49A Tail
WT/DIMS	.617 lbs. / 5.50" x 5.50" x 2"
WARRANTY	Three Year Warranty

ST47RB



HOLE CUT-OUT: 4.5"

ST70/75 SERIES

6" Oval Sealed Lights

- Sonically sealed, waterproof
- Shock-proof socket guarantees long bulb life
- Accepts standard PL-3 plug
- Kits include grommet and plug

ST70RB

ST70RBTK

ST70AB

ST75AB



ST70



ST75AB

HOLE CUT-OUT: 6.85" X 2.5" (1.25" R)

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED STOP/TURN/TAIL LIGHTS			
ST70RB	ST70RBP	Light	50
ST74RB	ST74RBP	Kit: ST70RB, A70GB & A45PB	50
ST70RBTK	ST70RBTKP	ST70RB light sealed to bracket	30
ST64RB	ST64RBP	Kit: ST70RB, A70GB & A47PB (plug attached to light)	50
ST65RB	ST65RBP	Kit: ST70RB, A70GB & A47PB	50
YELLOW SIGNAL LIGHTS			
ST70AB	ST70ABP	Parking/turn signal	50
ST74AB	ST74ABP	Kit: ST70AB, A70GB & A45PB	50
ST75AB	ST75ABP	Mid-ship turn signal/marker	50
ST77AB	ST77ABP	Kit: ST75AB, A70GB & A45PB	50
ACCESSORIES			
A70GB	A70GBP	Grommet	50
A45PB	A45PBP	Pigtail, 3-wire	100
A47PB	A47PBP	Right angle pigtail, 3-wire	100
BK70BB	BK70BBP	Black steel bracket	10
RETAIL			
ST70RK	Retail Ready	Kit: ST70RB, A70GB & A45PB, clam	6
ST70RS		Red light only, clam	6
ST70AS		Yellow light only, clam	6
ST75AS		Yellow mid-ship turn signal/marker, clam	6

FMVSS	ST70RB: S T I P2 ST70AB: I P P2 ST75AB: E P2 A
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 2.4A Stop/Turn, 0.50A Tail/Parking
WT/DIMS	ST70: .265 lb. / 6.5" x 2.313" x 2.375" ST75: .221 lbs. / 6.5" x 2.313" x 2.75"
WARRANTY	Three Year Warranty

ST33 SERIES
Rectangular Sealed Lights

- Sonically sealed, waterproof
- Shock-proof socket guarantees long bulb life
- Accepts standard PL-3 plug
- Kits include grommet and plug

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED STOP/TURN/TAIL LIGHTS			
ST33RB	ST33RBP	Light	10
ST34RB	ST34RBP	Kit: ST33RB, A33GB & A47PB	50
YELLOW PARKING/TURN LIGHTS			
ST33AB	ST33ABP	Light	10
ACCESSORIES			
A33GB	A33GBP	Grommet	50
A45PB	A45PBP	Pigtail, 3-wire	100
A47PB	A47PBP	Right angle pigtail, 3-wire	100

ST33RB

ST33AB

FMVSS	ST33RB: S T I P2 ST33AB: I P P2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 2.19A Stop/Turn, 0.49A Tail/Parking
WT/DIMS	.265 lb. / 5.313" x 3.438" x 1.938"
WARRANTY	Three Year Warranty



HOLE CUT-OUT: 5.453" X 3.578" (1" R)

ST40/42 SERIES

Flush Mount Stop/Turn/Tail Lights

ST40RB

ST42RB

A42GB

- Flush mount with acrylic lens, steel housing, gasket
- Replaceable lens and bulb
- Shock-proof socket guarantees long bulb life
- Hard wired

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED STOP/TURN/TAIL LIGHTS			
ST40RB	ST40RBP	Light, self grounding	50
ST42RB	ST42RBP	Light with reflex, ground wire	50
ACCESSORIES			
A40SRB	A40SRBP	Snap-in lens retention ring	100
A40RB	A40RBP	Red lens	25
A42GB	A42GBP	Gasket for flange	100
A43RB	A43RB	Red lens with reflex	25
A2057B	A2057BP	2057 bulb	50
RETAIL			
ST40RS	Retail Ready	Light, clam	6

FMVSS	ST40:	S T I
	ST42:	A I S T
MATERIALS	Acrylic lens, steel housing	
VOLT/AMP	12.8VDC - 2.4A Stop/Turn, 0.49A Tail/Parking	
WT/DIMS	.221 lbs. / 5.375" x 5.375" x 1.563"	
WARRANTY	Three Year Warranty	



HOLE CUT-OUT: 4.5"

ST90 SERIES

7” Transit Lights for Surface Mount

- Screw-on lens, easy to change bulb
- Surface mount on 6-1/4” centers
- Grounds through mounting hardware
- Acrylic lens, steel base plate

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED STOP/TAIL LIGHTS			
ST90RB	ST90RBP	Light, 1157 bulb	5
YELLOW TURN SIGNAL			
ST90AB	ST90ABP	Light, 1156 bulb	5
ACCESSORIES			
A90RB	A90RBP	Red lens	5
A90AB	A90ABP	Yellow lens	5
A1157B	A1157BP	1157 replacement bulb	50

FMVSS	Red: S T I, Yellow: I
MATERIALS	Acrylic lens and steel housing
VOLT/AMP	12.8VDC - 2.4A Stop, 0.5A Tail/Parking
WT/DIMS	1.146 lbs. / 7.125” x 7.125” x 2.188”
WARRANTY	Three Year Warranty



ST90RB



ST90AB



ST92 SERIES

7" Transit Warning Lights for Surface Mount

ST92RB

ST92AB

A94VB

- School bus warning lamps
- Screw-on lens, easy to change halogen bulb
- Hard wired, includes lead and ground wire
- Acrylic lens, steel base plate

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED WARNING LIGHT			
ST92RB	ST92RBP	Warning light	5
YELLOW WARNING LIGHT			
ST92AB	ST92ABP	Warning light	5
ACCESSORIES			
A94VB	A94VBP	Black visor	25
RETAIL			
A700	Retail Ready	12V H3 55W replacement bulb, clam	12

FMVSS	W W2
MATERIALS	Acrylic lens and steel housing
VOLT/AMP	12.8VDC - 4.6A
WT/DIMS	1.146 lbs. / 7.063" x 7.063" x 2.25"
WARRANTY	Three Year Warranty



ST51/52/53 SERIES
Pedestal Mount Lights

- Snap-on lens, easy to change bulb
- ST51/52 mount with single post and are self grounding; ST53 with dual post mounts on 2” centers and includes ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED - SINGLE FACE			
ST51RB	ST51RBP	Round, red, single face	10
YELLOW - DUAL FACE			
-	ST52AAP	Round, yellow, dual face	10
ST53AAB	ST53AABP	Square, yellow dual face with side marker/reflex, 1156 bulb	10
RED/YELLOW DUAL FACE			
ST52RB	ST52RBP	Dual face yellow/red stop/turn/tail light	10
ACCESSORIES			
A52RB	A52RBP	Red lens, round	25
A52AB	A52ABP	Yellow lens, round	25
A2057B	A2057BP	2057 replacement bulb	50
RETAIL			
ST51RS	Retail Ready	Red stop/turn/tail light, clam	6
ST52AA		Dual yellow/yellow parking/turn, clam	6
ST52RA		Dual yellow/red stop/turn/tail light, clam	6

FMVSS	ST51/52:	S T I
	ST53AA:	Tail: S T I P, Side marker/reflex: P2 A
MATERIALS	ST51/52:	Acrylic lens and plastic housing
	ST53AA:	Acrylic lens and plastic housing
VOLT/AMP	ST51/52:	12.8VDC - 2.3A Stop/Turn, 1.2A Tail/Parking
	ST53AA:	12.8VDC - 2.3A Stop/Turn, .248A Marker
WT/DIMS	ST51/52:	.463 lb. / 4.313” x 4.313” x 2.375”
	ST53AA:	.794 lb. / 4.563” x 5” x 2.5”
WARRANTY	Three Year Warranty	



ST51/52



ST53AAB

ST51RB

ST52AA

ST52RB

ST53AAB

COMBINATION TAIL LIGHTS & KITS

ST24/25 SERIES

Stud Mount Stop/Turn/Tail Lights

ST24RB

ST25RB



- Snap-on lens, easy to change bulb
- Stud mount on 2" centers
- Grounds through mounting hardware
- Acrylic lens, corrosion proof plastic housing
- Driver side light includes license illuminator

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
STOP/TURN/TAIL LIGHTS			
ST24RB	ST24RBP	Passenger side light	50
ST25RB	ST25RBP	Driver side light with license illuminator	50
ACCESSORIES			
A24RB	A24RBP	Red lens	25
A2057B	A2057BP	2057 replacement bulb	50

FMVSS	ST24RB: S T I P, ST25RB: S T I P L
MATERIALS	Acrylic lens and plastic housing
VOLT/AMP	12.8VDC - 2.5A Stop/Turn, 1.0A Tail
WT/DIMS	.309 lb. / 4.313" x 4.313" x 3.375"
WARRANTY	Three Year Warranty

ST20/21 SERIES

Surface Mount Stop/Turn/Tail Lights

ST21RS

ST20RS



ST20RS



ST21RS

- Screw-on lens, easy to change bulb
- Surface mount on 2" centers
- Grounds through mounting hardware
- Acrylic lens, steel housing
- Driver side light includes license illuminator

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RETAIL			
ST20RS		Passenger side, clam	6
ST21RS	Retail Ready	Driver side, clam	6
A20R		Red lens, slipover blister	12
ACCESSORIES			
A1157B	A1157BP	1157 replacement bulb	50

FMVSS	ST20RS: S T I, ST21RS: S T I L
MATERIALS	Acrylic lens and steel housing
VOLT/AMP	12VDC - 2.3A Stop/Turn, 0.90A Tail
WT/DIMS	.551 lbs / 3.875" x 3.875" x 3.063"
WARRANTY	Three Year Warranty

ST8/9 SERIES
Universal Mount Combination Tail Lights

- Screw-on lens, easy to change bulbs
- Stud mount on 2” centers
- Grounds through mounting studs
- Shock-proof socket guarantees long bulb life
- Acrylic lens, corrosion proof plastic housing
- Passenger side light is 6-function: stop, turn, tail, rear reflex, side marker, and side reflex
- Driver side light also includes license illuminator
- Bulk models are designed with Plug-n-go connections for quick connect wiring
- Retail models are hard wired, self grounding

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
STOP/TURN/TAIL LIGHTS			
ST8RB	ST8RBP	Passenger side light	50
ST9RB	ST9RBP	Driver side light with license illuminator	50
ST8RHB	ST8RHBP	Passenger side light, hard wired	50
ST9RHB	ST9RHBP	Driver side light, hard wired	50
TL27BK	-	Kit: ST8RB, ST9RB, (2) MC36AB amber marker lights with reflex, LP10SB license plate bracket; 20-ft harness, box	1
TL29BK	-	Kit: ST8RB, ST9RB, (2) MC36AB amber marker lights with reflex, LP10SB license plate bracket; 25-ft harness, box	1
ACCESSORIES			
A8RB	A8RBP	Tail light lens	50
A9RB	A9RBP	Side marker light lens	50
A1157B	A1157BP	1157 replacement bulb	50
RETAIL			
ST8RS		Passenger side light, clam	6
ST9RS		Driver side with license illuminator, clam	6
TL11RK	Retail Ready	Kit: ST8RB, ST9RB, license plate bracket, 20-ft harness, mounting hardware, clam	3
TL8RK		Kit: ST8RB, ST9RB, license plate bracket, 20-ft harness, mounting hardware, clam	2
A8RK		Tail and side marker lens set, clam	12
A8R		Tail light lens, clam	12
A9R		Side marker light lens, clam	12

FMVSS	ST8RB: A S T, A P2, ST9RB: A S T, A P2, L
MATERIALS	Acrylic lens and plastic housing
VOLT/AMP	12.8VDC - 2.5A Stop/Turn, 1.0A Tail
WT/DIMS	.309 lb. / 4.563” x 4.563” x 2.875”
WARRANTY	Three Year Warranty

ST9RB

ST8RB

TL8RK



ST6/7 SERIES

Submersible Universal Mount Combination Tail Lights

ST7RB

ST6RB

TL5RK



- Submersible design suitable for many applications
- Screw-on lens, easy to change bulbs
- Stud mount on 2" centers
- Grounds through mounting studs
- Shock-proof socket guarantees long bulb life
- Acrylic lens, corrosion proof plastic housing
- Passenger side light is 6-function: stop, turn, tail, rear reflex, side marker, and side reflex
- Driver side light also includes license illuminator

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
STOP/TURN/TAIL LIGHTS			
ST6RB	ST6RBP	Passenger side light	50
ST7RB	ST7RBP	Driver side light with license illuminator	50
ST6RPG	ST6RPGP	Passenger side light, 2-way plug	50
ST7RPG	ST7RPGP	Driver side light with license illuminator, 2-way plug	50
ACCESSORIES			
A8RB	A8RBP	Tail light lens	50
A9RB	A9RBP	Side marker light lens	25
A1157B	A1157BP	1157 replacement bulb	50
RETAIL			
ST6RS	Retail Ready	Passenger side light, clam	6
ST7RS		Driver side with license illuminator, clam	6
TL5RK		Deluxe kit: ST6RB, ST7RB, (2) MC36AB amber marker lights with reflex, LP10SB license plate bracket, 25-ft harness, mounting hardware, clam	2
TL14RK		Kit: ST6RB, ST7RB, (2) MC31AB amber marker lights with reflex, LP10SB license plate bracket, 25-ft. harness, mounting hardware, clam	2
TL9RK		Kit: ST6RB, ST7RB, LP10SB license plate bracket, 25-ft harness, mounting hardware, clam	2
A8RK		Tail and side marker lens set, clam	12
A8R		Tail light lens, clam	12
A9R		Side marker light lens, clam	12

FMVSS	ST6RB: A S T, A P2, ST7RB: A S T, A P2, L
MATERIALS	Acrylic lens and plastic housing
VOLT/AMP	12.8VDC - 2.5A Stop/Turn, 1.0A Tail
WT/DIMS	.309 lb. / 4.563" x 4.563" x 2.875"
WARRANTY	Three Year Warranty

ST2/3 SERIES

Universal Mount Combination Tail Lights for Over 80" Applications

- Screw-on lens, easy to change bulbs
- Stud mount on 2" centers
- Grounds through mounting studs
- Shock-proof socket guarantees long bulb life
- Acrylic lens, corrosion proof plastic housing
- Passenger side light is 7-function: stop, turn, tail, rear clearance, rear reflex, side marker, and side reflex
- Driver side light also includes license illuminator
- Designed with Plug-n-go connections for quick connect wiring
- Also availabe in hard wired models

ST3RB

ST2RB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
STOP/TURN/TAIL LIGHTS			
ST2RB	ST2RBP	Passenger side, quick connect	50
ST2RHB	ST2RHBP	Passenger side, hard wired	50
ST3RB	ST3RBP	Driver side with license illuminator, quick connect	50
ST3RHB	ST3RHBP	Driver side, hard wired	50
ACCESSORIES			
A8RB	A8RBP	Tail light lens	50
A2RB	A2RBP	Side marker light lens	25
A1157B	A1157BP	1157 replacement bulb	50





FMVSS	ST2RB: S T I A, P2 PC A, ST3RB: S T I A, P2 PC A, L
MATERIALS	Acrylic lens and plastic housing
VOLT/AMP	12.8VDC - 2.5A Stop/Turn, 1.0A Tail
WT/DIMS	.441 lb. / 6.125" x 4.563" x 2.875"
WARRANTY	Three Year Warranty

ST4/5 SERIES

Submersible Universal Mount Combination Tail Lights for Over 80" Applications

ST5RB

ST4RB

- Submersible design suitable for many applications
- Screw-on lens, easy to change bulbs
- Stud mount on 2" centers
- Grounds through mounting studs
- Shock-proof socket guarantees long bulb life
- Acrylic lens, corrosion proof plastic housing
- Passenger side light is 7-function: stop, turn, tail, rear clearance, rear reflex, side marker, and side reflex
- Driver side light also includes license illuminator

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
STOP/TURN/TAIL LIGHTS			
ST4RB	ST4RBP	Passenger side light	50
ST5RB	ST5RBP	Driver side light with license illuminator	50
ACCESSORIES			
A8RB	A8RBP	Tail light lens	50
A2RB	A2RBP	Side marker light lens	25
A1157B	A1157BP	1157 replacement bulb	50
RETAIL			
ST4RS	Retail Ready	Passenger side light, clam	6
ST5RS		Driver side with license illuminator, clam	6
TL60RK		Set: ST4RB, ST5RB, mounting hardware, clam	2
A8R		Tail light lens, clam	12

TL60RK

FMVSS	ST6RB: S T I A, A P2, ST7RB: S T I A, A P2, L
MATERIALS	Acrylic lens and plastic housing
VOLT/AMP	12.8VDC - 2.5A Stop/Turn, 1.0A Tail
WT/DIMS	.441 lb. / 6.125" x 4.563" x 2.875"
WARRANTY	Three Year Warranty



ST16/17 SERIES
Waterproof Universal Mount Combination Tail Lights

- Waterproof, low profile design for marine applications
- Replaceable lenses and bulbs
- Mount on 2” centers
- Includes separate ground wire with eyelet
- Acrylic lens, corrosion proof plastic housing
- Passenger side light is 7-function: stop, turn, tail, rear clearance, rear reflex, side marker, and side reflex
- Driver side light also includes license illuminator



ST17RB



ST16RB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
STOP/TURN/TAIL LIGHTS			
ST16RB	ST16RBP	Passenger side light	20
ST17RB	ST17RBP	Driver side light with license illuminator	20
ST26RPG	ST26RPGP	Passenger side light, self grounding, 2-way plug	20
ST27RPG	ST27RPGP	Driver side light with license illuminator, self grounding, 2-way plug	20
ACCESSORIES			
A16RB	A16RBP	Tail light lens	50
A17RB	A17RBP	Side marker light lens	50
A2057B	A2057BP	2057 replacement bulb	50
RETAIL			
ST16RS	Retail Ready	Passenger side light, clam	6
ST17RS		Driver side with license illuminator, clam	6
TL16RK		Deluxe kit: ST16RB, ST17RB, LP10SB license plate bracket, (2) MC91AB yellow marker lights with bases, (2) RE11AB yellow reflectors, 25-ft harness, stainless steel mounting hardware, clam	2
TL15RK		Kit: ST16RB, ST17RB, LP10SB license plate bracket, 25-ft harness, mounting hardware, clam	2
A16R		Tail light lens, clam	12



TL16RK

TL15RK



FMVSS	ST16RB: S T I A P2 PC; ST17RB: S T I A P2 PC, L
MATERIALS	Acrylic lens and plastic housing
VOLT/AMP	12.8VDC - 2.3A Stop/Turn, 0.9A Tail
WT/DIMS	.661 lb. / 8.063” x 2.875” x 2.813”
WARRANTY	Three Year Warranty

ST36/37 SERIES

Waterproof Universal Mount Combination Tail Lights

ST37RPG

ST36RPG

- Waterproof, low profile design for marine applications
- Screw-on lens, easy to change bulbs
- Mount on 2” centers
- Includes separate ground wire with eyelet
- Shock-proof socket guarantees long bulb life
- Acrylic lens, corrosion proof plastic housing
- Passenger side light is 7-function: stop, turn, tail, rear clearance, rear reflex, side marker, and side reflex
- Driver side light also includes license illuminator
- Stainless steel mounting hardware

TL36RK

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
STOP/TURN/TAIL LIGHTS			
ST36RPG	ST36RPGP	Passenger side light, self grounding, 2-way plug	20
ST37RPG	ST37RPGP	Driver side light with license illuminator, self grounding, 2-way plug	20
ACCESSORIES			
A39RB	A39RBP	Tail light lens	10
A37RB	A37RBP	Side marker light lens	50
A1157B	A1157BP	1157 replacement bulb	50
RETAIL			
ST36RS	Retail Ready	Passenger side light, clam	6
ST37RS		Driver side with license illuminator, clam	6
TL36RK		Deluxe kit: ST36RB, ST37RB, LP10SB license plate bracket, (2) MC91AB yellow marker lights with bases, 25-ft harness, stainless steel mounting hardware, clam	2
A36R		Tail and marker light lenses, clam	12



FMVSS	ST36RB: S T I A P2, A P2; ST37RB: S T I A P2, A P2, L
MATERIALS	Acrylic lens and plastic housing
VOLT/AMP	12.8VDC - 2.3A Stop/Turn, 0.9A Tail
WT/DIMS	.992 lb. / 7.875” x 3.25” x 2.875”
WARRANTY	Three Year Warranty

ST56/57 SERIES

Submersible Universal Mount Combination Tail Lights for Over 80" Applications

- Waterproof design for marine applications
- Shock mount guarantees long bulb life
- Mount on 2" centers
- Includes separate ground wire with eyelet
- Acrylic lens, corrosion proof plastic housing
- Passenger side light is 7-function: stop, turn, tail, rear clearance, rear reflex, side marker, and side reflex
- Driver side light also includes license illuminator
- Stainless steel mounting hardware

ST57RS

ST56RS

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RETAIL			
ST56RS	Retail Ready	Passenger side light, clam	6
ST57RS		Driver side with license illuminator, clam	6
ACCESSORIES			
A2057B	A2057BP	2057 replacement bulb	50
A194B	A194BP	194 replacement bulb	100

FMVSS	ST56RB: S2 T2 I6 PC A; ST57RB: S2 T2 I6 PC A, L
MATERIALS	Acrylic lens and plastic housing
VOLT/AMP	12.8VDC - 2.3A Stop/Turn, 0.9A Tail
WT/DIMS	.639 lb. / 6.063" x 3.75" x 2.25"
WARRANTY	Three Year Warranty



ST60 SERIES

Universal Mount Combination Tail Lights

ST60RB





- Stud mount stop/turn/tail light with back-up and license illuminator built in
- Screw-on lens, easy to change bulbs
- Grounds through mounting studs
- Shock-proof socket guarantees long bulb life
- Acrylic lens, corrosion proof plastic housing

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		STOP/TURN/TAIL LIGHTS	
ST60RB	ST60RBP	Combination tail light	20
		ACCESSORIES	
A60RB	A60RBP	Tail light lens	25
A2057B	A2057BP	2057 replacement bulb	50
		RETAIL	
ST60RS	Retail Ready	Combination tail light, clam	6

FMVSS	S T A I R
MATERIALS	Acrylic lens and plastic housing
VOLT/AMP	12.8VDC - 2.3A Stop/Turn, 0.9A Tail
WT/DIMS	.992 lb. / 5.75" x 6.625" x 2.813"
WARRANTY	Three Year Warranty

ST31 SERIES

Weatherproof Surface Mount Light

ST31RS

- Snap-on lens, easy to change bulb
- Surface mount on 3-1/2" centers
- Hard wired, includes lead and ground wire
- Polycarbonate lens, steel base plate

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	Retail Ready	**RETAIL**	
ST31RS		Light, clam	12
		ACCESSORIES	
A2057B	A2057BP	2057 replacement bulb	50





FMVSS	S T I
MATERIALS	Polycarbonate lens and steel housing
VOLT/AMP	12.8VDC - 2.3A Stop/Turn, 0.90A Tail
WT/DIMS	.309 lb. / 4.563" x 2.5" x 1.75"
WARRANTY	Three Year Warranty

TL21/22RK
Magnetic Mount Towing Light Kit

- Magnetic mount towing light kit
- Pair of DOT compliant stop/turn/tail lights
- 20-ft wishbone style wiring harness and 4-ft trunk connector with 4-way flat plug
- Replaceable lens and bulb

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		RETAIL	
TL21RK	Retail Ready	Towing light kit, heavy duty	2
TL22RK		Towing light kit	2
		ACCESSORIES	
A52RB	A52RBP	Tail light lens	25
A2057B	A2057BP	2057 replacement bulb	50

FMVSS	S T I
MATERIALS	Acrylic lens and plastic housing
VOLT/AMP	12.8VDC - 2.3A Stop/Turn, 0.9A Tail
WT/DIMS	3.53 lbs. / 7" x 4" x 2.125"
WARRANTY	Three Year Warranty

TL22RK

TL21RK

BU11CS
Back-Up Light

BU11CS

- Single wire, grounds through mounting hardware
- Replaceable bulb (1156)

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	RETAIL		
BU11CS	Retail Ready	Back-up light, chrome housing	12

FMVSS	R
MATERIALS	Polycarbonate lens and plastic housing
VOLT/AMP	12.8VDC - 0.4A
WT/DIMS	.221 lbs. / 3.25" x 3.25" x 1.938"
WARRANTY	Three Year Warranty

BU41 SERIES
Flange Mount Back-Up Light

BU41CB



- Hard wired, includes both lead and ground wire
- Replaceable bulb (1056)

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
	BACK-UP LIGHT		
BU41CB	BU41CBP	Back-up light	50
	ACCESSORIES		
A40SRB	A40ARBP	Snap retention ring	300
A41CB	A41CBP	Clear replacement lens for BU41	25

FMVSS	R
MATERIALS	Acrylic lens, steel housing
VOLT/AMP	12.8VDC - 1.182A
WT/DIMS	.441 lbs. / 5.375" x 5.375" x 1.563"
WARRANTY	Three Year Warranty

BU33/45/70 SERIES
Sealed Back-Up Lights

- 4” round, 6” oval and rectangular models
- Sonically sealed, waterproof
- Flush mount design accepts standard two-way plug
- Shock proof socket guarantees long bulb life
- Kits include grommet and plug

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
4” ROUND BACK-UP LIGHTS			
BU45CB	BU45CBP	Back-up light	50
BU44CB	BU44CBP	Kit: BU45CB, A45GB & A45CB	50
BU49CB	BU49CBP	Kit: BU45CB & A45GB	10
6” OVAL BACK-UP LIGHTS			
BU70CB	BU70CBP	Back-up light	50
BU74CB	BU74CBP	Kit: BU70CB, A70GB & A45CB	50
BU64CB	BU64CBP	Kit: BU70CB, A70GB & A49PB (pigtail attached to light)	50
RECTANGULAR BACK-UP LIGHTS			
BU33CB	BU33CBP	Back-up light	10
BU33CRXLB	BU33CRXLBP	Back-up light with red reflex	20
BU33CRX24LB	BU33CRX24LBP	Back-up light with red reflex, 24V	20
ACCESSORIES			
A45GB	A45GBP	4” round grommet	50
A70GB	A70GBP	6” oval grommet	50
A33GB	A33GBP	Rectangular grommet	50
A45CB	A45CBP	Straight two-wire pigtail	100
A49PB	A49PBP	Right angle two-wire pigtail	100

FMVSS	R BU33CRX: (2)R A
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	BU45: 12.8VDC - 2.182A BU70: 12.8VDC - 0.4A BU33: 12.8VDC - 1.6A; 24.0VDC - .87A
WT/DIMS	BU45: .176 lbs. / 4.25” x 4.25” x 2.063” BU70: .265 lbs. / 6.5” x 2.25” x 2.375” BU33: .441 lbs. / 5.313” x 3.438” x 1.938”
WARRANTY	Three Year Warranty

BU45CB



HOLE CUT-OUT: 4.5”

BU70CB



HOLE CUT-OUT: 6.85” x 2.5” (1.25” R)

BU33CB



BU33CRXLB



HOLE CUT-OUT: 5.453” x 3.578” (1” R)

DOT COMPLIANT BACK-UP LIGHTS

M1 SERIES

Millennium Series® 6.5" Marker/Clearance Lights

- Replaceable lens and bulb
- Hard wired, includes separate ground wire
- Available with .180 male bullets or metripack connector
- Choose from light only or kit with chrome bezel

M1 WITH BEZEL

M1 WITH BEZEL

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW			
00212351B	00212351P	12V, .180 bullets	20
00212331B	00212331P	12V Kit: .180 bullets, bezel	20
00212362B	00212362P	12V, Metripack connector	20
00212342B	00212342P	12V Kit: Metripack connector, bezel	20
RED			
00212333B	00212333P	12V Kit: .180 bullets, bezel	20
ACCESSORIES			
00212317B	00212327P	Bezel	100/20

FMVSS	P2
MATERIALS	Polycarbonate lens, housing and bezel
VOLT/AMP	12.8VDC - 0.33A; 24.0VDC - 0.17A
WT/DIMS	.22 lbs. / 6.625" x 2.188" x 1"
WARRANTY	Three Year Warranty



HOLE CUT-OUT: 1.5"

M3 SERIES

Millennium Series® 3" Marker/Clearance Lights

- Replaceable lens and bulb
- Hard wired, includes separate ground wire
- Molded .180 male bullets

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		YELLOW	
00212251B	00212251P	.180 bullets	20
		RED	
00212253B	00212253P	.180 bullets	20
00212233B	00212233P	Kit: .180 bullets, bezel	20
		CLEAR	
00212239B	00212239P	Kit: .180 bullets, bezel	20
		ACCESSORIES	
00212217B	00212227P	Bezel	500/20

FMVSS	P2
MATERIALS	Polycarbonate lens, housing and bezel
VOLT/AMP	12.8VDC - 0.33A
WT/DIMS	.20 lbs. / 3" x 2" x 1"
WARRANTY	Three Year Warranty



HOLE CUT-OUT: 1.375"



M3 WITH BEZEL

M3 WITH BEZEL

M3 CLEAR LENS WITH BEZEL

MC25/27 SERIES

2” & 2.5” Sealed Beehive Style Marker/Clearance Lights

MC25AB

MC27AB

- Sonically sealed, waterproof
- Accepts standard two-pin PL-10 plug

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		YELLOW	
MC25AB	MC25ABP	2” light	20
MC27AB	MC27ABP	2.5” light	20
		ACCESSORIES	
A46PB	A46PBP	Straight PL-10 plug, 6” lead	100
A86PB	A86PBP	Straight PL-10 plug, 18” lead	100
A54GB	A54GBP	2” Flush mount grommet	100
A54GK	A54GKP	2” Kit: A54GB and A46PB	100
A55CB	A55CBP	2” Chrome trim ring	20
A55GB	A55GBP	2.5” Flush mount grommet (open back)	50
A56GB	A56GBP	2.5” Recess mount grommet (closed back)	100
A57GB	A57GBP	2.5” Recess mount grommet (open back)	50
A55GK	A55GKP	2.5” Kit: A55GB and A46PB	100
A57GK	A57GKP	2.5” Kit: A57GB and A46PB	100
A57CB	A57CBP	2.5” Chrome trim ring	20
BK5557GB	BK5557GBP	2”/2.5” Cam-on mounting bracket	50

FMVSS	P2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.2A
WT/DIMS	MC25: .088 lbs. / 2” x 2” x 1.75”
	MC27: .110 lbs. / 2.5” x 2.5” x 2.313”
WARRANTY	Three Year Warranty



MC25 SERIES
HOLE CUT-OUT: 2.313"



MC27 SERIES
HOLE CUT-OUT: 2.75"

MC52 SERIES

2" Round Sealed Recess Flange Mount Marker/Clearance Lights

- Sonically sealed, waterproof light for recess mount
- Accepts standard two-pin PL-10 plug
- Available in yellow and red models, with black or reflex flange
- Reflex flange model meets SAE "A" requirements for conspicuity

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW			
MC52AB	MC52ABP	Yellow, black flange	50
MC52AXB	MC52AXBP	Yellow, reflex lens and flange	50
RED			
MC52RB	MC52RBP	Red, black flange	50
MC52RXB	MC52RXBP	Red, reflex lens and flange	50
ACCESSORIES			
A46PB	A46PBP	Straight PL-10 plug, 6" lead	100
A86PB	A86PBP	Straight PL-10 plug, 18" lead	100
A3TRSSB	A3TRSSBP	Stainless steel flange cover	100

FMVSS	Black flange: P2 Reflex flange: A P2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.2A
WT/DIMS	Black flange: .066 lbs. / 2.938" x 2.938" x .813" Reflex flange: .066 lbs. / 2.984" x 2.984" x .75"
WARRANTY	Three Year Warranty

MC52AB

MC52RB



MC52AXB

MC52RXB



MC52 Black Flange



MC52 Reflex Flange

MC53 & MC54 SERIES

2" Sealed Marker/Clearance Lights

- Sonically sealed, waterproof
- Accept standard two-pin PL-10 plugs
- Available in yellow, red, and yellow ABS models
- Available in recess and surface mount models



HOLE CUT-OUT: 2.313"



SURFACE MOUNT

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW			
MC53AB	MC53ABP	Recess mount	50
MC53ABSB	MC53ABSBP	Recess mount "ABS"	50
MC53AKB	MC53AKBP	Kit: MC53AB, A54GB and A46PB	50
MC54AB	MC54ABP	Flange surface mount	50
MC505ABSB	MC505ABSBP	Flange surface mount "ABS"	50
RED			
MC53RB	MC53RBP	Recess mount	50
MC53RKB	MC53RKBP	Kit: MC53RB, A54GB and A46PB	50
MC54RB	MC54RBP	Flange surface mount	50
ACCESSORIES			
A46PB	A46PBP	Straight PL-10 plug, 6" lead	100
A86PB	A86PBP	Straight PL-10 plug, 18" lead	100
A54GB	A54GBP	2" Flush mount grommet	100
A54GK	A54GKP	2" Kit: A54GB and A46PB	100
A55CB	A55CBP	2" Chrome trim ring	20
BK5557GB	BK5557GBP	Cam-on mounting bracket	50
RETAIL			
MC53AS	Retail Ready	Yellow recess mount light, clam	12
MC53RS		Red recess mount light, clam	12

FMVSS	P2 PC
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.2A
WT/DIMS	MC53: .066 lbs. / 2" x 2" x .688"
	MC54/505: .066 lbs. / 2.938" x 2.938" x .813"
WARRANTY	Three Year Warranty

MC55 & MC57 SERIES

2.5" Sealed Marker/Clearance Lights for Recess Mount

- Sonically sealed, waterproof design for recess mount
- Accept standard two-pin PL-10 plug
- MC55 series lights are PC rated
- MC57 series lights feature built-in reflex

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		YELLOW	
MC55AB	MC55ABP	PC rated light	50
MC57AB	MC57ABP	P2 rated light with reflex	50
		RED	
MC55RB	MC55RBP	PC rated light	50
MC57RB	MC57RBP	P2 rated light with reflex	50
		ACCESSORIES	
A46PB	A46PBP	Straight PL-10 plug, 6" lead	100
A86PB	A86PBP	Straight PL-10 plug, 18" lead	100
A55GB	A55GBP	Flush mount grommet, open back	50
A56GB	A56GBP	Recess mount grommet, closed back	100
A57GB	A57GBP	Recess mount grommet, open back	50
A55GK	A55GKP	Kit: A55GB & A46PB	100
A57GK	A57GKP	Kit: A57GB & A46PB	100
A57CB	A57CBP	Chrome trim ring	20
BK5557GB	BK5557GBP	Cam-on mounting bracket	50
		RETAIL	
MC57AS	Retail Ready	Yellow light with reflex, clam	12
MC57RS		Red light with reflex, clam	12

MC55AB

PC Rated

MC55RB



MC57AB
MC57AS

SAE A REFLEX
P2 RATED

MC57RB
MC57RS



HOLE CUT-OUT: 2.75"

FMVSS	MC55: P2 PC MC57: A P2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.2A
WT/DIMS	.066 lbs. / 2.5" x 2.5" x .688"
WARRANTY	Three Year Warranty

MC56 SERIES

2.5" Sealed Recess Flange Mount Marker/Clearance Lights

MC56AB

MC56RB

- Sonically sealed, waterproof light for recess mount
- Accepts standard two-pin PL-10 plug

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW			
MC56AB	MC56ABP	Recess flange mount	50
RED			
MC56RB	MC56RBP	Recess flange mount	50
ACCESSORIES			
A46PB	A46PBP	Straight PL-10 plug, 6" lead	100
A86PB	A86PBP	Straight PL-10 plug, 18" lead	100

FMVSS	P2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.2A
WT/DIMS	.11 lb. / 3.438" x 3.438" x .938"
WARRANTY	Three Year Warranty



HOLE CUT-OUT: 2.75"

MC61ABKB

Sealed Marker/Clearance Light and Reflector in Elevated Bracket

- Sonically sealed, waterproof
- PC rated light fulfills front side marker requirement when properly mounted on a 15 degree angle
- Corrosion proof, surface mount wedge base
- Single wire design grounds through mounting hardware

MC61ABKB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		LIGHT/REFLECTOR ASSEMBLY	
MC61ABKB	MC61ABKBP	Light & reflector in bracket	20

FMVSS	Light: P2 PC; Reflector: A
MATERIALS	Polycarbonate lens and housing; Acrylic reflector
VOLT/AMP	12.8VDC - 0.2A
WT/DIMS	.066 lbs. / 6.687" x 1.5" x 1.625"
WARRANTY	Three Year Warranty



MC65/67 & BA65 SERIES
Sealed Fender Lights

MC65ARB



MC67ARB





- Sonically sealed, waterproof
- PC rated design includes two bulbs
- Multiple mounting and wiring options available
- Single wire design grounds through mounting hardware
- Two-wire design includes both lead and ground wires

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		AMBER/RED FENDER LIGHT	
MC65ARB	MC65ARBP	Light only	50
MC67ARB	MC67ARBP	Kit: MC65ARB & A65PB bracket/plug	50
		AMBER/RED FENDER LIGHT ASSEMBLIES	
BA65ARLB	BA65ARLBP	Fender light assembly, left side: MC65AB & MC65RB in fender mount bracket	25
BA65ARRB	BA65ARRBP	Fender light assembly, right side: MC65AB & MC65RB in fender mount bracket	25
		ACCESSORIES	
A67BB	A67BBP	Fender bracket, black	50
A65B	A65BP	Black bracket	50
A65P	A65PP	Single wire plug, .156 male bullet	50
A65PB	A65PBP	Kit: A65B black bracket & A65P plug	50
A66PB	A66PBP	Kit: Gray bracket & A65P plug	50
A67CB	A67CBP	Kit: Chrome bracket & A65P plug	50
A68PB	A68PBP	Kit: Black bracket & 2-wire plug	50

For more details on mounting and wiring accessories, see Accessories section at back of catalog.

BA65ARLB



FMVSS	MC65ARB:	P2
	BA65:	P2 P3 PC2
MATERIALS	MC65:	Polycarbonate lens and housing
	BA65:	Polycarbonate lens and housing, plastic bracket
VOLT/AMP	MC65:	12.8VDC - 0.689A
	BA65:	12.8VDC - 0.8A
WT/DIMS	MC65:	.066 lbs. / 3.938" x 1.25" x .875"
	BA65:	.375 lbs. / 9.188" x 4.688" x 1.875"
WARRANTY	Three Year Warranty	

MC65/67 SERIES
Sealed Marker/Clearance Lights

- Sonically sealed, waterproof
- PC rated design includes two bulbs
- Multiple mounting and wiring options available
- Single wire design grounds through mounting hardware
- Two-wire design includes both lead and ground wires

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		YELLOW	
MC65AB	MC65ABP	Light only	50
MC67AB	MC67ABP	Kit: MC65AB & A65PB	50
		RED	
MC65RB	MC65RBP	Light only	50
MC67RB	MC67RBP	Kit: MC65RB & A65PB	50
		ACCESSORIES	
A65B	A65BP	Black bracket	50
A65P	A65PP	Single wire plug, .156 male bullet	50
A65PB	A65PBP	Kit: A65B black bracket & A65P plug	50
A66PB	A66PBP	Kit: Gray bracket & A65P plug	50
A67CB	A67CBP	Kit: Chrome bracket & A65P plug	50
A68PB	A68PBP	Kit: Black bracket & 2-wire plug	50
		For more details on mounting and wiring accessories, see Accessories section at back of catalog.	
		RETAIL	
MC67AK		Yellow kit: MC65AB & A65PB, clam	12
MC67RK		Red kit: MC65RB & A65PB, clam	12
MC65AS		Yellow light, clam	12
MC65RS		Red light, clam	12

FMVSS	P2 P3 PC2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.4A
WT/DIMS	.066 lbs. / 3.938" x 1.25" x .875"
WARRANTY	Three Year Warranty

MC65AB



MC65RB

MC67AB
MC67AK



MC67RB
MC67RK



MC65



MC67

MC91 SERIES
Sealed Marker/Clearance Lights

- Sonically sealed, waterproof
- PC rated design
- Multiple mounting and wiring options available
- Single wire design grounds through mounting hardware
- Two-wire design includes both lead and ground wires

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		YELLOW	
A91AB	A91ABP	Light only	100
MC91AB	MC91ABP	Kit: A91AB, A91CB & A91LW	50
MC92AB	MC92ABP	Kit: A91AB, A91BB & A91LW	50
		RED	
A91RB	A91RBP	Light only	100
MC92RB	MC92RBP	Kit: A91RB, A91BB & A91LW	50
		ACCESSORIES	
A46PB	A46PBP	2-wire plug, 6" lead	100
A86PB	A86PBP	2-wire plug, 18" lead	100
A90CB	A90CBP	Chrome snap-on cover	100
A91LW	A91LWP	1-wire plug, 12" lead	100
A91BB	A91BBP	Black base, self grounding	100
A91BOB	A91BOBP	Black base, open back	100
A91CB	A91CBP	Chrome base, self grounding	100
A91OB	A91OBP	Chrome base, open back	100
A91GB	A91GBP	Grommet	100
		RETAIL	
MC90AS		Yellow light only, clam	12
MC90RS		Red light only, clam	12
MC91AS		Yellow light kit: A91AB, A91CB chrome base, A91LW single wire plug, clam	12
MC91RS		Red light kit: A91RB, A91CB chrome base, A91LW single wire plug, clam	12
MC92AS		Yellow light kit: A91AB, A91BB black base, A91LW single wire plug, clam	12
MC92RS		Red light kit: A91RB, A91BB black base, A91LW single wire plug, clam	12



A91
light only



MC90/91/92
kits

FMVSS	P2 PC
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.2A
WT/DIMS	.066 lbs. / 2.5" x 1.188" x .875"
WARRANTY	Three Year Warranty

MC11 SERIES
Mini Marker/Clearance Lights

- Surface mount on 2-3/4" centers
- Single wire design grounds through mounting hardware
- Snap-on lens, replaceable bulb

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		YELLOW	
MC11AB	MC11ABP	Yellow, black base	50
		RED	
MC11RB	MC11RBP	Red, black base	50
		ACCESSORIES	
A11AB	A11ABP	Yellow replacement lens	50
A11RB	A11RBP	Red replacement lens	50
A194B	A194BP	194 replacement bulb	100
		RETAIL	
MC11AS	Retail Ready	Yellow light, clam	12
MC11RS		Red light, clam	12
MC11AK		(6) MC11AB, hardware, connectors, clam	6
UL11BS		Blue utility light, clam	12

FMVSS	P2 (except UL11BS)
MATERIALS	Acrylic lens, ABS housing
VOLT/AMP	12.8VDC - 0.4A
WT/DIMS	.044 lbs. / 3.188" x 1" x 1.125"
WARRANTY	Three Year Warranty

MC11AB

MC11RB

UL11BS



MC11AK

MC30 SERIES
Marker/Clearance Light with Reflex

- Surface mount on 2" centers
- Plug-n-go design for quick connection to power and ground
- Snap-on lens, replaceable bulb

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		YELLOW	
MC30AB	MC30ABP	Yellow	20
		ACCESSORIES	
A194B	A194BP	194 replacement bulb	100

FMVSS	A P2 PC
MATERIALS	Acrylic lens, ABS housing
VOLT/AMP	12.8VDC - 0.2A
WT/DIMS	.11 lb. / 3" x 2.25" x .938"
WARRANTY	Three Year Warranty

PC Rated

MC30AB



MC21/22 SERIES
Beehive Marker/Clearance Lights

MC22AB

MC22RB

MC21AS


MC21RS

- Surface mount on 3/4" centers
- Single wire design grounds through mounting hardware
- Snap-on lens, replaceable bulb

PC Rated

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		YELLOW	
MC22AB	MC22ABP	Yellow	50
		RED	
MC22RB	MC22RBP	Red	50
		ACCESSORIES	
A21AB	A21ABP	Yellow replacement lens for MC21	50
A21RB	A21RBP	Red replacement lens for MC21	50
		RETAIL	
MC21AS	Retail Ready	Yellow light, clam	12
MC21RS		Red light, clam	12

FMVSS	P2 PC
MATERIALS	Acrylic lens, steel bracket
VOLT/AMP	12.8VDC - 0.4A
WT/DIMS	MC22: .176 lbs. / 2.563" x 2.563" x 3.688"
	MC21: .176 lbs. / 2.563" x 2.563" x 4.063"
WARRANTY	Three Year Warranty



MC21



MC22

MC31/32 SERIES

Surface Mount Marker/Clearance Lights with Reflex

- Surface mount on 3” centers
- Lens with reflex eliminates need for separate reflector
- MC31 is single wire design, grounds through mounting hardware
- MC32 has twist-in socket with separate ground wire
- Snap-on lens, replaceable 194 bulb

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		YELLOW	
MC31AB	MC31ABP	Oval, black base, single wire	50
MC31A15B2	MC31A15B2P	MC31AB with .156 female barrels	50
MC32AB	MC32ABP	Oblong, white base, two-wire	100
MC32ABB	MC32ABBP	Oblong, black base, two-wire	100
		RED	
MC31RB	MC31RBP	Oval, black base, single wire	50
MC31R15B2	MC31R15B2P	MC31RB with .156 female barrels	50
MC32RB	MC32RBP	Oblong, white base, two-wire	100
MC32RBB	MC32RBBP	Oblong, black base, two-wire	100
		ACCESSORIES	
A31AB	A31ABP	Yellow replacement lens, MC31	50
A31RB	A31RBP	Red replacement lens, MC31	50
A32AB	A32ABP	Yellow replacement lens, MC32	50/10
A32RB	A32RBP	Red replacement lens, MC32	50/10
A32GB	A32GBP	Mounting gasket, white	500
A194B	A194BP	194 replacement bulb	100
		RETAIL	
MC31AS	Retail Ready	MC31AB, clam	12
MC31RS		MC31RB, clam	12
MC32AS		MC32AB, clam	12
MC32ABS		MC32ABB, clam	12
MC32RS		MC32RB, clam	12
MC32RBS		MC32RBB, clam	12

FMVSS	A P2
MATERIALS	Acrylic lens, ABS housing
VOLT/AMP	12.8VDC - 0.2A
WT/DIMS	MC31: .088 lb. / 4” x 2.063” x 1.094”
	MC32: .11 lb. / 4” x 2” x 1.125”
WARRANTY	Three Year Warranty

MC31AB

MC31RB







MC32AB

MC32RB



A32GB

MC35/36 SERIES

Surface Mount Marker/Clearance Lights with Reflex

MC35AB



MC35AEB

MC36AB

MC36RB

- Surface mount lights; choose from ear mount or stud mount versions
- Lens with reflex eliminates need for separate reflector
- MC35 is ear mount version
- MC36 is stud mount version
- Single wire design grounds through mounting hardware
- Screw-on lens, replaceable bulb, black plastic base

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		YELLOW	
MC35AB	MC35ABP	Yellow ear mount	50
MC35AEB	MC35AEBP	Yellow ear mount, rectangular	200
MC36AB	MC36ABP	Yellow stud mount	50
		RED	
MC36RB	MC36RBP	Red stud mount	50
		ACCESSORIES	
A35AEB	A35AEBP	Yellow replacement lens	50
A36AB	A36ABP	Yellow replacement lens	50
A36RB	A36RBP	Red replacement lens	50
A194B	A194BP	194 replacement bulb	100
		RETAIL	
MC35AS	Retail Ready	Yellow ear mount light, clam	12
MC36AS		Yellow stud mount light, clam	12
MC36AS6		Yellow stud mount light, clam	6
MC36RS		Red stud mount light, clam	12
MC36RS6		Red stud mount light, clam	6

FMVSS	A P2
MATERIALS	Acrylic lens, ABS housing
VOLT/AMP	12.8VDC - 0.2A
WT/DIMS	MC35: .132 lb. / 3.875" x 2.375" x 1.094"
	MC35AEB: .132 lb. / 3.75" x 2.063" x .938"
	MC36: .132 lb. / 2.75" x 2.125" x 1"
WARRANTY	Three Year Warranty



MC35



MC35AEB



MC36

800-364-5483 / 918-683-9514

MC37 SERIES

Stud Mount Marker/Clearance Light with Reflex

- Stud mount design; grounds through mounting stud
- Lens with reflex eliminates need for separate reflector
- Replaceable bulb
- Polycarbonate lens and housing



MC37AB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		YELLOW	
MC37AB	MC37ABP	Yellow	50
		ACCESSORIES	
A194B	A194BP	194 replacement bulb	100

FMVSS	A P2
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.2A
WT/DIMS	.11 lb. / 2.875" x 2.125" x .938"
WARRANTY	Three Year Warranty





MC38 SERIES

Surface Mount Marker/Clearance Lights with Reflex

- Surface mount on 3" centers
- Lens with reflex eliminates need for separate reflector
- Single wire design grounds through mounting hardware
- Snap-on lens, replaceable bulb

MC38AB

MC38RB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		YELLOW	
MC38AB	MC38ABP	Yellow	50
		RED	
MC38RB	MC38RBP	Red	50
		ACCESSORIES	
A38AB	A38ABP	Yellow replacement lens	50
A38RB	A38RBP	Red replacement lens	50
A194B	A194BP	194 replacement bulb	100

FMVSS	A P2
MATERIALS	Acrylic lens, ABS housing
VOLT/AMP	12.8VDC - 0.2A
WT/DIMS	.11 lb. / 4" x 2.063" x 1.156"
WARRANTY	Three Year Warranty



MC42 SERIES

Dual Bulb Marker/Clearance Lights

- Dual bulb, bullseye style lights with black base
- Snap-on lens and replaceable bulbs
- Surface mount on 3” centers
- Single wire design grounds through mounting hardware

MC42AB

MC42RB



BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		YELLOW	
MC42AB	MC42ABP	Yellow	50
		RED	
MC42RB	MC42RBP	Red	50
		ACCESSORIES	
A42AB	A42ABP	Yellow replacement lens	10
A42RB	A42RBP	Red replacement lens	10
A194B	A194BP	194 replacement bulb	100
		RETAIL	
MC42AS	Retail Ready	Yellow light, clam	12
MC42RS		Red light, clam	12

FMVSS	P2
MATERIALS	Acrylic lens, ABS housing
VOLT/AMP	12.8VDC - 0.4A
WT/DIMS	.088 lb. / 4.094” x 2.125” x 1.125”
WARRANTY	Three Year Warranty

MC48 SERIES

Marker/Clearance Lights with Reflex

- Flush mount on 3-3/8” centers
- Lens with reflex eliminates need for separate reflector
- Twist-in socket with replaceable bulb and ground wire

MC48AB/APG



MC48RB/RPG



BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		YELLOW	
MC48AB	MC48ABP	Yellow	50
MC48APG	MC48APGP	Yellow with .156 female barrels	50
		RED	
MC48RB	MC48RBP	Red	50
MC48RPG	MC48RPGP	Red with .156 female barrels	50
		ACCESSORIES	
A194B	A194BP	194 replacement bulb	100

FMVSS	A P2
MATERIALS	Acrylic lens, ABS housing
VOLT/AMP	12.8VDC - 0.2A
WT/DIMS	.132 lb. / 3.906” x 1.843” x 1.031”
WARRANTY	Three Year Warranty

MC44 & BA44 SERIES

Surface Mount Marker/Clearance Lights with Reflex

- Surface mount on 3” centers
- Lens with reflex eliminates need for separate reflector
- Two-wire design includes both lead and ground wire
- Snap-on lens, replaceable bulb
- Fender light assembly includes one each MC44AB and MC44RB in black ABS bracket; female plug on power wire, grounding eyelet on ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW			
MC44AB	MC44ABP	Yellow, two-wire	50
MC44AB1	MC44AB1P	Yellow, single wire	50
RED			
MC44RB	MC44RBP	Red, two-wire	50
MC44RB1	MC44RB1P	Red, single wire	50
YELLOW/RED FENDER LIGHT ASSEMBLY			
BA44FNL	BA44FNLP	Left side	25
BA44FNR	BA44FNRP	Right side	25
ACCESSORIES			
MC441WB	-	Single wire base only	500
MC442WB	-	Two-wire base only	50
A44A500B	-	Yellow replacement lens, 500-pack	500
A44R500B	-	Red replacement lens, 500-pack	500
A44AB	A44ABP	Yellow replacement lens	10
A44RB	A44RBP	Red replacement lens	10
A194B	A194BP	194 replacement bulb	100
A44GTB	-	Mounting gasket, thick, white	1000
RETAIL			
MC44AS	Retail Ready	Yellow light, clam	12
MC44RS		Red light, clam	12



MC44AB

MC44RB

A44GB



BA44FNR



FMVSS	A P2
MATERIALS	Acrylic lens, ABS housing
VOLT/AMP	MC44: 12.8VDC - 0.4A
	BA44: 12.8VDC - 0.8A
WT/DIMS	MC44: .066 lb. / 4” x 1.5” x .938”
	BA44: .353 lb. / 8.5” x 3.875” x 1.75”
WARRANTY	Three Year Warranty

MC58 SERIES

2.5" Marker/Clearance Lights

- Surface mount on 1-1/2" centers
- Single wire design grounds through mounting hardware
- Snap-on lens, replaceable bulb

MC58RS MC58AS



BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RETAIL			
MC58AS	Retail Ready	Yellow light, clam	12
MC58RS		Red light, clam	12
ACCESSORIES			
A194B	A194BP	194 replacement bulb	100

FMVSS	P2
MATERIALS	Acrylic lens, ABS housing
VOLT/AMP	12.8VDC - 0.2A
WT/DIMS	.066 lbs. / 2.5" x 2.5" x 1.063"
WARRANTY	Three Year Warranty

MC66 SERIES

Surface Mount Dual Bulb Marker/Clearance Lights

- Surface mount on 3" centers
- Includes both lead and ground wires
- Snap-on lens, replaceable bulb

PC Rated

MC66AB

MC66RB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW			
MC66AB	MC66ABP	Yellow	50
MC66HAB	MC66HABP	Yellow, single wire, self grounding	50
RED			
MC66RB	MC66RBP	Red	50
ACCESSORIES			
A66AB	A66ABP	Yellow replacement lens	50
A66RB	A66RBP	Red replacement lens	50
A194B	A194BP	194 replacement bulb	100
RETAIL			
MC66AS	Retail Ready	Yellow light, clam	12
MC66RS		Red light, clam	12



FMVSS	P2 PC
MATERIALS	Acrylic lens, ABS housing
VOLT/AMP	12.8VDC - 0.4A
WT/DIMS	.132 lb. / 4" x 2.063" x 1.063"
WARRANTY	Three Year Warranty

MC68 SERIES
Oblong Marker/Clearance Lights

- Surface mount on 2-3/4” centers
- Single wire design grounds through mounting hardware
- Snap-on lens, replaceable bulb

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		YELLOW	
MC68AB	MC68ABP	Yellow, self grounding	50
		RED	
MC68RB	MC68RBP	Red, self grounding	50
		ACCESSORIES	
A68AB	A68ABP	Yellow replacement lens	50
A68RB	A68RBP	Red replacement lens	50
		RETAIL	
MC68AS	Retail Ready	Yellow light, clam	12
MC68RS		Red light, clam	12

FMVSS	P2
MATERIALS	Acrylic lens, ABS housing
VOLT/AMP	12.8VDC - 0.2A
WT/DIMS	.088 lb. / 3.5” x 1.125” x 1”
WARRANTY	Three Year Warranty

MC68AB

MC68RB



MC70 SERIES
Marker/Clearance Lights with Reflex

- Surface mount on 4-13/16” centers
- Lens with reflex eliminates need for separate reflector
- Weathertight plug included

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		YELLOW	
MC70AB	MC70ABP	Yellow	20
		RED	
MC70RB	MC70RBP	Red	20
		RETAIL	
MC70AS	Retail Ready	Yellow light, clam	6
MC70RS		Red light, clam	6

FMVSS	A P2
MATERIALS	Acrylic lens, plastic housing
VOLT/AMP	12.8VDC - 0.422A
WT/DIMS	.132 lb. / 5.813” x 2” x 1.188”
WARRANTY	Three Year Warranty

MC70AB

MC70RB



MC71 SERIES
Marker/Clearance Lights

MC71AS

MC71RS





- Flush mount on 2" centers; chrome finish bezel
- Twist-in socket, includes both lead and ground wire
- Replaceable bulb

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		RETAIL	
MC71AS	Retail Ready	Yellow light, clam	12
MC71RS		Red light, clam	12
		ACCESSORIES	
A194B	A194BP	194 replacement bulb	100

FMVSS	P2
MATERIALS	Acrylic lens, ABS housing and bezel
VOLT/AMP	12.8VDC - 0.4A
WT/DIMS	.132 lb. / 3.75" x 2.25" x 0.5"
WARRANTY	Three Year Warranty

MC76 SERIES
Marker/Clearance Light with Reflex



MC76AB





- Dual bulb light with built-in reflex
- Lens with reflex eliminates need for separate reflector
- Surface mount on 4-13/16" centers
- Hard wired, single wire design is self grounding

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		YELLOW	
MC76AB	MC76ABP	Yellow	50
		ACCESSORIES	
A194B	A194BP	194 replacement bulb	100

FMVSS	A P2
MATERIALS	Acrylic lens, ABS housing
VOLT/AMP	12.8VDC - 1.0A
WT/DIMS	.132 lb. / 6" x 2.063" x 1"
WARRANTY	Three Year Warranty

MC81 SERIES
Chrome Marker/Clearance Lights

- Surface mount on 3-7/8" centers
- Single wire design grounds through mounting hardware
- Replaceable lens and bulb

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		YELLOW	
MC81AB	MC81ABP	Yellow, self grounding	50
		RED	
MC81RB	MC81RBP	Red, self grounding	50
		ACCESSORIES	
A81AB	A81ABP	Yellow replacement lens	50
A81RB	A81RBP	Red replacement lens	50
A194B	A194BP	194 replacement bulb	100

FMVSS	P2
MATERIALS	Acrylic lens, ABS housing
VOLT/AMP	12.8VDC - 0.2A
WT/DIMS	.176 lb. / 4.781" x 2.125" x 1.375"
WARRANTY	Three Year Warranty

MC81AB

MC81RB



MC82 SERIES
Armored Marker/Clearance Lights

- Surface mount on 3-7/8" centers
- Single wire design grounds through mounting hardware
- Replaceable lens and bulb

PC Rated

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		YELLOW	
MC82AB	MC82ABP	Yellow	20
		RED	
MC82RB	MC82RBP	Red	20
		ACCESSORIES	
A82AB	A82ABP	Yellow replacement lens	50
A82RB	A82RBP	Red replacement lens	50
A194B	A194BP	194 replacement bulb	100

FMVSS	P2 PC
MATERIALS	Acrylic lens, steel housing
VOLT/AMP	12.8VDC - 0.2A
WT/DIMS	.441 lb. / 4.5" x 2" x 1.5"
WARRANTY	Three Year Warranty

MC82AB

MC82RB



MC95 SERIES
Sealed Marker/Clearance Lights

MC95AB

MC95RB



- Sonically sealed, waterproof
- Stainless steel base
- Single wire design grounds through mounting hardware

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		YELLOW	
MC95AB	MC95ABP	Yellow	50
MC95APG	MC95APGP	Yellow, .180 male bullet	50
		RED	
MC95RB	MC95RBP	Red	50
		RETAIL	
MC95AS	Retail Ready	Yellow light, clam	12
MC95RS		Red light, clam	12

FMVSS	P2 P3
MATERIALS	Polycarbonate lens and housing, stainless steel base
VOLT/AMP	12.8VDC - 0.2A
WT/DIMS	.088 lb. / 2.063” x .688” x 1”
WARRANTY	Three Year Warranty

CB11 SERIES
Yellow Cab/Clearance Lights

- White and black base models, mounts on 3” centers
- Replaceable lens and bulb (67 bulb)
- Includes both lead and ground wires

PC Rated

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
CAB/CLEARANCE LIGHT			
CB11WAB	CB11WABP	Yellow, white base	50
CB11AB	CB11ABP	Yellow, black base	50
RETAIL			
CB11AS		Cab light, black base, clam	12
CB11AS6	Retail Ready	Cab light, black base, clam	6
CB15AK		5-pc cab light kit, black base, clam	6

FMVSS	P2 PC
MATERIALS	Acrylic lens, ABS housing
VOLT/AMP	12.8VDC - 0.569A
WT/DIMS	CB11: .176 lb. / 5.5” x 2.375” x 1.625”
	CB15: 1.191 lbs. / 5.5” x 2.375” x 1.625”
WARRANTY	Three Year Warranty



CB11WAB

CB11AS

CB15AK

CB20 SERIES
Yellow Cab/Clearance Light

CB20AB



- Surface mount on 1-1/2" centers, gasket included
- Sealed polycarbonate lens and housing
- Includes both lead and ground wires

PC Rated

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
CAB/CLEARANCE LIGHT			
CB20AB	CB20ABP	Yellow	50
RETAIL			
CB20AS	Retail Ready	Yellow, clam	12

FMVSS	P2 PC
MATERIALS	Acrylic lens, ABS housing
VOLT/AMP	12.8VDC - 0.2A
WT/DIMS	.265 lb. / 3.5" x 2.75" x 1.688"
WARRANTY	Three Year Warranty

CB22 SERIES
Cab/Clearance Lights

PC Rated

CB22AB

CB22RB



- Surface mount on 1-3/4" centers, gasket included
- Sealed polycarbonate lens and housing
- Twist-in socket with both lead and ground wires

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW			
CB22AB	CB22ABP	Yellow	50
RED			
CB22RB	CB22RBP	Red	50
ACCESSORIES			
A194B	A194BP	194 replacement bulb	100
RETAIL			
CB22AS	Retail Ready	Yellow, clam	12

FMVSS	P2 PC
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.2A
WT/DIMS	.132 lb. / 3.875" x 3.125" x 1.625"
WARRANTY	Three Year Warranty

MC77RB
Identification Light Bar

- Steel base with white finish
- Surface mount on 7” centers
- Snap-on lens and replaceable bulb
- Single wire design, self grounding

MC77RB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED ID LIGHT BAR			
MC77RB	MC77RBP	ID light bar	20
ACCESSORIES			
A68RB	A68RBP	Red replacement lens	50

FMVSS	P2
MATERIALS	Acrylic lens, ABS housing, steel base
VOLT/AMP	12.8VDC - 1.0A (193 bulb)
WT/DIMS	.265 lb. / 15.563” x 1.188” x 1.313”
WARRANTY	Three Year Warranty



MC93 SERIES
Sealed Identification Light Bars

- Surface mount on 7-1/2” centers
- Sealed, waterproof lights
- Hard wired, power and ground

MC93AB



MC93RB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW			
MC93AB	MC93ABP	Yellow	20
RED			
MC93RB	MC93RBP	Red	20
MC93RPG	MC93RPGP	Red, .180 male bullet on power wire	20
MC93R2PG	MC93R2PGP	Red, .180 male bullets on both wires	20
ACCESSORIES			
A91AB	A91ABP	Yellow replacement light	100
A91RB	A91RBP	Red replacement light	100
A93PB	A93PBP	Harness for light bar	100
RETAIL			
MC93RK	Retail Ready	Red ID light bar, clam	6

FMVSS	P2
MATERIALS	Polycarbonate lens and housing, ABS base
VOLT/AMP	12.8VDC - 1.0A
WT/DIMS	.397 lb. / 17” x 1.438” x 1.625”
WARRANTY	Three Year Warranty



MC94RB
Identification Light Bar

MC94RB

- Stainless steel base
- Surface mount on 16-1/16” centers
- Sealed, waterproof lights
- Hard wired, power and ground

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED ID LIGHT BAR			
MC94RB	MC94RBP	ID light bar	20
ACCESSORIES			
A91RB	A91RBP	Red replacement light	100
A93PB	A93PBP	Harness for light bar	100



FMVSS	P2
MATERIALS	Polycarbonate lens and housing, stainless steel base
VOLT/AMP	12.8VDC - 1.0A
WT/DIMS	.441 lb. / 16.5” x 1.375” x 1.625”
WARRANTY	Three Year Warranty

MC97 SERIES
Sealed Identification Light Bars

MC97RB

- Stainless steel base
- Surface mount on 8-1/2” centers
- Sealed, waterproof lights
- Single wire, self grounding

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED ID LIGHT BARS			
MC97RB	MC97RBP	Red	20
MC97R70PG	-	Red, .156 female plug, 70” lead	20
CLEAR UTILITY LIGHT			
UL97CPG	UL97CPGP	Clear	50
ACCESSORIES			
MC95RB	MC95RBP	Red replacement light	50
RETAIL			
MC97RK	Retail Ready	Red ID light bar, clam	6



FMVSS	P2
MATERIALS	Polycarbonate lens and housing, stainless steel base
VOLT/AMP	12.8VDC - 1.0A
WT/DIMS	.441 lb. / 14.25” x 1.188” x 1.313”
WARRANTY	Three Year Warranty

MC99 SERIES
Identification Light Bars

- Steel base with white finish
- Surface mount on 14-3/8” centers
- Snap-on lens, replaceable bulbs
- Single wire, self grounding

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		YELLOW	
MC99AB	MC99ABP	Yellow	20
		RED	
MC99RB	MC99RBP	Red	20
		ACCESSORIES	
A11AB	A11ABP	Yellow replacement lens	50
A11RB	A11RBP	Red replacement lens	50
A194B	A194BP	194 replacement bulb	100
		RETAIL	
MC99AK	Retail Ready	Yellow ID light bar, clam	6
MC99RK		Red ID light bar, clam	6

FMVSS	P2
MATERIALS	Acrylic lens, ABS housing, steel base
VOLT/AMP	12.8VDC - 1.0A
WT/DIMS	.353 lb. / 15.063” x 1.375” x 1.438”
WARRANTY	Three Year Warranty



LP11 SERIES
Snap-In Mini License Plate Lights

LP11CB

- Chrome plated brass construction
- Easy snap-in mounting
- Replaceable bulb (67)
- Single wire, self grounding

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
LICENSE LIGHTS			
LP11CB	LP11CBP	License light	50
LP11CPG	LP11CPGP	License light, .180 male bullet	50
RETAIL			
LP11CS	Retail Ready	License light, clam	12



FMVSS	(2) L
MATERIALS	Brass, chrome plated
VOLT/AMP	12.8VDC - 0.4A
WT/DIMS	.066 lb. / 1.5" x 1.5" x 2"
WARRANTY	Three Year Warranty

LP21 SERIES
Heavy Duty License Plate Lights

LP21CB

- Armored light made of durable chrome plated steel
- Surface mount on 2" centers
- Replaceable bulb (67)
- Single wire, self grounding

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
LICENSE LIGHTS			
LP21CB	LP21CBP	License light	50
RETAIL			
LP21CS	Retail Ready	License light, clam	12
LP21CS6		License light, clam	6



FMVSS	L
MATERIALS	Brass, chrome plated
VOLT/AMP	12.8VDC - 0.2A
WT/DIMS	.132 lb. / 2.5" x 1.813" x 2"
WARRANTY	Three Year Warranty

LP31 SERIES
Mini License Plate Light

- Surface mount on 2” centers
- Replaceable bulb
- Two-wire design includes both lead and ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
LICENSE LIGHTS			
LP31CB	LP31CBP	License light	50
LP31CPG	LP31CPGP	License light, .156 female barrels	50
LPB31CPG	LPB31CPGP	License light mounted on black plastic bracket, .156 female barrels	25
ACCESSORIES			
A194B	A194BP	194 replacement bulb	100
RETAIL			
LP31CS	Retail Ready	License light, clam	12

FMVSS	(2) L
MATERIALS	Brass, chrome plated bezel; stainless steel bulb socket
VOLT/AMP	12.8VDC - 0.261A
WT/DIMS	.088 lb. / 2.563” x 1.25” x 1” (light only)
WARRANTY	Three Year Warranty

LP31CB

LPB31CPG



LPB31CPG



LP31CB

LP41 SERIES
Stud Mount License Plate Light

LP41CB



- Chrome plated cover, black base
- Stud mount on 1-3/4" centers
- Replaceable bulb
- Single wire, self grounding

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
LICENSE LIGHTS			
LP41CB	LP41CBP	License light	50
ACCESSORIES			
A194B	A194BP	194 replacement bulb	100
RETAIL			
LP41CS	Retail Ready	License light, clam	12
LP41CS6		License light, clam	6

FMVSS	L
MATERIALS	Brass, chrome plated
VOLT/AMP	12.8VDC - 0.2A
WT/DIMS	.11 lb. / 2.625" x 1.563" x 2.188"
WARRANTY	Three Year Warranty

LP51 SERIES
Surface Mount License Plate Light

LP51CB



- Gray coated cover, stainless steel mounting base
- Stud mount on 3-1/4" centers
- Replaceable bulb
- Single wire, self grounding

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
LICENSE LIGHTS			
LP51CB	LP51CBP	License light	20
ACCESSORIES			
A194B	A194BP	194 replacement bulb	100

FMVSS	L
MATERIALS	Stainless steel mounting base, plastic cover
VOLT/AMP	12.8VDC - 0.2A
WT/DIMS	.309 lb. / 4" x 1.75" x 2.313"
WARRANTY	Three Year Warranty

LP52/54 SERIES

License Plate Light with Bracket

- Light features gray coated cover, stainless steel mounting base; bracket is steel with black finish
- Surface mount on 3.5” centers, hardware included
- Replaceable bulb



LP52CB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		LICENSE LIGHTS	
LP52CB	LP52CBP	License light, single wire	10
LP54CB	LP54CBP	License light, two-wire	10
		ACCESSORIES	
LP52HP	LP52HPP	Mounting hardware	100
A194B	A194BP	194 replacement bulb	100

FMVSS	L
MATERIALS	Stainless steel mounting base, plastic cover, steel bracket
VOLT/AMP	12.8VDC - 0.2A
WT/DIMS	.309 lb. / 8.5” x 2.875” x 2.375”
WARRANTY	Three Year Warranty



LP55 SERIES

License Plate Light with Bracket

- Light features gray coated cover, stainless steel mounting base; bracket is black heavy duty plastic
- Surface mount on 6-7/16” centers
- Includes both lead and ground wires
- Replaceable bulb (67)

LP55CB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		LICENSE LIGHTS	
LP55CB	LP55CBP	License light	10

FMVSS	L
MATERIALS	Stainless steel mounting base, plastic cover, plastic bracket
VOLT/AMP	12.8VDC - 0.2A
WT/DIMS	.176 lb. / 8.625” x 3.25” x 2.313”
WARRANTY	Three Year Warranty



LP56 SERIES
Surface Mount License Plate Light

- Surface mount with included adhesive
- Replaceable bulb (67)
- Single wire, self grounding

LP56CB



BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
LICENSE LIGHTS			
LP56CB	LP56CBP	License light	50

FMVSS	L
MATERIALS	Gray plastic housing
VOLT/AMP	12.8VDC - 0.2A
WT/DIMS	.11 lb. / 2.625” x 1.625” x 2”
WARRANTY	Three Year Warranty

LP65 SERIES
Sealed License Plate Light

- Sonically sealed, waterproof
- Multiple mounting and wiring options

LP65CB

LP65CS



BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
LICENSE LIGHTS			
LP65CB	LP65CBP	License light	50
ACCESSORIES			
A65B	A65BP	Black bracket	50
A65P	A65PP	Single wire plug, .156 male bullet	50
A65PB	A65PBP	Kit: A65B black bracket & A65P plug	50
A66PB	A66PBP	Kit: Gray bracket & A65P plug	50
A67CB	A67CBP	Kit: Chrome bracket & A65P plug	50
A68PB	A68PBP	Kit: Black bracket & 2-wire plug	50
For more details on mounting and wiring accessories, see Accessories section at back of catalog.			
RETAIL			
LP65CS	Retail Ready	License light, clam	12

FMVSS	L
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.656A
WT/DIMS	.066 lb. / 3.938” x 1.25” x 0.875”
WARRANTY	Three Year Warranty

LP71 SERIES
Chrome License Plate Light

- Chrome-plated brass and steel housing
- Mount on 2-5/8” centers
- Replaceable bulb (67)
- Single wire, self grounding
- Two units required for legal license illumination

LP71CB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
LICENSE LIGHTS			
LP71CB	LP71CBP	License light	25
RETAIL			
LP71CS	Retail Ready	License light, clam	12



FMVSS	(2) L
MATERIALS	Brass and stainless steel housing
VOLT/AMP	12.8VDC - 0.2A
WT/DIMS	.058 lb. / 3.375” x 2.375” x 2.188”
WARRANTY	Three Year Warranty

LP81 SERIES
Surface Mount License Plate Light

- Surface mount on 3-7/16” centers
- Replaceable bulb
- Includes both lead and ground wires
- Available in standard black and optional gray color

LP81BB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
LICENSE LIGHTS			
LP81BB	LP81BBP	License light, black housing	50
LP81BPG	-	License light, black housing, .180 male plug on power, eyelet on ground	50
LP81GB	-	License light, grey housing	50
ACCESSORIES			
A194B	A194BP	194 replacement bulb	100





FMVSS	L
MATERIALS	Polycarbonate housing
VOLT/AMP	12.8VDC - 0.2A
WT/DIMS	.11 lb. / 4” x 1.563” x 2.625”
WARRANTY	Three Year Warranty

LP97 SERIES
Sealed License/Utility Light

LP97CB



- Sonically sealed, waterproof
- Terminal is two .156 female barrels

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
LICENSE LIGHTS			
LP97CB	LP97CBP	License light	50
ACCESSORIES			
A46PB	A46PBP	Straight PL-10 plug, 6" lead	100
A86PB	A86PBP	Straight PL-10 plug, 18" lead	100

FMVSS	L
MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.2A
WT/DIMS	.11 lb. / 3.375" x 1.25" x 2.375"
WARRANTY	Three Year Warranty

LP95CBF
Sealed Stud Mount License/Utility Light

LP95CBF



- Sonically sealed, waterproof
- Design includes both lead and ground wires with .180 female barrels

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
LICENSE/UTILITY LIGHTS			
LP95CBF	-	License/utility light	50

MATERIALS	Polycarbonate lens and housing, stainless steel base
VOLT/AMP	12.8VDC - 0.2A
WT/DIMS	.066 lb. / 2.063" x .688" x 1"
WARRANTY	Three Year Warranty

LP91 SERIES
Sealed License/Utility Light

- Sonically sealed, waterproof
- Multiple mounting and wiring options

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
LICENSE/UTILITY LIGHTS			
LP91CB	LP91CBP	License/utility light	50
LP26SKB	LP26SKBP	Kit: LP91CB, LP25SGGB, gasket, .180 male bullets on power and ground	50
LICENSE LIGHT BRACKET			
LP25SB	LP25SBP	Vertical bracket, black coated	100
ACCESSORIES			
A25GB	A25GBP	Gasket	100
A46PB	A46PBP	2-wire plug, 6" lead	100
A86PB	A86PBP	2-wire plug, 18" lead	100
A91LW	A91LWP	1-wire plug, 12" lead	100
A91BB	A91BBP	Black base, self grounding	100
A91BOB	A91BOBP	Black base, open back	100
A91CB	A91CBP	Chrome base, self grounding	100
A91OB	A91OBP	Chrome base, open back	100
A91GB	A91GBP	Grommet	100
LP25SB	LP25SBP	Black vertical bracket	100
LP25SGGB	LP25SGGBP	Grey vertical bracket	100
RETAIL			
LP91CS	Retail Ready	License light, clam	12

MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.2A
WT/DIMS	.066 lb. / 2.5" x 1.1885" x 0.875"
WARRANTY	Three Year Warranty

LP91CB



LP26SKB



UL94 SERIES

Sealed Stud Mount License/Utility Light

UL94CB



- Sonically sealed, waterproof
- Polycarbonate housing, stainless steel base, clear lens
- Single wire design grounds through mounting hardware

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
LICENSE/UTILITY LIGHT			
UL94CB	UL94CBP	License/utility light	50

MATERIALS	Polycarbonate lens and housing, stainless steel base
VOLT/AMP	12.8VDC - 0.2A
WT/DIMS	.088 lb. / 2.125" x 1.125" x 1.063"
WARRANTY	Three Year Warranty

UL53 SERIES
2” Sealed Utility Light

- Sonically sealed, waterproof
- Accepts standard two-pin PL-10 plug

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
UTILITY LIGHT			
UL53CB	UL53CBP	Utility light	100/50
ACCESSORIES			
A46PB	A46PBP	Straight plug, 6” lead	100
A86PB	A86PBP	Straight plug, 18” lead	100
A54GB	A54GBP	2” Flush mount grommet	100
A54GK	A54GKP	2” Kit: A54GB and A46PB	100
A55CB	A55CBP	2” Chrome trim ring	20
BK5557GB	BK5557GBP	Cam-on mounting bracket	50

MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.6A
WT/DIMS	.044 lb. / 2” x 2” x .688”
WARRANTY	Three Year Warranty

UL53CB



UL56 SERIES
2.5” Sealed Utility Light

- Sonically sealed, waterproof
- Accepts standard two-pin PL-10 plug
- Flush mount design with flange sealed to light

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
UTILITY LIGHT			
UL56CB	UL56CBP	Utility light	100/50
ACCESSORIES			
A46PB	A46PBP	Straight plug, 6” lead	100
A86PB	A86PBP	Straight plug, 18” lead	100

MATERIALS	Polycarbonate lens and housing
VOLT/AMP	12.8VDC - 0.6A
WT/DIMS	.044 lb. / 3.438” x 3.438” x .0938”
WARRANTY	Three Year Warranty

UL56CB



UL97 SERIES
Sealed Utility Light Bar

UL97CPG

- Sonically sealed, waterproof
- Polycarbonate lens and housing, stainless steel base
- Single wire design grounds through mounting hardware
- Plug-n-go connector

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		UTILITY LIGHT	
UL97CPG	UL97CPGP	Utility light bar	50



MATERIALS	Polycarbonate lens and housing, stainless steel base
VOLT/AMP	12.8VDC - 0.4A
WT/DIMS	.265 lb. / 14.25" x 1.188" x 1.313"
WARRANTY	Three Year Warranty

IL21 SERIES
Interior Dome Light

- Surface mount dome light with or without on/off switch
- Mounts on 3-1/2” centers
- Includes both lead and ground wire
- Replaceable bulb (1156)

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
INTERIOR LIGHTS			
IL21CB	IL21CBP	Interior light with switch, two-wire	50
IL21CPG	-	Interior light with switch, single wire with .180 male bullet	50
RETAIL			
IL21CS	Retail Ready	Interior dome light with switch, clam	12
IL21CS6		Interior dome light with switch, clam	6

MATERIALS	Polycarbonate lens, steel base plate
VOLT/AMP	12.8VDC - 2.4A
WT/DIMS	.309 lb. / 4.563” x 2.5” x 1.75”
WARRANTY	Three Year Warranty

IL21CB





IL31CS
Porch or Cabin Light

- Surface mount light with on/off switch
- Aluminum base, durable plastic lens
- Single wire design grounds through mounting hardware
- Replaceable bulb (1156)

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RETAIL			
IL31CS	Retail Ready	Porch/cabin light, clam	6

MATERIALS	Plastic lens, aluminum housing
VOLT/AMP	12.8VDC - 2.2A
WT/DIMS	.375 lb. / 5.125” x 5.125” x 1.813”
WARRANTY	Three Year Warranty

IL31CS



IL61 SERIES
Dome Light with Switch

IL61CB



- Surface mount light with on/off switch
- Aluminum base, durable plastic lens
- Single wire design grounds through mounting hardware
- Replaceable bulb (1141)

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
DOME LIGHT			
IL61CB	IL61CBP	Dome light	50

MATERIALS	Plastic lens, aluminum housing
VOLT/AMP	12.8VDC - 0.4A
WT/DIMS	.221 lb. / 5.875" x 5.875" x 1.5"
WARRANTY	Three Year Warranty

IL91 SERIES
6" Steel Dome Light

IL91CB

- Surface mount steel base, chrome plated
- Includes both lead and ground wires
- Replaceable bulb (1141)

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
DOME LIGHT			
IL91CB	IL91CBP	Dome light	50

MATERIALS	Polycarbonate lens, steel housing
VOLT/AMP	12.8VDC - 0.4A
WT/DIMS	.485 lb. / 6.438" x 6.438" x 1.75"
WARRANTY	Three Year Warranty



QH16CTS & QH36CTS
55W Halogen Area Lights

- Area lights with post mount bases
- 12V 35W H3 halogen bulb
- Include both lead and ground wires
- QH36CTS has multi-directional bracket that adjusts both horizontally and vertically and stainless steel hardware

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		AREA LIGHT	
QH16CTS	QH16CTSP	Post mount area light	50
QH36CTS	QH36CTSP	Multi-directional post mount area light with stainless steel hardware	50
		RETAIL	
A700	12V 55W H3 quartz halogen bulb, clam	Retail Ready	12

MATERIALS	Plastic housing, glass lens
VOLT/AMP	12.8VDC - 4.5A
WT/DIMS	0.663 lb. / 5.875" x 3" x 2.75"
WARRANTY	Three Year Warranty

QH16CTS

QH36CTS

TL10 SERIES
5" Work Lights, Rubber Housings

- Utility/work/ag light with shock proof rubber housing
- #4411 sealed beam
- Include both lead and ground wires
- Steel bracket, 5/16" mounting post

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		WORK/UTILITY/AG LIGHTS	
TL10CB	TL10CBP	12V, 2-wire	25
TL11CPG	-	12V, self grounding, .180 male bullet	25
		RETAIL	
TL10CS	12V Work/utility/ag light, clam	Retail Ready	6
TL106CS	6V Work/utility/ag light, clam		6
TL10SS	12V Work/utility/ag light, stainless steel bracket, clam		6
TL12CS	12V Work/utility/ag light, recessed bulb, clam		6

MATERIALS	Rubber housing, glass lens, steel bracket
VOLT/AMP	12.8VDC - 2.8A
WT/DIMS	1.235 lbs. / 4.75" x 4.75" x 2.5"
WARRANTY	Three Year Warranty

TL10CB





TL35/46 SERIES

55W Rectangular Utility/Ag Lights

TL35FS/TS

TL46FS/TS

- Utility/ag light with heavy duty plastic housing
- 12V 55W H3 halogen bulb
- Include both lead and ground wires
- Adjustable, steel mounting bracket

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
UTILITY/AG LIGHTS			
TL35TB	-	3" x 5" lens, trapezoid beam	20
RETAIL			
TL35FS		3" x 5" lens, flood beam, box	3
TL35TS		3" x 5" lens, trapezoid beam, box	3
TL46FS		4" x 6" lens, flood beam, clam	3
TL46TS		4" x 6" lens, trapezoid beam, clam	3
A700		12V 55W H3 quartz halogen bulb, clam	12

Retail Ready

MATERIALS	Plastic housing, glass lens, steel bracket
VOLT/AMP	12.8VDC - 4.5A
WT/DIMS	TL35: 1.5 lbs. / 6.5" x 4.375" x 3.75"
	TL46: 1.5 lbs. / 5.375" x 4.5" x 2.25"
WARRANTY	Three Year Warranty

RB10A

Magnet Mount Rotary Beacon

RB10A

- 12V rotary beacons for magnet mount
- 10-ft coil cord with power plug
- Replaceable bulb

BULK P/N	DESCRIPTION	QTY
RETAIL		
RB10A	Yellow rotary beacon, clam	6

Retail Ready

MATERIALS	Acrylic lens
VOLT/AMP	12.8VDC - 1.45A
WT/DIMS	1.6 lb. / 4.75" x 4.75" x 5.25"
WARRANTY	Three Year Warranty

DL16 SERIES
55W Docking Lights

- Docking light with heavy duty plastic housing, glass lens
- 12V 55W H3 halogen bulb
- Includes both lead and ground wires with male bullets
- Stainless steel mounting bracket with rubber cover
- Kits include two lights, wiring, mounting hardware and switch

DL16CC

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		RETAIL	
DL16CC		Kit, black housing, clam	3
DL16WC		Kit, white housing, clam	3
A700		12V 55W H3 quartz halogen bulb, clam	12

MATERIALS	Plastic housing, glass lens, stainless steel bracket
VOLT/AMP	12.8VDC - 4.5A
WT/DIMS	0.663 lb. / 5.875" x 3" x 2.75"
WARRANTY	Three Year Warranty

DL16WC

HALOGEN LIGHTS

DL55 SERIES
55W Marine Flood Lights

- Flood light with heavy duty plastic housing, glass lens
- 12V 55W H3 halogen bulb
- Includes both lead and ground wires
- Stainless steel mounting bracket

DL55CS

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		RETAIL	
DL55CS		55W marine flood light, clam	6
A700		12V 55W H3 quartz halogen bulb, clam	12

MATERIALS	Plastic housing, glass lens, stainless steel bracket
VOLT/AMP	12.8VDC - 4.5A
WT/DIMS	1.333 lb. / 6.25" x 4.25" x 3"
WARRANTY	Three Year Warranty

RVSTL10/11 SERIES
LED RV Combination Tail Lights

RVSTL10

RVSTL11

- Combination stop/turn/tail light for surface mount
- Low profile, round design
- Driver side light includes LED license plate illuminator and mounting bracket
- Hard wired, ground wire included

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED STOP/TURN/TAIL LIGHT - 6 DIODES			
RVSTL10	RVSTL10P	Passenger side	25
RVSTL11	RVSTL11P	Driver side, 2-LED license light	25
RETAIL			
RVSTL10K	Retail Ready	Set: RVSTL10, RVSTL11, mounting hardware, clam	2

FMVSS	S2 T2 I6 A L
MATERIALS	Acrylic lens and plastic housing
VOLT/AMP	12.8VDC - Stop/Turn .117/Tail .053
WT/DIMS	RVSTL10: .44 lbs / 5.9" x 5.61" x 1.33"
	RVSTL11: .475 lbs / 8" x 7" x 1.33"
WARRANTY	Lifetime LED Warranty



RVSTL10



RVSTL11

LED LIFETIME WARRANTY
NO BULBS TO REPLACE, EVER!

RVSTL20/21 SERIES
LED RV Combination Tail Lights

- Combination stop/turn/tail light for surface mount
- Low profile, oblong arched design
- Driver side lights include LED license plate illuminator and mounting bracket
- Hard wired, ground wire included

RVSTL20

RVSTL21

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RED STOP/TURN/TAIL LIGHT - 6 DIODES			
RVSTL20	RVSTL20P	Passenger side	25
RVSTL21	RVSTL21P	Driver side, with 2-LED license light	25
RETAIL			
RVSTL20K	Retail Ready	Set: RVSTL20, RVSTL21, mounting hardware, clam	2

FMVSS	S2 T2 I6 A L
MATERIALS	Acrylic lens and plastic housing
VOLT/AMP	12.8VDC - 0.117A Stop/Turn, .053A Tail
WT/DIMS	RVSTL20: .418 lbs / 7.50" x 3.77" x 1.29"
	RVSTL21: .468 lbs / 7.5" x 5.02" x 1.29"
WARRANTY	Lifetime LED Warranty



RVSTL20



RVSTL21

LED LIFETIME WARRANTY
NO BULBS TO REPLACE, EVER!

RV COMBINATION TAIL LIGHTS

RVSTL60/61 SERIES

LED Low Profile RV Combination Tail Lights

RVSTL60
RVSTLB60

RVSTL61

RVSTLB61

- 9-LED combination stop/turn/tail light for surface mount
- Driver side lights include 3-LED license plate illuminator and mounting bracket
- Snap-on, replaceable lens
- Available with white or black base
- Hard wired, ground wire included

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
LED RV COMBINATION TAIL LIGHTS - 9 DIODES			
RVSTL60	RVSTL60P	Passenger side, white base	48
RVSTL61	RVSTL61P	Driver side, white base, 3-LED license light	48
RVSTLB60	RVSTLB60P	Passenger side, black base	48
RVSTLB61	RVSTLB61P	Driver side, black base, 3-LED license light	48
ACCESSORIES			
RV60BK	RV60BKP	Wedge base, white	100
RV60BBK	RV66BBKP	Wedge base, black	100
AST60B	AST60BP	Replacement lens, passenger side	10
AST61B	AST61BP	Replacement lens, driver side	10
RETAIL			
RVSTL60S	Passenger side, white base, clam		6
RVSTL61S	Driver side, white base, clam		6
RVSTLB60FS	Passenger side, black base, clam		6
RVSTLB61FS	Driver side, black base, clam		6

Retail Ready

LED LIFETIME WARRANTY
NO BULBS TO REPLACE, EVER!

FMVSS	A S2 T2 I6
MATERIALS	Acrylic lens and plastic housing
VOLT/AMP	12.8VDC - .243A Stop/Turn, .046A Tail
WT/DIMS	RVSTL60: .419 lb. / 8.625" x 3.188" x 2.25"
	RVSTL61: .419 lb. / 8.625" x 5" x 2.25"
WARRANTY	Lifetime LED Warranty









RVSTL61
RVSTLB61





RVSTL60
RVSTLB60



RVSTL0060/61 SERIES

ONE™ LED Series RV Combination Tail Lights

ONE LED LAMPS

- ONE™ LED Combination stop/turn/tail light with built-in reflex
- Driver side lights include LED license plate illuminator and mounting bracket
- Surface mount design with snap-on lens
- Available with white or black base
- Hard wired, ground wire included

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
ONE™ LED RV COMBINATION TAIL LIGHTS			
RVSTL0060	RVSTL0060P	Passenger side, white base	48
RVSTL0061	RVSTL0061P	Driver side, white base	48
RVSTLB0060	RVSTLB0060P	Passenger side, black base	48
RVSTLB0061	RVSTLB0061P	Driver side, black base	48
ACCESSORIES			
RV60BK	RV60BKP	Wedge base, white	100
RV60BBK	RV66BBKP	Wedge base, black	100
RETAIL			
RVSTL0060RFK	Set: pair of tail lights, white base, clam	Retail Ready	2

FMVSS	A S2 T2 I6
MATERIALS	Acrylic lens and plastic housing
VOLT/AMP	RVSTL0060: 12.8VDC .34A Stop/Turn, .01A Tail
	RVSTL0061: 12.8VDC .43A Stop/Turn, .094A Tail
WT/DIMS	RVSTL0060 .456 lbs. / 8.688" x 3.188" x 2.25"
	RVSTL0061 .513 lbs. / 8.688" x 5" x 2.25"
WARRANTY	Lifetime LED Warranty



RVSTL0060

RVSTL0061

RVSTLB0060

RVSTLB0061

LED LIFETIME WARRANTY
NO BULBS TO REPLACE, EVER!



RVSTL0061
RVSTLB0061



RVSTL0060
RVSTLB0060

RV COMBINATION TAIL LIGHTS

RVST60/61 SERIES

Low Profile RV Combination Tail Lights

RVST60
RVSTB60

RVST61

RVSTB61

RV60BK

- Combination stop/turn/tail light for surface mount
- Driver side lights include license plate illuminator and mounting bracket
- Snap-on lens and replaceable bulb
- Available with white or black base
- Hard wired, ground wire included

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RV COMBINATION TAIL LIGHTS			
RVST60	RVST60P	Passenger side RV tail light, white base	48
RVST61	RVST61P	Driver side RV tail light, white base	48
RVSTB60	RVSTB60P	Passenger side RV tail light, black base	48
RVSTB61	RVSTB61P	Driver side RV tail light, black base	48
ACCESSORIES			
RV60BK	RV60BKP	Wedge base, white	100
RV60BBK	RV66BBKP	Wedge base, black	100
AST60B	AST60BP	Replacement lens, passenger side	10
AST61B	AST61BP	Replacement lens, driver side	10
A1157B	A1157BP	1157 replacement bulb	50
RETAIL			
RVST60S	Passenger side, white base, clam	Retail Ready	6
RVST61S	Driver side, white base, clam		6

FMVSS	A S2 T2 I6
MATERIALS	Acrylic lens and plastic housing
VOLT/AMP	12.8VDC - 2.65A Stop, 2.10A Tail
WT/DIMS	RVST60: .419 lb. / 8.625" x 3.188" x 2.25"
	RVST61: .419 lb. / 8.625" x 5" x 2.25"
WARRANTY	Three Year Warranty



RVST60
RVSTB60



RVST61
RVSTB61

RVCST90 SERIES
Streamline Sealed LED Lights

- Sonically sealed, waterproof
- Assemblies include two clear lens red stop/turn/tail lights and one clear lens yellow turn signal
- Hard wired with separate ground wire
- Durable corrosion proof housing with chrome finish

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		TAIL LIGHT ASSEMBLIES	
RVCST90BL		Left side, black housing; two clear lens red stop/tail lights, one clear lens yellow turn signal	2
RVCST90BR		Right side, black housing; two clear lens red stop/ tail lights, one clear lens yellow turn signal	2

FMVSS	S T I
MATERIALS	Polycarbonate lens, plastic housing
VOLT/AMP	12.8V - Stop 1.15A/Tail 0.08A
WT/DIMS	2.0 lbs. / 12.875" x 21.875" x 1.75"
WARRANTY	Lifetime LED Warranty



RVCST90BL

RVCST90BR

LED LIFETIME WARRANTY
NO BULBS TO REPLACE, EVER!

RVPLL11/13 SERIES

LED Oval Porch/Utility Lights

RVPLL11AB

RVPLL13CB





- LED surface mount porch utility lights available with or without switch
- Black housing with snap-on lens and 16 SMD LEDs
- Available with yellow or clear lens
- Hard wired with separate ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW PORCH LIGHTS - 16 DIODES			
RVPLL11AB	RVPLL11ABP	Black housing	50
RVPLL13AB	RVPLL13ABP	Black housing, switch	50
CLEAR UTILITY LIGHTS - 16 DIODES			
RVPLL11CB	RVPLL11CBP	Black housing	50
RVPLL13CB	RVPLL13CBP	Black housing, switch	50
RVPLL13CWB	RVPLL13CWBP	White housing, switch	50
RETAIL			
RVPLL11AFS	Yellow light, black housing, clam	Retail Ready	12
RVPLL11CFS	Clear light, black housing, clam		12

CERTIFICATION	
MATERIALS	Acrylic lens and plastic housing
VOLT/AMP	12.8VDC - Amber .295A, White .32A
WT/DIMS	0.5 lb / 6.375" x 3.312" x 1.437"
WARRANTY	Lifetime LED Warranty

LED LIFETIME WARRANTY
NO BULBS TO REPLACE, EVER!

800-364-5483 / 918-683-9514

RVPL1/3 SERIES
Rectangular Porch/Utility Lights

- Surface mount porch/cabin lights (CSA/UL listed)
- White housing with snap-on lens and replaceable bulb (1141)
- Available with yellow or clear lens
- Hard wired with separate ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW PORCH LIGHTS			
RVPL1A	RVPL1AP	Yellow porch light, no switch	50
RVPL3A	RVPL3AP	Yellow porch light with switch	50
CLEAR UTILITY LIGHTS			
RVPL1C	RVPL1CP	Clear utility light, no switch	50
RVPL3C	RVPL3CP	Clear utility light with switch	50
ACCESSORIES			
APL1AB	APL1ABP	Yellow replacement lens	10
APL1CB	APL1CBP	Clear replacement lens	10
RETAIL			
RVPL3CFS		Clear utility light, clam	12

CERTIFICATION	CSA / UL
MATERIALS	Acrylic lens and plastic housing
VOLT/AMP	12.8VDC - 1.4A
WT/DIMS	.419 lb. / 6.375" x 3.5" x 2.094"
WARRANTY	Three Year Warranty



RVPL1A

RVPL3A

RVPL1C

RVPL3C

RVPL5/7 SERIES
Oval Porch/Utility Lights

RVPL5A

RVPL5AB

RVPL7A

RVPL7AB

RVPL5CB

RVPL7C

RVPL7CB

- Surface mount porch utility lights available with or without switch
- White or black housing with snap-on lens and replaceable bulb (1141)
- Available with yellow or clear lens
- Hard wired with separate ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
YELLOW PORCH LIGHTS			
RVPL5A	RVPL5AP	Yellow porch light, white housing, no switch	50
RVPL5AB	RVPL5ABP	Yellow porch light, black housing, no switch	50
RVPL7A	RVPL7AP	Yellow porch light, white housing, with switch	50
RVPL7AB	RVPL7ABP	Yellow porch light, black housing, with switch	50
CLEAR UTILITY LIGHTS			
RVPL5CB	RVPL5CBP	Clear utility light, black housing, no switch	50
RVPL7C	RVPL7CP	Clear utility light, white housing, with switch	50
RVPL7CB	RVPL7CBP	Clear utility light, black housing, with switch	50
ACCESSORIES			
APL5AB	APL5ABP	Yellow replacement lens	10
APL5CB	APL5CBP	Clear replacement lens	10
RETAIL			
RVPL5AFS	Yellow porch light, white housing, clam	Retail Ready	12
RVPL7CFS	Clear utility light, white housing, clam		12
RVPL7CBFS	Clear utility light, black housing, clam		12

CERTIFICATION	CSA / UL
MATERIALS	Acrylic lens and plastic housing
VOLT/AMP	12.8VDC - 1.4A
WT/DIMS	.265 lb. / 6.25" x 3.438" x 1.875"
WARRANTY	Three Year Warranty



RVSL21/31 SERIES
Scare Lights

- Surface mount security lights with mounting gasket (CSA)
- Stainless steel or white housing with screw-on lens and replaceable bulb (1156)
- Hard wired with separate ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
CLEAR SECURITY LIGHTS			
RVSL21	RVSL21P	Scare light, stainless housing	25
RVSL31	RVSL31P	Scare light, white housing	25

CERTIFICATION	CSA
MATERIALS	Acrylic lens, metal housing
VOLT/AMP	12.8VDC - 1.4A
WT/DIMS	0.97 lb. / 8.656" x 8.656" x 1.969"
WARRANTY	Three Year Warranty

RVSL21

RVSL31



RVILL39

LED Surface Mount Interior Ceiling Light

RVILL39

- Surface mount ceiling light with switch
- Effective lumen output 230 lm
- Replaceable white snap-on bezel
- Dual power: use with 12VDC and 24VDC systems
- 18-gauge, 6-inch lead and ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
INTERIOR CEILING LIGHTS - 9 DIODES			
RVILL39	RVILL39P	Interior light with switch	10

Raw lumen output: 280 lm
Effective lumen ouput: 230 lm

MATERIALS	Clear PMMA lens, ABS bezel
VOLT/AMP	12.8VDC - 0.25A
WT/DIMS	.325 lb. / 7.188" x 5.188" x 1.438"
WARRANTY	Lifetime LED Warranty



LED LIFETIME WARRANTY
NO BULBS TO REPLACE, EVER!

RVILL40 SERIES
LED Surface Mount Interior Light

- Surface mount ceiling light with on/off switch
- Low profile design - only 1” thick
- Color temperature 4500K - bright white illumination
- Hard wired with separate ground wire
- Available in bulk, polypack and retail packaging

RVILL40

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
INTERIOR CEILING LIGHTS - 9 DIODES			
RVILL40	RVILL40P	Interior light, on/off switch, 2-wire	10
RETAIL			
RVILL40FS		Interior light, on/off switch, 2-wire, clam (Retail Ready)	12

Raw lumen output: 290 lm
Effective lumen ouput: 140 lm

MATERIALS	Plastic
VOLT/AMP	12.8VDC - 0.3A
WT/DIMS	.02 lb. / 6.3” x 4” x 1”
WARRANTY	Lifetime LED Warranty

LED LIFETIME WARRANTY
NO BULBS TO REPLACE, EVER!



RVILL33/34 SERIES
LED Interior RV Lights

- Surface mount interior lights with switch (CSA)
- Single or double lights with snap-on lens
- LED technology – uses 90% less energy
- Hard wired with separate ground wire

RVILL33

RVILL34

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
LED INTERIOR LIGHTS			
RVILL33	RVILL33P	Single, on/off switch, 9 diodes	50
RVILL34	RVILL34P	Double, on/off switch, 18 diodes	25
RVILL33PB	RVILL33PBP	Single, on/off switch, .180 male bullet on power, ring terminal on ground	50
RETAIL			
RVILL33FS	Single, on/off switch, 9 diodes, clam	Retail Ready	6
RVILL34FS	Double, on/off switch, 18 diodes, clam		6

RVILL33 lumen output (raw/effective): 460 lm / 407 lm
RVILL34 lumen ouput (raw/effective): 920 lm / 815 lm

CERTIFICATION	CSA	
MATERIALS	Polycarbonate lens and plastic housing	
VOLT/AMP	RVILL33:	12.8VDC - 0.3A
	RVILL34:	12.8VDC - 0.6A
WT/DIMS	RVILL33:	.794 lb. / 6.377" x 4.173" x 1.787"
	RVILL34:	1.587 lb. / 10.283" x 4.173" x 1.787"
WARRANTY	Lifetime LED Warranty	

RV INTERIOR LIGHTS

LED LIFETIME WARRANTY
NO BULBS TO REPLACE, EVER!



RVILL33



RVILL34

800-364-5483 / 918-683-9514

RVIL35
Interior RV Light

- Surface mount interior light with switch (CSA)
- Snap-on lens and replaceable bulb
- Hard wired with separate ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
INTERIOR RV LIGHTS			
RVIL35	RVIL35P	Single, on/off switch	50
ACCESSORIES			
ARVIL35B	ARVIL35BP	Replacement lens	10
A921B	-	921 replacement bulb	50

CERTIFICATION	CSA
MATERIALS	Polycarbonate lens and plastic housing
VOLT/AMP	12.8VDC - 1.3A
WT/DIMS	.794 lb. / 6.375" x 4.125" x 1.75"
WARRANTY	Three Year Warranty

RVIL35



RVIL35

RVIL21/22 SERIES
RV Interior Lights

RVIL21

RVIL22

- Surface mount ceiling lights with switch (CSA)
- Single or double lights with snap-on lens and replaceable bulb
- Hard wired with separate ground wire

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		RV INTERIOR LIGHTS	
RVIL21	RVIL21P	Single, on/off switch	50
RVIL22	RVIL22P	Double, on/off switch	25
		ACCESSORIES	
AIL21B	AIL21BP	Clear replacement lens	10
A921B	-	921 replacement bulb	50
		RETAIL	
RVIL21S	Single, on/off switch, clam	Retail Ready	6
RVIL22S	Double, on/off switch, clam		6

CERTIFICATION	CSA / UL
MATERIALS	Acrylic lens and plastic housing
VOLT/AMP	RVIL21: 12.8VDC - 0.5A
	RVIL22: 12.8VDC - 1.4A
WT/DIMS	RVIL21: .794 lb. / 7.078" x 4.25" x 1.969"
	RVIL22: 1.587 lb. / 12" x 4.25" x 1.844"
WARRANTY	Three Year Warranty



RVIL21



RVIL22

800-364-5483 / 918-683-9514

COMPACT COURTESY LIGHTS

- Select LED or Incandescent
- Choose from surface mount and flush mount lights
- Hard wired, include lead and ground

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
COURTESY LIGHTS			
16802LB	16802LBP	LED black hooded light	50
16802B	16802P	Black hooded light (bulb 194; .24A)	100
19102B	19102P	Flush mount light (bulb 194; .24A)	50

CERTIFICATION	CSA
MATERIALS	Plastic
VOLT	12.8VDC
WT/DIMS	16802B/LB: .2 lb. / 2.75" x 1.75" x 1.5"
	19102B: .2 lb. / 4.5" x 1.25"
WARRANTY	Three Year Warranty/ Lifetime LED Warranty

16802B

19102B

CHROME COURTESY LIGHTS

- Hooded lights with chrome finish, white lens
- Hard wired, include lead and ground

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
COURTESY LIGHTS			
068NME	068NMEP	Snap-in light	50
068WMTE	068WMTEP	Light with stainless steel mounting plate	50

CERTIFICATION	UL
MATERIALS	Metal (068WMTE - stainless steel plate), polycarbonate lens
VOLT/AMP	12.8VDC - 0.59A (bulb 67, 12V 4CP)
WT/DIMS	068NME: .2 lb. / 1.5" x 1.5" x 2"
	068WMTE: .2 lb. / 2.75" x 1.625" x 2"
WARRANTY	Three Year Warranty

068NME

068WMTE

WATERPROOF COURTESY LIGHT

24074B

- Submersible design with gaskets
- Hard wired, includes lead and ground

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
COURTESY LIGHT			
24074B	24074P	Rear mount light with nut	50

CERTIFICATION	CSA
MATERIALS	Plastic
VOLT/AMP	12.8VDC - 1.25A (bulb 194)
WT/DIMS	.2 lb. / 2" x 2" x 1.75"
WARRANTY	Three Year Warranty

OVAL COURTESY LIGHTS

2407764B

2407765B

2407771C

04440013B

04440016B

- Semi-recessed with clear lens
- Hard wired, includes lead and ground

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
COURTESY LIGHTS			
04440016B	0440016P	Charcoal finish	100
2407771C	2407771CP	Black finish, chrome reflector	50
04440013B	04440013P	Medium saddle finish	50
2407764B	2407764P	White finish	100
2407765B	2407765P	Dream white finish	50

CERTIFICATION	CSA
MATERIALS	Plastic
VOLT/AMP	12.8VDC - .17A (bulb 161, wedge base)
WT/DIMS	.2 lb. / 4" x 2.625" x 1.25"
WARRANTY	Three Year Warranty

AURORA SERIES
Bullet Light

- Metal directional light with adjustable bracket and switch
- Surface mount with no exposed fasteners
- Hard wired, include lead and ground
- Bulb 922 wedge base incandescent

04010040B

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
BULLET LIGHTS			
04010040B	04010040P	Brushed nickel, black switch	30

CERTIFICATION	CSA
MATERIALS	Metal housing
VOLT/AMP	12.8VDC - 0.98A (bulb 922 wedge base)
WT/DIMS	.5 lb. / 2.75" x 3.75" x 4.625"
WARRANTY	Three Year Warranty

CO-PILOT LIGHTS
Halogen and Incandescent

- Map lights for sidewalls, drink trays and dashboards
- Switch is incorporated into light design
- Flexible 18" arm

03001175B

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
CO-PILOT LIGHTS			
03001175B	03001175P	Halogen (5W bulb/0.35A)	10

CERTIFICATION	UL
MATERIALS	Metal, black finish
VOLT	12.8VDC
WT/DIMS	.6 lb. / 18"
WARRANTY	Three Year Warranty

GALAXY LED SERIES

LED Directional Lights

- Recess mount lights with swivel globes and switches
- Removable snap-on trim ring, sold separately
- Hard wired, includes lead and ground

240047171LB & 24004TR71

240147171LB & 24014TR71

LED LIFETIME WARRANTY
NO BULBS TO REPLACE, EVER!

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
LED DIRECTIONAL LIGHTS			
240047171LB	-	LED Single fixture	50
240147171LB	-	LED Double fixture	20
24004TR71	24004TR71P	Trim ring for single fixture, black	50
24014TR71	24014TR71P	Trim ring for double fixture, black	50

CERTIFICATION	CSA	
MATERIALS	Plastic	
VOLT/AMP	Single:	12.8VDC - 0.020A
	Double:	12.8VDC - 0.054A
WT/DIMS	Single:	.15 lb. / 3.5” x 4.875” x 1.75”
	Double:	.31 lb. / 3.5” x 9.625” x 1.75”
WARRANTY	Lifetime LED Warranty	

GALAXY SERIES

Directional Lights

- Recess mount lights with swivel globes and switches
- Removable snap-on trim ring, sold separately
- Hard wired, includes lead and ground

240047171B & 24004TR71

240147171B & 24014TR71

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
DIRECTIONAL LIGHTS			
240047171B	240047171P	Single fixture	50
240147171B	240147171P	Double fixture	20
24004002B	24004002BP	Single fixture with reflector & 5W bulb	50
06001022B	06001022P	Single fixture with reflector	50
24004TR71	24004TR71P	Trim ring for single fixture, black	50
24014TR71	24014TR71P	Trim ring for double fixture, black	50

CERTIFICATION	CSA	
MATERIALS	Plastic	
VOLT/AMP	Single:	12.8VDC - 0.35A (bulb 168 wedge base)
	Double:	12.8VDC - 0.70A (bulb 168 wedge base)
WT/DIMS	Single:	.24 lb. / 3.5” x 4.875” x 1.75”
	Double:	.47 lb. / 3.5” x 9.625” x 1.75”
WARRANTY	Three Year Warranty	

UNITEK LED SERIES
LED Directional Lights

- Recess mount LED fixtures with multi-locking pivoting globes that activate lights
- Removable snap-on trim ring, sold separately
- Three-terminal hook-up for dome light application

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
LED DIRECTIONAL LIGHTS			
825LED	825LEDP	Single fixture, 9 diodes, black	50
826LED	826LEDP	Double fixture, 18 diodes, black	50
825TR02	825TR02P	Single trim ring, black	50
826TR02	826TR02P	Double trim ring, black	75
826TR12	826TR12P	Double trim ring, light gray	25
826TR90	826TR90P	Double trim ring, platinum silver	25

CERTIFICATION	UL
MATERIALS	Plastic
VOLT/AMP	12.8VDC - Single 0.35A , Double 0.70A
WT/DIMS	Single: .25 lb. / 4.125" x 3.5" x 1.5"
	Double: .48 lb. / 7" x 3.875" x 1.375"
WARRANTY	Lifetime LED Warranty

825LED & 825TR02

826LED & 826TR02

LED LIFETIME WARRANTY
NO BULBS TO REPLACE, EVER!

UNITEK SERIES
Directional Light

- Recess mount fixture with multi-locking pivoting globes that activate lights
- Removable lenses allow easy bulb replacement
- Removable snap-on trim ring, sold separately
- Three-terminal hook-up for dome light application

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
DIRECTIONAL LIGHT			
826L	826LP	Double fixture, black	48
See complete listing of trim rings above			

CERTIFICATION	UL
MATERIALS	Plastic
VOLT/AMP	12.8VDC 0.70A (bulb 168 wedge base)
WT/DIMS	.48 lb. / 7" x 3.875" x 1.375"
WARRANTY	Three Year Warranty

826L & 826TR02

ULTRATEK SERIES
Directional Lights

06001013B & 3802071BZL

06001014B & 3801071BZL

- Flush mount fixtures with pivoting globes that activate lights
- Removable snap-on trim ring, sold separately
- Removable lens for easy bulb replacement
- Three-terminal hook-up for dome light application

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
DIRECTIONAL LIGHTS			
06001013B	06001013P	Single fixture, black	120
06001014B	06001014P	Double fixture, black	120
3802071BZL	3802071BZLP	Single trim ring, black	30
3801071BZL	3801071BZLP	Double trim ring, black	30

CERTIFICATION	CSA / NRTL/C / ANSI/UL	
MATERIALS	Plastic	
VOLT/AMP	Single:	12.8VDC - 0.37A (bulb 590 xenon 4cp)
	Double:	12.8VDC - 0.74A (bulb 590 xenon 4cp)
WT/DIMS	Single:	.27 lb. / 3.75" x 3.5" x 1.5"
	Double:	.40 lb. / 5.875" x 3.5" x 1.5"
WARRANTY	Three Year Warranty	

AUTOTEK SERIES
Directional Lights

725022B

726022B

- Low profile aircraft-style lights with switch
- Removable grids allow easy bulb replacement
- Snap-on trim ring covers mounting screws
- Three-terminal hook-up for dome light application

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
DIRECTIONAL LIGHTS			
725022B	725022P	Single fixture, black	25
726022B	726022P	Double fixture, black	20

CERTIFICATION	CSA / UL	
MATERIALS	Plastic	
VOLT/AMP	Single:	12.8VDC - 0.69A (bulb 906 T5 wedge base)
	Double:	12.8VDC - 1.38A (bulb 906 T5 wedge base)
WT/DIMS	Single:	.32 lb. / 4.625" x 3.5" x 2.25"
	Double:	.52 lb. / 7.625" x 3.5" x 2.25"
WARRANTY	Three Year Warranty	

EUROPA SERIES
Directional Lights

- Choose from single recess mount and single/double surface mount series with on/off switches
- Prismatic reflector globes for bright directional beams
- Easy bulb replacement (168 wedge base)

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
RECESS MOUNT			
06001072B	06001072P	Single fixture, black	20
SURFACE MOUNT			
06001026B	06001026P	Single fixture, black	20
06001015B	06001015P	Double fixture, black	20
06001061B	06001061P	Double fixture plus dome light, black	20

CERTIFICATION	UL / CSA	
MATERIALS	Plastic	
VOLT/AMP	Single:	12.8VDC - 0.35A (bulb 168 wedge base)
	Double:	12.8VDC - 0.70A (bulb 168 wedge base)
WT/DIMS	06001072B/P:	.18 lb. / 4.5" x 3.75" x 1.75"
	06001026B/P:	.16 lb. / 4.125" x 2.937" x 1.625"
	06001015B/P:	.28 lb. / 2.75" x 6.25" x 1.75"
	06001061B/P:	.46 lb. / 8.375" x 2.75" x 1.75"
WARRANTY	Three Year Warranty	

06001072B

06001026B
06001015B
06001061B

EUROPA SERIES
Ultrabright Directional Lights

- High output for bright, directional reading light
- Easy bulb replacement (1003 bayonet base)
- Separate switches for each bulb

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
ULTRA BRIGHT SURFACE MOUNT			
06001048B	06001048P	Single fixture, black	20
06001037B	06001037P	Double fixture, black	20

CERTIFICATION	UL	
MATERIALS	Plastic	
VOLT/AMP	Single:	12.8VDC - 0.94A (bulb 1003 bayonet base)
	Double:	12.8VDC - 0.94A (bulb 1003 bayonet base)
WT/DIMS	Single:	.25 lb. / 4" x 2.875" x 2.5"
	Double:	.47 lb. / 6.125" x 2.75" x 2.625"
WARRANTY	Three Year Warranty	

06001048B

06001037B

ODYSSEY SERIES
Directional Light

0601B & 060102B

- Recess mount light with press on/off feature at lens
- Removable snap-on trim ring, sold separately
- Hard wired, includes lead and ground

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
DIRECTIONAL LIGHTS			
0601B	0601P	Light, black	200
060102B	060102P	Trim ring, black	50

CERTIFICATION	CSA / NRTL/C / ANSI/UL
MATERIALS	Plastic
VOLT	12.8VDC - 0.94A (bulb 906 T5 wedge base)
WT/DIMS	.26 lb. / 3.125" x 5" x 2"
WARRANTY	Three Year Warranty

STARGAZER SERIES
Directional Lights

06001001B & 06300004B

- Recess mount fixtures with multi-locking, pivoting globes that activate lights
- Removable snap-on trim ring, sold separately
- Removable lens for easy bulb replacement
- Three-terminal hook-up for dome light application

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
DIRECTIONAL LIGHTS			
06001001B	06001001P	Single fixture, black	50
06300004B	-	Single trim ring, black	50

CERTIFICATION	CSA / NRTL/C / ANSI/UL
MATERIALS	Plastic
VOLT/AMP	12.8VDC - 0.35A (bulb 168 wedge base)
WT/DIMS	.25 lb. / 3.375" x 4" x 1.5"
WARRANTY	Three Year Warranty

CENTURA SERIES

- Simple design with aluminum base, acrylic lens and single or dual switch
- Slim design: only 2.5” wide and 1.13” thick
- Available in 5.5” and 12.5” lengths

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
SURFACE MOUNT			
105500SP	-	Single bulb, 5.5”	50
105520B	105520BP	Triple bulb, 12.5”	25

MATERIALS	Aluminum base, acrylic lens	
VOLT/AMP	5.5”:	12.8VDC - 0.97A (bulb 211)
	12.5”:	12.8VDC - 2.91A (bulb 211-2)
WT/DIMS	5.5”:	.20 lb. / 5.75” x 2.5” x 1.25”
	12.5”:	.44 lb. / 12.75” x 2.5” x 1.25”
WARRANTY	Three Year Warranty	

105500SP

105520B

SLIMLINE SERIES

- Contemporary design with switch
- Low profile: 4” wide and only 1.5” thick
- Available in two lengths

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
SURFACE MOUNT			
18543910B	-	Single bulb, 4”, no switch, white	25
18543916B	18543916BP	Single bulb, 5.5”, switch, white	100

MATERIALS	Plastic	
VOLT/AMP	12.8VDC - 1.0A (bulb 912)	
WT/DIMS	4”:	.4 lb. / 4” x 4” x 1.5”
	5.5”:	.6 lb. / 5.5” x 4” x 1.5”
WARRANTY	Three Year Warranty	

18543910B

18543916B

24113160B DOME LIGHT

24113160B

- Halogen dome light with switch for general illumination
- Designed for overhead or bulkhead surface mount
- White plastic construction with frosted lens

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
DOME LIGHT			
24113160B	24113160P	5.75" white dome light	30

CERTIFICATION	NRTL/C
MATERIALS	Plastic
VOLT/AMP	12.8VDC - 0.78A (bulb G4 bi-pin)
WT/DIMS	.4 lb. / 5.75" x 5.75" x 1.5"
WARRANTY	Three Year Warranty

357B DOME LIGHT

357B

- 8.5" semi-recess mount light with one halogen and one incandescent bulb
- Chrome plated housing, Lexan lens, replaceable bulbs

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
DOME LIGHT			
357B	357P	Dome light, chrome-plated	40

MATERIALS	Metal housing, Lexan lens
VOLT/AMP	12.8VDC - 2.79A (GH9 37.5W), 0.68A (906 T5 wedge)
WT/DIMS	1.25 lbs. / 8.75" x 8.75" x 1.875"
WARRANTY	Three Year Warranty

800-364-5483 / 918-683-9514

69000201B DOME LIGHT

- 6-3/8” surface mount light with gray base
- Two-wire, replaceable 1142 bulb

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		DOME LIGHT	
69000201B	69000201P	Dome light, gray base	40

VOLT/AMP	12.8VDC - 1.44A (bulb 1142)
WT/DIMS	.75 lb. /6.25” x 6.25” x 2”
WARRANTY	Three Year Warranty

69000201B

69000300B DOME LIGHT

- 5-3/4” surface mount light with red and white bulbs
- Dual switch, frosted lens, white housing

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		DOME LIGHT	
69000300B	69000300P	Dome light, red/white bulbs	20

VOLT/AMP	12.8VDC - 1.00A (bulb 912)
WT/DIMS	.48 lb. / 5.75” x 5.75” x 1.5”
WARRANTY	Three Year Warranty

69000300B

193 SERIES DOME LIGHTS

- Semi-recessed design with domed clear lens
- Replaceable bulb (1003 bayonet)

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		DOME LIGHT	
193BSP	193BSPP	Dome light, black	10
193G	193P	Dome light, gray	10

MATERIALS	Steel housing, polycarbonate lens
VOLT/AMP	12.8VDC - 0.94A (bulb 1003 bayonet)
WT/DIMS	.25 lb. / 5.75” x 2.688” x 1.5”
WARRANTY	Three Year Warranty

193BSP

193G

RV MOUNTING ACCESSORIES

RV60BK



RV60BBK

- Wedge base mounting bezels for RV combination tail lights
- Constructed of heavy duty, corrosion proof plastic for durability

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
MOUNTING BASES			
RV60BK	RV60BKP	Wedge base mounting bezel, white RVST60/61, RVSTL60/61, RVSTL0060/0061	100
RV60BBK	RV60BBKP	Wedge base mounting bezel, black RVSTB60/61, RVSTLB60/61, RVSTLB0060/0061	100

MATERIALS	Plastic
WT/DIMS	8.563” x 3.125” x 1.125”
WARRANTY	Three Year Warranty

WALL PLATES

13000018B

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
WALL PLATES / ACCESSORIES			
13000018B	13000018P	Standard 12V outlet, plastic	20
014BCRCW	014BCRCWP	Chrome 12V receptacle with cap	100
7850NFRC	7850NFRCP	Chrome 12V receptacle with cap & wires	250
RC	RCP	Rubber cap for 12V outlet	500

800-364-5483 / 918-683-9514

DOOR PULLS & SPRING LOADED HANDLES

- 11” door pulls with hinged end caps for easy installation
- Include steel reinforced mounting bases
- Spring loaded handle, may also be used as a clothes hanger; choose from three colors

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
DOOR PULLS			
01180071B	01180071P	Black	25
01180089B	01180089P	Fawn	25
01180090B	01180090BP	Platinum silver	25
SPRING LOADED HANDLES			
2500128B	2500128P	GM pewter	50
2500171B	2500171P	Black	50
2500189B	2500189P	Fawn	50

MATERIALS	Pulls: ABS, Handles: Steel base, ABS handle
WT/DIMS	Pulls: .31 lb. / 8.75” x 1.125” x 3”
	Handles: .18 lb. / 11” x 1.75” x 1”
WARRANTY	Three Year Warranty

01180071B
01180089B
01180090B



2500128B



2500171B



2500189B

ASH TRAYS

530002B

500302B

510001B

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
ASH TRAYS			
510001B	510001P	Drop-in ashtray	50
530002B	530002P	Round drop-in ashtray	40
500302B	500302P	Black lighter	25

BEVERAGE HOLDERS

09017101B

302B

3202B

1502B

- Versatile beverage holder for cups, cans and mugs
- Two-tier design includes a handle recess for cups and mugs, and rubber flaps to secure cans and smaller cups
- Black finish on all

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
CUP HOLDERS			
09017101B	09017101P	Dual purpose drop-in, handle cavity	50
3202B	3202P	3” two-tier drop-in	50
302B	302P	3” single tier drop-in	50
1502B	1502P	1.5” single tier drop-in	50
15202B	15202P	1.5” two-tier drop-in	50
2409171B	2409171BP	Adjustable, fold-down	100

REPLACEMENT BULBS RV LIGHTING

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
BULBS			
30000000B	-	12” fluorescent, cool white	1
30031010B	-	18” fluorescent, cool white, Philips	24
30655010B	-	10W halogen	1

RECTANGULAR REFLECTORS

- Select from multiple shapes, sizes and mounting methods; available in bulk, polypack and retail clams
- Acrylic construction; meet FMVSS “A” for reflex when properly applied

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		REFLECTORS	
RE10AB	RE10ABP	Rectangular, yellow, self adhesive	100
RE10RB	RE10RBP	Rectangular, red, self adhesive	100
RE11AB	RE11ABP	Oblong, yellow, self adhesive/screw mount	100
RE11RB	RE11RBP	Oblong, red, self adhesive/screw mount	100
RE15AB	RE15ABP	Thinline, yellow, adhesive/screw mount	100
RE15RB	RE15RBP	Thinline, red, adhesive/screw mount	100
RE52AB	RE52ABP	Rectangular, yellow, self adhesive	50
RE52RB	RE52RBP	Rectangular, red, self adhesive	50
		RETAIL - CLAM	
RE10AK		Rectangular, yellow, self adhesive	12
RE10RK	Retail Ready	Rectangular, red, self adhesive	12
RE10ARFK		(2) each yellow and red RE10, adhesive	12
RE12AK		Oblong, yellow, self adhesive/screw mount	12
RE12RK		Oblong, red, self adhesive/screw mount	12
RE12ARK		(2) each yellow and red RE12	12
RE15AK		Thinline, yellow, adhesive/screw mount	12
RE15RK		Thinline, red, adhesive/screw mount	12
RE15ARK		Thinline, red & yellow, adhesive/screw mount	12
RE52ARK		(2) each yellow and red RE52	12

FMVSS	A
MATERIALS	Acrylic
WARRANTY	Three Year Warranty


RE10AB RE10RB




RE11AB

RE11RB




RE15AB

RE15RB




RE52ARK

4" W X 1.25" H X 0.75" D

ROUND & OVAL REFLECTORS



RE13AB RE13RB



- Select from multiple shapes, sizes and mounting methods; available in bulk, polypack and retail clams
- Acrylic construction; meet FMVSS “A” for reflex when properly applied



RE21AB RE21RB



RE31AS RE31RS



BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		REFLECTORS	
A11AXB	A11AXBP	Yellow reflector for 3/4” lights, self adhesive	100
A11RXB	A11RXBP	Red reflector for 3/4” lights, self adhesive	100
RE13AB	RE13ABP	3” round, yellow, center mount	50
RE13RB	RE13RBP	3” round, red, center mount	50
RE21AB	RE21ABP	3” round, yellow, self adhesive	50
RE21RB	RE21RBP	3” round, red, self adhesive	50
RE35AB	RE35ABP	2” round, yellow, center mount	100
RE35RB	RE35RBP	2” round, red, center mount	100
RE37AB	RE37ABP	2” round, yellow, self adhesive	100
RE37RB	RE37RBP	2” round, red, self adhesive	100
		RETAIL - CLAM	
RE21AS	Retail Ready	3” round, yellow, self adhesive	12
RE21RS		3” round, red, self adhesive	12
RE21ARK		3” round, red & yellow, self adhesive	12
RE31AS		3” armored aluminum, yellow, screw mount	12
RE31RS		3” armored aluminum, red, screw mount	12

FMVSS	A
MATERIALS	Acrylic
WARRANTY	Three Year Warranty



RE35AB RE35RB





RE37AB RE37RB





A11AXB / A11RXB



RT10 SERIES
Rectangular Adhesive Tape Reflectors

- Oralite® V32 SAE reflectors are SAE J578 and J594 compliant
- Designed for rugged outdoor use on the sides and rear of trucks, trailers and equipment
- Meet FMVSS “A” for reflex when properly applied
- Reflector dimensions 3.5” x 2”, supplied in rolls
- Select 100 or 500 reflectors per roll

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
SELF-ADHESIVE REFLECTORS			
RT10AB	-	Yellow 3.5”x2”, roll of 100	100
RT10A1B	-	Yellow 3.5”x2”, roll of 500	500
RT10RB	-	Red 3.5”x2”, roll of 100	100
RT10R1B	-	Red 3.5”x2”, roll of 500	500

FMVSS	A
MATERIAL	Polyester
WT/DIMS	.58 lbs / 167’ x 2.50”
WARRANTY	Seven Year Warranty

RT21 SERIES
Round Adhesive Tape Reflectors



- Oralite® V32 SAE reflectors are SAE J578 and J594 compliant
- Designed for rugged outdoor use on the sides and rear of trucks, trailers and equipment
- Meet FMVSS “A” for reflex when properly applied
- 3” diameter, supplied in 26-ft x 4-in rolls
- 100 reflectors per roll

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
SELF-ADHESIVE REFLECTORS - 7 YEAR			
RT21AB	-	Yellow 3” round	100
RT21RB	-	Red 3” round	100

FMVSS	A
MATERIAL	Polyester
WT/DIMS	.55 lbs / 26’ x 4”
WARRANTY	Seven Year Warranty

ORALITE®

VEHICLE CONSPICUITY TAPE



RTR150711B

RT150WBD

RE418T

RTR10150711CB

RTR10150WB

RTR03150711CB

- Alternating red/white pattern available in 11” red/7” white and 6” red/6” white patterns
- Solid white tape also available
- All tape is 2” wide, supplied in 150-ft rolls
- Choose from V92, V82 and V42 series tape
- Marked “DOT-C2” per NHTSA 9CFR571.108

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
V92 CONSPICUITY TAPE - 5 YEAR			
RTR15066B	RTR15066BP	6” red/6” white, continuous	1
RTR15066PB	RTR15066PBP	6” red/6” white, perforated	1
RTR150711B	RTR150711BP	11” red/7” white, continuous	1
RTR150711PB	RTR150711PBP	11” red/7” white, perforated	1
RE10018T	-	100 18” strips, 11” red/7” white	1
RT150W12B	RT150W12BP	Solid white, 12” sections on roll	1
RT150WBD	RT150WBDP	Solid white, continuous	1
RETAIL			
RE418T	Retail Ready	4-strip kit, 11” red/7” white	12
RE18T		8-strip kit, 11” red/7” white	12
RE2018T		20-strip kit, 11” red/7” white	5
RE21T		21-ft roll, 11” red/7” white	12

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
V82 CONSPICUITY TAPE - 10 YEAR			
RTR1015066CB	-	6” red/6” white, continuous	1
RTR10150711CB	-	11” red/7” white, continuous	1
RTR10150WB	-	Solid white, continuous	1

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
V42 CONSPICUITY TAPE - 3 YEAR			
RTR03150711CB	-	11” red/7” white, continuous	1
RTR0315066CB	-	6” red/6” white, continuous	1

FMVSS	DOT-C2	
WARRANTY	V92:	Five Year Warranty
	V82:	Ten Year Warranty
	V42:	Three Year Warranty

SCHOOL BUS CONSPICUITY TAPE

ORALITE®

- Yellow tape available in 1” and 2” widths
- All tape is supplied in 150-ft rolls
- Choose from V99 and V82 series tape
- Meets ASTM D4956-05 (Type V), FMVSS 131 & 217, CSA D250 requirements



BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
V99 CONSPICUITY TAPE - 5 YEAR			
RT150Y1DB	RT150Y1DBP	1” yellow, diamond pattern	1
RT150Y2DB	RT150Y2DBP	2” yellow, diamond pattern	1

V82 CONSPICUITY TAPE - 10 YEAR		
RT150Y1B	RT150Y1BP	1” yellow	1
RT150Y2B	RT150Y2BP	2” yellow	1



FMVSS	ASTM D4956-05 (Type V), FMVSS 131 & 217, CSA D250	
WARRANTY	V99:	Five Year Warranty
	V82:	Ten Year Warranty

VEHICLE CONSPICUITY TAPE

ORALITE®

- Conformable sheeting for emergency vehicles
- Supplied in 6” wide, 150-ft rolls
- Choose from fluorescent lime, red and orange (other colors available upon request)
- Use red/lime sheeting to meet fire apparatus regulation NFPA 1901



BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
V98 CONFORMABLE SHEETING			
RTRE150RB	RTRE150RBP	6” red, diamond pattern	1
RTRE150GB	RTRE150GBP	6” lime, diamond pattern	1
RTRE150OB	RTRE150OBP	6” orange, diamond pattern	1

FMVSS	NFPA 1901	
WARRANTY	Red/Orange:	Five Year Warranty
	Lime:	Three Year Warranty

HARNESS PROTECTORS

Trailer Harness Plug Protectors

ACP5B

ACP7B



- Secure and protect trailer harness plugs from damage, corrosion and debris
- Helps maintain electrical system reliability
- Easy, surface mount installation
- Corrosion proof design

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
PLUG PROTECTORS			
ACP5B	ACP5BP	5-way flat harness plug protector	50
ACP7B	ACP7BP	7-way round harness plug protector	64
RETAIL			
ACP5S	Retail Ready	4-way & 5-way flat plug protector, clam	10
ACP7S		7-way round plug protector, clam	5

MATERIAL	PVC
WT/DIMS	ACP5B: .025 lbs 1.48” x 1.24” x .45”
	ACP7B .162 lbs 3.17” x 2.93 ”x 2.2”
WARRANTY	Three Year Warranty



3/4" GROMMETS & BRACKETS

Grommets and Brackets for 3/4" Round Sealed Lights

- PVC grommets for flush mount of 3/4" round lights
- Snap-in mounting flange for secure installation
- Stainless steel trim ring covers grommet
- License plate light brackets for use with LPL12CB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
GROMMETS & BRACKETS			
A10BB	A10BBP	Surface mount base, black	100
A10GB	A10GBP	Sealing grommet	100
A11GB	A11GBP	Standard grommet	100
A11G1B	A11G1BP	Grommet, EPDM, 45-55 durometer	100
A11GSDB	A11GSDBP	Grommet, softer durometer	100
A11DB	A11DBP	Adaptor cover 2" and 2.5" holes, accepts 3/4" lights	50
A12GB	A12GBP	Sealing grommet, for material thickness .070-.125"	100
A14GB	A14GBP	Sealing grommet, for material thickness .1250-.250"	100
A11PB	A11PBP	Snap-in mounting flange	100
REFLECTORS/TRIM RINGS			
A11AXB	A11AXBP	Yellow reflector, self adhesive	100
A11RXB	A11RXBP	Red reflector, self adhesive	100
A11SSB	A11SSBP	Stainless steel trim ring	120
A11CRB	A11CRBP	Chrome finish cover	120
LICENSE PLATE LIGHT BRACKETS/ACCESSORIES			
A11GLPB	A11GLPBP	License light bracket, gray	50
A11BLPB	A11BLPBP	License light bracket, black	50
A12B2LPB	A12B2LPBP	Vertical license light bracket	50
A12GLPB	A12GLPBP	Grommet for A12B2LPB bracket	50

P/N	MATERIALS	WT/DIMS
A10BB	ABS	.05 lb. / 3.25" x 1.063" x .938"
A10GB	PVC	.01 lb. / 1.313" x 1.313" x .875"
A11GB	PVC	.05 lb. / 1.083" x 1.083" x.456"
A11G1B	EPDM	.05 lb. / 1.083" x 1.083" x.456"
A11GSDB	PVC	.05 lb. / 1.083" x 1.083" x.456"
A11DB	ABS	.038 lb. / 3.563" x 3.563" x .375"
A12GB	PVC	.05 lb. / 1.094" x 1.094" x .465"
A14GB	PVC	.05 lb. / 1.094" x 1.094" x .465"
A11PB	Polycarbonate	.05 lb. / 1.156" x 1.156" x 0.75"
A11SSB	Stainless steel	.05 lb. / 1.313" x 1.313" x 0.125"
A11CRB	Chrome	.01 lb. / 1.1" x 1.1" x 0.1"
A11GLPB/BLPB	Polycarbonate	.08 lb. / 2.25" x 1.375" x 0.625"
A12GLPB	PVC	.12 lb. / 3.438" x 2.688" x 2.313"
A11AXB/RXB	Acrylic	.05 lb. / 4" x 1.5" x.188"

A10BB

A10GB

A11GB
A12GB
A14GB

A11DB

A11PB

A11SSB



A11GLPB

A12B2LPB bracket shown with light and A12GLPB grommet

2" GROMMETS & ACCESSORIES

Grommets, Mounting Brackets and Trim Rings for 2" Round Lights

A53GB



- PVC grommet for flush mount of 2" round lights provides shock mount to lengthen bulb life
- Choice of two surface mount brackets
- Trim rings for grommet or flange mount lights, screw mount

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
MOUNTING ACCESSORIES			
A53GB	A53GBP	Extra-flex flush mount grommet	100
A54GB	A54GBP	Flush mount grommet	100
A54GK	A54GKP	Kit: A54GB & A46PB PL-10 plug	100
A2CBGB	A2CBGBP	Closed back grommet	50
BK5557GB	BK5557GBP	Cam-on mounting bracket	50
A55CB	A55CBP	Chrome trim ring, grommet mount	20
A3TRSSB	A3TRSSBP	Stainless steel trim ring, flange mount	100
BK53BB	BK53BBP	Branch deflector bracket, gray	50
WIRING ACCESSORIES			
A46PB	A46PBP	Two-pin plug with 6" lead, #10 terminal on ground	50

A54GB



HOLE CUT-OUT: 2.313"

P/N	MATERIALS	WT/DIMS
A53GB	PVC	.05 lb. / 3" x 3" x 1"
A54GB	PVC	.05 lb. / 2.625" x 2.625" x 0.75"
BK5557GB	ABS	.05 lb. / 4" x 2.125" x 1"
A55CB	ABS	.05 lb. / 3.25" x 3.25" x 0.438"
A3TRSSB	Stainless steel	.05 lb. / 3.063" x 3.063" x 0.125"
BK53BB	ABS	.05 lb. / 5.375" x 2.75"

A55CB



A3TRSSB



BK5557GB





BK53BB



2.5” GROMMETS

Mounting Grommets for 2.5” Round Sealed Lights

- PVC grommets for flush mount of 2.5” round lights
- Grommet provides shock mount to lengthen bulb life

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
MOUNTING ACCESSORIES			
A55GB	A55GBP	Open back, flush mount, black	50
A55GK	A55GKP	Kit: A55GB & A46PB PL-10 plug	100
A56GB	A56GBP	Closed back, recess mount, black	100
A57GB	A57GBP	Open back, recess mount, black	50
A57GK	A57GKP	Kit: A57GB & A46PB PL-10 plug	100
A58GB	A58GBP	Angled grommet, black	100
WIRING ACCESSORIES			
A46PB	A46PBP	PL-10 plug with 6” lead, #10 terminal on ground	100

P/N	MATERIALS	WT/DIMS
A55GB/GWB	PVC	.132 lb. / 3.5” x 3.5” x .938”
A56GB	PVC	.132 lb. / 3.25” x 3.25” x 1.125”
A57GB	PVC	.11 lb. / 3.25” x 3.25” x 1.125”
A58GB	PVC	.132 lb. / 3.438” x 3.438” x 0.875”

A55GB



HOLE CUT-OUT: 3”

A56GB



HOLE CUT-OUT: 2.75”

A57GB



HOLE CUT-OUT: 2.75”

A58GB



HOLE CUT-OUT: 2.75”

2.5" BRACKETS & TRIM RINGS

Mounting Brackets and Ornamental Trim Rings for 2.5" Round Sealed Lights

- Choice of three brackets for surface mount of 2.5" round sealed lights
- Trim rings for grommet or flange mount lights, screw mount

BK55BB



BK57BB



BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
MOUNTING ACCESSORIES			
BK55BB	BK55BBP	Black steel bracket for use with grommet; no cut-out in trailer frame required	20
BK57BB	BK57BBP	Surface mount branch deflector bracket, gray plastic	50
BK5557GB	BK5557GBP	Cam-on mounting bracket with built-in branch deflector, suitable for use with PC rated lights	50
A25TRSSB	A25TRSSBP	Stainless steel trim ring, flange mount	50
A57CB	A57CBP	Chrome trim ring, grommet mount	20

P/N	MATERIALS	WT/DIMS
BK55BB	Steel	.375 lb. / 4" x 4.75" x 1.75"
BK57BB	Polycarbonate	.066 lb. / 5.688" x 3.125" x 0.938"
BK5557GB	Plastic	.066 lb. / 4" x 2.125" x 1"
A25TRSSB	Stainless steel	.04 lb. / 3.5" x 3.5" x 0.125"
A57CB	Plastic	.11 lb. / 4" x 4" x 0.415"

A25TRSSB

A57CB



BK5557GB







4" ROUND GROMMETS and BRACKETS

Mounting Grommets & Brackets for Sealed 4" Round Lights

- PVC grommets for flush mount of 45 series lights; grommet provides shock mount to lengthen life of light
- Mounting flanges for flush mount of 45 series lights; lights snap into flange
- Steel bracket mounts to trailer frame; no panel cutout required. Use with A45GB grommet. Durable powder coated finish.

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		GROMMETS	
A45GB	A45GBP	PVC grommet, flush mount	50
A46GB	A46GBP	Extra-flex PVC grommet, flush mount	50
		BRACKETS	
A45BB	A45BBP	Black plastic mounting flange	100
A45SB	A45SBP	Stainless steel mounting flange	20
BK45BB	BK45BBP	Steel mounting bracket, powder coated	10

P/N	MATERIALS	WT/DIMS
A45GB	PVC	.176 lb. / 5.375" x 5.375" x 1.063"
A45BB	Plastic	.11 lb. / 5.5" x 5.5" x 1"
A45SB	Stainless steel	.19 lb. / 5.563" x 5.563" x 0.75"
A46GB	PVC	.05 lb. / 5.625" x 5.625" x 1.063"
BK45BB	Steel	.794 lb. / 6" x 5.813" x 1.375"

A45GB



A45SB



BK45BB



A46GB



HOLE CUT-OUT: 4.5"

A45BB



4" ROUND TRIM RINGS

Trim Rings for Sealed 4" Round Lights

A5TRSSB



- Stainless steel models fit flange mount lights
- Chrome-plated plastic model fits grommet mount lights
- Trim rings mount using screws

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
TRIM RINGS			
A5TRSSB	A5TRSSBP	Stainless steel trim ring for flange mount lights	100
A45CGB	A45CGBP	Chrome-plated plastic trim ring for grommet mount lights	20
A101TRSSB	A101TRSSBP	Stainless steel trim ring for STL/ BUL101 flange mount lights	50

A45CGB



P/N	MATERIALS	WT/DIMS
A5TRSSB	Stainless steel	.132 lb. / 5.625" x 5.625" x 0.188"
A45CGB	Plastic	.132 lb. / 5.813" x 5.813" x 0.5"
A101TRSSB	Stainless steel	.132 lb. / 5.625" x 5.625" x 0.188"

A101TRSSB



6" OVAL GROMMETS/BRACKETS

Mounting Grommets & Brackets for Sealed 6" Oval Lights

A70GB



HOLE CUT-OUT: 6.85" x 2.5" (1.25" R)

- PVC grommets for flush mount of 70 series lights; grommet provides shock mount to lengthen life of light
- Steel brackets mount to trailer frame; no panel cutout required. Use with A70GB grommet or recess flange mount lights.

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		GROMMETS	
A60GB	A60GBP	PVC grommet	50
A70GB	A70GBP	PVC grommet, flush mount	50
A70GBD	A70GBDP	PVC grommet	50
A80GB	A80GBP	PVC grommet, flush mount	50
		BRACKETS	
A77S1B	A77S1BP	Steel mounting bracket, gray	50
BK70BB	BK70BBP	Steel mounting bracket, powder coated	10
BK70B	BK70BP	Steel mounting bracket, no coating	10

BK70BB



P/N	MATERIALS	WT/DIMS
A60GB	PVC	.132 lb. / 7.625"x3.375"x1.125"
A70GB	PVC	.132 lb. / 7.625" x 3.375" x 1.125"
A80GB	PVC	.132 lb. / 7.625"x3.375"x1.125"
A77S1B	Steel	.132 lb. / 8.25" x 5.75" x 1.375"
BK70BB	Steel	.728 lb. / 8.25" x 4" x 1.625"
BK70B	Steel	1 lb. / 8.25" x 4" x 1.625"

A77S1B



6" OVAL FLANGE COVERS

Trim Rings for 6" Oval Sealed Flange Mount Lights



A7TRSSB



- Choose from stainless steel, chrome-plated plastic and red reflex models
- A7TRSSB mounts to STL75AMFB flange using screws
- A78CB1 and A78RXB snap onto flange/surface mount lights
- A78RXB fulfills rear reflex function, eliminating the need for a separate reflector

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
FLANGE COVERS			
A7TRSSB	A7TRSSBP	Stainless steel, screw mount (STL75AMFB)	100
A78CB1	A78CB1P	Chrome-plated plastic, snap-on	25
A78RXB	A78RXBP	Red reflex, snap-on	25
A78NCCB	A7NNBP	Paintable trim ring, snap-on	50
A78NCCBB	A7NCCBBP	Black trim ring, snap-on	50
A111TRSSB	A111TRSSBP	Stainless steel screw mount trim ring for STL/BUL111 flange mount lights	50
A178TRSSB	A178TRSSBP	Stainless steel screw mount trim ring for STL178 flange mount lights	50
A211CB1	A211CB1P	Chrome bezel, snap-on	25
A211NCCB	A211NCCBP	Paintable trim ring, snap-on	50
A211RXB	A211RXBP	Red reflex flange ring	25

A78CB1



P/N	MATERIALS	WT/DIMS
A7TRSSB	Stainless steel	.066 lb. / 8" x 3.438" x 0.188"
A78CB1	ABS Plastic	.066 lb. / 7.875" x 3.625" x 0.5"
A78RXB	Acrylic	.066 lb. / 7.875" x 3.625" x 0.391"
A78NCCB	Plastic	.100 lb. / 7.875" x 3.625" x 0.5"
A78NCCBB	Plastic	.100 lb. / 7.875" x 3.625" x 0.5"
A111TRSSB	Stainless steel	.066 lb. / 7.625" x 3.25" x 0.25"
A178TRSSB	Stainless steel	.066 lb. / 7.563" x 3.313" x 0.188"
A211CB1	Plastic	.066 lb. / 7.5" x 3.25" x .5"
A211NCCB	Plastic	.100 lb. / 7.875" x 3.625" x 0.5"
A211RXB	Plastic	.066 lb. / 7.875" x 3.625" x 0.5"

A78RXB



A111TRSSB



A178TRSSB



91 SERIES GROMMETS

Mounting Grommets for A91, AL90, AL191 and AL91 Series Lights

- PVC grommets for flush mount of 90/91 series lights
- A91G15B1 allows light to be mounted at 15 degrees

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		GROMMETS	
A91GB	A91GBP	Black grommet, flush mount	100
A91GOB	A91GOBP	Black open back grommet	100
A91G15B1	A91G15B1P	Black 15 degree angled grommet	100
A91GZB	-	Black vertical mount grommet	50
		WIRING ACCESSORIES	
A46PB	A46PBP	Two-wire plug, standard PL-10 connector	100

P/N	MATERIALS	WT/DIMS
A91GB/GOB	PVC	.066 lb. / 3.313" x 1.938" x 0.5"
A91G15B1	PVC	.066 lb. / 3.313" x 1.938" x 1.313"



A91GB



A91GB



A91G15B1



91 SERIES BRACKETS

Mounting Brackets for A91, AL90, AL191 and AL91 Series Lights

- Corrosion proof brackets for surface mount of 90/91 series lights
- Self grounding bases ground through mounting hardware and should be used with A91LW plug
- Open back bases should be used with A46PB two-wire plug

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		SURFACE MOUNT BRACKETS	
A91BB	A91BBP	Black base, self grounding	100
A91BS	–	A91BB, retail clam	12
A91BOB	A91BOBP	Black base, open back	100
A91CB	A91CBP	Chrome base, self grounding	100
A91OB	A91OBP	Chrome base, open back	100
A90CB	A90CBP	Chrome cover, snap-on	50
		WIRING ACCESSORIES	
A91LW	A91LWP	Single wire plug, molded male bullet	100
A46PB	A46PBP	Two-wire plug, standard PL-10 connector	100

P/N	MATERIALS
All Brackets	Plastic

A91CB



A91BB/CB

A91BOB



A91BOB/OB

MOUNTING & WIRING ACCESSORIES

MC65/A67 SERIES BRACKETS

Mounting Brackets for MCL61 & MC/MCL65 Series Lights

A65B



A65PB

A67BB

- Corrosion proof brackets for surface mount of 61/65 series lights
- Single wire design grounds through mounting hardware
- Two-wire design includes both lead and ground wires
- A67BB bracket for use in exterior (top) fender applications with MC65ARB, MCL61ARB and MCL65ARB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
SURFACE MOUNT BRACKETS			
A65B	A65BP	Black bracket only	50
A65PB	A65PBP	Kit: A65B & A65P single wire plug	50
A65PS	-	A65PB, retail clam	12
A65PBPG	A65PBPGP	Kit: A65B & A65P single wire plug with .180 molded male bullet	50
A65TB	A65TBP	Black bracket only, thick base	50
A66PB	A66PBP	Kit: Gray bracket & A65P single wire plug	50
A67CB	A67CBP	Kit: Chrome bracket & A65P, 12" lead	50
A67CBPG	A67CBPGP	Kit: Chrome bracket & single wire plug with .180 molded male bullet, 18" lead	50
A67P10G	A67P10GP	Kit: Chrome bracket & single wire plug with .180 molded male bullet, 10" lead	100
A68PB	A68PBP	Kit: A65B & A68P two-wire plug	50
A68P1B	A68P1BP	Kit: Tall bracket, black, with A68P two-wire plug	50
A65PRXB	A65PRXBP	Kit: Black bracket with red reflector installed & single wire plug	50
SURFACE MOUNT FENDER BRACKETS			
A67BB	A67BBP	Black fender bracket with self grounding, single wire plug	50
WIRING ACCESSORIES			
A65P	A65PP	One-wire plug, grounds through mounting hardware	50
A68P	A68PP	Two-wire plug, includes lead and ground	50



A68P1B

P/N	MATERIALS
All brackets	Plastic

LICENSE LIGHT BRACKETS

LP25SB surface mount bracket accepts LP91 and LPL91 series lights; mounting gasket sold separately

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
LICENSE LIGHT BRACKETS			
LP25SB	LP25SBP	Black bracket for LP/LPL91 lights	100
LP25SGGB	LP25SGGBP	Grey bracket for LP/LPL91 lights	100
A25GB	A25GBP	Gasket for LP25SB	100

P/N	MATERIALS	WT/DIMS
LP25SB/GGB	Polycarbonate	.066 lb. / 3.438" x 2.688" x 2.313"
A25GB		.010 lb. / 3.438" x 1.9" x 0.70"

LP25SB

LP25SGGB



A25GB

LICENSE PLATE BRACKETS

- Select from heavy duty metal and corrosion proof plastic
- Accept stud mount license plate lights
- LP35BB license plate holder is design for mounting on flat surfaces

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		BRACKETS	
LP5SB	LP5SBP	Black heavy duty plastic	100
LP10SB	LP10SBP	Black heavy duty plastic	50
LP15SB	LP15SBP	Zinc plated steel	12
LP20SB	LP20SBP	Powder coated steel	25
LP31SB	LP31SBP	Black heavy duty plastic for low temps	50
LP35BB	LP35BBP	Black license plate holder	25
BK31BB	BK31BBP	Black heavy duty plastic	50
		RETAIL	
LP10S	Retail Ready	Black heavy duty plastic, clam	12
LP15S		Zinc plated steel, clam	12

P/N	MATERIALS	WT/DIMS
LP5SB	Plastic	.17 lb. / 8.25" x 4.25" x .813"
LP10SB	Plastic	.17 lb. / 9.5" x 4.813"
LP15SB	Steel	.397 lb. / 8.438" x 3.625" x 1.5"
LP20SB	Steel	.132 lb. / 8.5" x 2.875"
LP31SB	Plastic - low temp	.17 lb. / 8.25" x 4.25" x .813"
LP35BB	Plastic	.122 lb. / 14.5" x 8.25"
BK31BB	Plastic	.17 lb. / 8.25" x 4.25" x .813"

LP5SB



LP10SB



BK31BB
LP31SB



LP15SB



LP20SB





LP35BB

MOUNTING ACCESSORIES

Trim Rings and Bezels

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
TRIM RINGS/BEZELS			
00212317B	00212327P	M1 series chrome bezel (poly case qty: 20)	200
00212217B	00212227P	M3 series chrome bezel (poly case qty: 20)	500
00212117B	00212127P	M4 series chrome bezel (poly case qty: 20)	70
00212717B	00212727P	M5 series chrome bezel (poly case qty: 20)	500
060102B	060102P	Trim ring for Odyssey directional light, black	50
24004TR71	24004TR71P	Trim ring for Galaxy single fixture 240047171B and 240047171LB, black	50
24014TR71	24014TR71P	Trim ring for Galaxy double fixtures 240147171B and 240147171LB	50
825TR02	825TR02P	Single trim ring for Unitek directional lights 825L and 825LED, black	50
826TR02	826TR02P	Double trim tring for Unitek directional lights 826L and 826LED, black	75
826TR12	826TR12P	Double trim tring for Unitek directional lights 826L and 826LED, light grey	25
826TR90	826TR90P	Double trim tring for Unitek directional lights 826L and 826LED, platinum silver	25

P/N	MATERIALS	WT/DIMS
00212317B	Chrome	.047 lb. / 6.625" x 2.188" x .75"
00212217B	Chrome	.010 lb. / 3 "x 2" x .7"
00212117B	Chrome	.010 lb. / 9" x 3.25" x .7"
00212717B	Chrome	.010 lb. / 4.188" x 1.5" x.7"
060102B	Chrome	.010 lb. / 5" x 3.125" x 1"
24004TR71	Plastic	.010 lb. / 3.875" x 5.25" x .75"
24014TR71	Plastic	.020 lb. / 4" x 10" x .25"
825TR02	Plastic	.010 lb. / 4.875" x 3.625" x 1"
826TR02/TR12/TR90	Plastic	.20 lb. / 7.25" x 3.875" x 1"

00212317B

00212217B

0212117B

00212717B

060102B

24004TR71

24014TR71


826TR12


826TR90

825TR02

826TR02

MOUNTING ACCESSORIES

Trim Rings and Bezels

3802071BZL

3801071BZL

0630004B

A0028CRB

A15CB/A15CGB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		BASES/BEZELS	
3802071BZL	3802071BZLP	Single trim ring for Ultratek directional light 06001013B, black	30
3801071BZL	3801071BZLP	Double trim ring for Ultratek directional light 06001014B, black	30
06300004B	06300004P	Single trim ring for Stargazer directional, black	150
A0028CRB	A0028CRBP	Chrome snap-on bezel fits MCL0028 and MCL0030 series	50
A06TR	A06TRP	White trim ring for ILL06/07	50
A09BB	A09BBP	UCL09 trim ring, black	50
A09CB	A09CBP	UCL09 trim ring, chrome	50
A09WB	A09WBP	UCL09 trim ring, white	50
A13B2B	A13B2BP	MCL/UCL13 base/bezel, black	100
A13B210B	A13B210BP	MCL/UCL13 base/bezel, matte black, fits #10 screw	100
A13C2B	A13C2BP	MCL/UCL13 base/bezel, chrome	100
A13C210B	A13C210BP	MCL/UCL13 base/bezel, chrome, fits #10 screw	100
A13NCC2B	A13NCC2BP	MCL/UCL13 base/bezel, unfinished	100
A15CB	A15CBP	MCL15 base/bezel, chrome	100
A15CGB	A15CGBP	MCL15 base/bezel, chrome with gasket	100

A06TR

A13C2B/A13C210B

A13B2B/A13B210B

A13NCC2B

A09BB

A09WB

P/N	MATERIALS	WT/DIMS
3802071BZL	Plastic	.010 lb. / 3.875" x 3.625" x .1875"
3801071BZL	Plastic	.020 lb. / 6.125" x 3.625" x .1875"
06300004B	Plastic	.10 lb. / 3.625" x 4.375" x 1.25"
A0028CRB	Plastic	.010 lb. / 4" x 2" x .70"
A06TR	ABS	.06 lb. / 11" x 4" x .25"
A09BB/CB/WB	ABS	.06 lb. / 3.421" x 3.421" x .287"
A13B2B/B210B	ABS	.088 lb. / 3.236" x 1.791" x .43"
A13C2B/C210B	Plastic	.088 lb. / 3.236" x 1.791" x .43"
A13NCC2B	Plastic	.088 lb. / 3.25" x 1.791" x .43"
A15CB/CGB	ABS	.088 lb. / 3.938" x 1.374" x .5"

MOUNTING ACCESSORIES
Trim Rings, Bases and Bezels

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		TRIM RINGS/BEZELS	
A17CB	A17CBP	Chrome bezel for MCL17 series marker/clearance light	100
A19CB	A19CBP	Chrome bezel for MCL19 series marker/ clearance light	100
A21CHB	A21CHBP	ILL21 bezel, chrome	25
A41CBB	A41CBBP	UCL41B bezel, black	50
A41CRB	A41CRBP	UCL41B bezel, chrome	50
A48CB	A48CBP	MCL48 & MCL73 bezel, chrome	50
A64BB	A64BBP	STL64/264 base/bezel, black	50
A64CRB	A64CRBP	STL64/264 base/bezel, chrome	50
A68SSB	A68SSB	Stainless steel snap-on trim ring for STL68RB	20
A69CB	A69CBP	STL69 & MCL70 base/bezel, chrome	10
A69NCCB	A69NCCBP	STL69 & MCL70 base/bezel, unfinished	50
A69RXCB	A69RXCBP	STL69RRXB base/bezel, chrome	10

A17CB

A19CB

A21CHB

A48CB

P/N	MATERIALS	WT/DIMS
A17CB	Plastic	.010 lb. / 4.188” x 1.375” x 0.625”
A19CB	Plastic	.020 lb. / 5.75” x 1.563” x.5”
A21CHB	ABS	.088 lb. / 6.313” x 6.313” x .563”
A41CBB/CRB	Plastic	.10 lb. / 8.7” x 2.95” x 1.59”
A48CB	ABS	.088 lb. / 6” x 2.25” x 1.125”
A64BB/CRB	Chrome	.20 lb. / 21.5” x 1.5” x 0.5”
A68SSB	SS	.088 lb / 10.125” x 3” x .375”
A69CB	ABS	.176 lb. / 16.313” x 1.625” x 0.813”
A69RXCB	ABS	.176 lb. / 16.313” x 1.875” x 0.813”

A41CBB

A41CRB

A64BB

A64CRB

A68SSB

A69CB

A69RXCB

MOUNTING ACCESSORIES

Trim Rings, Bases and Bezels

A70ECBB

A70ECCRB



BK42CB

BK66DB

BK66D1B

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		BASES/BEZELS	
A70ECBB	A70ECBBP	Black end cap for ILL70 series	100
A70ECCRB	A70ECCRBP	Chrome end cap for ILL70 series	100
A71CBAWN	A71CBAWNP	Chrome finish plastic base for ILL71CBAWN	10
A71CCBWAN	A71CCBWANP	Chrome finish plastic base/ bezel for ILL71CBAWN	10
A71C1BAWN	A71C1BAWNP	Chrome base for ILL71C1BAWN	25
A79CB	A79CBP	MCL78/88 and STL79/80/89/90 series base/bezel, chrome	10
A94VB	A94VP	Black steel visor for 7" warning lamps	25
BK42CB	BK42CBP	Steel mounting bracket, chrome plated	100
BK66DB	BK66DBP	Heavy duty armored base for MCL66 series lights; die cast metal	50
BK66D1B	BK66D1BP	Heavy duty armored base for MCL66 series lights; die cast metal, black finish	50

A94VB

P/N	MATERIALS	WT/DIMS
A70ECCB/ECCRB	Plastic	.010 lb.
A71CBAWN	ABS	.176 lb. / 18" x 2" x 1"
A71CCBWAN	Plastic	.020 lb. / 18" x 2.125" x 1.063"
A71C1BAWN	Chrome	.10 lb. / 16.866" x 1.91" x.526"
A79CB	ABS	.176 lb. / 18.875" x 2" x 0.813"
A94VB	Steel	.81 lb. / 7.25" x 7.25" x 4"
BK42CB	Steel	.243 lb. / 5.438" x 2.375" x 1.125"
BK66DB	Metal	.132 lb. / 4.25" x 1.125" x 1.688"
BK66D1B	Metal	.132 lb. / 4.25" x 1.125" x 1.688"

A79CB

A71CCBWAN

A71C1BAWN

MOUNTING ACCESSORIES

Miscellaneous Mounting Grommets, Brackets & Accessories

- A33GB is PVC grommet for flush mount of 33/35 series lights; grommet provides shock mount to lengthen life of light
- A40SRB secures lens of ST series lights

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
GROMMET - ST/STL33 SERIES			
A33GB	A33GBP	PVC grommet, flush mount	50
LOCKING RING - MCL11 SERIES			
A11SRB	A11SRBP	Stainless steel locking ring for MCL11S series	100
RETENTION RING - ST40 SERIES			
A40SRB	A40SRBP	Snap ring for ST40 series lights	100
BRACKETS - UCL SERIES			
BK20BB	BK20BBP	Bracket kit, UCL series	25

P/N	MATERIALS	WT/DIMS
A33GB	PVC	.353 lb. / 6.25" x 4.125" x 1.625"
A11SRB	Steel	.05 lb. / 1.5" diameter x 0.125"
A40SRB	Metal	.066 lb. / 5.125" diameter x 0.125"
BK20BB	Aluminum	.75 lb.

A33GB



HOLE CUT-OUT: 5.453" x 3.578" (1" R)

A11SRB



BK20BB

A40SRB



MOUNTING GASKETS

Closed Cell Foam Gaskets

A13G2B

A17GB

A66GB

A42GB

A90GB

Closed cell foam gaskets provide weather tight seal to mounting surface

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
FOAM GASKETS			
A13G2B	A13G2BP	MCL/UCL13 series, black	200
A15GB	A15GBP	MCL15 series, black	50
A17GB	A17GBP	MCL17 series, black	100
A32GB	A32GBP	MC32 series, white	500
A42GB	A42GBP	4” flange mount lights, black	100
A43FMBB	A43FMBBP	Gasket for STL43RBHX	50
A44GTB	A44GTBP	Thick, white	1000
A52GB	A52GBP	MCL52 series, black	100
A66GB	A66GB	MCL66 series, black	100
A69GB	A69GBP	MCL70/STL69 series, black	50
A73GB	A73GBP	STL73, non-adhesive, black	100
A76GB	A76GBP	Gasket for MCL76	100
A90GB	A90GBP	STL90, 5mm, black	50

REPLACEMENT LENSES

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
REPLACEMENT LENSES			
AL16RB	AL16RBP	Red tail light lens for STL16/17RB/RS and TLL16/160RK	50
AL17RB	AL17RBP	Red side marker lens for STL16/17RB/RS and TLL16/160RK	50
A2RB	A2RBP	Red side marker lens for ST2/3/4/5	25
A8RB	A8RBP	Red, tail light lens for ST/2/3/4/5/6/7/8/9	50
A9RB	A9RBP	Red side marker lens for ST6/7/8/9	50
A10R1B	A10R1BP	Red lens for RVSTL10/11	25
A11AB	A11ABP	Yellow marker lens for MC11	50
A11RB	A11ABP	Red marker lens for MC11	50
A16RB	A16RBP	Set: Red tail light lens, side marker lens for ST16/17	50
A17RB	A17RBP	Red side marker lens for ST16/17	50
A24RB	A24RBP	Red lens for ST24/25	25
A0028AB	A0028ABP	Yellow lens for MCL0028ABB	50
A0028RB	A0028RBP	Red lens for MCL0028ABB	50
A31AB	A31ABP	Yellow lens for MC31	50
A31RB	A31RBP	Red lens for MC31	50
A32AB	A32ABP	Yellow lens for MC/MCL32	10
A32RB	A32RBP	Red lens for MC/MCL32	50
A35AEB	A35AEBP	Yellow lens for MC35AEB	50
A35RB	A35RBP	Red lens for MC35	50
A36AB	A36ABP	Yellow lens for MC36	50
A36RB	A36RBP	Red lens for MC36	50
A37RB	A37RBP	Red side marker lens for ST36/37	50
A38AB	A38AB	Yellow lens for MC38	50
A38RB	A38RB	Red lens for MC38	50
A39RB	A39RBP	Red tail light lens for ST36/37	10
A40RB	A40RBP	Red lens for ST40	25
A41CB	A41CBP	Clear lens for BU41	25
A42AB	A42ABP	Yellow lens for MC42	10
A42RB	A42RBP	Red lens for MC42	10
A43RB	A43RBP	Red lens with reflex for ST42	25
A44AB	A44ABP	Yellow lens for MC/MCL44	10
A44A500B	-	Yellow lens for MC/MCL44, 500-pack	500
A44RB	A44RBP	Red lens for MC/MCL44	10
A44R500B	-	Red lens for MC/MCL44, 500-pack	500
A52AB	A52ABP	Yellow lens for ST52	25
A52RB	A52RBP	Yellow lens for ST52	25
A60RB	A60RBP	Red tail light lens for ST60	25

P/N	WT/DIMS
AL16RB	.010 lb. / 8.063" x 2.875" x .25"
AL17RB	.010 lb. / 2.813" x 2.875" x .25"
A2RB	.020 lb. / 2.75" x 2" x 1.5"
A8RB	.010 lb. / 4.563" x 4.563" x .25"
A9RB	.010 lb. / 2.75" x 2.125" x .25"
A11AB	.010 lb. / 2." x 1" x .875"
A11RB	.010 lb. / 2." x 1" x .875"
A16RB	.020 lb. / 8.063" x 2.875" x .25"
A17RB	.010 lb. / 2.75" x 2.125" x .125"
A24RB	.010 lb. / 4.313" x 4.313" x .5"
A0028AB	.010 lb. / 4" x 2" x .5"
A0028RB	.010 lb. / 4" x 2" x .5"
A31AB	.010 lb. / 4" x 2" x .75"
A31RB	.010 lb. / 4" x 2" x .75"
A32AB	.010 lb. / 4" x 2" x .5"
A32RB	.010 lb. / 4" x 2" x .5"
A35AEB	.010 lb. / 2.75" x 2" x.5"
A36AB	.010 lb. / 2.75" x 2" x .125"
A36RB	.010 lb. / 2.75" x 2" x .125"
A37RB	.010 lb. / 3.25" x 2" x .125"
A38AB	.010 lb. / 4" x 2" x .875"
A38RB	.010 lb. / 4" x 2" x .875"
A39RB	.020 lb. / 7.75" x 3.25" x .5"
A40RB	.010 lb. / 4.25" x 4.25" x .125"
A41CB	.010 lb. / 4.25" x 4.25" x .125"
A42AB	.010 lb. / 4" x 2" x .75"
A42RB	.010 lb. / 4" x 2" x .75"
A43RB	.010 lb. / 4.25" x 4.25" x .125"
A44AB	.010 lb. / 4" x 1.5" x .875"
A44A500B	.010 lb. / 4" x 1.5" x .875"
A44RB	.010 lb. / 4" x 1.5" x .875"
A44R500B	.010 lb. / 4" x 1.5" x .875"
A52AB	.010 lb. / 4.313" x 4.313" x.5"
A52RB	.010 lb. / 4.313" x 4.313" x.5"
A60RB	.020 lb. / 6.5" x 5.5" x.125"

Continued on the next page —>

REPLACEMENT LENSES

REPLACEMENT LENSES

P/N	WT/DIMS
A66AB	.010 lb. / 4" x 2" x .875"
A66RB	.010 lb. / 4" x 2" x .875"
A68AB	.010 lb. / 3.5" x 1.125" x .875"
A68RB	.010 lb. / 3.5" x 1.125" x .875"
A90AB	.020 lb. / 7.125" x 7.125" x 2"
A90RB	.020 lb. / 7.125" x 7.125" x 2"
AIL21B	.010 lb. / 5.75" x 4" x 1.75"
APL1AB	.010 lb. / 5.875" x 2.5" x .625"
APL1CB	.010 lb. / 5.875" x 2.5" x .625"
APL5AB	.010 lb. / 5.5" x 2.75" x .75"
APL5CB	.010 lb. / 5.5" x 2.75" x .75"
APL11AB	.010 lb. / 5.5" x 2.75" x .75"
APL11CB	.010 lb. / 5.5" x 2.75" x .75"
ARVIL35B	.010 lb. / 4.5" x 4" x .875"
AST60B	.020 lb. / 8.625" x 3.125" x 1.875"
AST61B	.020 lb. / 8.625" x 3.125" x 1.875"

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
REPLACEMENT LENSES			
A66AB	A66ABP	Yellow lens for MC66	50
A66RB	A66RBP	Red lens for MC66	50
A68AB	A68ABP	Yellow lens for MC68	50
A68RB	A68RBP	Red lens for MC68	50
A90AB	A90ABP	Yellow lens for ST90AB	5
A90RB	A90RBP	Red lens for ST90AB	5
AIL21B	AIL21BP	Clear lens for RVILL21/22	10
AL9RB	AL9RBP	Red side marker lens for STL8/9	30
APL1AB	APL1ABP	Yellow lens for RVPL1/3	10
APL1CB	APL1CBP	Clear lens for RVPL1/3	10
APL5AB	APL5ABP	Yellow lens for RVPL5/7	10
APL5CB	APL5CBP	Clear lens for RVPL5/7	10
APLL11AB	APLL11ABP	Yellow lens for RVPLL11AB and RVPLL13AB	200
APLL11CB	APLL11CBP	Clear lens for RVPLL11AB and RVPLL13AB	200
ARVIL35B	ARVIL35BP	Clear lens for RVIL35/36	10
AST60B	AST60BP	Red tail passenger light lens for RVST60/61 and RVSTL0060/61	10
AST61B	AST61BP	Red driver side tail light lens for RVST60/61 and RVSTL0060/61	10
	Retail Ready	**RETAIL**	
A8RK		Tail and side marker lens set, clam	12
A8R		Tail light lens, clam	12
A9R		Red side marker lens, clam	12
A16R		Lens set: tail light and side marker, clam	12
A20R		Red lens for ST20/21	12
A36R		Lens set: tail light and side marker, clam	12

SINGLE WIRE PLUG

Wiring/Molded Plug for Marker/Clearance & Utility Lights

- Molded male plug with lead wire
- For use with sealed marker/clearance and utility lights installed in self-grounding base

A91LW

A91LRW

A61EZPG

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
SINGLE WIRE PLUG			
A91LW	A91LWP	Single wire plug, 12", .156 male	100
A91LRW	A91LRWP	Single wire plug, 7", red, .180 male	500
A61EZPG	A61EZPGP	Single wire, 9" .180 male to .156 male	100
WT	0.044 lb.		

SINGLE & TWO-WIRE PLUGS

Wiring/Molded Plug for Thinline Marker/Clearance & Utility Lights

- Standard .156 male bullet on 6" lead wire
- Molded plug fits into surface mount bracket for MC/MCL/UL/UCL65 and MCL61 series lights
- Single wire plug grounds through mounting hardware
- Two-wire plug includes both lead and ground wire

A65P

A68P

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
MOLDED PLUGS FOR THINLINE LIGHTS			
A65P	A65PP	Single wire plug, 6"	50
A68P	A68PP	Two-wire plug, 6"	50
WT	Plugs weigh approximately 0.044 lb. each		

A42PMB

2-WIRE PIGTAILS

Wiring/Molded Plugs for Single Contact Sealed Lights

- Standard two terminal plug with male pins, bare lead wire and #10 ring terminal on ground wire
- For use with back-up and utility lights



A45CB



A49PB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
TWO-WIRE PIGTAILS			
A42PMB	A42PMBP	Weathertight pigtail, 10”	100
A45CB	A45CBP	Straight pigtail, 10”	100
A49PB	A49PBP	Right angle pigtail, 10”	100
A49PBB	A49PBBP	Right angle pigtail, 6”, no eyelet on ground	100
WT	All weigh approximately 0.044 lb. each		



MOUNTING HARDWARE

Mounting Hardware for Vehicle Lighting

Hardware sets for mounting vehicle lights. Components packaged separately.

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
HARDWARE			
A830B	-	(1) each: 1/4” 20 flange lock nut, 1/4” flat washer, 1/4” split lock washer; stainless steel	100
A839B	-	(1) each: 1/4” 20 flange lock nut, 1/4” flat washer, 1/4” split lock washer; zinc plated	100
BK21BB	BK21BBP	Kit: 3-piece set of mounting brackets and hardware for UCL32CDTB	2
LP52HP	LP52HPP	Mounting hardware for license plate lights; includes two each bolts, washers and weld nuts	100

2-WIRE PIGTAILS

Wiring/Molded Plugs for Sealed Marker/Clearance & Utility Lights

AL42PB

- Pigtails feature standard PL-10 plug with male pins; bare lead wires and #8 ring terminal on ground wire unless noted in description
- For use with sealed marker/clearance and utility lights


A46PB



BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		TWO-WIRE PL-10 PLUGS	
A12PB	A12PBP	12” adaptor, .180 male bullets to .180 female barrels	100
AL42PB	AL42PBP	MCL42 weathertight pigtail	100
AL42PG	AL42PGP	MCL42 weathertight pigtail, .180 bullets	100
AL421PG	AL421PGP	MCL42 weathertight pigtail, .180 male bullet on power, eyelet on ground	100
A42PMB	A42PMBP	Weathertight pigtail, 10”	100
A46PB	A46PBP	Straight pigtail, 6”	100
A46PBB	A46PBBP	Straight pigtail, 6”, no eyelet on ground	100
A46PPG	A46PPGP	Straight pigtail, 6”, male plug on power	100
A46P135B	-	Straight pigtail, 135”, no ring terminal on ground wire	100
A46P75B	-	Straight pigtail, 75”, no ring terminal on ground wire	100
A46P36B	-	Straight pigtail, 36”, no ring terminal on ground wire	100
A86PB	A86PBP	Straight pigtail, 18”	100
		RETAIL	
A46PS	Retail Ready	Straight pigtail, 6”, clam	12
WT	All weigh approximately 0.044 lb. each		

ID LIGHT BAR HARNESS

Wiring/Molded Plugs for 3-pc Sealed Identification Light Bars

A93PB

- Standard two terminal plugs with male pins; 65” bare lead wire and #10 ring terminal on 19” ground wire
- For use with identification light bars featuring sealed lights

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		ID LIGHT BAR HARNESS	
A93PB	A93PBP	ID light bar harness	100
WT	0.4 lb.		

3-WIRE PIGTAILS

Wiring/Molded Plugs for Double Contact Sealed Lights

A45PB



A47PB



A45PMB



AL45PWTB

- A45PB & A47PB feature standard PL-3 plug with male pins, bare lead wires and #10 ring terminal on ground wire
- For use with stop/turn/tail, parking/turn and warning lights

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
STANDARD PL-3			
A45PB	A45PBP	Straight pigtail,10”	100
A47PB	A47PBP	Right angle pigtail, 10”	100
A47PBB	A47PBBP	Straight pigtail, 10”, no eyelet on ground	100
WEATHERPROOF			
A45PMB	A45PMBP	Weathertight plug to bare wire, 10”	50
AL45PWTB	AL45PWTBP	Weathertight plug with female PL-3, 10”	50
AL145PWTB	AL145PWTBP	Weathertight plug, right angle PL-3, 10”	50
RETAIL			
A45PS	Retail Ready	Straight pigtail, 6”, clam	50
A47PS		Right angle pigtail, 10”, clam	50

WT	All weigh approximately 0.044 lb. each

TRUNK & TRAILER CONNECTORS

- A10TH5B tongue extension features 5-way flat plug with one female/four male pins on one end; on other end 5-way flat plug with one male/three female pins, female barrel on blue wire
- A4TC4WB and A6TC4WB trunk connectors feature 4-way flat plug with three female/one male pins
- A18TC replacement trailer connector has one female/three male pins; A185TC has one female/four male pins
- A48TC replacement trunk connector has one male/three female pins

A48TC

A18TC

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		CONNECTORS	
A10TH5B	A10TH5BP	5-way harness tongue extension, 10-ft	50
A4TC4WB	A4TC4WBP	4-way to bare wire, 4-ft	100
A6TC4WB	A6TC4WBP	4-way to bare wire, 6-ft	50
A6TC5B	A6TC5BP	5-way to bare wire, 6-ft.	50
		RETAIL	
A18TC	Retail Ready	4-way trailer connector, 18", clam	12
A185TC		5-way trailer connector, 18", clam	12
A48TC		4-way trunk connector, 4-ft, clam	12

7-5 WAY ADAPTORS/PLUGS

A57WB

A57CCB

A75TB

A7WCB

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		7-WAY WIRING HARNESSES	
A7W6FTB	-	7-way molded plug with 6-ft. cable	5
A7W8FTB	-	7-way molded plug with 8-ft. cable	5
		7-5 WAY ADAPTORS	
A57WB	A57WBP	5-flat to 7-round, 16" cable	25
A57CCB	A57CCBP	5-flat to 7-round , coil cord	30
A75TB	A75TBP	5-flat to 7-round, single piece	50
A7WCB	A7WCBP	7-way power plug, round	50
		RETAIL	
A57WH		5-flat to 7-round, 16" cable, clam	6
A75TC	Retail Ready	5-flat to 7-round, single piece, clam	12
A75TC6		5-flat to 7-round, single piece, clam	6

4-WAY WISHBONE STYLE WIRING HARNESSES



Split wishbone four-conductor harnesses

WIRE DESCRIPTIONS:
WHITE - GROUND
BROWN - TAIL LAMPS
YELLOW - DRIVER SIDE STOP/TURN
GREEN - PASSENGER SIDE STOP/TURN

Additional harness configurations available. Contact Sales: sales@optronicsinc.com

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		4-WAY HARNESSES	
A20WB	A20WBP	20-ft	50
A25WB	A25WBP	25-ft	50
A25R10WB	A25R10WBP	25-ft, #10 ring terminal on ground	50
A25W42B	A25W42BP	25-ft, 42” ground wire	50
A30WB	A30WBP	30-ft	50
A30W10B	A30W10BP	30-ft, 10-ft ground wire	50
A35WB	A35WBP	35-ft	25
A35R10WB	A35R10WBP	35-ft, #10 ring terminal on ground	25
A35W42B	A35W42BP	35-ft, 42” ground wire	50
A36WRB	A36WRBP	36-ft ribbon wiring harness	25
A40W42B	A40W42BP	40-ft with tubing, 42” ground wire	25
		RETAIL	
A25WH	Retail Ready	25-ft harness with 4-ft trunk connector, clam	6

5-WAY WISHBONE STYLE WIRING HARNESSES



Split wishbone five-conductor harnesses have fifth wire for lights or brakes

WIRE DESCRIPTIONS:
WHITE - GROUND
BROWN - TAIL LAMPS
YELLOW - DRIVER SIDE STOP/TURN
GREEN - PASSENGER SIDE STOP/TURN
BLUE - AUXILIARY USE

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		5-WAY HARNESSES	
A25W5B	A25W5BP	25-ft, 30” ground, 5-ft blue wire	25
A30W5B	A30W5BP	30-ft, 30” ground, 5-ft blue wire	25
A30W5BLB	-	30-ft, 40” ground, 30-ft blue wire	25
A35W5B	A35W5BP	35-ft, 30” ground, 5-ft blue wire	25
A40W5B	A40W5BP	40-ft, 30” ground, 5-ft blue wire	25
		RETAIL	
A255WH	Retail Ready	25-ft harness with 4-ft trunk connector, clam	6

REPLACEMENT BULBS

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		BULBS	
A1157B	A1157BP	1157, 14V 26.9/8.3W, 1200/5000 hour rating	100
A194B	A194BP	194 wedge base, 14V 4CP, 2500 hour rating	100
		RETAIL	
A400	Retail Ready	Set, (1) each: 2057, 1157, 194, 168; clam	12
A700		12V 55W H3 quartz halogen, clam	12

ALEDRST Series

LED Load Resistor

- Upgrade from incandescent turn signals to LED models for safer, cost-efficient lights
- Makes turn signal flash at proper flash rate
- 50W, 6 ohm in-line resistor





BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		LOAD RESISTOR	
ALEDRST1B	ALEDRST1BP	LED load resistor with lead	50
ALEDRST2B	ALEDRST2BP	LED load resistor with lead and female PL-3 plug	50

VOLT/AMP	WARRANTY
12V / 50W	Three Year Warranty

UCL90 SERIES CONNECTORS

LED Strip Lighting Connectors

- Connects strips of lights without soldering
- Snap-on design is quick and easy to install
- For use with UCL90/91/92 series

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		BRACKETS	
A90PB	A90PBP	Snap-on connector with leads	20
A90P1B	A90P1BP	Snap-on connector	20

MATERIALS	Plastic
VOLT/AMP	12.8VDC
WT/DIMS	0.01 lbs. / 1" long
WARRANTY	Three Year Warranty

A0116AWGBLWSB

A011AWGBRGRSB

A011AWGBRSB

A0118AWGBRYLWSB

A0118AWGWHTSB

BULK WIRE

- Bulk wire on spools
- Select from 16AWG or 18AWG in assorted colors

BULK P/N	DESCRIPTION	QTY
	BULK WIRE	
A0114AWG2BLWHSB	14AWG, White/Black, 2,500-ft. spool	1
A0114AWGBLKWHTB	14AWG, White/Black, 1,640-ft. spool	1
A0116AWGBLWSB	16AWG, Blue/White, 1,640-ft. spool	1
A0118AWGBRGRSB	18AWG Brown/Green, 1,640-ft. spool	1
A0118AWGBRSB	18AWG, Brown 2,985-ft. spool	1
A0118AWGBRYLWSB	18AWG, Brown/Yellow, 1,640-ft. spool	1
A0118AWGWHTSB	18AWG, White, 2,985-ft spool	1
A0118AWGBRYLGRB	18AWG, Brown/Yellow/Green, 1,640-ft. spool	1
A0118AWGWHT5KSB	18AWG, White, 5,000-ft spool	1
A0118AWGBR5KSB	18AWG, Brown 5,000-ft. spool	1
A0118AWGBRGR5KSB	18AWG Brown/Green, 5,000-ft. spool	1
A0118AWGRESB	18AWG, Red 5,000-ft. spool	1
A0118AWGBLSB	18AWG, Black 5,000-ft. spool	1
A0118AWGYESB	18AWG, Yellow 5,000-ft. spool	1
A0118AWGBRRE5KSB	18AWG Brown/Red, 5,000-ft. spool	1
A0118AWGGRSB	18AWG, Green, 5,000-ft. spool	1
A0118AWGRESB	18AWG, Red, 5,000-ft. spool	1

FLASHER

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
		FLASHER	
ALEDFB	ALEDFBP	LED flasher with connectors	10
		RETAIL	
ALEDFS	Retail Ready	LED flasher with connections, clam	12

DOCUMENT HOLDER

- Twist-on cover with gasket protects documents from dirt and moisture while allowing convenient access
- Easy installation

DH55

BULK P/N	POLYPACK P/N	DESCRIPTION	QTY
DOCUMENT HOLDER			
DH55	DH55P	Document holder	10
ADH55B	ADH55BP	Replacement lid	50

P/N	MATERIALS	WT/DIMS
DH55	Polycarbonate	0.46 lb. / 5.5” x 5.5” x 2.125”

FEDERAL LIGHTING REGULATIONS FOR TRAILERS

IMPORTANT NOTE: Every lamp, reflex reflector, and conspicuity treatment must be permanently attached in the location specified below and must comply with all applicable requirements prescribed for it by FMVSS/CMVSS 108. The face of any device on the front/rear and sides should be, repectively perpendicular and parallel to the vehicle's centerline, unless it is photometrically certified at installation angle. No part of the vehicle shall prevent any device from meeting its prescribed requirements unless an auxiliary device meeting all prescribed requirements is installed. **IN CANADA:** Manufacturers and importers of vehicles must have the proper certification test records demonstrating compliance of lighting components with all prescribed requirements.

Transport Canada NHTSA

BASIC EQUIPMENT REQUIRED ON ALL TRAILERS

DESCRIPTION				MANDATORY REQUIREMENTS			
Area	Equipment	SAE Lens Coding	Functional Purpose	Quantity	Color	Location	Height mm(in.) from the ground
1	Tail Lamps	(T)	Indicate vehicle's presence and width	Minimum 2	Red	On the rear - symmetrical as far apart as practicable	380-1830 (15-72)
	Stop Lamps	(S)	Indicate braking	Minimum 2	Red	On the rear - symmetrical as far apart as practicable	380-1830 (15-72)
	Rear Turn Signal Lamps	(I)	Indicate direction of turn	Minimum 2	Red or Yellow	On the rear - symmetrical as far apart as practicable	380-2110 (15-83)
	Rear Reflex Relectors	(A)	Indicate vehicle's presence and width	Minimum 2	Red	On the rear - symmetrical as far apart as practicable facing rearward	380-1530 (15-60)
2	License Plate Lamp(s)	(L)	Illuminates license plate	Minimum 1	White	On the rear - above or at the sides of license plate	No requirement
3	Rear Side Marker Lamps *photometrically certified at installation angle	(P2, PC* or P3, PC2*)	Front and rear side marker lamps / side reflex reflectors indicate vehicle's presence and length	Minimum 2	Red	Each side at rear as far back as practicable	380-1530 (15-60) no max. for veh. under 2032mm (80") wide
	Rear Side Reflex Relectors	(A)		Minimum 2	Red	Each side at rear as far back as practicable facing sideward	380-1530 (15-60)
4 a	Front Side Marker Lamps *photometrically certified at installation angle	(P2, PC* or P3, PC2*)		Minimum 2	Yellow	Each side at front as far forward as practicable	380 (15) minimum
4 b	Front Side Reflex Reflectors	(A)		Minimum 2	Yellow	Each side at front as far forward as practicable facing sideward	380-1530 (15-60)

ADDITIONAL EQUIPMENT FOR TRAILERS EXCEEDING THE FOLLOWING PARAMETERS

Length 9.1m (30 ft.) or longer

DESCRIPTION				MANDATORY REQUIREMENTS			
Area	Equipment	SAE Lens Coding	Functional Purpose	Quantity	Color	Location	Height mm(in.) from the ground
5 a	Intermediate Side Marker Lamps	(P2 or P3)	Indicate presence of a long vehicle	Minimum 2	Yellow	Each side near center facing sideward	380 (15) minimum
5 b	Intermediate Side Reflex Reflectors	(A)	Indicate presence of a long vehicle	Minimum 2	Yellow	Each side near center facing sideward	380-1530 (15-60)

Width 2032mm (80 in.) or wider

DESCRIPTION			MANDATORY REQUIREMENTS				
Area	Equipment	SAE Lens Coding	Functional Purpose	Quantity	Color	Location	Height
6	Rear Clearance Lamps *photometrically certified at installation angle	(P2, PC* or P3, PC2*)	Show vehicle's width MAY NOT be combined with tail lamps	Minimum 2	Red	At widest point - symmetrical on the rear or near the rear facing rearward	As high as practicable may be lower only if ID lamps are at the top
7	Rear Identification (ID) Lamps	(P2 or P3)	Indicate presence of a wide vehicle	Exactly 3	Red	On the rear - center horizontally spaced 150mm (6 in.) to 300mm (12 in.) apart facing rearward	At the top - may be lower if door header narrower than 25mm
8	Front Clearance Lamps *photometrically certified at installation angle	(P2, PC* or P3, PC2*)	Show vehicle's width	Minimum 2	Yellow	At widest point - symmetrical on the front or near the front facing forward	As high as practicable

Width 2032mm (80 in.) or wider AND GVWR 4536 kg (10,000 lb.) or more

DESCRIPTION		MANDATORY REQUIREMENTS					
Area	Conspicuity Treatment	DOT Coding	Quantity	Color	Location	Height	Options
9	Rear Upper Body Markings	DOT-C DOT-C2 DOT-C3 DOT-C4	Exactly 2 pairs of 300mm long strips	White	On the rear upper corners facing rearward	At the top	Reflex reflectors may not be required if they are replaced in their required location with conspicuity treatment. **Optional in Canada:** Rear lower body and side conspicuity treatment may also be solid white, solid yellow, or white and yellow.
10	Bumper Bar Marking		Continuous	Red/White	On the rear bumper bar's horizontal element full width - facing rearward	No requirement	
11	Rear Lower Body Marking		Continuous	Red/White *(see options)*	On the rear full width of the vehicle facing rearward	As horizontal as practicable and as close as practicable to the range of 375 to 1525mm from the ground	
12	Side Marking		(see location)	Red/White *(see options)*	Each side - facing sideward continuous, or evenly spaced over minimum of 50% of length starts and ends as close to the front and rear of the vehicle as practicable	As horizontal as practicable and as close as practicable to the range of 375 to 1525mm from the ground	

NOTE: The edge of red conspicuity tape shall not be closer than 75 mm to the edge of any amber lamp and the edge of white conspicuity tape shall not be closer than 75 mm to the edge of any lamp

For more information contact: Transport Canada: Motor Vehicle Safety Enforcement Branch
National Highway Traffic Safety Administration: Office of Safety Performance Standards


8
3
8
4ab


6
1
2
7
1
6
123 456


5ab
4ab
3
12
12
8


9
6
1
2
11
1
6
123 456
7
10


5a
4a
3
12
*upper OR
lower position
5ab
8
12
4ab


9
7
9
6
1
1
6
123 456
2
10


8
5a
4a
3
12
5ab
12
4ab


9
6
7
6
9
1
2
11
1
123 456
10


4ab
8
3


7
6
6
123 456
2
1
1


3
8
4ab


6
6
123 456
2
7
1
1


8
4a
3
4ab


6
7
6
1
1
123 456
2


4a
3
4ab
8


7
6
6
123 456
2
1
1

FEDERAL LIGHTING REGULATIONS FOR TRUCKS, BUSES & MPVs

IMPORTANT NOTE: Every lamp, reflex reflector, and conspicuity treatment must be permanently attached in the location specified below and must comply with all applicable requirements prescribed for it by FMVSS/CMVSS 108. The face of any device on the front/rear and sides should be, repectively perpendicular and parallel to the vehicle's centerline, unless it is photometrically certified at installation angle. No part of the vehicle shall prevent any device from meeting its prescribed requirements unless an auxiliary device meeting all prescribed requirements is installed. **IN CANADA:** Manufacturers and importers of vehicles must have the proper certification test records demonstrating compliance of lighting components with all prescribed requirements.

Transport Canada NHTSA

BASIC EQUIPMENT REQUIRED ON ALL TRUCKS, BUSES & MPVs

DESCRIPTION				MANDATORY REQUIREMENTS			
Area	Equipment	SAE Lens Coding	Functional Purpose	Quantity	Color	Location	Height mm(in.) from the ground
1	Headlamps - Lower Beam US requires "DOT" lettering on lens US & Canada - light source code required on lens	(H, HR)	Forward road illumination	Minimum 2	White	On the front - symmetrical as far apart as practicable If 4 lamp system - outboard or above upper beams	560-1370 (22-54)
	Headlamps - Upper Beam US requires "DOT" lettering on lens US & Canada - light source code required on lens	(H, HR)	Forward road illumination	Minimum 2	White	On the front - symmetrical If 4 lamp system - inboard or below lower beams	560-1370 (22-54)
	Parking Lamps Vehicles less than 2032mm wide	(P)	Indicate parked vehicle	Minimum 2	White or Yellow	On the front - symmetrical as far apart as practicable	380-1830 (15-72)
	Daytime Running Lamps (DRL) Canada - required / US - option US requires "DRL" lettering on lens if not headlamp	(Y2)	Indicate in use vehicle	Minimum 2	White or Yellow	On the front - symmetrical as far apart as practicable	380 (15) min. Max. depends on type of DRL
	Front Turn Signal/ Hazard Warning Lamps	(I)	Indicate direction of turn/ identify disabled vehicle	Minimum 2	Yellow	On the front - symmetrical as far apart as practicable	380-2110 (15-83)
2	Front Clearance Lamps Vehicles 2032mm wide or wider *photometrically certified at installation angle	(P2, PC* or P3, PC2*)	Show vehicle's width	Minimum 2	Yellow	At widest point - symmetrical on the front or near the front facing forward	As high as practicable
3	Front Identification Lamps (ID) Vehicles 2032mm wide or wider	(P2 or P3)	Indicate presence of a wide vehicle	Exactly 3	Yellow	On the front - center horizontally spaced 150mm (6 in.) to 300mm (12 in.) apart	As high as practicable or on top of the cab
4a	Front Side Marker Lamps *photometrically certified at installation angle	(P2, PC* or P3, PC2*)	Front and rear side marker lamps / side reflex reflector indicate vehicle's presence and length	Minimum 2	Yellow	Each side at front as far forward as practicable	380 (15) minimum
4b	Front Side Reflex Reflectors	(A)		Minimum 2	Yellow	Each side at front as far forward as practicable facing sideward	380-1530 (15-60)
5a	Rear Side Marker Lamps** *photometrically certified at installation angle	(P2, PC* or P3, PC2*)		Minimum 2	Red	Each side at rear as far back as practicable	380 (15) minimum
5b	Rear Side Reflex Reflectors** **not required on Truck Tractors	(A)		Minimum 2	Red	Each side at rear as far back as practicable facing sideward	380-1530 (15-60)
6	Rear Clearance Lamps Vehicles 2032mm wide or wider Not required on Truck Tractors *photometrically certified at installation angle	(P2, PC* or P3, PC2*)	Show vehicle's width MAY NOT be combined with tail lamps	Minimum 2	Red	At widest point - symmetrical on the rear or near the rear facing rearward	As high as practicable may be lower only if rear ID lamps are at the top
7	Rear Identification (ID) Lamps Vehicles 2032mm wide or wider Not required on Truck Tractors	(P2 or P3)	Indicate presence of a wide vehicle	Exactly 3	Red	On the rear - center horizontally spaced 150mm (6 in.) to 300mm (12 in.) apart facing rearward	At the top - may be lower if door header narrower than 25mm
8	Tail Lamps	(T)	Indicate vehicle's presence and width	Minimum 2	Red	On the rear - symmetrical as far apart as practicable	380-1830 (15-72)
	Stop Lamps	(S)	Indicate braking	Minimum 2	Red	On the rear - symmetrical as far apart as practicable	380-1830 (15-72)
	Rear Turn Signal/ Hazard Warning Lamps	(I)	Indicate direction of turn/ identify disabled vehicle	Minimum 2	Red or Yellow	On the rear - symmetrical as far apart as practicable	380-2110 (15-83)
	Rear Reflex Reflectors	(A)	Show vehicle's presence and width	Minimum 2	Red	On the rear - symmetrical as far apart as practicable	380-1530 (15-60)
9	Backup Lamp	(R)	Illuminates ground behind the vehicle and alert road users	Minimum 1	White	Rear	No requirement
10	License Plate Lamp(s)	(L)	Illuminates license plate	Minimum 1	White	On the rear - above or at the sides of license plate	No requirement
11	Center High Mounted Stop Lamp Vehicles less than 2032mm wide and 4536kg	(U3)	Indicates braking	1	Red	On the rear - centerline of the vehicle	860 (34) minimum

ADDITIONAL EQUIPMENT FOR SPECIFIC VEHICLES — VEHICLES 9.1m (30 ft.) LONG OR LONGER

DESCRIPTION				MANDATORY REQUIREMENTS			
Area	Equipment	SAE Lens Coding	Functional Purpose	Quantity	Color	Location	Height mm(in.) from the ground
12a	Intermediate Side Marker Lamps	(P2 or P3)	Indicate presence of a long vehicle	Minimum 2	Yellow	Each side near center	380 (15) minimum
12b	Intermediate Side Reflex Reflectors	(A)	Indicate presence of a long vehicle	Minimum 2	Yellow	Each side near center facing sideward	380-1530 (15-60)

Truck Tractors

DESCRIPTION		MANDATORY REQUIREMENTS					
Area	Conspicuity Treatment	DOT Coding	Quantity	Color	Location	Height	Options
13	Rear Upper Body Markings	DOT-C DOT-C2 DOT-C3 DOT-C4	Exactly 2 pairs of 300mm long strips	White	Rear upper corners of cab facing rearward	As high as practicable excluding fairings	
14	Rear Marking		Exactly 2 sections of min. 600mm each	Red/White	Rear - facing rearward - on fenders, on mud flap brackets, or within 300mm below the top of mud flaps	As horizontal as practicable and not higher than 1525mm from the ground	If mud flaps not used - on the cab or frame mounted brackets

NOTE: The edge of red conspicuity tape shall not be closer than 75 mm to the edge of any amber lamp and the edge of white conspicuity tape shall not be closer than 75 mm to the edge of any lamp

For more information contact: Transport Canada: Motor Vehicle Safety Enforcement Branch
National Highway Traffic Safety Administration: Office of Safety Performance Standards


12a
2
5a
3
*on cab
OR on box
5ab
12ab
4ab
1


6
7
6
8
10
8
9


5a
3
5ab
2
12ab
4ab
1


7
6
8
8
6
10
9


2
4a
12a
12ab
4ab
1


13
13
8
14
14
8
10

optronics


12a
2
3
5a
5ab
12ab
4ab
1


6
7
6
10
8
8
9


12a
2
3
5a
5ab
12ab
4ab
1


6
7
6
8
8
10
9


12a
4a
2
3
5a
5ab
12ab
4ab
1


6
7
6
10
8
8
9


12a
2
5a
3
*on cab
OR on box
5ab
12ab
4ab
1


6
6
8
8
10
7
9

Truck & Trailer Regulation – FMVSS 108 (49CFR 571.108)





APPLICATION LOCATIONS:

Rear Upper Body

12" WHITE strips placed in the upper rear corners

Rear Lower Body

- 2" wide RED/WHITE tape placed on rear full width of vehicle
- 2" wide RED/WHITE tape minimum 24" length on fender, mudflap brackets or within 12" below the top of mudflaps

Side Marking

2" wide RED/WHITE tape placed on each side of trailer continuous or evenly spaced over 50% of the vehicle

School Bus Regulation – FMVSS 131 & 217



Each opening for a required emergency exit shall be outlined around its outside perimeter with a retroreflective tape with a minimum width of 1 inch and either red, white, or yellow in color, that when tested under the conditions specified in S6.1 of Standard No. 131 (49 CFR 571.131), meets the criteria specified.

APPLICATION LOCATIONS:

- 1" strips used to mark side emergency exit windows
- 1" strips used to mark back emergency exit windows

DOT FMVSS 108 COMPLIANT

00212104B 106
00212117B 341
00212127P 341
00212135P 106
00212137P 106
00212155P 106
00212157P 106
00212207B 105
00212209B 105
00212213B 105
00212217B 341
00212227P 341
00212233B 251
00212233P 251
00212235P 105
00212236P 105
00212237P 105
00212238P 105
00212239B 251
00212239P 251
00212251B 251
00212251P 251
00212253B 251
00212253P 251
00212255P 105
00212256P 105
00212257P 105
00212258P 105
00212263P 105
00212276B 105
00212278B 105
00212307B 104
00212309B 104
00212316B 104
00212317B 341
00212327P 341
00212331B 250
00212331P 250
00212333B 250
00212333P 250
00212335P 104
00212336P 104
00212337P 104
00212338P 104
00212342B 250
00212342P 250
00212345P 104
00212346P 104
00212347P 104
00212351B 250
00212351P 250
00212355P 104
00212356P 104
00212357P 104
00212358P 104
00212362B 250
00212362P 250
00212365P 104
00212367P 104
00212368P 104
00212376B 104
00212378B 104
00212386B 104
00212700B 107
00212701B 107
00212702B 107
00212703B 107
00212704P 107
00212705P 107
00212706P 107
00212707P 107
00212708P 107
00212709P 107
00212710P 107
00212711P 107
00212712P 107
00212717B 341
00212727P 341
01180071B 321
01180071P 321
01180089B 321
01180089P 321
01180090B 321
01180090BP 321
014BCRCW 320
014BCRCWP 320
03001175B 311
03001175P 311
04010040B 311
04010040P 311
04440013B 310
04440013P 310
04440016B 310
04440016P 310
06001001B 316
06001001P 316
06001013B 314
06001013P 314
06001014B 314
06001014P 314
06001015B 315
06001015P 315
06001022B 312
06001022P 312
06001026B 315
06001026P 315
06001037B 315
06001037P 315
06001048B 315
06001048P 315
06001061B 315
06001061P 315
06001072B 315
06001072P 315
060102B 316
060102P 316
0601B 316
0601P 316
06300004B 316
06300004P 316
068NME 309
068NMEP 309
068WMTE 309
068WMTEP 309
09017101B 322
09017101P 322
105500SP 317
105520B 317
105520BP 317
11212207B 102
11212209B 102
11212235P 102
11212236P 102
11212237P 102
11212238P 102
11212255P 102
11212256P 102
11212257P 102
11212258P 102
11212276B 102
11212278B 102
11212307B 101
11212309B 101
11212335P 101
11212336P 101
11212337P 101
11212338P 101
11212355P 101
11212356P 101
11212357P 101
11212358P 101
11212376B 101
11212378B 101
11212700B 103
11212700BB 103
11212700BBP 103
11212701B 103
11212702B 103
11212703B 103
11212704P 103
11212705P 103
11212706P 103
11212707P 103
11212708P 103
11212709P 103
11212710P 103
11212711P 103
13000018B 320
13000018P 320
1502B 322
1502P 322
15202B 322
15202P 322
16802B 309
16802LB 309
16802P 309
18543910B 317
18543916B 317
18543916BP 317
19102B 309
19102P 309
193BSP 319
193BSPP 319
193G 319
193P 319
24004002B 312
240047171B 312
240047171LB 312
240047171P 312
24004TR71 312
24004TR71P 312
240147171B 312
240147171LB 312
240147171P 312
24014TR71 312
24014TR71P 312
24074B 310
24074P 310
2407764B 310
2407764P 310
2407765B 310
2407765P 310
2407771C 310
2407771CP 310
2409171B 322
2409171BP 322
24113160B 318
24113160P 318
2500128B 321
2500128P 321
2500171B 321
2500171P 321
2500189B 321
2500189P 321
30000000B 322
30031010B 322
302B 322
302P 322
30655010B 322
3202B 322
3202P 322
357B 318
357P 318
3801071BZL 314
3801071BZLP 314
3802071BZL 314
3802071BZLP 314
500302B 322
500302P 322
510001B 322
510001P 322
530002B 322
530002P 322
69000201B 319
69000201P 319
69000300B 319
69000300P 319
725022B 314
725022P 314
726022B 314
726022P 314
7850NFRC 320
7850NFRCP 320
825LED 313

825TR02 313
825TR02P 313
826L 313
826LED 313
826LEDP 313
826LP 313
826TR02 313
826TR02P 313
826TR12 313
826TR12P 313
826TR90 313
A0028AB 347
A0028CRB 342
A0028RB 347
A0114AWG2BLWHSB 356
A0114AWGBLKWHTB 356
A0116AWGBLWSB 356
A0118AWGBLSB 356
A0118AWGBR5KSB 356
A0118AWGBRGR5KSB .. 356
A0118AWGBRGRSB 356
A0118AWGBRRE5KSB ... 356
A0118AWGBRSB 356
A0118AWGBRYLGRB 356
A0118AWGBRYLWSB 356
A0118AWGGRESB 356
A0118AWGGRSB 356
A0118AWGRESB 356
A0118AWGWHT5KSB 356
A0118AWGWHTSB 356
A0118AWGYESB 356
A06TR 342
A06TRP 342
A09BB 342
A09BBP 342
A09CB 342
A09CBP 342
A09WB 342
A09WBP 342
A101TRSSB 334
A101TRSSBP 334
A10BB 329
A10BBP 329
A10GB 329
A10GBP 329
A10R1B 347
A10TH5B 353
A10TH5BP 353
A111TRSSB 336
A111TRSSBP 336
A1157B 355
A1157BP 355
A11AB 347
A11ABP 347
A11AXB 324
A11AXBP 324
A11BLPB 329
A11BLPBP 329
A11CRB 329
A11CRBP 329
A11DB 329
A11DBP 329
A11G1B 329
A11G1BP 329
A11GB 329
A11GBP 329
A11GLPB 329
A11GLPBP 329
A11GSDB 329
A11PB 329
A11PBP 329
A11RB 347
A11RBP 347
A11RXB 324
A11RXBP 324
A11SRB 345
A11SRBP 345
A11SSB 329
A11SSBP 329
A12B2LPB 329
A12B2LPBP 329
A12GB 329
A12GBP 329
A12GLPB 329
A12GLPBP 329
A12PB 351
A12PBP 351
A13B210B 342
A13B2B 342
A13B2BP 342
A13C210B 342
A13C210BP 342
A13C2B 342
A13C2BP 342
A13G2B 346
A13G2BP 346
A13NCC2B 342
A13NCC2BP 342
A14GB 329
A14GBP 329
A15CB 342
A15CBP 342
A15CGB 342
A15GB 346
A15GBP 346
A16R 348
A16RB 347
A16RBP 347
A178TRSSB 336
A178TRSSBP 336
A17CB 343
A17GB 346
A17GBP 346
A17RB 347
A17RBP 347
A185TC 353
A18TC 353
A194B 355
A194BP 355
A19CB 343
A20R 348
A20WB 354
A20WBP 354
A211CB1 336
A211NCCB 336
A211RXB 336
A21AB 262
A21CHB 343
A21CHBP 343
A21RB 262
A21RBP 262
A24RB 347
A24RBP 347
A255WH 354
A25GB 339
A25GBP 339
A25R10WB 354
A25R10WBP 354
A25TRSSB 332
A25TRSSBP 332
A25W42B 354
A25W42BP 354
A25W5B 354
A25W5BP 354
A25WB 354
A25WBP 354
A25WH 354
A2CBGB 330
A2RB 347
A2RBP 347
A30W10B 354
A30W10BP 354
A30W5B 354
A30W5BLB 354
A30W5BP 354
A30WB 354
A30WBP 354
A31AB 347
A31ABP 347
A31RB 347
A31RBP 347
A32AB 347
A32ABP 347
A32GB 346
A32GBP 346
A32RB 347
A32RBP 347
A33GB 345
A33GBP 345
A35AEB 347
A35AEBP 347
A35R10WB 354
A35R10WBP 354
A35RB 347
A35W42B 354
A35W42BP 354
A35W5B 354
A35W5BP 354
A35WB 354
A35WBP 354
A36AB 347
A36ABP 347
A36R 348
A36RB 347
A36RBP 347
A36WRB 354
A36WRBP 354
A37RB 347
A37RBP 347
A38AB 347
A38ABP 347
A38RB 347
A38RBP 347
A39RB 347
A39RBP 347
A3TRSSB 330
A3TRSSBP 330
A400 355
A40RB 347
A40RBP 347
A40SRB 345
A40SRBP 345
A40W42B 354
A40W42BP 354
A40W5B 354
A40W5BP 354
A41CB 347
A41CBB 343
A41CBP 347
A41CRB 343
A42AB 347
A42ABP 347
A42GB 346
A42GBP 346
A42PMB 350
A42PMBP 350
A42RB 347
A42RBP 347
A43FMBB 346
A43RB 347
A43RBP 347
A44A500B 347
A44AB 347
A44ABP 347
A44GTB 346
A44GTBP 346
A44R500B 347
A44RB 347
A44RBP 347
A45BB 333
A45BBP 333
A45CB 350
A45CBP 350
A45CGB 334
A45CGBP 334
A45GB 333
A45GBP 333
A45PB 352
A45PBP 352
A45PMB 352
A45PMBP 352
A45PS 352
A45SB 333
A45SBP 333

A46GB..... 333
A46GBP..... 333
A46P135B..... 351
A46P36B..... 351
A46P75B..... 351
A46PB..... 351
A46PBB..... 351
A46PBBP 351
A46PBP..... 351
A46PPG 351
A46PPGP 351
A46PS..... 351
A47PB..... 352
A47PBB..... 352
A47PBBP 352
A47PBP..... 352
A47PS..... 352
A48CB..... 343
A48CBP..... 343
A48TC 353
A49PB..... 350
A49PBB..... 350
A49PBBP 350
A49PBP..... 350
A4TC4WB..... 353
A4TC4WBP..... 353
A52AB 347
A52ABP 347
A52GB..... 346
A52GBP..... 346
A52RB..... 347
A52RBP 347
A53GB..... 330
A53GBP..... 330
A54GB..... 330
A54GBP..... 330
A54GK..... 330
A54GKP 330
A55CB..... 330
A55CBP..... 330
A55GB..... 331
A55GBP..... 331
A55GK..... 331
A55GKP 331
A56GB..... 331
A56GBP..... 331
A57CB..... 332
A57CBP..... 332
A57CCB..... 353
A57CCBP..... 353
A57GB..... 331
A57GBP..... 331
A57GK..... 331
A57GKP 331
A57WB 353
A57WBP 353
A57WH..... 353
A58GB..... 331
A58GBP..... 331
A5TRSSB 334
A5TRSSBP 334
A60GB..... 335
A60GBP..... 335
A60RB..... 347
A60RBP 347
A61EZPG..... 349
A64BB..... 343
A64BBP..... 343
A64CRB..... 343
A65B..... 338
A65BP..... 338
A65P..... 349
A65PB..... 338
A65PBP..... 338
A65PBPG 338
A65PBPGP 338
A65PRXB 338
A65PRXBP 338
A65PS..... 338
A65TB 338
A65TBP 338
A66AB 348
A66ABP 348
A66GB..... 346
A66GBP..... 346
A66PB..... 338
A66PBP..... 338
A66RB..... 348
A66RBP 348
A67BB..... 338
A67BBP..... 338
A67CB..... 338
A67CBP..... 338
A67CBPG..... 338
A67CBPGP 338
A67P10G..... 338
A67P10GP 338
A68AB 348
A68ABP 348
A68P..... 349
A68P1B..... 338
A68PB..... 338
A68PBP..... 338
A68RB..... 348
A68RBP 348
A68SSB 343
A68SSBP 343
A69CB..... 343
A69CBP..... 343
A69GB..... 346
A69GBP..... 346
A69NCCB 343
A69RXCB 343
A69RXCBP 343
A6TC4WB..... 353
A6TC4WBP..... 353
A6TC5B 353
A700..... 355
A70ECBB..... 344
A70ECCRB..... 344
A70GB..... 335
A70GBD..... 335
A70GBDP..... 335
A70GBP..... 335
A71C1BAWN..... 344
A71CBAWN..... 344
A71CBAWNP..... 344
A71CCBWAN 344
A73GB..... 346
A73GBP..... 346
A75TB 353
A75TBP 353
A75TC 353
A75TC6 353
A76GB..... 346
A77S1B 335
A77S1BP..... 335
A78CB1 336
A78CB1P..... 336
A78NCCB 336
A78NCCBB 336
A78RXB 336
A78RXBP 336
A79CB..... 344
A79CBP..... 344
A7TRSSB 336
A7TRSSBP 336
A7W6FTB 353
A7W8FTB 353
A7WCB 353
A7WCBP 353
A80GB..... 335
A830B..... 350
A839B..... 350
A86PB..... 351
A86PBP..... 351
A8R..... 348
A8RB..... 347
A8RBP 347
A8RK..... 348
A90AB 348
A90ABP 348
A90CB..... 337
A90GB..... 346
A90P1B..... 355
A90PB..... 355
A90RB..... 348
A90RBP 348
A91AB 260
A91ABP 260
A91BB..... 337
A91BBP..... 337
A91BOB..... 337
A91BOBP 337
A91BS 337
A91CB..... 337
A91CBP..... 337
A91G15B1..... 337
A91G15B1P..... 337
A91GB..... 337
A91GBP..... 337
A91GOB..... 337
A91GOBP 337
A91GZB..... 337
A91GZBP..... 337
A91LRW..... 349
A91LRWP 349
A91LW..... 349
A91LWP..... 349
A91OB..... 337
A91OBP..... 337
A91RB..... 260
A91RBP 260
A93PB..... 351
A93PBP..... 351
A94VB 344
A94VBP 344
A9R..... 348
A9RB..... 347
A9RBP 347
ACP5B..... 328
ACP5BP..... 328
ACP5S..... 328
ACP7B..... 328
ACP7BP..... 328
ACP7S..... 328
ADH55B..... 357
AIL21B 348
AIL21BP 348
AL145PWTB..... 352
AL145PWTBP..... 352
AL16RB..... 347
AL16RBP..... 347
AL17RB..... 347
AL17RBP..... 347
AL421PG..... 351
AL42PB..... 351
AL42PBP..... 351
AL42PG..... 351
AL42PGP..... 351
AL45PWTB..... 352
AL45PWTBP..... 352
AL82AB 131
AL82ABP 131
AL82RB..... 131
AL82RBP..... 131
AL90AB 132
AL90ABP 132
AL90AK 132
AL90AS..... 132
AL90RB..... 132
AL90RBP..... 132
AL90RCB..... 132
AL90RCBP..... 132
AL90RK..... 132
AL90RS 132
AL91A1224B 131
AL91AB 131
AL91ABP 131
AL91CAB..... 131
AL91CABP 131
AL91RB..... 131
AL91RBP..... 131
AL9RB..... 348

AL9RBP 348
ALEDFB 356
ALEDFBP 356
ALEDFS 356
ALEDRST1B 355
ALEDRST1BP 355
ALEDRST2B 355
ALEDRST2BP 355
APL1AB 348
APL1ABP 348
APL1CB 348
APL1CBP 348
APL5AB 348
APL5ABP 348
APL5CB 348
APL5CBP 348
APLL11AB 348
APLL11CB 348
ARVIL35B 348
ARVIL35BP 348
AST60B 348
AST60BP 348
AST61B 348
AST61BP 348
BA44FNL 267
BA44FNLP 267
BA44FNR 267
BA44FNRP 267
BA65ARLB 258
BA65ARLBP 258
BA65ARRB 258
BA65ARRBP 258
BK20BB 345
BK20BBP 345
BK21BB 350
BK31BB 340
BK31BBP 340
BK42CB 344
BK42CBP 344
BK45BB 333
BK45BBP 333
BK53BB 330
BK53BBP 330
BK5557GB 330
BK5557GBP 330
BK55BB 332
BK55BBP 332
BK57BB 332
BK57BBP 332
BK66D1B 344
BK66D1BP 344
BK66DB 344
BK66DBP 344
BK70B 335
BK70BB 335
BK70BBP 335
BU11CS 248
BU33CB 249
BU33CBP 249
BU33CRX24LB 249
BU33CRX24LBP 249
BU33CRXLB 249
BU33CRXLBP 249
BU41CB 248
BU41CBP 248
BU44CB 249
BU44CBP 249
BU45CB 249
BU45CBP 249
BU49CB 249
BU49CBP 249
BU64CB 249
BU64CBP 249
BU70CB 249
BU70CBP 249
BU74CB 249
BU74CBP 249
BUL002CB 87
BUL002CBP 87
BUL002CM3B 87
BUL002CM3BP 87
BUL003C1224B 81
BUL003C1224BP 81
BUL003CB 81
BUL003CBP 81
BUL003CKB 81
BUL003CKBP 81
BUL06C1224B 80
BUL06C1224BP 80
BUL06CB 80
BUL06CBP 80
BUL06CFB 80
BUL06CFBP 80
BUL06CFMB 80
BUL06CFMBP 80
BUL06CK1MB 80
BUL06CK1MBP 80
BUL06CKB 80
BUL06CKBP 80
BUL06CMB 80
BUL06CMBP 80
BUL101CB 78
BUL101CBP 78
BUL101CKB 78
BUL101CKBP 78
BUL10CB 85
BUL10CBP 85
BUL111CB 84
BUL111CBP 84
BUL11CB 79
BUL11CBP 79
BUL11CBX 79
BUL11CBXP 79
BUL11CKB 79
BUL11CKBP 79
BUL11CM24B 79
BUL11CM24BP 79
BUL11CMB 79
BUL11CMBP 79
BUL12C1224B 86
BUL12C1224BP 86
BUL12CB 86
BUL12CB1FPG 86
BUL12CB1FPGP 86
BUL12CBP 86
BUL12CFB 86
BUL12CFBP 86
BUL12CKB 86
BUL12CKBP 86
BUL12CSB 86
BUL12CSBP 86
BUL13CB 179
BUL13CBP 179
BUL22CB 85
BUL22CBP 85
BUL23C24B 82
BUL23C24BP 82
BUL23CB 82
BUL23CBP 82
BUL24CB 88
BUL24CBP 88
BUL28CLPB 181
BUL28CLPBP 181
BUL35CB 88
BUL35CBP 88
BUL43CB 179
BUL43CBK 179
BUL43CBKP 179
BUL43CBP 179
BUL52CB 85
BUL52CBP 85
BUL53CB 82
BUL53CBP 82
BUL602CB 83
BUL602CBP 83
BUL602CRB 83
BUL602CRBP 83
BUL603CB 77
BUL603CBP 77
BUL603CRB 77
BUL603CRBP 77
BUL69CB 180
BUL69CBMCV2B 180
BUL69CBMCV2BP 180
BUL69CBP 180
BUL69CPG 180
BUL69CPGP 180
BUL72CB 180
BUL72CBGK 180
BUL72CBGKP 180
BUL72CBP 180
BUL73CB 181
BUL73CBP 181
BUL74CBK 180
BUL74CBKP 180
BUL78C3MB 181
BUL78C3MBP 181
BUL78CB 181
BUL78CBP 181
BUL78CEZB 181
BUL78CEZBP 181
BUL90C24B 88
BUL90C24BP 88
BUL90CB 88
BUL90CBP 88
CB11AB 273
CB11AS 273
CB11AS6 273
CB11WAB 273
CB11WABP 273
CB15AK 273
CB20AB 274
CB20ABP 274
CB20AS 274
CB22AB 274
CB22ABP 274
CB22AS 274
CB22RB 274
CB22RBP 274
CBL22AB 160
CBL22ABP 160
CBL22AS 160
CBL22CAB 160
CBL22CABP 160
CBL22RB 160
CBL22RBP 160
DH55 357
DH55P 357
DL16CC 293
DL16WC 293
DL55CS 293
DLL50CB 222
DLL50CBP 222
DLL50CC 222
FTL42A1224B 14
FTL42A1224BP 14
FTL53ALCPG 14
FTL53ALCPGP 14
HLL70HLB 2
HLL70HLBP 2
HLL70HLS 2
HLL78LB 4
HLL78LBP 4
HLL78LS 4
HLL79HB 4
HLL79HBP 4
HLL79HS 4
HLL88LB 5
HLL88LBP 5
HLL89HB 5
HLL89HBP 5
HLL90HLB 5
HLL90HLBP 5
HLL93HLB 3
HLL93HLBP 3
HLL93HLS 3
IL21CB 289
IL21CBP 289
IL21CPG 289
IL21CS 289
IL21CS6 289
IL31CS 289
IL61CB 290
IL61CBP 290

IL91CB 290
IL91CBP 290
ILL01RB 182
ILL01RBP 182
ILL06COB 182
ILL06COBP 182
ILL07COB 182
ILL07COBP 182
ILL08COB 183
ILL08COBP 183
ILL08COPG 183
ILL08COPGP 183
ILL10CCB 183
ILL10CCBP 183
ILL11CCB 184
ILL11CCBP 184
ILL124CPG 186
ILL124CPGP 186
ILL21CB 185
ILL21CBP 185
ILL21CTPB 185
ILL22C1224B 185
ILL22C1224BP 185
ILL22CB 185
ILL22CBB 185
ILL22CBBP 185
ILL22CBP 185
ILL22CFS 185
ILL22CHB 185
ILL22CHBP 185
ILL24CB 186
ILL24CBP 186
ILL24CPG 186
ILL28CMB 183
ILL28CMBP 183
ILL28CMPG 183
ILL28CMPGP 183
ILL29CB 187
ILL29CBP 187
ILL29CFB 187
ILL29CFBP 187
ILL30CBB 188
ILL30CBBP 188
ILL31CB 188
ILL31CBP 188
ILL32CB 188
ILL32CBP 188
ILL32CPG 188
ILL33CB 189
ILL33CBP 189
ILL35CB 188
ILL35CBP 188
ILL36CB 189
ILL36CBP 189
ILL36CPG 189
ILL36CPGP 189
ILL38CMB 190
ILL38CMBP 190
ILL39CB 191
ILL39CBP 191
ILL39RCB 191
ILL45CB 191
ILL45CBP 191
ILL46CB 192
ILL46CBP 192
ILL48CB 192
ILL70ABBAWN 194
ILL70ABBAWNP 194
ILL70C24B 193
ILL70C24BP 193
ILL70CB 193
ILL70CBAWN 194
ILL70CBAWNFS 194
ILL70CBAWNP 194
ILL70CBBAWN 194
ILL70CBBAWNP 194
ILL70CBP 193
ILL70CBSBAWN 194
ILL70CBSBAWNP 194
ILL70CCSBAWN 194
ILL70CCSBAWNP 194
ILL70CSB 193
ILL70CSBP 193
ILL71C1BAWN 194
ILL71CB 193
ILL71CBAWN 194
ILL71CBAWNFS 194
ILL71CBAWNP 194
ILL71CBP 193
ILL71CPG 193
ILL71CPGP 193
ILL71CSB 193
ILL71CSBP 193
ILL72CB 193
ILL72CBP 193
ILL85CB 195
ILL85CBP 195
ILL86BCB 195
ILL86BCBP 195
ILL86CB 195
ILL86CBP 195
ILL87CB 196
ILL87CBP 196
ILL91CB 196
ILL91CBP 196
ILL91CPG 196
ILL91CPGP 196
LM315BB 197
LM315BBP 197
LM835CB 197
LM835CBP 197
LP10S 340
LP10SB 340
LP10SBP 340
LP11CB 278
LP11CBP 278
LP11CPG 278
LP11CPGP 278
LP11CS 278
LP15S 340
LP15SB 340
LP15SBP 340
LP20SB 340
LP20SBP 340
LP21CB 278
LP21CBP 278
LP21CS 278
LP21CS6 278
LP25SB 339
LP25SBP 339
LP25SGGB 339
LP26SKB 285
LP26SKBP 285
LP31CB 279
LP31CBP 279
LP31CPG 279
LP31CPGP 279
LP31CS 279
LP31SB 340
LP31SBP 340
LP35BB 340
LP35BBP 340
LP41CB 280
LP41CBP 280
LP41CS 280
LP41CS6 280
LP51CB 280
LP51CBP 280
LP52CB 281
LP52CBP 281
LP52HP 350
LP52HPP 350
LP54CB 281
LP54CBP 281
LP55CB 281
LP55CBP 281
LP56CB 282
LP56CBP 282
LP5SB 340
LP5SBP 340
LP65CB 282
LP65CBP 282
LP65CS 282
LP71CB 283
LP71CBP 283
LP71CS 283
LP81BB 283
LP81BBP 283
LP81BPG 283
LP81BPGP 283
LP81GB 283
LP91CB 285
LP91CBP 285
LP91CS 285
LP95CBF 284
LP97CB 284
LP97CBP 284
LPB31CPG 279
LPB31CPGP 279
LPL11CB 170
LPL11CBP 170
LPL11CPG 170
LPL11CPGP 170
LPL12CB 171
LPL12CBP 171
LPL12CKF2B 171
LPL12CKF2BP 171
LPL12CKM2B 171
LPL12CKM2BP 171
LPL12CKMB 171
LPL12CKMBP 171
LPL12CPGB 171
LPL12CPGBP 171
LPL21CB 172
LPL21CBP 172
LPL26SKB 178
LPL26SKBP 178
LPL31C1PG 172
LPL31CB 172
LPL31CBP 172
LPL31CEZB 172
LPL31CEZBP 172
LPL31CPG 172
LPL31CPGP 172
LPL31CS 172
LPL31CSB 172
LPL31CSBP 172
LPL41CB 173
LPL41CBP 173
LPL42CBF 173
LPL42CBFP 173
LPL43CB 173
LPL43CBP 173
LPL43CGBF 173
LPL43CGBFP 173
LPL55CB 173
LPL55CBP 173
LPL55CKB 173
LPL55CKBP 173
LPL55CPG 173
LPL55CPGP 173
LPL56CB 173
LPL56CBP 173
LPL57CB 174
LPL57CBP 174
LPL57CKB 174
LPL57CKBP 174
LPL58CB 175
LPL58CBP 175
LPL59CB 175
LPL59CBP 175
LPL61C24B 176
LPL61C24BP 176
LPL61C24PG 176
LPL65CB 176
LPL65CBB 176
LPL65CBBP 176
LPL65CBP 176
LPL81CB 177
LPL81CBP 177
LPL82CB 177
LPL82CBB 177
LPL91CAB 178
LPL91CABP 178

LPL91CB 178
LPL91CBP 178
LPL91CKALPB 178
LPL91CKALPBP 178
LPL91CPG 178
LPL91CPGP 178
LPL91CS 178
LPLB31CPG 172
MC11AB 261
MC11ABP 261
MC11AK 261
MC11AS 261
MC11RB 261
MC11RBP 261
MC11RS 261
MC21AS 262
MC21RS 262
MC22AB 262
MC22ABP 262
MC22RB 262
MC22RBP 262
MC25AB 252
MC25ABP 252
MC27AB 252
MC27ABP 252
MC30AB 261
MC30ABP 261
MC31A15B2 263
MC31AB 263
MC31ABP 263
MC31AS 263
MC31R15B2 263
MC31RB 263
MC31RBP 263
MC31RS 263
MC32AB 263
MC32ABB 263
MC32ABBP 263
MC32ABP 263
MC32ABS 263
MC32AS 263
MC32RB 263
MC32RBB 263
MC32RBBP 263
MC32RBP 263
MC32RBS 263
MC32RS 263
MC35AB 264
MC35ABP 264
MC35AEB 264
MC35AEBP 264
MC35AS 264
MC36AB 264
MC36ABP 264
MC36AS 264
MC36AS6 264
MC36RB 264
MC36RBP 264
MC36RS 264
MC36RS6 264
MC37AB 265
MC37ABP 265
MC38AB 265
MC38ABP 265
MC38RB 265
MC38RBP 265
MC42AB 266
MC42ABP 266
MC42AS 266
MC42RB 266
MC42RBP 266
MC42RS 266
MC441WB 267
MC442WB 267
MC44AB 267
MC44AB1 267
MC44AB1P 267
MC44ABP 267
MC44AS 267
MC44RB 267
MC44RB1 267
MC44RB1P 267
MC44RBP 267
MC44RS 267
MC48AB 266
MC48ABP 266
MC48APG 266
MC48APGP 266
MC48RB 266
MC48RBP 266
MC48RPG 266
MC48RPGP 266
MC505ABSB 254
MC505ABSBP 254
MC52AB 253
MC52ABP 253
MC52AXB 253
MC52AXBP 253
MC52RB 253
MC52RBP 253
MC52RXB 253
MC52RXBP 253
MC53AB 254
MC53ABP 254
MC53ABSB 254
MC53ABSBP 254
MC53AKB 254
MC53AKBP 254
MC53AS 254
MC53RB 254
MC53RBP 254
MC53RKB 254
MC53RKBP 254
MC53RS 254
MC54AB 254
MC54ABP 254
MC54RB 254
MC54RBP 254
MC55AB 255
MC55ABP 255
MC55RB 255
MC55RBP 255
MC56AB 256
MC56ABP 256
MC56RB 256
MC56RBP 256
MC57AB 255
MC57ABP 255
MC57AS 255
MC57RB 255
MC57RBP 255
MC57RS 255
MC58AS 268
MC58RS 268
MC61ABKB 257
MC61ABKBP 257
MC65AB 259
MC65ABP 259
MC65ARB 258
MC65ARBP 258
MC65AS 259
MC65RB 259
MC65RBP 259
MC65RS 259
MC66AB 268
MC66ABP 268
MC66AS 268
MC66HAB 268
MC66HABP 268
MC66RB 268
MC66RBP 268
MC66RS 268
MC67AB 259
MC67ABP 259
MC67AK 259
MC67ARB 258
MC67ARBP 258
MC67RB 259
MC67RBP 259
MC67RK 259
MC68AB 269
MC68ABP 269
MC68AS 269
MC68RB 269
MC68RBP 269
MC68RS 269
MC70AB 269
MC70ABP 269
MC70AS 269
MC70RB 269
MC70RBP 269
MC70RS 269
MC71AS 270
MC71RS 270
MC76AB 270
MC76ABP 270
MC77RB 275
MC77RBP 275
MC81AB 271
MC81ABP 271
MC81RB 271
MC81RBP 271
MC82AB 271
MC82ABP 271
MC82RB 271
MC82RBP 271
MC90AS 260
MC90RS 260
MC91AB 260
MC91ABP 260
MC91AS 260
MC91RS 260
MC92AB 260
MC92ABP 260
MC92AS 260
MC92RB 260
MC92RBP 260
MC92RS 260
MC93AB 275
MC93ABP 275
MC93R2PG 275
MC93R2PGP 275
MC93RB 275
MC93RBP 275
MC93RK 275
MC93RPG 275
MC93RPGP 275
MC94RB 276
MC94RBP 276
MC95AB 272
MC95ABP 272
MC95APG 272
MC95AS 272
MC95RB 272
MC95RBP 272
MC95RS 272
MC97R70PG 276
MC97RB 276
MC97RBP 276
MC97RK 276
MC99AB 277
MC99ABP 277
MC99AK 277
MC99RB 277
MC99RBP 277
MC99RK 277
MCL002AXB 130
MCL002RXB 130
MCL0030ABB 144
MCL0030RBB 144
MCL0032ABB 148
MCL0032ABBP 148
MCL0032ABS 148
MCL0032RBB 148
MCL0032RBBP 148
MCL0032RBS 148
MCL0039ABB 145
MCL0039ABBP 145
MCL0039RBB 145
MCL0039RBBP 145
MCL10AB 112
MCL10ABP 112
MCL10ACK12JPG 112
MCL10ACK3L12B 163

MCL10ACKA12B 112
MCL10ACKA12PG 112
MCL10ACKB 112
MCL10ACKPG 112
MCL10ACKPGP 112
MCL10AK1224B 112
MCL10AK1224BP 112
MCL10AK12JPG 112
MCL10AK1FPG 112
MCL10AKA10PG 112
MCL10AKA12B 112
MCL10AKB 112
MCL10AKBP 112
MCL10AKL12B 112
MCL10AKL12PG 112
MCL10AKL12PGN 112
MCL10AKL18JPG 112
MCL10CAK14B 112
MCL10CAK14BP 112
MCL10CRK14B 113
MCL10CRK14BP 113
MCL10RB 113
MCL10RBP 113
MCL10RCK12JPG 113
MCL10RCK3L12B 163
MCL10RCKA12B 113
MCL10RCKA12PG 113
MCL10RCKB 113
MCL10RCKPG 113
MCL10RCKPGP 113
MCL10RK1224B 113
MCL10RK1224BP 113
MCL10RK12JPG 113
MCL10RK1FPG 113
MCL10RKA10PG 113
MCL10RKA12B 113
MCL10RKB 113
MCL10RKBP 113
MCL10RKDTPG 113
MCL10RKDTPGP 113
MCL10RKL12B 113
MCL10RKL12PG 113
MCL10RKL12PGN 113
MCL10RKL18JPG 113
MCL110AB 109
MCL110ABP 109
MCL110AKB 109
MCL110AKBF 109
MCL110AKBFP 109
MCL110AKBP 109
MCL110RB 109
MCL110RBP 109
MCL110RKB 109
MCL110RKBF 109
MCL110RKBFP 109
MCL110RKBP 109
MCL111AB 110
MCL111ABP 110
MCL111AKB 110
MCL111AKBP 110
MCL111AKPG 110
MCL111AKPGP 110
MCL111RB 110
MCL111RBP 110
MCL111RKB 110
MCL111RKBP 110
MCL111RKPG 110
MCL111RKPGP 110
MCL112AKB 111
MCL112AKBP 111
MCL112RB 111
MCL112RBP 111
MCL112RKB 111
MCL112RKBP 111
MCL11A24KB 114
MCL11AB 114
MCL11ABP 114
MCL11AHPG 114
MCL11AHPGP 114
MCL11AK12B 114
MCL11AK12PG 114
MCL11AKAB 114
MCL11AKABP 114
MCL11AKB 114
MCL11AKBF 114
MCL11AKBFP 114
MCL11AKBP 114
MCL11AKPRB 114
MCL11AKPVG 114
MCL11AKPVGP 114
MCL11APG 114
MCL11APGP 114
MCL11CAB 114
MCL11CABP 114
MCL11CAKB 114
MCL11CAKBF 114
MCL11CAKBP 114
MCL11CAKPG 114
MCL11CAKPGP 114
MCL11CRB 114
MCL11CRBP 114
MCL11CRKB 114
MCL11CRKBF 114
MCL11CRKBP 114
MCL11CRKPG 114
MCL11CRKPGP 114
MCL11R24KB 114
MCL11RB 114
MCL11RBP 114
MCL11RHPG 114
MCL11RHPGP 114
MCL11RK12B 114
MCL11RK12PG 114
MCL11RKAB 114
MCL11RKB 114
MCL11RKBF 114
MCL11RKBFP 114
MCL11RKBP 114
MCL11RKPV4G 114
MCL11RKPVG 114
MCL11RKPVGP 114
MCL11RPG 114
MCL11RPGP 114
MCL11SAB 108
MCL11SABP 108
MCL11SACKB 108
MCL11SACKBP 108
MCL11SAK1B 108
MCL11SAK1BP 108
MCL11SAKB 108
MCL11SAKBP 108
MCL11SRB 108
MCL11SRBP 108
MCL11SRCKB 108
MCL11SRCKBP 108
MCL11SRK1B 108
MCL11SRK1BP 108
MCL11SRKB 108
MCL11SRKBP 108
MCL121AK9PVG 110
MCL121AK9PVGP 110
MCL121RK9PVG 110
MCL121RK9PVGP 110
MCL12AB 115
MCL12ABP 115
MCL12AK 115
MCL12AKB 115
MCL12AKBP 115
MCL12AKPG 115
MCL12ARLB 116
MCL12ARLBP 116
MCL12ARRB 116
MCL12ARRBP 116
MCL12CA2RLB 116
MCL12CA2RRB 116
MCL12RB 115
MCL12RBP 115
MCL12RK 115
MCL12RK3B 164
MCL12RK3BP 164
MCL12RK3RMB 164
MCL12RKB 115
MCL12RKBP 115
MCL12RKPG 115
MCL131A210B 139
MCL131A2B 139
MCL131A2BP 139
MCL131AC210B 139
MCL131CA3B 139
MCL131CR3B 139
MCL131R210B 139
MCL131R2B 139
MCL131R2BP 139
MCL131RC210B 139
MCL13A21PG 139
MCL13A2B 139
MCL13A2BP 139
MCL13A2MB 139
MCL13A2MBP 139
MCL13APG 139
MCL13APGP 139
MCL13AS 139
MCL13ATRS 139
MCL13CA2B 139
MCL13CA2BP 139
MCL13CA3B 139
MCL13CA3BP 139
MCL13CR2B 139
MCL13CR2BP 139
MCL13R21PG 139
MCL13R2B 139
MCL13R2BP 139
MCL13R2MB 139
MCL13R2MBP 139
MCL13RS 139
MCL13RTRS 139
MCL14A12GB 140
MCL14A12GBP 140
MCL14AB 140
MCL14ABF 140
MCL14ABFP 140
MCL14ABP 140
MCL14AGB 140
MCL14AGBP 140
MCL14AGPB 140
MCL14AGPBP 140
MCL14CABF 140
MCL14CABFP 140
MCL14CAGB 140
MCL14CRBF 140
MCL14CRBFP 140
MCL14CRGB 140
MCL14R2B 140
MCL14R2BP 140
MCL14RB 140
MCL14RBF 140
MCL14RBFP 140
MCL14RBP 140
MCL14RGB 140
MCL14RGBP 140
MCL14RPG 140
MCL14RPGP 140
MCL155AB 118
MCL155ABP 118
MCL155RB 118
MCL155RBP 118
MCL157AB 125
MCL157ABP 125
MCL157RB 125
MCL157RBP 125
MCL15AKPG 141
MCL15AKPGP 141
MCL15APG 141
MCL15APGP 141
MCL15RKPG 141
MCL15RKPGP 141
MCL15RPG 141
MCL15RPGP 141
MCL165AB 133
MCL165ABP 133
MCL165RB 133
MCL165RBP 133
MCL17AB 143
MCL17ABB 143

MCL17ABP 143
MCL17CAB 143
MCL17CABP 143
MCL17CRB 143
MCL17CRBP 143
MCL17RB 143
MCL17RBB 143
MCL17RBP 143
MCL180ARB 161
MCL180ARBP 161
MCL180ARFK 161
MCL181ARCRB 162
MCL181ARCRGB 162
MCL181ARCRL12B 162
MCL19AB 143
MCL19ABP 143
MCL19CAB 143
MCL19CABP 143
MCL19CRB 143
MCL19CRBP 143
MCL19RB 143
MCL19RBP 143
MCL21AB 117
MCL21ABP 117
MCL21AKRGVB 114
MCL21AKRYVB 114
MCL21RB 117
MCL21RBP 117
MCL21RKPV4G 114
MCL21RKPVG 114
MCL22RK3B 164
MCL22RK4B 164
MCL22RK5B 164
MCL23AB 117
MCL23ABP 117
MCL23RB 117
MCL23RBP 117
MCL290APG 142
MCL290RPG 142
MCL299AB 142
MCL299ABP 142
MCL299RB 142
MCL299RBP 142
MCL31AB 146
MCL31ABP 146
MCL31RB 146
MCL31RBP 146
MCL31RPG 146
MCL32AB 147
MCL32ABB 147
MCL32ABBP 147
MCL32ABP 147
MCL32ABS 147
MCL32AS 147
MCL32ATB 147
MCL32ATBP 147
MCL32RB 147
MCL32RBB 147
MCL32RBBP 147
MCL32RBP 147
MCL32RBS 147
MCL32RS 147
MCL35A32G 149
MCL35A32GP 149
MCL35AEB 149
MCL35AEBP 149
MCL36AB 150
MCL36ABP 150
MCL36AS 150
MCL36AS6 150
MCL36RB 150
MCL36RBP 150
MCL40AB 151
MCL40ABP 151
MCL40APB 151
MCL40APBP 151
MCL40AS 151
MCL40RB 151
MCL40RBP 151
MCL40RS 151
MCL44AB 151
MCL44AB1 151
MCL44AB1P 151
MCL44ABP 151
MCL44RB 151
MCL44RB1 151
MCL44RB1P 151
MCL44RBP 151
MCL45AB 152
MCL45ABP 152
MCL45AS 152
MCL45RB 152
MCL45RBP 152
MCL45RS 152
MCL46AB 152
MCL46ABP 152
MCL46RB 152
MCL46RBP 152
MCL48AB 154
MCL48ABP 154
MCL48AKB 154
MCL48AKBP 154
MCL48CAB 154
MCL48CABP 154
MCL49AB 153
MCL49ABP 153
MCL49RB 153
MCL49RBP 153
MCL505ABSB 120
MCL505ABSBP 120
MCL505GABSB 120
MCL505GABSBP 120
MCL50AB 123
MCL50ABP 123
MCL50RB 123
MCL50RBP 123
MCL527AB 127
MCL527ABP 127
MCL527AFB 127
MCL527AFBP 127
MCL527AK 127
MCL527AK6 127
MCL527AMB 127
MCL527AS 127
MCL527RB 127
MCL527RBP 127
MCL527RFB 127
MCL527RFBP 127
MCL527RK 127
MCL527RK6 127
MCL527RMB 127
MCL527RS 127
MCL52AB 124
MCL52ABP 124
MCL52AHXB 122
MCL52AHXBP 122
MCL52AMB 124
MCL52AMBP 124
MCL52RB 124
MCL52RBP 124
MCL52RMB 124
MCL52RMBP 124
MCL54AB 124
MCL54ABP 124
MCL54RB 124
MCL54RBP 124
MCL55A1224B 119
MCL55A1224BP 119
MCL55AB 119
MCL55ABP 119
MCL55ACB 119
MCL55ACBP 119
MCL55AK 119
MCL55FRB 119
MCL55FRBP 119
MCL55R1224B 119
MCL55R1224BP 119
MCL55RB 119
MCL55RBP 119
MCL55RCB 119
MCL55RCBP 119
MCL55RK 119
MCL56AB 121
MCL56ABP 121
MCL56AFB 121
MCL56AFBP 121
MCL56AFMB 121
MCL56AK 121
MCL56AK6 121
MCL56AS 121
MCL56RB 121
MCL56RBP 121
MCL56RFB 121
MCL56RFBP 121
MCL56RFMB 121
MCL56RK 121
MCL56RK6 121
MCL56RMB 121
MCL56RS 121
MCL57A24B 126
MCL57A24BP 126
MCL57AB 126
MCL57ABP 126
MCL57ACB 126
MCL57ACBP 126
MCL57AK 126
MCL57R1224B 126
MCL57R1224BP 126
MCL57RB 126
MCL57RBP 126
MCL57RCB 126
MCL57RCBP 126
MCL57RK 126
MCL57RKB 126
MCL57RKBP 126
MCL58AB 128
MCL58ABP 128
MCL58ACB 128
MCL58ACBP 128
MCL58AMFB 128
MCL58AMFBP 128
MCL58APMB 128
MCL58RB 128
MCL58RBP 128
MCL58RMFB 128
MCL58RMFBP 128
MCL58RPMB 128
MCL59A1224B 129
MCL59A1224BP 129
MCL59AB 129
MCL59ABP 129
MCL59R1224B 129
MCL59R1224BP 129
MCL59RB 129
MCL59RBP 129
MCL61AB 135
MCL61ABP 135
MCL61AK 135
MCL61AR26BK 137
MCL61AR26BKP 137
MCL61ARB 137
MCL61ARBP 137
MCL61AS 135
MCL61RB 135
MCL61RBP 135
MCL61RK 135
MCL61RS 135
MCL63AB 136
MCL63ABP 136
MCL63CAB 136
MCL63CABP 136
MCL63CRB 136
MCL63CRBP 136
MCL63RB 136
MCL63RBP 136
MCL65A24B 134
MCL65A24BP 134
MCL65AB 134
MCL65ABP 134
MCL65AKB 134
MCL65ARB 137
MCL65ARBP 137
MCL65CAB 134
MCL65CABP 134

MCL65CARB..... 137
MCL65CARBP..... 137
MCL65CRB 134
MCL65CRBP 134
MCL65R24B 134
MCL65R24BP 134
MCL65RB 134
MCL65RBP 134
MCL65RKB 134
MCL66A24B..... 155
MCL66A24BP..... 155
MCL66AB..... 155
MCL66ABP..... 155
MCL66APG..... 155
MCL66APGP..... 155
MCL66AS 155
MCL66CAB..... 155
MCL66CABP..... 155
MCL66CRB 155
MCL66CRBP 155
MCL66R24B 155
MCL66R24BP 155
MCL66RB 155
MCL66RBP 155
MCL66RPG 155
MCL66RPGP 155
MCL66RS..... 155
MCL67AB..... 134
MCL67ABP..... 134
MCL67ARB..... 137
MCL67ARBP..... 137
MCL67RB 134
MCL67RBP 134
MCL70RB 166
MCL70RBF2..... 166
MCL70RBF2P 166
MCL70RBP 166
MCL70RCB 166
MCL70RCBP 166
MCL70RCGB 166
MCL70RS..... 166
MCL71RB 156
MCL71RBP 156
MCL73AB..... 154
MCL73ABP..... 154
MCL73RB 154
MCL73RBP 154
MCL75AB..... 134
MCL75ABP..... 134
MCL75RB 134
MCL75RBP 134
MCL76AB..... 156
MCL76ABP..... 156
MCL76AS 156
MCL76RB 156
MCL76RBP 156
MCL76RS..... 156
MCL77AB..... 134
MCL77ABP..... 134
MCL77RB 134
MCL77RBP 134
MCL78RB 166
MCL78RBP 166
MCL81AB..... 158
MCL81ABP..... 158
MCL81RB 158
MCL81RBP 158
MCL82AB..... 157
MCL82RB 157
MCL83RB 167
MCL83RBP 167
MCL83RK 167
MCL84RB 169
MCL84RBP 169
MCL85AB..... 158
MCL85ABP..... 158
MCL85AS 158
MCL85RS..... 158
MCL86AB..... 159
MCL86ABP..... 159
MCL86RB 159
MCL86RBP 159
MCL88RCB 166
MCL88RCBP 166
MCL90AS 131
MCL90RS..... 131
MCL914R1PG 168
MCL91AB..... 131
MCL91ABP..... 131
MCL91AK..... 131
MCL91RB 131
MCL91RBP 131
MCL91RK 131
MCL922RB 164
MCL922RBP 164
MCL93RB 168
MCL93RBP 168
MCL93RK 168
MCL93RPG 168
MCL93RPGP 168
MCL95AB..... 159
MCL95ABF 159
MCL95ABFP 159
MCL95ABP..... 159
MCL95AS 159
MCL95RB 159
MCL95RBF..... 159
MCL95RBFP 159
MCL95RBP 159
MCL95RS..... 159
MCL964RB 167
MCL96AB..... 131
MCL96ABP..... 131
MCL96RB 131
MCL96RBP 131
MCL97RB 169
MCL97RBP 169
MCL97RK 169
MCL97RPG 169
MCL97RPGP 169
MCL98RB 165
MCL98RBP 165
MCL98RBTKPG 165
MCL98RK 165
MCL98RL601B..... 165
MCL98RL60B..... 165
MCL99AB..... 138
MCL99ABP..... 138
MCL99AC1B..... 138
MCL99AC1BP..... 138
MCL99RB 138
MCL99RBP 138
MCL99RC1B 138
MCL99RC1BP 138
QH16CTS..... 291
QH16CTSP..... 291
QH36CTS..... 291
QH36CTSP..... 291
RB10A..... 292
RBL10AS 93
RBL10CA 92
RBL10CC..... 92
RBL13AB..... 94
RBL14AB..... 94
RC 320
RCP 320
RE10018T..... 326
RE10AB..... 323
RE10ABP..... 323
RE10AK..... 323
RE10ARFK..... 323
RE10RB 323
RE10RBP 323
RE10RK 323
RE11AB..... 323
RE11ABP..... 323
RE11RB 323
RE11RBP 323
RE12AK..... 323
RE12ARK 323
RE12RK 323
RE13AB..... 324
RE13ABP..... 324
RE13RB 324
RE13RBP 324
RE15AB..... 323
RE15ABP..... 323
RE15AK..... 323
RE15ARK 323
RE15RB 323
RE15RBP 323
RE15RK 323
RE18T..... 326
RE2018T..... 326
RE21AB..... 324
RE21ABP..... 324
RE21ARK 324
RE21AS 324
RE21RB 324
RE21RBP 324
RE21RS 324
RE21T..... 326
RE31AS 324
RE31RS 324
RE35AB..... 324
RE35ABP..... 324
RE35RB 324
RE35RBP 324
RE37AB..... 324
RE37ABP..... 324
RE37RB 324
RE37RBP 324
RE418T..... 326
RE52AB..... 323
RE52ARK 323
RE52RB 323
RT10A1B 325
RT10AB 325
RT10R1B..... 325
RT10RB..... 325
RT150W12B 326
RT150W12BP 326
RT150WBD..... 326
RT150WBDP 326
RT150Y1B..... 327
RT150Y1BP 327
RT150Y1DB..... 327
RT150Y1DBP..... 327
RT150Y2B..... 327
RT150Y2BP 327
RT150Y2DB..... 327
RT150Y2DBP..... 327
RT21AB 325
RT21RB..... 325
RTR0315066CB..... 326
RTR03150711CB..... 326
RTR03150711CBP 326
RTR1015066CB..... 326
RTR10150711CB..... 326
RTR10150WB 326
RTR10150WBP 326
RTR15066B..... 326
RTR15066BP 326
RTR15066PB 326
RTR15066PBP 326
RTR150711B..... 326
RTR150711BP 326
RTR150711PB 326
RTR150711PBP 326
RTRE150GB 327
RTRE150GBP 327
RTRE150OB 327
RTRE150OBP 327
RTRE150RB 327
RTRE150RBP 327
RV60BBK..... 320
RV60BBKP 320
RV60BK..... 320
RV60BKP 320
RVCST90BL..... 299
RVCST90BR 299
RVIL21 308
RVIL21P 308
RVIL21S..... 308

RVIL22 308
RVIL22P 308
RVIL22S 308
RVIL35 307
RVIL35P 307
RVILL33 306
RVILL33FS 306
RVILL33P 306
RVILL33PB 306
RVILL34 306
RVILL34FS 306
RVILL34P 306
RVILL39 304
RVILL39P 304
RVILL40 305
RVILL40FS 305
RVILL40P 305
RVPL1A 301
RVPL1AP 301
RVPL1C 301
RVPL1CP 301
RVPL3A 301
RVPL3AP 301
RVPL3C 301
RVPL3CFS 301
RVPL3CP 301
RVPL5A 302
RVPL5AB 302
RVPL5ABP 302
RVPL5AFS 302
RVPL5AP 302
RVPL5CB 302
RVPL5CBP 302
RVPL7A 302
RVPL7AB 302
RVPL7ABP 302
RVPL7AP 302
RVPL7C 302
RVPL7CB 302
RVPL7CBFS 302
RVPL7CBP 302
RVPL7CFS 302
RVPL7CP 302
RVPLL11AB 300
RVPLL11ABP 300
RVPLL11AFS 300
RVPLL11CB 300
RVPLL11CFS 300
RVPLL13AB 300
RVPLL13CB 300
RVPLL13CBP 300
RVPLL13CWB 300
RVSL21 303
RVSL21P 303
RVSL31 303
RVSL31P 303
RVST60 298
RVST60P 298
RVST60S 298
RVST61 298
RVST61P 298
RVST61S 298
RVSTB60 298
RVSTB60P 298
RVSTB61 298
RVSTB61P 298
RVSTL0060 297
RVSTL0060P 297
RVSTL0060RFK 297
RVSTL0061 297
RVSTL0061P 297
RVSTL10 294
RVSTL10K 294
RVSTL10P 294
RVSTL11 294
RVSTL11P 294
RVSTL20 295
RVSTL20K 295
RVSTL20P 295
RVSTL21 295
RVSTL21P 295
RVSTL60 296
RVSTL60P 296
RVSTL60S 296
RVSTL61 296
RVSTL61P 296
RVSTL61S 296
RVSTLB0060 297
RVSTLB0060P 297
RVSTLB0061 297
RVSTLB0061P 297
RVSTLB60 296
RVSTLB60FS 296
RVSTLB60P 296
RVSTLB61 296
RVSTLB61FS 296
RVSTLB61P 296
SLL15AC1B 95
SLL15ACC2B 95
SLL15ARC3B 95
SLL15C1B 95
SLL16C1B 96
SLL17AC1B 97
SLL17ACC2B 97
SLL17ARC3B 97
SLL17C1B 97
SLL22ACB 98
SLL22ACBP 98
SLL43AB1 89
SLL43AB1P 89
SLL43AB2 89
SLL43AB2P 89
SLL43AKB1 89
SLL43AKB1P 89
SLL43AKB2 89
SLL43AKB2P 89
SLL51ACB 99
SLL51ACBP 99
SLL51CB 99
SLL51CBP 99
SLL72AB1 90
SLL72AB1P 90
SLL72AB2 90
SLL72AB2P 90
SLL72AKB1 90
SLL72AKB1P 90
SLL72AKB2 90
SLL72AKB2P 90
SLL81ACB 100
SLL81ACBP 100
SLL81CB 100
SLL81CBP 100
SLL93AB 91
SLL93ABP 91
SLL93RB 91
SLL93RBP 91
ST16RB 243
ST16RBP 243
ST16RS 243
ST17RB 243
ST17RBP 243
ST17RS 243
ST20RS 238
ST21RS 238
ST24RB 238
ST24RBP 238
ST25RB 238
ST25RBP 238
ST26RPG 243
ST26RPGP 243
ST27RPG 243
ST27RPGP 243
ST2RB 241
ST2RBP 241
ST2RHB 241
ST31RS 246
ST33AB 233
ST33ABP 233
ST33RB 233
ST33RBP 233
ST34RB 233
ST34RBP 233
ST36RPG 244
ST36RPGP 244
ST36RS 244
ST37RPG 244
ST37RPGP 244
ST37RS 244
ST3RB 241
ST3RBP 241
ST3RHB 241
ST40RB 234
ST40RBP 234
ST40RS 234
ST42RB 234
ST42RBP 234
ST44AB 230
ST44ABP 230
ST44RB 230
ST44RBP 230
ST45AB 230
ST45ABP 230
ST45RB 230
ST45RBP 230
ST45RGB 230
ST45RGBP 230
ST45RK 230
ST45RS 230
ST46RB 230
ST46RBP 230
ST47RB 231
ST47RBP 231
ST47RKB 231
ST47RKBP 231
ST4RB 242
ST4RBP 242
ST4RS 242
ST51RB 237
ST51RBP 237
ST51RS 237
ST52AA 237
ST52AAP 237
ST52RA 237
ST52RB 237
ST52RBP 237
ST53AAB 237
ST53AABP 237
ST56RS 245
ST57RS 245
ST5RB 242
ST5RBP 242
ST5RS 242
ST60RB 246
ST60RBP 246
ST60RS 246
ST64RB 232
ST64RBP 232
ST65RB 232
ST65RBP 232
ST6RB 240
ST6RBP 240
ST6RPG 240
ST6RPGP 240
ST6RS 240
ST70AB 232
ST70ABP 232
ST70AS 232
ST70RB 232
ST70RBP 232
ST70RBTK 232
ST70RBTKP 232
ST70RK 232
ST70RS 232
ST74AB 232
ST74ABP 232
ST74RB 232
ST74RBP 232
ST75AB 232
ST75ABP 232
ST75AS 232
ST77AB 232
ST77ABP 232
ST7RB 240
ST7RBP 240

ST7RPG 240
ST7RPGP 240
ST7RS 240
ST8RB 239
ST8RBP 239
ST8RHB 239
ST8RS 239
ST90AB 235
ST90ABP 235
ST90RB 235
ST90RBP 235
ST92AB 236
ST92ABP 236
ST92RB 236
ST92RBP 236
ST9RB 239
ST9RBP 239
ST9RHB 239
ST9RS 239
STL0016RB 71
STL0016RBP 71
STL0016RP2G 71
STL0016RP2GP 71
STL0016RS 71
STL0017RB 71
STL0017RBP 71
STL0017RP2G 71
STL0017RP2GP 71
STL0017RS 71
STL002AB 38
STL002ABP 38
STL002RB 38
STL002RBP 38
STL002RFB 38
STL002RFBP 38
STL002RK 38
STL002RK2B 38
STL002RK2BP 38
STL002RMB 38
STL002RMBP 38
STL002RS 38
STL003A1224B 24
STL003A1224BP 24
STL003AB 24
STL003ABP 24
STL003R1224B 24
STL003R1224BP 24
STL003RB 24
STL003RBP 24
STL003RFB 24
STL003RFBP 24
STL003RFLB 24
STL003RFLBP 24
STL003RFMB 24
STL003RFMBP 24
STL003RK 24
STL003RMB 24
STL003RMBP 24
STL003RS 24
STL008RB 65
STL008RBP 65
STL008RPG 65
STL008RPGP 65
STL008RS 65
STL009RB 65
STL009RBP 65
STL009RPG 65
STL009RPGP 65
STL009RS 65
STL101AB 16
STL101ABP 16
STL101ACB 16
STL101ACBP 16
STL101R1224B 16
STL101R1224BP 16
STL101RB 16
STL101RBP 16
STL101RCB 16
STL101RCBP 16
STL101RCFB 17
STL101RCFBP 17
STL101RCFMB 17
STL101RCFMBP 17
STL101RCMB 16
STL101RCMBP 16
STL101RFB 17
STL101RFBP 17
STL101RFMB 17
STL101RFMBP 17
STL101RKB 16
STL101RKBP 16
STL101RMB 16
STL101RMBP 16
STL108RB 61
STL108RBP 61
STL109RB 61
STL109RBP 61
STL111AB 29
STL111ABP 29
STL111ACB 29
STL111ACBP 29
STL111R1224B 29
STL111R1224BP 29
STL111RB 29
STL111RBP 29
STL111RCB 29
STL111RCBP 29
STL111RCFB 30
STL111RCFBP 30
STL111RCFMB 30
STL111RCFMBP 30
STL111RCMB 29
STL111RCMBP 29
STL111RFB 30
STL111RFBP 30
STL111RFMB 30
STL111RFMBP 30
STL111RHB 29
STL111RHBP 29
STL111RMB 29
STL111RMBP 29
STL116RB 67
STL116RBP 67
STL117RB 67
STL117RBP 67
STL1211RCFHPG 9
STL1211RCFHPGP 9
STL12AB 35
STL12ABP 35
STL12R1224B 35
STL12R1224BP 35
STL12RB 35
STL12RBP 35
STL12RCB 35
STL12RCBP 35
STL12RCKB 35
STL12RCKBP 35
STL12RK 35
STL12RK2B 35
STL12RK2BP 35
STL12RK3B 35
STL12RK3BP 35
STL12RK4B 35
STL12RK4BP 35
STL12RKB 35
STL12RKBP 35
STL12RLVB 35
STL12RLVBP 35
STL12RMB 35
STL12RMBP 35
STL12RS 35
STL13AB 21
STL13ABP 21
STL13R1224B 21
STL13R1224BP 21
STL13RB 21
STL13RBP 21
STL13RFB 22
STL13RFBP 22
STL13RFHXB 22
STL13RFMB 22
STL13RFMBP 22
STL13RFS 22
STL13RGB 21
STL13RGBP 21
STL13RH1B 21
STL13RH1BP 21
STL13RH3B 21
STL13RH3BP 21
STL13RHBB 21
STL13RHBBP 21
STL13RK 21
STL13RKB 21
STL13RKBP 21
STL13RLVB 21
STL13RLVBP 21
STL13RMB 21
STL13RMB10GK 21
STL13RMB10GKP 21
STL13RMBP 21
STL13RS 21
STL14R1B 70
STL14R1BP 70
STL14RB 70
STL14RBP 70
STL153ARDBB 54
STL153ARDBBP 54
STL153ARPBB 54
STL153ARPBBP 54
STL15R1B 70
STL15R1BP 70
STL15RB 70
STL15RBP 70
STL161RB 58
STL161RBP 58
STL161RLB 58
STL161RLBP 58
STL16NTRB 69
STL16NTRBP 69
STL16RB 69
STL16RBP 69
STL16RS 69
STL175AMFB 41
STL175AMFBP 41
STL178RB 31
STL178RBP 31
STL178RCCFPB 31
STL178RCCFPBP 31
STL178RFPB 31
STL178RFPBP 31
STL178RK1B 31
STL178RK1BP 31
STL179RB 48
STL179RBP 48
STL17NTRB 69
STL17NTRBP 69
STL17RB 69
STL17RBP 69
STL17RS 69
STL190AB 56
STL190ABP 56
STL190RB 56
STL190RBP 56
STL190RPG 56
STL190RPGP 56
STL201RFMB 6
STL201RFMBP 6
STL201XR1224B 7
STL201XR1224BP 7
STL201XRB 7
STL201XRBP 7
STL201XRFHXB 8
STL201XRFHXBP 8
STL211XRB 10
STL211XRBP 10
STL211XRCB 10
STL211XRCBP 10
STL211XRFHB 11
STL211XRFHBP 11
STL211XRFHPG 11
STL211XRFHPGP 11
STL22AB 39
STL22ABP 39
STL22CCAB 39

STL22CCABP 39
STL22CCRB 39
STL22CCRBP 39
STL22RB 39
STL22RBH 39
STL22RBHP 39
STL22RBP 39
STL22RCB 39
STL22RCBP 39
STL23A24B 25
STL23A24BP 25
STL23AB 25
STL23ABP 25
STL23CCRB 25
STL23CCRBP 25
STL23R24B 25
STL23R24BP 25
STL23RB 25
STL23RBP 25
STL24AB 45
STL24ABP 45
STL24RB 45
STL24RBP 45
STL264RB 13
STL264RBP 13
STL264RCB 13
STL264RCBP 13
STL26RB 72
STL26RBP 72
STL27RB 72
STL27RBP 72
STL28RB 66
STL28RBP 66
STL29RB 66
STL29RBP 66
STL2RB 64
STL2RBP 64
STL2RGB 64
STL2RGBP 64
STL33RB 44
STL33RBP 44
STL34RB 44
STL34RBP 44
STL35AB 45
STL35ABP 45
STL35ACB 45
STL35ACBP 45
STL35CCRB 45
STL35CCRBP 45
STL35RB 45
STL35RBP 45
STL36RB 73
STL36RBP 73
STL36RPG 73
STL36RPGP 73
STL36RS 73
STL37RB 73
STL37RBP 73
STL37RPG 73
STL37RPGP 73
STL37RS 73
STL38RB 62
STL38RBP 62
STL39RB 62
STL39RBP 62
STL3RB 64
STL3RBP 64
STL3RGB 64
STL3RGBP 64
STL412RB 37
STL412RBP 37
STL413RB 23
STL413RBP 23
STL413RFHXB 23
STL413RFHXBP 23
STL413RMB 23
STL413RMBP 23
STL42AB 19
STL42ABP 19
STL42AMB 19
STL42AMBP 19
STL42RB 19
STL42RBP 19
STL42RMB 19
STL42RMBP 19
STL42RS 19
STL43A24B 18
STL43A24BP 18
STL43AB 18
STL43ABP 18
STL43ABX 20
STL43ABXP 20
STL43ABXS 20
STL43AKB 18
STL43AKBP 18
STL43R24B 18
STL43R24BP 18
STL43RB 18
STL43RBHX 20
STL43RBHXP 20
STL43RBP 18
STL43RBX 20
STL43RBXP 20
STL43RBXS 20
STL43RK 18
STL43RKB 18
STL43RKBP 18
STL43RMB 18
STL43RMBP 18
STL512RB 32
STL512RBP 32
STL512RCB 32
STL512RCBP 32
STL52ARB 55
STL52ARBP 55
STL52ARS 55
STL53ARDB 55
STL53ARDBP 55
STL53ARPB 55
STL53ARPBP 55
STL53RCB 18
STL53RCBP 18
STL543RB 26
STL543RBP 26
STL55AB 27
STL55ABP 27
STL55RB 27
STL55RBP 27
STL55RFMB 27
STL55RFMBP 27
STL55RMB 27
STL55RMBP 27
STL56RB 74
STL56RBP 74
STL572AB 40
STL572ABP 40
STL572RB 40
STL572RBP 40
STL57RB 74
STL57RBP 74
STL59RB 51
STL59RBP 51
STL59RCB 51
STL59RCBP 51
STL602RB 28
STL602RBP 28
STL603RB 15
STL603RBP 15
STL60RB 59
STL60RBP 59
STL60RLB 59
STL60RLBP 59
STL616NTRB 68
STL616NTRBP 68
STL617NTRB 68
STL617NTRBP 68
STL61RB 59
STL61RBP 59
STL61RLB 59
STL61RLBP 59
STL63CRB 46
STL63CRBP 46
STL63RB 46
STL63RBP 46
STL64RB 52
STL64RBP 52
STL64RCB 52
STL64RCBP 52
STL68RB 12
STL68RBP 12
STL68RPB 12
STL68RPBP 12
STL69CRPG 47
STL69CRPGP 47
STL69R2PG 47
STL69R2PGP 47
STL69RB 47
STL69RBP 47
STL69RCB 47
STL69RCBP 47
STL69RK 47
STL69RPG 47
STL69RPGP 47
STL69RRXB 47
STL69RRXBP 47
STL69RRXBPG 47
STL69RRXBPGP 47
STL69RRXCS 47
STL69RRXPG 47
STL69RRXPGP 47
STL69RS 47
STL6RS 62
STL70AB 40
STL70ABP 40
STL70RB 40
STL70RBP 40
STL71AKMB 42
STL71AKMBP 42
STL71AMB 42
STL71AMBP 42
STL72AB 33
STL72ABP 33
STL72AMB 33
STL72AMBP 33
STL72CAB 33
STL72CABP 33
STL72R1224B 33
STL72R1224BP 33
STL72RB 33
STL72RBP 33
STL72RK 33
STL72RKB 33
STL72RKBP 33
STL72RMB 33
STL72RMBP 33
STL72RS 33
STL73RB 36
STL73RBP 36
STL73RCB 36
STL73RCBP 36
STL73REZB 36
STL73REZBP 36
STL73RK 36
STL73RKB 36
STL73RKBP 36
STL74RBK 33
STL74RBKP 33
STL74RKB 33
STL74RKBP 33
STL75AB 43
STL75ABP 43
STL75AMB 43
STL75AMBP 43
STL75AMFB 42
STL75AMFBP 42
STL75AS 43
STL76RB 50
STL76RBP 50
STL78AB 34
STL78ABP 34
STL78RB 34
STL78RBP 34
STL78REZB 34
STL78REZBP 34

STL78RK 34
STL78RLPB 34
STL78RLPBP 34
STL78RPG 34
STL78RPGP 34
STL79RB 49
STL79RBP 49
STL79RPG 49
STL79RPGP 49
STL79RS 49
STL7RS 62
STL80RB 49
STL80RBP 49
STL82RB 60
STL82RBP 60
STL82RCB 33
STL82RCBP 33
STL83RB 60
STL83RBP 60
STL87RCB 53
STL87RCBP 53
STL87RCPG 53
STL87RCPGP 53
STL88RC1PG 34
STL88RC1PGP 34
STL88RCB 34
STL88RCBP 34
STL88RCBPG 34
STL88RCBPGP 34
STL88RCPG 34
STL88RCPGP 34
STL89RCB 49
STL89RCBP 49
STL8R3B 63
STL8R3BP 63
STL8RB 63
STL8RBP 63
STL8RGB 63
STL8RGBP 63
STL90A24B 57
STL90A24BP 57
STL90AB 57
STL90ABP 57
STL90R24B 57
STL90R24BP 57
STL90RB 57
STL90RBP 57
STL9R3B 63
STL9R3BP 63
STL9RB 63
STL9RBP 63
STL9RGB 63
STL9RGBP 63
TL106CS 291
TL10CB 291
TL10CBP 291
TL10CS 291
TL10SS 291
TL11CPG 291
TL11CPGP 291
TL11RK 239
TL12CS 291
TL14RK 240
TL15RK 243
TL16RK 243
TL21RK 247
TL22RK 247
TL27BK 239
TL29BK 239
TL35FS 292
TL35TB 292
TL35TS 292
TL36RK 244
TL46FS 292
TL46TS 292
TL5RK 240
TL60RK 242
TL8RK 239
TL9RK 240
TLL0016RK 71
TLL002RK 38
TLL008RK 65
TLL112RK 29
TLL12RK 35
TLL144FSL 213
TLL149FB 211
TLL149FBP 211
TLL150FSL 215
TLL152FSL 216
TLL160RK 69
TLL16RK 69
TLL170RK 67
TLL190RK 61
TLL211XRTMK 10
TLL21RK 75
TLL25FS 222
TLL26RK 72
TLL28RK 66
TLL29RK 66
TLL30FB 212
TLL30FBP 212
TLL31RK 76
TLL36RK 73
TLL44FB 213
TLL44FBP 213
TLL45FB 213
TLL45FBP 213
TLL46CFB 214
TLL46CFBP 214
TLL46TB 214
TLL46TBP 214
TLL48FB 215
TLL48FBP 215
TLL50FB 215
TLL50FBP 215
TLL51FB 216
TLL51FBP 216
TLL51FRPG 216
TLL52FB 216
TLL52FBP 216
TLL52FWB 216
TLL54TB 217
TLL54TBP 217
TLL55FB 217
TLL55FBP 217
TLL56FB 218
TLL56FBP 218
TLL56RK 74
TLL57FB 218
TLL57FBP 218
TLL60FB 218
TLL60FBP 218
TLL64FB 219
TLL64FBP 219
TLL70FB 219
TLL70FBP 219
TLL71FB 220
TLL71FBP 220
TLL72FB 220
TLL72FBP 220
TLL73FB 221
TLL73FBP 221
TLL80FB 222
TLL80FBP 222
TLL90RK 62
TLL9RK 62
UCL07CB 197
UCL07CBP 197
UCL09CB 198
UCL09CBB 198
UCL09CBBP 198
UCL09CBP 198
UCL09RCB 198
UCL09RCBP 198
UCL10BCKB 199
UCL10CK1B 199
UCL10CKB 199
UCL10CKBP 199
UCL11CB 200
UCL11CBP 200
UCL11CKB 200
UCL11CKBP 200
UCL11CKPG 200
UCL11CKPGP 200
UCL13C2PG 200
UCL13C2PGP 200
UCL13CB2B 200
UCL13CB2BP 200
UCL13CPG 200
UCL13CPGP 200
UCL160CB 204
UCL160CBP 204
UCL178RFP2B 208
UCL178RFP2BP 208
UCL19CB 201
UCL19CBP 201
UCL20CB 223
UCL21CB 224
UCL22CB 225
UCL23CB 226
UCL24CB 227
UCL24CFB 227
UCL25CB 228
UCL299CPG 209
UCL299CPGP 209
UCL32CDTB 229
UCL41CB 201
UCL41CBP 201
UCL50CB 202
UCL50CBP 202
UCL55CB 202
UCL55CBP 202
UCL59CB 203
UCL60CB 204
UCL60CBP 204
UCL60CBPG 204
UCL60CSBB 204
UCL60CSBBP 204
UCL60CSNB 204
UCL60CSNBP 204
UCL60CSWNB 204
UCL60CSWNBP 204
UCL65CB 205
UCL65CBP 205
UCL66GB 205
UCL90BCB 206
UCL90CB 206
UCL91BCB 207
UCL91BCKB 207
UCL91CB 207
UCL91CKB 207
UCL92BCB 207
UCL92BCKB 207
UCL92CB 207
UCL92CKB 207
UL11BS 261
UL53CB 287
UL53CBP 287
UL56CB 287
UL56CBP 287
UL94CB 286
UL94CBP 286
UL97CPG 288
UL97CPGP 288
ULL25CTB 209
ULL25CTBP 209
ULL25CTVRB 209
ULL25CTVRBP 209
ULL69APG 210

4-INCH STOP, TURN, TAIL LAMPS

Base P/N	STL003RB	STL413RB	STL13RB	STL43RB	STL603RB	STL543RB
Also Available				Clear lens, red LEDs		
Brand	ONE LED LAMPS	FLEET COUNT	FLEET COUNT	OPTRONICS LED	LIGHTGUIDE	HYPERX
LED Qty	1	4	7	10	12	12
Mounting	Recess Grommet Recess Flange	Recess Grommet Surface Mount Reflex Flange	Recess Grommet Recess Flange Surface Mount Reflex Flange	Recess Grommet Recess Flange Reflex Flange	Recess Grommet	Recess Grommet
Connections	 Locking PL3		Round male pin			
FMVSS	Red: S T I Yellow: I P White: (2) R	S2 T2 I6	Red: S T I Yellow: I6 P White: (2)R	Red: S T I P2 Yellow: I6 P White: (2)R	S2 T2 I6	S T I
Amp draw 12/24VDC	12.8VDC .007A Tail, .25A Stop	12.8VDC .008A Tail, .160A Stop	12.8VDC .033A Tail, .214A Stop	12.8VDC .027A Tail, .208A Stop 24VDC .014A Tail, .104A Stop	12.8VDC .114A Tail, .421A Stop	12.8VDC .043A Tail, .174A Stop
Tech Drawing						
Hole Cut-out	4.5"	4.5"	4.5"	4.5"	4.5"	4.5"
Retail	Retail Ready		Retail Ready	Retail Ready		

Accessories

A45GB	BK45BB	A45PB	A47PB	A45PMB
				
Grommet, flush mount	Steel mounting bracket	Straight pigtail, 6"	Right angle pigtail, 10"	Weathertight plug to bare wire, 10"
				

LED LIFETIME WARRANTY

STL55RB	STL23RB	STL101RB	STL201XRB	STL201XRFHXB	STL201RFMB
					
Optronics LED	LED MIRO-FLEX	GloLight	FUSION	FUSION	FUSION
21	12/16	21	20	20	24
Recess Grommet Recess Flange	Recess Grommet	Recess Grommet Recess Flange	Recess Grommet	Surface Mount Reflex Flange	Recess Flange
					
Red: S T I Yellow: I6 P	Red: S T I Yellow: I P	Red: S2 T2 I6 Yellow: I6 P White: (2)R	S2 T2 I6 (2)R	S2 T2 I6 (2)R A	S2 T2 I6 (2)R
12.8VDC .010A Tail, .280A Stop	12.8VDC .023A Tail, .181A Stop 24VDC .012A Tail, .091A Stop	12.8VDC .161A Tail, .361A Stop	12.8VDC / .240A Tail .265A Stop, .30A Back-Up	12.8VDC / .145A Tail .375A Stop, .30A Back-Up	12.8VDC / .139A Tail .324A Stop, .297A Back-Up
					
4.5"	4.5"	4.5"	4.5"	4.5"	4.5"

SMD LED TECHNOLOGY

- **S**urface **M**ount **D**evice
- Fewer connection points, fewer corrosion points
- Automated manufacturing increases production efficiency
- Thinner, more compact designs fit more applications

Better heat distribution

Increased durability



6-INCH STOP, TURN, TAIL LAMPS






Base P/N	STL002RB	STL412RB	STL12RB	STL72RB	STL512RB	STL572RB
Also Available				Additional options available	Clear lens, red LEDs	
Brand	ONE LED LAMPS	FLEET COUNT	FLEET COUNT	OptroNICS LED	HD500 SERIES	HYPERX
LED Qty	1	4	6	10	18	12
Mounting	Recess Grommet Surface Flange	Recess Grommet	Recess Grommet Surface Flange	Recess Grommet Surface Flange	Recess Grommet	Recess Grommet
Connections						
FMVSS	Red: S2 T2 I6 Yellow: I6 P White: (2) R	S T I	Red: S T I Yellow: I6 P White: (2) R	Red: S2 T2 I6 Yellow: I6 P White: (2) R	S T I	S T I
Amp draw 12/24VDC	12.8VDC .007A Tail, .25A Stop	12.8VDC .005A Tail, .14A Stop	12.8VDC .013A Tail, .161A Stop	12.8VDC .046A Tail, .243A Stop	12.8VDC .007A Tail, .174A Stop	12.8VDC .007A Tail, .174A Stop
Tech Drawing						
Hole Cut-out	6.85 x 2.5" (1.25" R)	6.85 x 2.5" (1.25" R)	6.85 x 2.5" (1.25" R)	6.85 x 2.5" (1.25" R)	6.85 x 2.5" (1.25" R)	6.85 x 2.5" (1.25" R)
Retail	Retail Ready		Retail Ready	Retail Ready		

Accessories

A70GB	BK70BB	A45PB	A47PB	A45PMB
				
Grommet, flush mount	Steel bracket	Straight pigtail, 6"	Right angle pigtail, 10"	Weathertight plug to bare wire, 10"
				

LED LIFETIME WARRANTY

STL22RB	STL602RB	STL111RB	STL70RB	STL1211RCFHPG	STL211XRB
Clear lens, red LEDs					Clear lens, red LEDs
LED MIRO-FLEX	LIGHT GUIDE	GloLight	optronics LED	GloLight FUSION	FUSION
12/16	22	22	48/56	22	16
Recess Grommet	Recess Grommet	Recess Grommet Recess Flange Surface Flange	Recess Grommet	Surface Flange	Recess Grommet Surface Flange
					
S T I	Red: S2 T2 I6 White: (2) R	Red: S2 T2 I6 Yellow: I6 P White: (2)R	Red: S T I P2 Yellow: I P2 P	S2 T2 I6 (2)R	S T I (2)R
12.8VDC .007A Tail, .187A Stop	12.8VDC .007A Tail, .187A Stop	12.8VDC / .268A Tail, .582A Stop, .386A Back-up	12.8VDC .054A Tail, .362A Stop	12.8VDC / .02A Tail, .375A Stop, .242A Back-Up	12.8VDC / .020A Tail, .375A Stop, .242A Back-up
					
6.85 x 2.5" (1.25" R)	6.85 x 2.5" (1.25" R)	6.85 x 2.5" (1.25" R)	6.85 x 2.5" (1.25" R)	7.52 x 3.25" (1.25" R)	6.85 x 2.5" (1.25" R)
		Retail Ready			Retail Ready

SMD LED TECHNOLOGY

- **S**urface **M**ount **D**evice
- Fewer connection points, fewer corrosion points
- Automated manufacturing increases production efficiency
- Thinner, more compact designs fit more applications

Better heat distribution

Increased durability



Opti-Brite™

LED WORK LIGHTS

SMD LED TECHNOLOGY FOR LONG TERM RELIABILITY

Raw Lumen	**4800**	**4000**	**3200**	**2400**	**2160**	**2160**	**2160**	**2160**	**2160**
Effective Lumen	**3360**	**2800**	**2240**	**1680**	**1510**	**1492**	**1490**	**1490**	**1490**
Bulk P/N	TLL70FB	TLL56FB	TLL64FB	TLL149FB	TLL55FB	TLL-46CFB	TLL71FB	TLL72FB	TLL73FB
LEDS	6 SMD	8 SMD	4 SMD	10 SMD	9 SMD	9 SMD	9 SMD	9 SMD	9 SMD
Beam	Flood	Flood	Flood	Flood	Flood	Flood	Flood	Flood	Flood
Lens	Poly-carbonate	Poly-carbonate	Poly-carbonate	Poly-carbonate	Poly-carbonate	Poly-carbonate	Poly-carbonate	Poly-carbonate	Poly-carbonate
Housing	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum
Hardware	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel
Weight	1.41 lbs.	3.53 lbs.	1.41 lbs.	.95 lbs.	1.35 lbs.	1.50 lbs.	1.41 lbs.	1.5 lbs.	1.61 lbs.
Dims	4.375"W 5.375"H 2.625"D	7.161"W 6.093"H 4.313"D	4.187"W 5.375"H 3.0"D	6.625"W 3.5"H 2.665"D	4.875"W 6.5"H 2.0"D	5.0"W 5.75"H 2.375"D	4.0"W 5.0"H 2.25"D	5.0"W 5.375"H 2.25"D	5.0"W 7.5"H 3.25"D
IP Rating	IP69K	IP69K	IP69K	IP69K	IP69K	IP69K	IP69K	IP69K	IP69K
Amp Draw 12.8VDC	2.8A	3.7A	2.9A	2.05A	1.5A	1.65A	1.43A	1.43A	1.43A
Amp Draw 24VDC	1.43A	2A	1.5A	.97A	.73A	1.0A	.66A	.66A	.66A

– Wide Angle Beam



Flood Beam Pattern



Spot Beam Pattern

IP69K RATING

Highest designation available for water ingress testing, offering increased reliability and service life when subjected to severe environmental conditions or cleaning methods.

LED LIFETIME WARRANTY

HEAVY DUTY CONSTRUCTION FOR DURABILITY AND PERFORMANCE

Opti-Brite™

2160	2160	1920	1440	1440	1440	960	800	720	324	270
1484	1346	1295	1036	1028	865	670	560	464	252	150
TLL54TB	TLL46TB	TLL45FB	TLL48FB	TLL44FB	TLL60FB	TLL30FB	TLL51FB	TLL52FB	TLL50FB	TLL80FB
9 SMD	9 SMD	8 SMD	6 SMD	6 SMD	6 SMD	4 SMD	1 SMD	3 SMD	9 SMD	6 SMD
Spot	Spot	Flood	Flood	Flood	Flood	Flood	Flood	Flood	Flood	Flood
Poly-carbonate	Poly-carbonate	Poly-carbonate	Poly-carbonate	Poly-carbonate	Poly-carbonate	Poly-carbonate	Poly-carbonate	Poly-carbonate	Poly-carbonate	Poly-carbonate
Aluminum	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum	Poly-carbonate	Aluminum
Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel
1.51 lbs.	1.50 lbs.	1.39 lbs.	1.14 lbs.	.98 lbs.	.95 lbs.	1.468 lbs.	.37 lbs.	.38 lbs.	.96 lbs	.7 lbs
5.0”W 5.75”H 2.375”D	5.0”W 5.75”H 2.375”D	4.5”W 5.75”H 2.0”D	4.125”W 5.281”H 2.125”D	4.0”W 5.125”H 2.375”D	6.0”W 3.25”H 2.438”D	3.27”W 4.5”H 2.375”D	2.0”W 3.0”H 2.5”D	2.75”W 4.0”H 1.687”D	4.938”W 5.75”H 2.375”D	3.0”W 2.0”H 1.563”D
IP69K	IP69K	IP69K	IP69K	IP69K	IP69K	IP69K	IP69K	IP69K	IP69K	IP55
1.5A	1.5A	1.5A	1.5A	1.1A	1.1A	.75A	.85A	.6A	.53A	.19A
.73A	.73A	.67A	.5A	.5A	.5A	.37A	.41A	.3A	.28A	NA

Lumen Ratings

The ***raw lumen*** output of a light is calculated by taking the number of LEDs in a light and multiplying that by their maximum output rating. The resulting value does not include real-world factors that can decrease light output by as much as 75 percent.

Effective lumens is an actual measurement of light output that takes into account thermal losses, current used to drive the LEDs, optical losses, and assembly variations. Measuring the effective lumen output of a light requires the use of high-tech photometry equipment.

SMD LED TECHNOLOGY

- Fewer connection points, fewer corrosion points
- Automated manufacturing increases production efficiency
- Thinner, more compact designs fit more applications
- Improved heat distribution increases component life

BETTER VALUE ▪ BETTER OPTIONS ▪ BETTER LIGHTING

OPTRONICS® LED LIFETIME LIMITED WARRANTY

Optronics LED lighting products are warranted for the lifetime of original purchaser from defects in workmanship and/or materials only. Optronics will replace the product to the original purchaser or refund the purchase price if the product fails because of defect due to workmanship and/or materials. This limited lifetime warranty covers every and all diodes within each unit. Connector failure is covered by our three year limited warranty. The LED Lifetime Warranty does not apply to severe applications such as construction or off-road use and does not cover damage resulting from accident, misuse, or abuse. If warrantor is unable to provide replacement and repair is not commercially practicable or cannot be timely made, then warrantor will refund the purchase price. This offer does not constitute in any way a product guarantee and Optronics does not assume any obligations beyond replacement of the product. This warranty is not transferable and applies to the original installation of the product.

INCANDESCENT 3-YEAR LIMITED WARRANTY

Optronics' incandescent 12-volt lighting products are warranted for a period of three years from defects in workmanship and/or materials only. Optronics will replace the product to the original purchaser or refund the purchase price if the product fails because of defect due to workmanship and/or materials within the limited warranty period from the date or lot code printed on the product. If warrantor is unable to provide replacement and repair is not commercially practicable or cannot be timely made, then warrantor will refund the purchase price. This offer does not constitute in any way a product guarantee and Optronics does not assume any obligations beyond replacement of the product. This warranty is not transferable and applies to the original installation of the product.

CONSPICUITY TAPE LIMITED WARRANTY

Optronics' conspicuity tape products are warranted for a period of seven years from defects in workmanship and/or materials and adhesion failure only. Optronics will replace the product to the original purchaser or refund the purchase price if the product fails within the limited warranty period from the date or lot code printed on the product. If warrantor is unable to provide replacement and repair is not commercially practicable or cannot be timely made, then warrantor will refund the purchase price. This offer does not constitute in any way a product guarantee and Optronics does not assume any obligations beyond replacement of the product. This warranty is not transferable and applies to the original installation of the product.

PRODUCT REPLACEMENT PROCEDURES

To be eligible for Limited Warranty consideration, please contact your local authorized distributor/dealer or Optronics' customer service. Optronics' authorized distributor/dealer has full authority to issue an upfront warranty replacement/credit. If the product is found to be out of warranty at a later date, Optronics' customer service will rebill the customer for the replacement/credit. Customer service will determine if the failed product requires a return to Optronics. If return is required, a RETURN GOODS AUTHORIZATION NUMBER (RGA) will be issued.

THESE WARRANTIES DO NOT COVER DAMAGE RESULTING FROM ACCIDENT, MISUSE, OR ABUSE. CONSEQUENTIAL DAMAGES ARE EXCLUDED UNDER THIS WARRANTY AND ANY IMPLIED WARRANTY, EXCEPT FOR PERSONAL INJURY. THIS WARRANTY IS OFFERED IN LIEU OF ALL OTHER WARRANTIES. HOWEVER, MODIFICATION, LIMITATIONS OR EXCLUSIONS ON IMPLIED WARRANTIES MAY BE UNENFORCEABLE IN SOME STATES. THIS WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS AND YOU ALSO HAVE OTHER RIGHTS THAT VARY FROM STATE TO STATE. SOME STATES DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES SO THE ABOVE LIMITATIONS OR EXCLUSIONS MAY NOT APPLY TO YOU.

OKLAHOMA
401 South 41st Street East
Muskogee OK 74403
Warranty Contact – Michelle Majors
Phone – 800-364-5483 ext. 349
Fax – 918-683-9517

INDIANA
3535 Corrie Drive
Goshen IN 46526
Warranty Contact – Keia Rolston
Phone – 800-826-5483 ext. 120
Fax – 574-389-0041

BETTER VALUE
BETTER OPTIONS
BETTER LIGHTING

optronics

www.optronicsinc.com

To access digital catalog, scan this QR code with your mobile device